



INTERNATIONAL
OLYMPIC
COMMITTEE

ODF/INT029 R2 v10.0 APP (CR)

Olympic Data Feed

ODF Cycling Road Data Dictionary

12 March 2012
Technology Department
© International Olympic Committee



License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic Games and/or (ii) to develop similar standards for other events than the Olympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.

2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.

3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.

4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.

The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.

5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.

6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.

**TABLE OF CONTENT**

TABLE OF CONTENT	3
1 Introduction	5
1.1 This document.....	5
1.2 Objective	5
1.3 Main Audience.....	5
1.4 Glossary	5
1.5 Related Documents.....	5
2 Overall Perspective	7
2.1 Objective	7
2.2 End to End data flow	7
3 Codes	8
4 Cycling Road Data Extension	9
4.1 General Issues	9
4.1.1 ODF header	9
4.1.2 Attributes Definition.....	9
5 Point in Time.....	10
5.1 Point in Time Applicable Messages	10
5.1.1 List of participants by discipline/ List of participants by discipline update	12
5.1.1.1 Description.....	12
5.1.1.2 Header Values.....	12
5.1.1.3 Trigger and Frequency	12
5.1.1.4 Message Structure	12
5.1.1.5 Message Values	12
5.1.1.6 Message sort	13
5.1.2 Start List.....	14
5.1.2.1 Description.....	14
5.1.2.2 Header Values.....	14
5.1.2.3 Trigger and Frequency	14
5.1.2.4 Message Structure	14
5.1.2.5 Message Values	14
5.1.2.6 Message sort	15
5.1.3 Event Unit Results	16
5.1.3.1 Description.....	16
5.1.3.2 Header Values.....	16
5.1.3.3 Trigger and Frequency	16
5.1.3.4 Message Structure	16
5.1.3.5 Message Values	16
5.1.3.6 Message sort	23
5.1.4 Event's Medallists	24
5.1.4.1 Description.....	24
5.1.4.2 Header Values.....	24
5.1.4.3 Trigger and Frequency	24
5.1.4.4 Message Structure	24
5.1.4.5 Message Values	24
5.1.4.6 Message sort	24
5.1.5 Official Communication.....	25
5.1.5.1 Description.....	25



5.1.5.2	Header Values	25
5.1.5.3	Trigger and Frequency	25
5.1.5.4	Message Structure	25
5.1.5.5	Message Values	25
5.1.5.6	Message sort	25
5.1.6	Discipline/venue good morning.....	26
5.1.6.1	Description.....	26
5.1.6.2	Header Values.....	26
5.1.6.3	Trigger and Frequency	26
5.1.6.4	Message Structure	26
5.1.6.5	Message Values	26
5.1.6.6	Message sort	26
5.1.7	Discipline/venue good night.....	27
5.1.7.1	Description.....	27
5.1.7.2	Header Values.....	27
5.1.7.3	Trigger and Frequency	27
5.1.7.4	Message Structure	27
5.1.7.5	Message Values	27
5.1.7.6	Message sort	27
5.1.8	Discipline Configuration	28
5.1.8.1	Description.....	28
5.1.8.2	Header Values.....	28
5.1.8.3	Trigger and Frequency	28
5.1.8.4	Message Structure	28
5.1.8.5	Message Values	28
5.1.8.6	Message sort	32
5.1.9	Event Unit Weather Conditions.....	33
5.1.9.1	Description.....	33
5.1.9.2	Header Values.....	33
5.1.9.3	Trigger and Frequency	33
5.1.9.4	Message Structure	33
5.1.9.5	Message Values	33
5.1.9.6	Message sort	33
6	Real time	34
6.1	Real Time Applicable Messages.....	34
6.1.1	RT Event Unit Results	35
6.1.1.1	Description.....	35
6.1.1.2	Header Values.....	35
6.1.1.3	Trigger and Frequency	35
6.1.1.4	Message Structure	35
6.1.1.5	Message Values	35
6.1.1.6	Message sort	41
	DOCUMENT CONTROL	42



1 Introduction

1.1 This document

This document includes the ODF Cycling Road Data Dictionary. This Data Dictionary refines the messages described in the ODF Central Messages Interface Document and ODF Sport Messages Interface Document specifically for Cycling Road, as well as defines the codes used in these messages.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Cycling Road Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the Cycling Road competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 Glossary

The following abbreviations are used in this document

- **IF** – International Federation
- **IOC** – International Olympic Committee
- **NOC** – National Olympic Committee
- **ODF** – Olympic Data Feed
- **ODF-RT** – Olympic Data Feed Real Time
- **RSC** – Results System Codes
- **CR** – Cycling Road
- **WNPA** – World News Press Agencies

1.5 Related Documents

Document Reference	Document Title	Document Description
ODF/INT001	ODF Message Transmission Document	This document describes the technical standards to be used to transfer ODF messages between the message generators and the final ODF



		users
ODF/COD001	ODF Common Codes Document	This document describes the ODF codes used across the rest of the ODF documents
ODF/INT003	ODF Central Messages Interface Document	This document describes the ODF central messages
ODF/INT004	ODF Sport Messages Interface Document	This document describes the ODF sport messages, generated independently by each sport



2 Overall Perspective

2.1 Objective

The objective of this document is to focus on the formal definition of the ODF Cycling Road Data Dictionary.

2.2 End to End data flow

The general rules as described in the documents referenced in the section 1.5 will have to be considered for a complete and formal definition. It is especially important the ODF Central Messages Interface Document and ODF Sport Messages Interface Document, since this ODF Cycling Road Data Dictionary is a particularization of those documents.

In the following sections, for each ODF sport message it will be explained in further detail those elements, attributes, codes, ODF header, the trigger and frequency for each message generation, as well as the sort of the message that are particular in the case of Cycling Road.

Any ODF Cycling Road message should follow all the previous definitions in order to be considered as an ODF compliant message.



3 Codes

Several codes are used in the definition of the messages in this document. Any code will be referenced the following way:

CC @CodeEntity

CodeEntity is the name of the entity that identifies a particular set of codes.

The following table describes the codes entities used in document sorted by name, indicating whether the set of values can be found in the ODF Common Codes Document, or listed in the table itself, otherwise. Please refer to ODF Sport Messages Interface Document to know the format of these codes.

Code Entity	Code Entity Set of Values	
CC @IRM The codes LAP, OTL and REL only send for Road raced	Code	Description
	DNF	Did not finish
	DNS	Did not start
	DSQ	Disqualified
	LAP	Lapped
	OTL	Over Time Limit, Riders placing are given by the Commissaries. Riders who have completed the race, but are outside of the time limit, should be presented with their actual time rather than the time limit.
CC @ResultType	REL	Relegated. Riders are ranked at the place given by the Commissaries (time for group is displayed)
	Code	Description
	IRM	IRM status
	RANK	Rank without final result time
CC @RunStatus	TIME	Time
	Code	Description
	F	finished
	NST	not started
CC @TemperatureType	ST	started
	Code	Description
	MIN	Minim temperature
CC @TemperatureUnit	MAX	Max temperature
	Code	Description
	C	Celsius



4 Cycling Road Data Extension

4.1 General Issues

The following sections extend and complete the information to be sent in each of the messages for this particular discipline, if some particularization is needed. If there are special considerations for any of the message types that have to be sent for this discipline, then they should be considered in the following sections. If nothing is mentioned for a particular message type, then the general rules, as defined either in the ODF Central Messages Interface Document or ODF Sport Messages Interface Document, should be respected for the messages described in the chapter 4 of this document.

4.1.1 ODF header

Regarding to the ODF header values, you should also follow the description in the ODF Central Messages Interface Document or ODF Sport Messages Interface Document. However, the following attributes could be refined for each message type regarding to the header values:

- ODF Header: DocumentCode.

4.1.2 Attributes Definition

The attributes types are explained in the section “5.1.2. Attributes Definition” of the ODF Central Messages Interface Document. Please, refer to that document for further information



5 Point in Time

5.1 Point in Time Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in Cycling Road, as well as the category of each message, which identifies if the message structure definition can be found either in the ODF Sport Messages Interface Document or ODF Central Messages Interface Document.

- The column “Message type” indicates the DocumentType that identifies a message
- The column “Message name” is the message name identified by the message type
- The column “Message documented” indicates the document where you should go to have the general definition for a particular Message type
- The column “Message used in this sport” indicates whether a message is used in particular for this sport or not. If it is not ticked (X), then the message should not be used for this sport.
- The column “Message extended in this document” indicates whether a particular message has extended definition in regards to those that are general for all sports. Any message ticked (X) in this column should also be ticked in the “Message used in this sport column”. If one message has extended definition, it should be considered both, the extensions as well as the general rules for one message that is used in the case of the sport. However, if one particular message is not extended, then it should follow the general definition rules.

Message Type	Message name	Message documented	Message used in this sport	Message extended in this document
DT_SCHEDULE	Competition schedule	Central	X	
DT_SCHEDULE_UPDATE	Competition schedule update	Central	X	
DT_PARTIC	List of participants by discipline	Central	X	X
DT_PARTIC_UPDATE	List of participants by discipline update	Central	X	X
DT_PARTIC_TEAMS	List of teams	Central		
DT_PARTIC_TEAMS_UPDATE	List of teams update	Central		
DT_PARTIC_HORSES	List of equestrian horses	Central		
DT_PARTIC_HORSES_UPDATE	List of horses update	Central		
DT_MEDALS	Medal standings	Central	Global	
DT_MEDALLISTS_DAY	Medallists of the day	Central	Global	
DT_HISTORIC_RECORD	Historical records	Central		
DT_HIST_REC_UPDATE	Historical records update	Central		



DT_GLOBAL_GM	Global good morning	Central	Global	
DT_GLOBAL_GN	Global good night	Central	Global	
DT_START_LIST	Start List	Sports	X	X
DT_RESULT	Event Unit Results	Sports	X	X
DT_PHASE_RESULT	Phase Results	Sports		
DT_CUMULATIVE_RESULT	Cumulative Results	Sports		
DT_POOL_STANDING	Pool Standings of group in a team competition	Sports		
DT_RANKING	Event Final ranking	Sports	X	
DT_STATS	Statistics table	Sports		
DT_MEDALLISTS	Medallists of one event	Sports	X	X
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	Sports	X	
DT_RECORD	Records	Sports		
DT_COMMUNICATION	Official Communication	Sports	X	X
DT_BRACKETS	Brackets	Sports		
DT_GM	Discipline/venue good morning	Sports	X	X
DT_GN	Discipline/venue good night	Sports	X	X
DT_FED_RANKING	Federation Ranking	Sports		
DT_CONFIG	Discipline configuration	Sports	X	X
DT_WEATHER	Event Unit Weather conditions	Sports	X	X
DT_SERIAL	List of Current PiT Serial	Sports	X	



5.1.1 List of participants by discipline/ List of participants by discipline update

5.1.1.1 Description

This message is the List of participants by discipline (and the update), for that discipline it is the list of athletes, as described in the ODF Central Messages Interface Document.

5.1.1.2 Header Values

The definition in the ODF Central Messages Interface Document is valid

5.1.1.3 Trigger and Frequency

The definition in the ODF Central Messages Interface Document is valid And in the case when the venue results becomes owner of data.

5.1.1.4 Message Structure

The optional elements defined for this message in the ODF Central Messages Interface Document that should be included in the case of Cycling Road are:

- EventEntry

In the next section (message values), there is a more detailed definition.

5.1.1.5 Message Values

The following table lists the “List of participants by discipline/ update” optional attributes (defined in the ODF Central Messages Interface Document) that are used in the case Cycling Road, as well as the attributes that have an extended definition.

Element	Attribute	M/O	Value	Comments
Participant	GivenName	M	S(25)	Given name in WNPA format (mixed case)
	BirthDate	O	YYYYMMDD	Date of birth
	Height	O	N(3) 999	Height in centimetres Send when this information is available
	Weight	O	N(3) 999	Weight in kilograms Send when this information is available
	MainFunctionId	M	CC @Function	Main function
Discipline	InternationalFederationId	Y	S(16)	UCI code (competitor's federation number for the discipline). It will be included.

The following table describes in more detail the EventEntry element in the case of Cycling Road.

Element: EventEntry			
Type	Code	Value	Description
E_ENTRY	E_SUBSTITUTE	S(1)	For @Type: Send proposed type
			For @Code: Send proposed code
			For @Value: Send "Y" if the competitor is a substitute or N if it is not more.

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
E_ENTRY /E_SUBSTITUTE	Flag that indicates the competitor is a	As soon as this information is (this



Type /Code	Description	Expected
	substitute.	information can be sent in both messages and only for Road Race Event)

5.1.1.6 Message sort

Please, follow the general definition.



5.1.2 Start List

5.1.2.1 Description

This message is the Start List message as described in the ODF Sport Messages Interface Document.

5.1.2.2 Header Values

The DocumentCode attribute in the ODF header will be sent according to the ODF Common Codes document (header values sheet).

5.1.2.3 Trigger and Frequency

Please, follow the general definition.

5.1.2.4 Message Structure

The optional elements defined for this message in the ODF Sport Messages Interface Document that should be included in the case of Cycling Road are:

- UnitDateTime (following the general rules for this element)
- UnitInfo
- Start /Competitor /Composition /Athlete /EventUnitEntry.

In the next section (message values), there is a more detailed definition.

5.1.2.5 Message Values

The following table lists the Start List optional attributes (defined in the ODF Sport Messages Interface Document) that are used in the case of Cycling Road, as well as the attributes that have an extended definition.

Element	Attribute	M/O	Value	Comments
Start	StartOrder	O	Numeric	The group number. This value will be display only for Individual time trial.
	SortOrder	M	Numeric	
Start /Competitor /Composition /Athlete	Code	M	S(20) with no leading zeroes	Athlete ID
	Bib	O	String	The athlete's race number

The following table describes in more detail the UnitInfo element in the case of Cycling Road, which should be used in the case of time Trial event units.

Element: UnitInfo			
Type	Code	Value	Description
UI_STARTLIST	CR_COMMUNIQUE	String	For @Type: Send proposed type
			For @Code: Send proposed code
			For @Value: Send the communiqué number.
UI_ST	CR_ENTRIES	Number	For @Type: Send proposed type
			For @Code: Send proposed code
			For @Value: Send the number of entries.
	CR_NOCS	Number	For @Type: Send proposed type



			For @Code: Send proposed code
			For @Value: Send the number of NOCs

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
UI_STARTLIST /CR_COMMUNIQUE	Communiqué number for the start list	When was available
UI_ST/CR_ENTRIES UI_ST/CR_NOCS	The numbers of entries and NOCs for the statistics	When was available

The following table describes in more detail the EventUnitEntry element in the case of Cycling Road, which should be used in the case of Time Trial event units.

Element: Competitor /Start /Competitor /Composition /Athlete /EventUnitEntry			
Type	Code	Value	Description
EUE_TIME	CR_STIME	HH:MM:SS 99:99:90	For @Type: Send proposed type
			For @Code: Send proposed code
			For @Value: Send the Start time for the competitor
EUE_CR	CR_IRM	CC @IRM	For @Type: Send proposed type
			For @Code: Send proposed code
			For @Value: Indicator as supplied by OVR for DNS or other possible results before the race.

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
EUE_TIME /CR_STIME	Start time	Always, for Time Trial event units
EUE_CR /CR_IRM	Invalid result mark supplied by OVR before the race.	As soon as this information is available

5.1.2.6 Message sort

Please, follow the general definition.



5.1.3 Event Unit Results

5.1.3.1 Description

This message is the Event Unit Results message as described in the ODF Sport Messages Interface Document.

5.1.3.2 Header Values

The DocumentCode attribute in the ODF header will be sent according to the ODF Common Codes document (header values sheet).

5.1.3.3 Trigger and Frequency

Please, follow the general definition, taking also into account the following

- For the Road Race event:
 - For intermediate results:
 - After the group including the 15th competitor of each lap
 - Partial Results:
 - After the group including the 15th competitor
 - Official results:
 - After the results for race are approved
- For the Time Trial event:
 - For intermediate results:
 - After each group finished.
 - Official results:
 - After the results for race are approved

5.1.3.4 Message Structure

The optional elements defined for this message in the ODF Sport Messages Interface Document that should be included in the case of Cycling Road are:

- UnitDateTime (following the general rules for this element)
- UnitInfo
- Competitor /Composition /Athlete /ExtendedResults /ExtendedResult
- Competitor /Composition /Athlete /ExtendedResults /ExtendedResult /Extensions /Extension

5.1.3.5 Message Values

The following table lists the Event Unit Results optional and/or extended attributes (defined in the ODF Sport Messages Interface Document), as well as the attributes that have an extended definition.

Element	Attribute	M/O	Value	Comments
Result	Rank	O	String	Rank of the competitor in the corresponding event unit. This attribute is optional.
	RankEqual	O	Y	Y in the case of equalled rank



Element	Attribute	M/O	Value	Comments
	ResultType	O	CC @ResultType	Result type. (see codes section)
	IRM	O	CC @IRM	IRM for the particular event unit. Only if the results are approved. Send just in the case @ResultType is IRM (see codes section)
	Result	O	Road Race: HH:MM:SS 99:90:00 Time trial: H:MM:SS.tt 99:90:00.00	Result for the particular event unit.
	SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the particular event unit.

The following table describes in more detail the UnitInfo element in the case of Cycling Road.

Element: UnitInfo					
Type	Code	Extension Code	Pos	Value	Description
UI_RESULTS	CR_COMMUNIQUE		N(1) 0	String	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Send 1 for final result Send 2 for race analysis For @Value: Send the communiqué number.
	CR_AFTER			String	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything. For @Value: Send sections who just to past until know. Example: PTP Start, Finish Only for Road Race
UI_ST	CR_FINISHED			Number	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything. For @Value: Send number of riders who finish the race.
	CR_y Where y=CC@IRM			Number	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything. For @Value: Send number of riders who have IRM. For CR_DNF only take account of riders who abandoned the race.
	CR_DNF_T			Number	For @Type: Send proposed type For @Code: Send proposed code



Element: UnitInfo						
Type	Code	Extension Code	Pos	Value	Description	
					For @Pos: Do not send anything.	
					For @Value: The total number of DNF riders. This should be calculated as Abandoned (@Code =CR_DNF) + Lapped (@Code =CR_LAP)	
UI_LEADER	CR_CURRENT			N(2) 90	For @Type: Send proposed type	
					For @Code: Send proposed code	
					For @Pos: Do not send anything	
					For @Value: Send the intermediate point was the current leader has most recently passed (Mass start)	
		CR_ID		S(20) with no leading zeroes	For @Type: Send proposed type	
					For @Code: Send proposed code	
					For @Pos: Do not send anything	
					For @Value: Send the Current Leader ID the intermediate (s)he has most recently passed (Mass start)	
		CR_INTERMEDIATE		N(2) 90	HH:MM:SS 99:90:00	For @Type: Send proposed type
					For @Code: Send proposed code	
				For @Pos: The number that identifies the intermediate result point, from 1 to the total number (n) of intermediate result points. Where n is when finish the race. According to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message		
				For @Value: Leader Time up to that point		
		CR_AVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type	
					For @Code: Send proposed code	
					For @Pos: Do not send anything	
					For @Value: Leader Average Speed up to that point	
		CR_LAVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type	
					For @Code: Send proposed code	
					For @Pos: Do not send anything	
					For @Value: Average Speed (last lap) km/h	
	CR_LAP		N(2) 90	HH:MM:SS 99:90:00	For @Type: Send proposed type	
					For @Code: Send proposed code	
					For @Pos:	



Element: UnitInfo					
Type	Code	Extension Code	Pos	Value	Description
					The number that identifies the lap, from 1 to the total number (n) of laps. According to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message For @Value: Time for that lap
		CR_AVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Average Speed (from start) in that lap
	CR_SECTION		N(2) 90	HH:MM:SS 99:90:00	For @Type: Send proposed type For @Code: Send proposed code For @Pos: The number that identifies the section, from 1 to the total number of sections. It is section between each intermediate point. For @Value: Time for that section
		CR_AVGSPEED		N(3).N(2) 990.00	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Leader Average Speed in that section Send a dash "-" is case of half laps

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
UI_RESULTS /CR_COMMUNIQUE	The communiqué number.	When was available
CR_AFTER	The race distance completed so far	When was available Only for Road Race
UI_ST /CR_FINISHED UI_ST /CR_y Where y = CC @IRM	Number of riders who finish in that moment and the number of riders who have IRM For CR_DNF only take account of riders who abandoned the race.	When was available
UI_ST /CR_DNF_T	The total number of DNF riders. This should be calculated as Abandoned (@Code =CR_DNF) + Lapped (@Code =CR_LAP)	
UI_LEADER /CR_CURRENT	Send the intermediate point where the current leader has most recently passed.	when it is available
CR_CURRENT /CR_ID	Send the ID of the current Leader	
UI_LEADER /CR_INTERMEDIATE	Are points in the race, from 1 to n (finish).	Road race: when it is available



	The @pos attribute should be according to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message	
CR_INTERMEDIATE/ CR_LAVGSPEED	Average speed from the time the leader at the first intermediate of a lap crosses this point until the time the leader crosses the last intermediate point of the lap.	
UI_LEADER /CR_LAP	Section between two intermediates points. The @pos attribute should be according to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message The @Value attribute is the Lap time.	Road race: when it is available
CR_LAP /CR_AVGSPEED	Average speed from the time competitor X crosses the first intermediate (competitor X may be in the lead or not) of a lap until the time competitor X (now the leader) crosses the last intermediate point of a lap.	
UI_LEADER /CR_SECTION	Section for the PTP	Road race: when it is available

The following table describes in more detail the Competitor /Composition /Athlete /ExtendedResults /ExtendedResult element.

Element: Competitor /Composition /Athlete /ExtendedResults /ExtendedResult					
Type	Code	Extension Code	Pos	Value	Description
ER_RESULTS	CR_SPRINTOFF			S(1)	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send "Y" for the indication of the sprint-off winner
	CR_STATUS			CC@RunStatus	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Race status for that athlete Only for Time trial
	CR_CURRENT			N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Intermediate point was the athlete has most recently passed If the competitor has an IRM: 1. In case the DNS or the athlete has an IRM before he crosses the first intermediate point: send 1. 2. In other cases, send the Intermediate point that he has crossed most recently plus 1.
	CR_INTERMEDIATE CR_LAP		N(2) 90	Road Race: HH:MM:SS	For @Type: Send proposed type



Element: Competitor /Composition /Athlete /ExtendedResults /ExtendedResult					
Type	Code	Extension Code	Pos	Value	Description
	CR_SECTION			99:90:00 Time trial: H:MM:SS.tt 99:90:00.00 Only for the final results (last intermediate point)	For @Code: Send proposed code For @Pos: Section/Lap/Intermediate number where the competition has taken place (1,2..) For @Value: Time after the Lap/intermediate/section. The time its cumulative for intermediate points/sections
		CR_RANK		String	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Athlete's rank after the Lap/intermediate point/section
		CR_ERANK		Y	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Y in the case of equalled rank
		CR_DIFF		Road Race: +H:MM:SS +9:90:00 Or 0:00 for leader Time trial: +HH:MM:SS.tt +9:90:00.00 Or 0:00.00 for leader	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: The difference time between that competitor and the leader until that intermediate point/section.
		CR_AVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: intermediate point/section average speed
		CR_IDX		N(3) 990	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Index based on whole list (with the ones who have not passed yet are indexed as well – after the ones who have finished, but before the IRMs. Sorted by the intermediate passed most recently, and by order there (if none, then by start order)). Overlapped (LAP) riders must be dropped to the bottom but above the DNF/DSQ/DNS riders.



Element: Competitor /Composition /Athlete /ExtendedResults /ExtendedResult					
Type	Code	Extension Code	Pos	Value	Description
					For tied athletes, the rider with the lowest bib number is listed first.
		CR_PASSIDX		N(3) 990	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Index based on only the ones who have finished or have an IRM
		CR_LASTFINISH		S(1)	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Send "Y" this attribute for the competitor who has just finished the split or the race.
		CR_OFFICIAL		S(1)	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Send Y when the time becomes official Send N when the time is unofficial. Only for Intermediate points. (Road race only)
	CR_PHOTO			S(1)	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: To know if the competitor's final result was decided by photo. Send Y for Evaluated Status Send P for Pending Status.

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
ER_RESULTS /CR_SPRINTOFF	Indication of the sprint-off winner	If it is necessary
ER_RESULTS /CR_STATUS	For know the status of the athlete's race.	Time trial: Always
ER_RESULTS /CR_CURRENT	Send for the athlete who has just finished the intermediate point or the race. If the competitor has an IRM: 1. In case the DNS or the athlete has an IRM before he crosses the first intermediate point: send 1. 2. In other cases, send the Intermediate point that he has crossed most recently plus 1.	Always
ER_RESULTS /CR_INTERMEDIATE	It's the intermediate point where the competitor has taken place (Time, Rank, Avr. Speed, Difference time).	Always
ER_RESULTS /CR_LAP	Section between two intermediates points (Time, Rank).	Always



ER_RESULTS /CR_SECTION	Section between two intermediates for PTP where the competitor has taken place (Time, Rank, diff. Avr. speed)	Only for road race
CR_IDX	Index based on whole list (with the ones who have not passed yet are indexed as well – after the ones who have finished, but before the IRMs. Sorted by the intermediate passed most recently and by order there (if none, then by start order)).	Always
CR_PASSIDX	Index based on only the ones who have finished or have an IRM	when it is available
CR_LASTFINISH	This attribute for the competitor who has just finished the split or the race.	If applies.
CR_INTERMEDIATE/CR_OFFICIAL	Use for show if the results are official. If the results are not official they should be in italics.	Road race: Always
ER_RESULTS /CR_PHOTO	It is an attribute for know if it is necessary made a photo for this competitor.	Road Race: At the end of the race. Only send for competitor who needs that.

5.1.3.6 Message sort

Please, follow the general definition.



5.1.4 Event's Medallists

5.1.4.1 Description

This message is the Event's Medallists message as described in the ODF Sport Messages Interface Document.

In the case of Cycling Road, the message has to be sent for all the competition events, as listed in the header values section.

5.1.4.2 Header Values

The DocumentCode attribute in the ODF header will be sent according for all the competition events to the ODF Common Codes document (header values sheet).

5.1.4.3 Trigger and Frequency

Please, follow the general definition.

5.1.4.4 Message Structure

Please, follow the general definition.

5.1.4.5 Message Values

Please, follow the general definition.

5.1.4.6 Message sort

Please, follow the general definition.



5.1.5 Official Communication

5.1.5.1 Description

This message is the Official Communication message as described in the ODF Sport Messages Interface Document.

5.1.5.2 Header Values

The DocumentCode attribute in the ODF header will be sent according to the ODF Common Codes document (header values sheet).

In case of Race Incidents send @DocumentSubcode with "RINCIDENT" and @DocumentSubcode always with "1".

5.1.5.3 Trigger and Frequency

- After each incident

5.1.5.4 Message Structure

The optional elements defined for this message in the ODF Sport Messages Interface Document that should be included in the case of Cycling Road are:

- JuryDecision (following the general rules for this element)
- RIncidents (following the general rules for this element and Send only for the race incidents)

5.1.5.5 Message Values

Please, follow the general definition.

5.1.5.6 Message sort

Please, follow the general definition.



5.1.6 Discipline/venue good morning

5.1.6.1 Description

This message is the Discipline/venue good morning message as described in the ODF Sport Messages Interface Document.

5.1.6.2 Header Values

The DocumentCode attribute in the ODF header will be sent according to the discipline/venue pairs as described in the ODF Common Codes document.

5.1.6.3 Trigger and Frequency

Please, follow the general definition.

5.1.6.4 Message Structure

Please, follow the general definition.

5.1.6.5 Message Values

Please, follow the general definition.

5.1.6.6 Message sort

Please, follow the general definition.



5.1.7 Discipline/venue good night

5.1.7.1 Description

This message is the Discipline/venue good night message as described in the ODF Sport Messages Interface Document.

5.1.7.2 Header Values

The DocumentCode attribute in the ODF header will be sent according to the discipline/venue pairs as described in the ODF Common Codes document.

5.1.7.3 Trigger and Frequency

Please, follow the general definition.

5.1.7.4 Message Structure

Please, follow the general definition.

5.1.7.5 Message Values

Please, follow the general definition.

5.1.7.6 Message sort

Please, follow the general definition.



5.1.8 Discipline Configuration

5.1.8.1 Description

This message is the Event unit configuration message as described in the ODF Sport Messages Interface Document.

5.1.8.2 Header Values

Please, follow the general definition.

5.1.8.3 Trigger and Frequency

Please, follow the general definition.

5.1.8.4 Message Structure

The optional elements defined for this message in the ODF Sport Messages Interface Document that should be included in the case of Cycling Road are:

- ExtendedConfigItem

5.1.8.5 Message Values

Send the attributes and codes according to the tables described in this section.

The following table lists the Discipline configuration optional attributes (defined in the ODF Sport Messages Interface Document) that are used in the case of Cycling Road, as well as the attributes that have an extended definition.

Element	Attribute	M/O	Value	Comments
Config	Gender	M	CC @Gender Or "0"	
	Event	M	CC @Event	

The following table describes in more detail the Competition ExtendedConfig element.

Element: ExtendedConfig						
Type	Code	ExtendedConfig Item Code	Pos	Value	Description	
EC_RACE (By event)	CR_RDISTANCE			Number	For @Type: Send proposed type	
					For @Code: Send proposed code	
					For @Pos: (see codes section)	
					For @Value: Send the total distance for the race in km.	
		CR_T_LAPS		N(2) 90		For @Type: Send proposed type
						For @Code: Send proposed code
						For @Pos: Do not send anything
		For @Value: Total Lap's numbers in the road race				
		CR_T_SECTION		N(1) 0		For @Type: Send proposed type
For @Code: Send proposed code						
For @Pos: Do not send anything						



Element: ExtendedConfig					
Type	Code	ExtendedConfig Item Code	Pos	Value	Description
					For @Value: Total PTP in the race
		CR_T_INTER		N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Total intermediate points in the race(not including the intermediate 0)
		CR_T_FFTP		N(1) 0	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Total PTP -Finish in the race Send if exist a PTP- Start/Finish
	CR_INTERMEDIATE		N(2) 90		For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Send the number that identifies the intermediate point, from 1 to n. Where n is when finish the race.
					For @Value: Do not send anything.
		CR_DISTANCE		N(3).N(1) 999.0	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: (see codes section)
					For @Value: Send distance in km.
		CR_IS_LAST		S(1)	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything.
					For @Value: Send "F". Only send for the last intermediate point (when finish the race).
	CR_LAP		N(2) 90		For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: The number that identifies the lap, from 1 to the total number of lap.
					For @Value: Do not send anything.
		CR_DISTANCE		N(3).N(1) 999.0	For @Type: Send proposed type
					For @Code: Send proposed code



Element: ExtendedConfig					
Type	Code	ExtendedConfig Item Code	Pos	Value	Description
					For @Pos: (see codes section)
					For @Value: Lap's distance in km.
		CR_START		N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the intermediate point when start the lap.
		CR_FINISH		N(2) 90 Or S(1)	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the intermediate point when finish the lap. For lap n, send "F", where n is the point in the race.
	CR_SECTION		N(1) 0		For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Send the number that identifies the PTP section.
					For @Value: Do not send anything.
		CR_DISTANCE		N(3).N(1) 999.0	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: (see codes section)
					For @Value: PTP's distance in km.
		CR_START		N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the intermediate point when start the PTP.
		CR_FINISH		N(2) 90 Or S(1)	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the intermediate point when finish the PTP. For lap n, send "F", where n is the point in the race.
EC_QUOTA	CC @Organisation			N(1)	For @Type:



Element: ExtendedConfig					
Type	Code	ExtendedConfig Item Code	Pos	Value	Description
				0	Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the quota per NOC for that event

For the table above, we have the following additional/summary information

Type /Code	Description	Expected
EC_RACE /CR_RDISTANCE	Race description(total race distance, total number of Laps, PTP finish, Section(PTP-Start) and intermediate points)	when it is available
EC_RACE /CR_INTERMEDIATE	<p>Are points in the race where taken results, from 0 to n. Where 0 is when start the race (at this point does not send results only to have a reference of where to start) and n is when finish the race. The PTP-Start/Finish are considerate an intermediate point.</p> <p>Example: If the race has: 1 PTP-Start+ 2 Lap + 1 PTP-Finish</p> <p>Race description: the description should be like bellow: _T_SECTION=1 _T_LAPS=2 _T_FPTP=1</p> <p>To know the distances _SECTION=1 @Value _LAP=1 @Value _LAP=2 @Value _LAP=3 @Value, for PTP-finish</p> <p>Results'Points-Road Race: We will need to know the times in all that points: _T_INTER=4 _INTERMEDIATE = 1,2,3 0 when start the race, but this will not be sent. 1 after the PTP-Start 2,3 after each lap 4 after the PTP-finish (at the end of the race), in this case send a "_IS_LAST" with "F".</p> <p>_SECTION =1, _START = 0, _FINISH = 1 (This is the PTP-Start) _LAP = 1, _START = 1, _FINISH = 2 _LAP = 2, _START = 2, _FINISH = 3 _LAP = 3, _START = 3, _FINISH = 4 (This is the PTP-Finish)</p> <p>Results'Points-Time Trial: We will need to know the times in differents points: _T_INTER=4 _INTERMEDIATE = 1,2,3 0 when start the race, but this will not be sent. 1 after the 1st pt 2 after the 2nd pt 3 after the 3rd pt 4 at the end of the race, in this case send a "_IS_LAST" with</p>	when it is available



Type /Code	Description	Expected
	<p>"F".</p> <p>_LAP = 1, _START = 0, _FINISH = 1 _LAP = 2, _START = 1, _FINISH = 2 _LAP = 3, _START = 2, _FINISH = 3 _LAP = 4, _START = 3, _FINISH = 4</p>	
EC_RACE /CR_LAP	<p>Are section between two intermediate points (not including the PTP), from 1 and n. Where n is the final point for that section. The lap 1 should be not include data from the PTP.</p> <p>Example – Road race: If don't exists PTP: The 1 lap start in 0 and finish in 1. If exist 1 PTP -start: The 1 lap start in 1 and finish in 2.</p> <p>Example – Time trial: The 1 lap starts in 0 and finish in 1.</p>	when it is available
CR_LAP/CR_START CR_LAP/CR_FINISH	<p>To know in which intermediate points start or finish that section.</p> <p>Example – Road Race: If the race has: 1 PTP-Start+ 2 Lap + 1 PTP-Finish The _LAP@pos=1 starts in the intermediate point "1" and finish in the "2". The _LAP@pos=2 starts in the intermediate point "2" and finish in the "3". The _LAP@pos=3 starts in the intermediate point "3" and finish in the "4".</p> <p>Example – Time trial: If the race has: 3 points for take the times The _LAP@pos=1 starts in the intermediate point "0" and finish in the "1". The _LAP@pos=2 starts in the intermediate point "1" and finish in the "2". The _LAP@pos=3 starts in the intermediate point "2" and finish in the "3".</p>	when it is available
EC_RACE /CR_SECTION	<p>Are sections for the PTP-Start in the race.</p> <p>Example: If the race has: 1 PTP-Start+ 2 Lap + 1 PTP-Finish _SECTION@pos=1</p>	when it is available
CR_SECTION /CR_START CR_SECTION /CR_FINISH	<p>To know in which intermediate points start or finish that section.</p> <p>Road Race - Example: If the race has: 1 PTP-Start+ 2 Lap + 1 PTP-Finish The _SECTION@pos=1 start in the intermediate point 0 and finish in 1.</p>	when it is available Only for Road Race
EC_QUOTA /CC@Organisation	Number of quotas per NOC by event	when it is available

5.1.8.6 Message sort

Please, follow the general definition.



5.1.9 Event Unit Weather Conditions

5.1.9.1 Description

This message is the Event Unit Weather Conditions message as described in the ODF Sport Messages Interface Document.

5.1.9.2 Header Values

The DocumentCode attribute in the ODF header will be sent according to the ODF Common Codes document (header values sheet).

5.1.9.3 Trigger and Frequency

Please, follow the general definition.

5.1.9.4 Message Structure

The optional elements defined for this message in the ODF Sport Messages Interface Document that should be included in the case of Cycling Road are:

- Competition /Weather /Conditions /Condition (following the general rules for this element)

5.1.9.5 Message Values

The following table lists the Event Unit Weather Conditions optional and/or extended attributes (defined in the ODF Sport Messages Interface Document), as well as the attributes that have an extended definition

Element	Attribute	M/O	Value	Comments
Conditions	Code	M	GL	GL for generically, because this information will only be measured once.
	Humidity	M	N(3) 990	Humidity in %
Competition /Weather /Conditions /Condition	Code	M	SKY	Weather condition type
	Value	M	CC @WeatherCondition	Codes that describe the weather
Competition /Weather /Conditions /Temperature	Code	M	AIR	Air
	Unit	M	CC @TemperatureUnit	Metric system unit for temperature
	Type	M	CC @TemperatureType	Type of @Code
	Value	M	N(2) 90	Temperature of the @Code

5.1.9.6 Message sort

Please, follow the general definition.



6 Real time

The following chapter describes the ODF-RT part of Cycling Road.

6.1 Real Time Applicable Messages

The next table is a full list of all ODF-RT messages and describes the list of messages used in Cycling Road the same way as it is done in the table of chapter 4.

Message Type	Message name	Message documented	Message used in this sport	Message extended in this document
DT_RT_GM	RT Discipline/Venue good morning	Sports	X	
DT_RT_GN	RT Discipline/venue good night	Sports	X	
DT_RT_KA	RT Discipline/venue keep alive	Sports	X	
DT_RT_RESULT	RT Event Unit Results	Sports	X	X
DT_RT_CUMULATIVE_RESULT	RT Cumulative Results	Sports		



6.1.1 RT Event Unit Results

6.1.1.1 Description

This message is the RT Event Unit Results message as described in the ODF Sport Messages Interface Document.

6.1.1.2 Header Values

The ODF header will be sent according to the ODF Common Codes document.

6.1.1.3 Trigger and Frequency

The following is the trigger for this message in ODF-RT:

- ResultStatus="LIVE_UPDATE"
 - T1: Trigger when status race changes.
 - T2: Trigger when an athlete passes by the intermediate point.
 - T3: Trigger when leader reach an intermediate point.
 - T4: Trigger during the race if the Status is required.
 - T5: Trigger throughout the race.
 - T6: Trigger after each competitor finishes.
- ResultStatus="LIVE_FULL"
 - This value should be suggested after further testing and sent in the DT_RT_GM message after further testing
 - Suggested to test frequency values around the average time used by the athlete to complete their participation in the course.

for the other ResultStatus, please, follow the general definition.

6.1.1.4 Message Structure

The optional elements defined for this message in the ODF Sport Messages Interface Document that should be included in the case of Cycling Road are:

- UnitInfo
- Competitor /Composition /Athlete /ExtendedResults /ExtendedResult

Please, follow the general considerations for all the different type of messages.

In the next section (message values), there is a more detailed definition.

6.1.1.5 Message Values

The following table describes in more detail the Result element.

Element	Attribute	M/O	Value	Comments	LIVE_UPDATE RT trigger expected
Result	Rank	O	String	Rank of the competitor in the corresponding event unit. This attribute is optional because the competitor could get an invalid rank mark.	Road race: T5(Only for those athletes who are at the same split as the leader), T1(if applies) Time trial: , T1(if applies), T6
	RankEqual	O	Y or N	Y in the case of equalled rank. N in the case of tie break.	



Element	Attribute	M/O	Value	Comments	LIVE_UPDATE RT trigger expected
	ResultType	O	CC @ResultType	Result type (see codes section)	Road race: T1, T4, T5 Time trial: T4, T6
	IRM	O	CC @IRM	IRM for the particular event unit Send just in the case @ResultType is IRM, or both time and IRM (see codes section)	T1, T4
	Result	O	Road Race: HH:MM:SS 99:90:00 Time trial: H:MM:SS.tt 99:90:00.00	Result for the particular event unit.	Road race: T6 Time trial: T6
	SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the particular event unit.	T2, T4, T5, T6

The following table describes in more detail the UnitInfo element in the case of Cycling Road.

Element: UnitInfo					
Type	Code	Extension Code	Pos	Value	Description
UI_LEADER	CR_CURRENT			N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the intermediate point was the current leader has most recently passed (Mass start)
	CR_ID			S(20) with no leading zeroes	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Send the Current Leader ID the intermediate (s)he has most recently passed (Mass start)
	CR_INTERMEDIATE			N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: The number that identifies the intermediate result point, from 1 to the total number (n) of intermediate result points. Where n is when finish the race.
					According to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message For @Value: Leader Time up to that point
CR_AVGSPEED				For @Type: Send proposed type	
				For @Code: Send proposed code	
				For @Pos: Do not send anything	
				For @Value: Leader Average Speed up to that point	
CR_LAVGSPEED				N(3).N(3)	For @Type:



Element: UnitInfo					
Type	Code	Extension Code	Pos	Value	Description
				990.000	Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Average Speed (last lap) km/h
	CR_LAP		N(2) 90	HH:MM:SS 99:90:00	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: The number that identifies the lap, from 1 to the total number (n) of laps.
					According to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message
					For @Value: Time for that lap
		CR_AVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Average Speed (from start) in that lap
	CR_SECTION		N(2) 90	HH:MM:SS 99:90:00	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: The number that identifies the section, from 1 to the total number of sections. It is section between each intermediate point.
					For @Value: Time for that section
		CR_AVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Leader Average Speed in that section Send a dash "-" is case of half laps

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
UI_LEADER /CR_CURRENT	Send the intermediate point where the current leader has most recently passed	when it is available
UI_LEADER /CR_INTERMEDIATE	Are points in the race, from 1 to n (finish). The @pos attribute should be according to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message	Road race: T3
CR_INTERMEDIATE/ CR_LAVGSPEED	Average speed from the time the leader at the first intermediate of a lap crosses this point	



	until the time the leader crosses the last intermediate point of the lap.	
UI_LEADER /CR_LAP	Section between two intermediates points. The @pos attribute should be according to the @pos of the EC_RACE /CR_INTERMEDIATE code at the DT_CONFIG message The @Value attribute is the Lap time.	Road race: T3
CR_LAP /CR_AVGSPEED	Average speed from the time competitor X crosses the first intermediate (competitor X may be in the lead or not) of a lap until the time competitor X (now the leader) crosses the last intermediate point of a lap.	
UI_LEADER /CR_SECTION	Section for the PTP	Road race: T3

The following table describes in more detail the Competitor /Composition /Athlete /ExtendedResults /ExtendedResult element.

Element: Competitor /Composition /Athlete /ExtendedResults /ExtendedResult					
Type	Code	Extension Code	Pos	Value	Description
ER_RESULTS	CR_STATUS			CC @RunStatus	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Race status for that athlete Only for Time trial
	CR_CURRENT			N(2) 90	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything
					For @Value: Intermediate point was the athlete has most recently passed If the competitor has an IRM: 1. In case the DNS or the athlete has an IRM before he crosses the first intermediate point: send 1. 2. In other cases, send the Intermediate point that he has crossed most recently plus 1.
	CR_INTERMEDIATE CR_LAP CR_SECTION		N(2) 90	Road Race: HH:MM:SS 99:90:00 Time trial: H:MM:SS.tt 99:90:00.00	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: The number that identifies lap/intermediate/sections, from 1 to the total number for that.
					For @Value: time after the Lap/intermediate/sections
		CR_RANK		String	For @Type: Send proposed type
					For @Code: Send proposed code
					For @Pos: Do not send anything



Element: Competitor /Composition /Athlete /ExtendedResults /ExtendedResult					
Type	Code	Extension Code	Pos	Value	Description
					For @Value: Rank up to that point
		CR_ERANK		Y or N	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Y in the case of equalled rank. N in the case of tie break.
		CR_DIFF		Road Race: +H:MM:SS +9:90:00 Or 0:00 for leader Time trial: +HH:MM:SS.tt +9:90:00.00O Or 0:00.00 for leader	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Time difference up to that point. Send only for athletes in the split of the leader.
		CR_AVGSPEED		N(3).N(3) 990.000	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Average Speed up to that point(time trial only)
		CR_IDX		N(3) 990	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Index based on whole list (with the ones who have not passed yet are indexed as well – after the ones who have finished, but before the IRMs. Sorted by the intermediate passed most recently, and by order there (if none, then by start order)). Overlapped (LAP) riders must be dropped to the bottom but above the DNF/DSQ/DNS riders. For tied athletes, the rider with the lowest bib number is listed first.
		CR_PASSIDX		N(3) 990	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Index based on only the ones who have finished or have an IRM
		CR_LASTFINISH		S(1)	For @Type: Send proposed type For @Code: Send proposed code For @Pos:



Element: Competitor /Composition /Athlete /ExtendedResults /ExtendedResult					
Type	Code	Extension Code	Pos	Value	Description
					Do not send anything
					For @Value: Send "Y" this attribute for the competitor who has just finished the split or the race Send "N" if in this moment the competitor has not finished the split or race. In any other case, send an empty value
		CR_OFFICIAL		S(1)	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: Send Y when the time becomes official Send N when the time is unofficial. Only for Intermediate points. (Road race only)
	CR_PHOTO			S(1)	For @Type: Send proposed type For @Code: Send proposed code For @Pos: Do not send anything For @Value: To know if the competitor's final result was decided by photo. Send Y for Evaluated Status Send P for Pending Status. Send N if Photo has been resolved

For the table above, we have the following additional/summary information:

Type /Code	Description	Expected
ER_RESULTS /CR_STATUS	For know the status of the athlete's race.	Time trial: Always
ER_RESULTS /CR_CURRENT	Send for the athlete who has just finished the intermediate point or the race. If the competitor has an IRM: 1. In case the DNS or the athlete has an IRM before he crosses the first intermediate point: send 1. 2. In other cases, send the Intermediate point that he has crossed most recently plus 1.	Always
ER_RESULTS /CR_INTERMEDIATE	Are points in the race where we have the competitor's results (time, rank, difference, avr, speed (only for time trial)).	when it is available
ER_RESULTS /CR_LAP	Section between two intermediate points	when it is available
CR_INTERMEDIATE /CR_RANK CR_INTERMEDIATE /CR_DIFF	Results in that intermediate point	Time trial: T5
CR_IDX	Index based on whole list (with the ones who have not passed yet are indexed as well – after the ones who have finished, but before the IRMs. Sorted by the intermediate passed most recently and by order there (if none, then by start order)).	Always
CR_PASSIDX	Index based on only the ones who have finished or have an IRM	when it is available
CR_LASTFINISH	This attribute for the competitor who has just finished the split or the race.	If applies
ER_RESULTS /CR_SECTION	Section between two points for PTP.	Road Race: when it is



Type /Code	Description	Expected
		available
CR_INTERMEDIATE/ CR_OFFICIAL	Use for show if the results are official. If the results are not official they should be in italics.	Road race: Always
ER_RESULTS /CR_PHOTO	It is an attribute for know if it is necessary made a photo for this competitor.	Road Race: At the end of the race. Only send for competitor who needs that.

6.1.1.6 Message sort

Please, follow the general definition.



DOCUMENT CONTROL

Version history

Version	Date	Comments
R2 v1.0	30 January 2009	Submitted for review version
R2 v2.0	27 February 2009	Comments after Interface meeting
R2 v3.0	27 March 2009	Document reformatted according to changes log
		Status changed to APP
R2 v4.0	22 May 2009	Changes after the WNPA meeting
R2 v4.1	19 June 2009	Add an attribute for Participant, change RT Event unit Result
R2 v4.2	17 July 2009	Some minor corrections and added the copyright
R2 v5.0	12 March 2010	Some minor corrections; Changes after ORIS and WNPA meeting
R2 v6.0	19 July 2010	Changes after the Pre Int Test and WNPA meeting
R2 v6.1	3 September 2010	Some issues
R2 v7.0	17 January 2011	IR022
R2 v8.0	2 September 2011	Defect 40236, 40776 & IR0447
R2 v9.0	10 February 2012	IR101,CR4913, CR5877, CR5943; Defect 55772
R2 v10.0	12 March 2012	Defect 64429, CR7292

File reference: ODF/INT029 R2 v10.0 APP (CR)



Change Log

Version	Status	Changes on version
R2 v1.0	SFR	<ul style="list-style-type: none">• First version
R2 v2.0	SFA	<ul style="list-style-type: none">• Add the messages DT_ORGANISATIONS• change the “message document” for DT_SCHEDULE_UPDATE, DT_PARTIC_ATHLETES_UPDATE, DT_PARTIC_OFFICIALS_UPDATE, DT_PARTIC_TEAMS_UPDATE, DT_PARTIC_HORSES_UPDATE to Central• Should be discussed for all sports DT_Participants/ DT_Teams: Entry Element shouldn't not start with [DD]_. The element should be starts with E_• Participants: change CR_SUBSTITUTE by E_SUBSTITUTE• change the Communique element from Number to Text.• Start_List: delete comments for SortOrder, add attribute BIB with the value “The athlete’s race number”, remove attribute Order• Event Unit Results/UnitInfo: delete UI_RACE_INCIDENTS element, CR_INCIDENTS should be a extension of CR_LAP and CR_Section, add CR_Section (could be used for PTP Section during the race)• Event Unit Results/UnitInfo: move CR_INTERMEDIATE and CR_LAP and CR_Section from Event Unit Results to Discipline Configuration, remove UI_Note, there is a new element for the Riders withdrawn from the race• Event Unit Results: remove CR_PTP, CR Section has the same elements like CR_INTERMEDIATE and CR_LAP- >□all 3 could be in 1 definition• Delete Federation Ranking• Discipline Configuration: delete EC_COURSE_MAP, replace CR_PTP_DISTANCE with CR_SECTION_DISTANCE, delete UC_ENTRY• RT Event Unit Results: UI_Result will be removed; the course description for RT and PIT will be defined in Discipline Configuration• RT Event Unit Results – Start: must be moved to UnitInfo except ER_RESULTS /CR_STATUS (can be deleted)• RT Event Unit Results – ExtendedResult: We need a status for Athlete: 1. not started; 2. started; 3. finished ;CR_SECTION can be part of the CR_INTERMEDIATE & CR_LAP definition ;change name of CR_CIS_ITALIC to CR_OFFICIAL• RT: delete the CM_MEDAL, will change the general message for that.
R2 v3.0	APP	<ul style="list-style-type: none">• Status changed to APP
R2 v4.0	APP	<ul style="list-style-type: none">• Changes after the WNPA meeting:<ul style="list-style-type: none">▪ Change “List of athletes by discipline” (DT_PARTIC_ATHLETES) by “List of participants by discipline” (DT_PARTIC), where this message is merging the messages list of athletes, list of officials and list of historical athletes.▪ Change “List of athletes by discipline update” (DT_PARTIC_ATHLETES_UPDATE) by “List of participants by discipline update” (DT_PARTIC_UPDATE), where this message is merging the messages list of athletes update and list of officials update.▪ Merge the messages “List of Teams” (DT_PARTIC_TEAMS) and “List of Historical teams” (DT_TEAMS_HISTORIC) in “List of Teams”.▪ Delete DT_ORGANISATIONS, DT_PARTIC_OFFICIALS, DT_PARTIC_OFFICIALS_UPDATE, DT_PARTIC_HISTORIC, DT_TEAM_HISTORIC.▪ Add a new message DT_HIST_REC_UPDATE, DT_WEATHER
R2 v4.1	APP	<ul style="list-style-type: none">• Participant: Add _UCIRANK• Event Unit Results: Change the @Value for _LASTFINISH
R2 v4.2	APP	<ul style="list-style-type: none">• Some minor corrections and added the copyright.• Delete “equestrian” from the description of DT_PARTIC_HORSES_UPDATE.• Discipline Configuration: delete the comments from Config element• Change CM_ by CR_• Removed CC @DistanceUnit. Because all send the same unit (km)• Results: Add a the element CR_INCID_DIST in the comments' table



Change Log

Version	Status	Changes on version
		<ul style="list-style-type: none">RT Result: Add the elements: CR_PASSIDX*, CR_LASTFINISH* in the comments' table



Change Log

Version	Status	Changes on version
R2 v5.0	APP	<ul style="list-style-type: none">• Participants: Add @MainFunctionId; Add @InternationalFederationId• General: Add a "N" for attributes who has "Y"• StartList: Add a _IRM for RT only for time trial• Results: @ResultType should be optional; @SorOrder must be mandatory; Merge RT Data in PiT.• Changes after the ORIS meeting:<ul style="list-style-type: none">▪ Codes: Add a new CC @IRM OTL; Add a new ResultType "RANK" because it is possible only know the rank and not the result; Add a CC @QualStatus; Add a CC @TemperatureUnit and CC @TemperatureType for Weather▪ Participants: Add E_Q_STATUS for the provisional Entry List; _UCIRANK should be removed because doesn't exist an official world rank (for time trial and road race).▪ Start List: Add _ENTRIES and _NOCS for statistics▪ Result: The intermediate report will be removed So remove all the references for that ;the Rank should be string; The communiqué number should be for the official results so add a @pos for _COMMUNIQUE more than one results (for final results and for race analysis); Removed the incidents; The results should be show the riders who just to finish, and the number for riders who are LAP, DNF,...; Add UI_ST for statistics; Add a flag _PHOTO To know if the competitor's final result was decided by photo; Add _AFTER to know the race distance completed so far; Change the time diff format▪ Communication: Add the Race incidents for that report.▪ Config: Add a _QUOTA for the provisional Entry List; _T_FFTP for the race description▪ Weather: new message▪ Update the triggers• Changes after the WNPA meeting :<ul style="list-style-type: none">▪ The Bib should be String
R2 v6.0	APP	<ul style="list-style-type: none">• General: Update the Y/N values; change the formats; change the formats; Change the E_Q_STATUS element by general EntryStatus attribute.• Changes after the WNPA meeting (IR003):<ul style="list-style-type: none">▪ Results: Add the attribute RankEqual or the element _ERANK when there are an attribute Rank to identify if this is equalled or not.• IR004:<ul style="list-style-type: none">▪ Results: Change the @pos by @Value in the _CURRENT element• Changes after the Pre Integration Test:<ul style="list-style-type: none">▪ Results: change for the official results for intermediate points, for the leader avr; Add a new value for photofinish;▪ Results: Removed the elements UI_ST /CR_ENTRIES and UI_ST /CR_NOCS▪ Results: Made a clarification for the _CURRENT element in the case of the competitor with IRM;
R2 v6.1	APP	<ul style="list-style-type: none">• Codes: remove CC @QualStatus
R2 v7.0	APP	<ul style="list-style-type: none">• Changes after the WNPA meeting (IR022):<ul style="list-style-type: none">▪ Start list/Results/Official communication/ Medallists of one event: Change the triggers and frequency as the revision of WNPA meeting▪ Codes: add a format column to Section 3 of the Data Dictionaries
R2 v8.0	APP	<ul style="list-style-type: none">• Defect 40236:<ul style="list-style-type: none">▪ <u>In Header Values:</u> Remove the sentence "Attribute @ResultStatus should always be either "LIVE_UPDATE" or "LIVE_FULL".", as this is already explained in the Sport Message Interface document.▪ <u>In Trigger and Frequencies:</u> Keep the part explaining the triggers for ResultStatus = "LIVE_UPDATE", and say that for the other ResultStatus we should follow the general definition.

**Change Log**

Version	Status	Changes on version
		<ul style="list-style-type: none"> ▪ <u>In Message Structure</u>: Remove part of the sentence “for both LIVE_UPDATE and LIVE_FULL messages” ▪ <u>In Message Values</u>: Remove the sentences “In the case of ResultStatus=”LIVE_FULL”, send <u>all</u> attributes and codes according to the tables described in this section. In the case of ResultStatus=”LIVE_UPDATE”, send <u>just the updated</u> attributes and codes according to the tables described in this section.”, as this is already explained in the Sport Message Interface document. • IR0447: Log changes in ODF documentation should be moved at the end • Defect 40776 : update the CR_LEADER/CR_INTERMEDIATE/ CR_LAVGSPEED and CR_LEADER/CR_LAP/ CR_AVGSPED
R2 v9.0	APP	<ul style="list-style-type: none"> • IR101: Add DT_SERIAL message in the PiT messages • CR4913: <ul style="list-style-type: none"> ▪ Result: The data for "Lap Time" should be the time for this lap (UI_LEADER / CR_LAP); • CR5877: <ul style="list-style-type: none"> ▪ Results: Update the time format (hh:mm:ss.tt) for the time trial events (CR_INTERMEDIATE/CR_DIFF , CR_LAP/CR_DIFF, CR_SECTION /CR_DIFF). • CR5943: (Defect 48253/47503): <ul style="list-style-type: none"> ▪ Start List: Add a _IRM for RT for all the events. • Defect 55772: Clarify description of following elements: CR_LASTFINISHED and CR_PHOTO for RT (Competitor /Composition /Athlete /ExtendedResults /ExtendedResult)
R2 v10.0	APP	<ul style="list-style-type: none"> • Defect 64429: Participants: Add an optional attribute @InternationalFederationId • CR7292: <ul style="list-style-type: none"> ▪ Codes: "REL - Relegated" should be removed from the list of Time trial event; clarification for IRM ▪ Pit Results: Use the UI_ST /CR_DNF only for riders who abandoned the race; add a new element (UI_ST /CR_DNF_T) for the total number of DNF riders. These include the Abandoned (UI_ST /CR_DNF) plus Lapped (UI_ST/CR_LAP) riders. ▪ Config: The course segment information should only be displayed if needed, so update the expected for EC_RACE /CR_RDISTANCE and EC_RACE /CR_LAP



This page has been intentionally left blank