

# OLYMPIC DATA FEED

## **ODF Archery Data Dictionary**

Tokyo 2020 - Games of the XXXII Olympiad

Technology and Information Department

© International Olympic Committee

ODF R-SOG-2020-ARC V1.0 SFR

1 Aug 2017

## License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.  
The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.
5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.

# 1 Introduction

## 1.1 This document

This document includes the ODF Archery Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for archery.

## 1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Archery Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the archery competition is run.

## 1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

## 1.4 2018 Youth Olympic Games

This document is to be applied for the 2018 Youth Olympic Games. All included concepts are applied.

## 1.5 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies

## 1.6 Related Documents

Document Title	Document Description
ODF General Principles Document	The document explains the environment and general principles for ODF.
ODF General Messages Interface Document	The document describes the ODF General Messages
ODF Common Codes	The document describes the ODF Common codes used across all ODF documents.
ODF Sport Codes	The document describes the ODF Sport codes used across all ODF documents
ODF Header Values	The document details the header values which show which RSCs are used in which messages.

## 2 Messages

### 2.1 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in archery.

- The column “Message type” indicates the DocumentType that identifies a message
- The column “Message name” is the message name identified by the message type
- The column “Message extended” indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it should follow the general definition rules.

Message Type	Message Name	Message extended
DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule / Competition schedule update	X
DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / List of participants by discipline update	X
DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of teams / List of teams update	X
DT_MEDALS	Medal standings	
DT_MEDALLISTS_DAY	Medallists of the day	
DT_GLOBAL_GM	Global good morning	
DT_GLOBAL_GN	Global good night	
DT_RESULT	Event Unit Start List and Results	X
DT_BRACKETS	Brackets	X
DT_STATS	Statistics	X
DT_RANKING	Event Final Ranking	X
DT_COMMUNICATION	Official Communication	
DT_CONFIG	Configuration	X
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_LOCAL_ON	Discipline/venue start transmission	
DT_KA	Keep Alive	

## 2.2 Messages

### 2.2.1 Competition schedule / Competition schedule update

#### 2.2.1.1 Description

The Competition schedule is a bulk message provided for one particular discipline. As a general rule, it contains the complete schedule information for all event units needed to run a competition and excludes event units for activities such as unofficial training and press conferences.

This message contains the competition timetable for a complete discipline as well as status for each competition unit and is updated from OVR via the schedule update message.

All event units in codes which have the 'schedule' flag set to 'Y' are included in schedule messages (and have status UNSCHEDULED or SCHEDULED).

The arrival of the competition schedule message resets all the previous schedule information for one particular discipline.

The StartList component of the message is only included in the case that the Unit Type is one of HATH, HCOUP, HNOC or HTEAM and at least one of the competitors are known.

The Composition component (i.e. listing athletes) is only included in the case that the Unit Type is one of HATH or HCOUP.

For reference the applicable unit types (from common codes) are:

HATH Individual Head to Head units (e.g. ARC, BDM, TEN etc)

HCOUP Pairs/Couples Head to Head units (e.g. BDM, TEN etc)

HNOC NOC Head to Head units (e.g. ARC)

HTEAM Teams Head to Head units (e.g. BKB, VBV, HOC etc)

Managing when start times are not known.

In some disciplines the start time of each unit is not known and the unit are managed by order rather than time.

In these disciplines usually only the time of the first unit (or first unit per location) is known and distributed. In this case all units should be sent with the same start time and those following units flagged as HideStartDate (and finish). To be able to correctly order these units then the Order attribute is used.

To ensure there are no incorrectly ordered units then the start time must not be updated to the actual start time (there is an actual start time field to cater for this).

If the discipline requires some text describing the order then StartText is used. Typical uses include 'Not before 17:00' or 'SUN 29 - 2nd match on CC' or 'Follows'.

Where HideStartDate='Y' is used then all start times for the units may be the same, usually the same as the

first unit in the session or location (which generally will not use HideStartDate='Y') but this is not mandatory and approximate start times may be used. The specific way this is managed in each sport is detailed in the specific sport data dictionary.

Advice for end users - how to sort event units and use DT\_SCHEDULE:

- When displaying the schedule users must use the following sort order to display as intended:

1. By day (or filter by day)
2. By location if applicable (in a small number of sports)
3. By Time (regardless if HideStartDate='Y')
4. By Order

- The Order is sent for all units where HideStartDate='Y' else only sent if a particular event order is expected.

Start with 1 each new session each day

- End users should display StartText if HideStartDate='Y'

Competition schedule update:

Competition schedule update is an update message. It is not a complete schedule information message, but only the schedule data being modified.

The arrival of this message updates the previous schedule information for one particular event unit, but does not notify any other change for the rest of the event units except for those contained in the message.

The key of the information updated is Unit @Code. Therefore, any new unit, deleted unit or updated unit will be identified by this attribute.

It has to be understood that if one DT\_SCHEDULE message arrives, then all previous DT\_SCHEDULE\_UPDATE messages should be discarded.

### 2.2.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC at discipline level	
DocumentType	DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule bulk / update
Version	1...V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Refer to the ODF header definition
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.1.3 Trigger and Frequency

The competition schedule will be sent as a bulk message (DocumentType='DT\_SCHEDULE') before the Games and then sent multiple times until a date to be confirmed after which only update messages will be sent (DocumentType='DT\_SCHEDULE\_UPDATE') by OVR. There is no automatic triggering and this (DT\_SCHEDULE) message must not be sent after the transfer of control to OVR.

The competition schedule update message should be triggered at any time there has been a competition schedule modification for any previously sent competition schedule bulk message or update message including the addition of start list details (H2H).

Generally start list details for H2H should be sent immediately when known and usually soon after the preceding unit changes to Official.

If any text descriptions change in a message (as opposed to the code) then this message is not resent to correct previous messages however the new data is to be used in future messages.

### 2.2.1.4 Message Values

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
SessionCode	M	S(5)	Format DDD00 where DDD is the discipline and 00 is the session number.
StartDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
EndDate	O	DateTime	End date. Example: 2006-02-26T10:00:00+01:00
Leadin	O	m:ss	Amount of time from session start to first scheduled unit.
Venue	M	CC @VenueCode	Venue where the session takes place
VenueName	M	S(25)	Venue name
ModificationIndicator	O	S(1)	Attribute is mandatory in the DT_SCHEDULE_UPDATE message. N = New or U = Update.
SessionStatus	M	CC @ScheduleStatus	nly use CANCELLED if applicable. All other sessions are assumed to be scheduled. There is no change to running or finished.
SessionType	O	CC @SessionType	Session Type of the session

Element: Competition /Session /SessionName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Language of the Session Description
Value	O	S(40)	Name of the session. (if no other name then is session code)

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Code	M	Full RSC for the unit	
PhaseType	M	Phase type for the unit	
UnitNum	O	S(6)	Match / Game / Bout / Race Number or similar
ScheduleStatus	M	CC @ScheduleStatus	Unit Status
StartDate	O	DateTime	Start date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED. For other statuses the StartDate is expected otherwise ordering is display is incorrect (including CANCELLED and POSTPONED.)  This is the scheduled Start date and time and will not be updated when an event unit starts (updated only with RESCHEDULED status)  Where HideStartDate='Y' then this should be filled with the session start time or the start time of a group of units for all similar units and Order used for sorting.  Example: 2006-02-26T10:00:00+01:00



Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
HideStartDate	O	S(1)	<p>Send 'Y' if StartDate (scheduled start time) should not be displayed. It may be an estimate or 'fake' time. Do not send if StartDate (scheduled start time) is to be displayed.</p> <p>Start times of some units depend on the finalisation of previous event units and therefore there is no fixed start time in these cases this field is set to 'Y'.</p> <p>When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed.</p>
EndDate	O	DateTime	<p>End date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED, POSTPONED or CANCELLED.</p> <p>Example: 2006-02-26T10:00:00+01:00</p>
HideEndDate	O	S(1)	<p>Send 'Y' if EndDate scheduled end time is not to be displayed.</p> <p>Some event units have a scheduled end time well bounded, however, some event units in some circumstances have a scheduled end time not quite variable (example, some press conferences or tennis matches, etc.) in these cases this field is set to 'Y' and should not be displayed.</p>
ActualStartDate	O	DateTime	<p>This attribute is expected once the event unit has started. Example: 2006-02-26T10:03:22+01:00</p>
ActualEndDate	O	DateTime	<p>This attribute is expected once the event unit has finished. Example: 2006-02-26T12:43:51+01:00</p>
Order	O	Numeric ###0	<p>Order of the units when displayed. This field is considered in two situations:</p> <ol style="list-style-type: none"> <li>1. If HideStartDate = 'Y' then send at least for all Units in an affected session though it is suggested to be sent for all units in a discipline where the concept is used in the discipline.</li> <li>2. If some units start at the same time and a particular order of the units is expected.</li> </ol> <p>It is generally recommended to start at 1 in each session each day though may be ordered independently by location starting at 1 for each location in each session (where the schedule is ordered by location) or using other numbers to ensure the order of two using starting at the same time are displayed in the appropriate order.</p>

<b>Element: Competition /Unit (0,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Medal	O	SC @UnitMedalType	Gold medal event unit or bronze medal event unit. Do not send if not a medal event unit
Venue	M	CC @VenueCode	VVenue where the unit takes place Use TBD if the Venue is not known yet (CC).
Location	M	CC @Location	Location where the unit takes place Use TBD if the Location is not known yet (CC) or a generic code for the discipline.
SessionCode	O	S(5)	Code of the session which contains this event unit. Usually in the format DDD00 where DDD is the discipline and 00 is the session number within the discipline. For example ATH02 for the second session in Athletics.
ModificationIndicator	O	N, U	Attribute is mandatory in the DT_SCHEDULE_UPDATE message only  N-New event unit U-Update event unit If ModificationIndicator='N', then include new event unit. It will be rarely used as most added units were available in "UNSCHEDULED" status.  If ModificationIndicator="U", then update the event unit.

<b>Element: Competition /Unit /StartText (0,N)</b>			
<b>This element is only used for Competition Schedules when HideStartDate is 'Y'. In this case, English Language is mandatory.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Language	M	CC @Language	Code Language of the @Value
Value	M	S(20)	Text to be displayed in the case that StartDate is not to be displayed (e.g. "After M.1" or "Followed by") Using a code set or fixed text will also be directly displayed and allow end user translation.

<b>Element: Competition /Unit /ItemName (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Language	M	CC @Language	Code Language of the @Value
Value	M	S(40)	Item Name / Unit Description.  For competition units show the short unit description from common codes which matches the RSC.

Element: Competition /Unit /VenueDescription (1,1)			
Attribute	M/O	Value	Description
VenueName	M	S(25)	Venue name in first language. This is the CC value from unit/venue
LocationName	M	S(30)	Location name in first language. This is the CC value from unit/location.

Element: Competition /Unit /StartList /Start (1,N)			
Attribute	M/O	Value	Description
StartOrder	O	Numeric	Competitor's start order
SortOrder	M	Numeric	Used to sort competitors in an event unit (for example, if there is no StartOrder). It is mainly used for display purposes.

Element: Competition /Unit /StartList /Start /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes, TBD or NOCOMP.	Competitor's ID, TBD in case that the competitor is not known at this time AND the other competitor is known. NOCOMP is sent when there is no competitor (and will not come later)
Type	M	T,A	T for team A for athlete
Organisation	O	CC @Organisation	Should be sent when known

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete (1,N)			
In case of the Competitor @Code='TBD' this element should not be sent.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete in the event unit.
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case). Send if not null.
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth.
IFId	O	S(16)	Athlete IF number, send if available, only for the current discipline.

### 2.2.1.5 Message Sort

The message is sorted by Unit@StartDate then by Unit@Order then Unit@Code.

In case of event unit with no Unit@StartDate defined (example, they are in an event unit status such as UNSCHEDULED), they will be listed at the end in Unit@Code order.

## 2.2.2 List of participants by discipline / List of participants by discipline update

### 2.2.2.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

This message includes historical athletes that do not participate in the current competition. Historical athletes will not be registered to any event.

It is important to note that all the sport messages that make references to athletes (start list, event unit results, etc.) will always match the athlete ID with the athlete ID in this message. The historical athletes will be used to match historical athlete information as it appears in the records message when sending the previous record information and this previous record was an historical record not being broken in the current competition.

List of participants by discipline (DT\_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message can include a list of current athletes, officials, coaches, guides, technical officials, Reserves and historical athletes regardless of status.

List of participants by discipline update (DT\_PARTIC\_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

### 2.2.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC. Discipline level	RSC at discipline level
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	List of participants by discipline message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.

Attribute	Value	Comment
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.2.3 Trigger and Frequency

The DT\_PARTIC message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT\_PARTIC\_UPDATE messages are sent.

The DT\_PARTIC\_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.

## 2.2.2.4 Message Values

Element: Participant (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	<p>Participant's ID.</p> <p>It identifies an athlete or an official and the holding participant's valid information for one particular period of time.</p> <p>It is used to link other messages to the participant's information.</p> <p>Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc.</p> <p>When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.</p>
Parent	M	S(20) with no leading zeroes	<p>Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent.</p> <p>The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.</p> <p>The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".</p>
Status	O	CC @ParticStatus	<p>Participant's accreditation status this attribute is Mandatory in the case of @Current="true" and it is optional in the case that @Current="false".</p> <p>To delete a participant, a specific value of the Status attribute is used.</p>
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)

Element: Participant (1,N)			
Attribute	M/O	Value	Description
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
LocalFamilyName	O	S(25)	Family name in the local language in the appropriate case for the local language (usually mixed case) Not for use in Rio 2016
LocalGivenName	O	S(25)	Given name in the local language in the appropriate case for the local language (usually mixed case). Not for use in Rio 2016
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth. This information may not be known at the very beginning, but it will be completed for all participants after successive updates
Height	O	S(3)	Height in centimetres. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
Weight	O	S(3)	Weight in kilograms. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC @Country	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC @Country	Country ID of Residence
Nationality	O	CC @Country	Participant's nationality.  Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC @ResultsFunction	Main function  In the Case of Current="true" this attribute is Mandatory.
Current	M	boolean	It defines if a participant is participating in the games (true) or is a Historical participant (false).
OlympicSolidarity	O	S(1)	'Y' or 'N' Flag to indicating if the participant participates in the Olympic Scholarship program.



<b>Element: Participant (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
ModificationIndicator	M	S(1)	<p>'N' or 'U' Attribute is mandatory in the DT_PARTIC_UPDATE message only</p> <p>N-New participant (in the case that this information comes as a late entry) U-Update participant</p> <p>If ModificationIndicator='N', then include new participant to the previous bulk-loaded list of participants</p> <p>If ModificationIndicator='U', then update the participant to the previous bulk-loaded list of participants</p> <p>To delete a participant, a specific value of the Status attribute is used.</p>

<b>Element: Participant /Discipline (1,1)</b>			
<p>All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.</p>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	CC @Discipline	It is the discipline code used to fill the OdfBody @DocumentCode attribute. (full RSC)
IFld	O	S(16)	Competitor's federation number for the corresponding discipline

<b>Element: Participant /Discipline /RegisteredEvent (0,N)</b>			
<p>All accredited athletes will be assigned to one or more events. There is one exception: in some sports, substitutes may be accredited without any associated event. Historical athletes are not registered to any event.</p>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Event	M	CC @Event	Full RSC of the event
Bib	O	S(4)	<p>Bib number (for current athletes only)</p> <p>Only included in update messages.</p>

<b>Element: Participant /Discipline /RegisteredEvent /EventEntry (0,N)</b>				
<b>Send if there are specific athlete's event entries.</b>				
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>	
ENTRY	HAND	N/A	Element Expected: If available (this information can be sent in both messages)	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	SC @Hand	Send the handedness code
ENTRY	QUAL_CITY	N/A	Element Expected: If available (this information can be sent in both messages)	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	S(25)	Send the location MQS (Minimum Qualification Standard)
ENTRY	QUAL_COUNTRY	N/A	Element Expected: If available (this information can be sent in both messages)	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	CC @Country	Send the location MQS (Minimum Qualification Standard) Country code
ENTRY	QUAL_DATE	N/A	Element Expected: If available (this information can be sent in both messages)	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	YYYY-MM-DD	Send the date when the MQS (Minimum Qualification Standard) was met
ENTRY	QUAL_SCORE	N/A	Element Expected: If available (this information can be sent in both messages)	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric ###0	Send the MQS (Minimum Qualification Standard) score
ENTRY	RANK_WLD	N/A	Element Expected: If available (this information can be sent in both messages)	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	S(3)	Send the athlete's World Archery Ranking

Element: Participant /OfficialFunction (0,N)			
Send if the official has optional functions. Do not send, otherwise.			
Attribute	M/O	Value	Description
FunctionId	M	CC @ResultsFunction	Additional officials' function code

### 2.2.2.5 Message Sort

The message is sorted by Participant @Code

## 2.2.3 List of teams / List of teams update

### 2.2.3.1 Description

DT\_PARTIC\_TEAMS contains the list of teams related to the current competition.

List of teams (DT\_PARTIC\_TEAMS) is a bulk message by discipline. The list is always complete. The arrival of this message resets all the previous participant teams' information for that discipline. It is assumed that all teams appearing in this list are valid, in the meaning that they are participating or they could participate in one event.

A historical team is defined as a group of athletes (team members) competing in the past in a competition event for an organisation. The historical team members appearing in this message will be listed in the list of historical athletes' messages. The list of historical teams just associates historical team members with the corresponding historical teams. Historical teams will not be registered to any event.

List of teams update (DT\_PARTIC\_TEAMS\_UPDATE) is an update message. It is not a complete list of teams' information message. It only contains the data of a team being modified.

### 2.2.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	RSC at the discipline level
DocumentType	DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of participant teams message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.3.3 Trigger and Frequency

The DT\_PARTIC\_TEAMS message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT\_PARTIC\_TEAMS\_UPDATE messages are sent.

The DT\_PARTIC\_TEAMS\_UPDATE message is triggered when there is a modification in the data for any team after the transfer of control to OVR.

### 2.2.3.4 Message Values

Element: Team (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Team's ID When the Team is an historical one, then this ID starts with "T".
Organisation	M	CC @Organisation	Team organisation's ID
Number	O	Numeric #0	Team's number. If there is not more than one team for one organisation participating in one event, it is 1. Otherwise, it will be incremental, 1 for the first organisation's team, 2 for the second organisation's team, etc. Required in the case of current teams.
Name	O	S(73)	Team's name.
TVTeamName	O	S(21)	TV Team Name
Gender	M	CC @DisciplineGender	Discipline Gender Code of the Team Char(1)
Current	M	boolean	It defines if a team is participating in the games (true) or it is a Historical team (false)
ModificationIndicator	M	N, U, D	Attribute is mandatory in the DT_PARTIC_TEAMS_UPDATE message only N-New team (in the case that this information comes as a late entry) U-Update team D-Delete team If ModificationIndicator='N', then include new team to the previous bulk-loaded list of teams If ModificationIndicator='U', then update the team to the previous bulk-loaded list of teams If ModificationIndicator='D', then delete the team to the previous bulk-loaded list of teams

Element: Team /Composition /Athlete (0,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID of the listed team's member. Therefore, he/she makes part of the team's composition.
Order	O	Numeric	Team member order

<b>Element: Team /TeamOfficials /Official (1,N)</b>			
<b>Send if there are specific officials for the team. Does not apply to historical teams.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	S(20) with no leading zeroes	Official's ID of the listed team's official. Therefore, he/she makes part of the team's officials.
Function	M	CC @ResultsFunction	Official's function for the team.

<b>Element: Team /Discipline (0,1)</b>			
<b>Discipline is expected unless ModificationIndicator="D"</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	CC @Discipline	Full RSC of the discipline
IFld	O	S(16)	Federation number for the corresponding discipline (include if the discipline assigns international federation codes to teams)

<b>Element: Team /Discipline /RegisteredEvent (0,1)</b>			
<b>Each current team is assigned to one event. Historical teams will not be registered to any event.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Event	M	CC @Event	Full RSC of the event

<b>Element: Team /Discipline /RegisteredEvent /EventEntry (0,N)</b>			
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>
ENTRY	RANK_WLD	N/A	Element Expected: When available
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Value	M	S(3)	Send the team's World Archery Ranking

### 2.2.3.5 Message Sort

The message is sorted by Team @Code.

## 2.2.4 Event Unit Start List and Results

### 2.2.4.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports. The definition includes as much generic information as possible due to the fact that each discipline and event has its own format for the results information (example: score of a match, time in a race, distance in a throw...).

This is always a full message and all applicable elements and attributes are always sent.

### 2.2.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	Not used	Not used
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	It indicates whether the result is official or unofficial (or intermediate etc). START_LIST OFFICIAL LIVE (used during the competition when nothing else applies). UNCONFIRMED (used after the competition is completed and before either UNOFFICIAL or OFFICIAL. It may be sent multiple times if modifications are required and the status has not changed)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.



Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.4.3 Trigger and Frequency

This message is sent with ResultStatus 'START\_LIST' as soon as the expected information is available and any changes to the information. Possible information is:

- As soon as each competitor is known and any changes in start list data (START\_LIST)

This message is then sent with ResultStatus 'LIVE' as soon as the unit starts and continues to be triggered on all updates. The message is also sent with ResultStatus 'UNCONFIRMED' when the competition finishes then followed by UNOFFICIAL and OFFICIAL as appropriate.

Trigger also after any change.

### 2.2.4.4 Message Values

Element: ExtendedInfos /UnitDateTime (0,1)			
Attribute	M/O	Value	Description
StartDate	M	DateTime	Actual start date-time. Do not include until unit starts.

<b>Element: ExtendedInfos /ExtendedInfo (0,N)</b>			
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>
DISPLAY	CURRENT	N/A	Element Expected: Sent for individual events.
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	S(20)
			Send the id of the current athlete shooting. Send after the result of the previous competitor is received. Do not send when the result of the last shoot in the match is received.
UI	ARROW_NUM	N/A	Element Expected: Always, if available
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric #0
			Total number of arrows in the unit (not considering shoot-off)
UI	ARROW_SET	N/A	Element Expected: Always, if applies (after ranking round)
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	O	Numeric #0
			Send the total number of the arrows to be shoot by each athlete(in the individual event)/team(in the team event)
<b>Sub Element: ExtendedInfos /ExtendedInfo /Extension</b>			
<b>Expected: Always, if applies (after ranking round)</b>			
	<b>Attribute</b>	<b>Value</b>	<b>Description</b>
	Code	ARROW_ID	
	Pos	Numeric #0	Send the arrow number
	Value	Numeric #0	Send the number of the set to which belongs

<b>Element: ExtendedInfos /ExtendedInfo (0,N)</b>				
Type	Code	Pos	Description	
UI	ARROW_SETTB	N/A	Element Expected: Always, if applies (after ranking round) Sent every time a new shoot off set is decided in the team events  Sent every time new arrows are decided for the individual shoot-off set.	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	O	Numeric #0	Send the total number of the shoot off sets.
<b>Sub Element: ExtendedInfos /ExtendedInfo /Extension</b> <b>Expected: Always, if applies (after ranking round)</b> <b>Sent every time a new shoot off set is decided in the team events</b> <b>Sent every time new arrows are decided for the individual shoot-off set.</b>				
	<b>Attribute</b>	<b>Value</b>	<b>Description</b>	
	Code	ARROW_ID		
	Pos	Numeric #0	Send the arrow number	
	Value	Numeric #0	Send the number of the set to which belongs.	
UI	CURRENT_SETTB	N/A	Element Expected: Always, if applies (after ranking round) Sent every time a new shoot off set is decided in the team events  Sent every time new arrows are decided for the individual shoot-off set.	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric #0	The number of the last set of Tie-Break used for the final score. Requested in both individual and team events.

<b>Element: ExtendedInfos /ExtendedInfo (0,N)</b>			
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>
UI	SECTOR	Numeric 0	Pos Description: Sector number Element Expected: Always in Ranking Round
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Value	O	String	Sector description in case of ranking round (e.g., 1st Half)
<b>Sub Element: ExtendedInfos /ExtendedInfo /Extension Expected: Always in Ranking Round</b>			
<b>Attribute</b>	<b>Value</b>	<b>Description</b>	
Code	ARROW_NUM		
Pos	N/A	N/A	
Value	Numeric #0	Send the number of arrows in the sector.	
UI	SET	N/A	Element Expected: Always, if applies (after ranking round)
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Value	M	Numeric #0	Send the total number of sets in the match
<b>Sub Element: ExtendedInfos /ExtendedInfo /Extension Expected: Always, if applies (after ranking round)</b>			
<b>Attribute</b>	<b>Value</b>	<b>Description</b>	
Code	ARROW_NUM		
Pos	Numeric #0	Send the set number	
Value	Numeric #0	Send the number of arrows to be shot by each athlete in the set.	

**Sample (individual)**

```

....
<ExtendedInfos>
  <UnitDateTime StartDate="2012-07-28T12:00:00+01:00" />
  <ExtendedInfo Type="UI" Code="UNIT_NUM" Value="10" />
  <ExtendedInfo Type="UI" Code="ARROW_NUM" Value="15" />
  <ExtendedInfo Type="UI" Code="SET" Value="5" >
    <Extension Code="ARROW_NUM" Pos="1" Value="3" />
    <Extension Code="ARROW_NUM" Pos="2" Value="3" />
    <Extension Code="ARROW_NUM" Pos="3" Value="3" />
    <Extension Code="ARROW_NUM" Pos="4" Value="3" />
    <Extension Code="ARROW_NUM" Pos="5" Value="3" />
  </ExtendedInfo>
  <ExtendedInfo Type="UI" Code="ARROW_SET" Value="15" >
    <Extension Code="ARROW_ID" Pos="1" Value="1" />
    <Extension Code="ARROW_ID" Pos="2" Value="1" />
    <Extension Code="ARROW_ID" Pos="3" Value="1" />
    <Extension Code="ARROW_ID" Pos="4" Value="2" />
    <Extension Code="ARROW_ID" Pos="5" Value="2" />
  ...
  <Extension Code="ARROW_ID" Pos="14" Value="5" />
  <Extension Code="ARROW_ID" Pos="15" Value="5" />
  </ExtendedInfo> (if after 3 shoot-off arrows the tie is still on)
  <ExtendedInfo Type="UI" Code="ARROW_SETTB" Value="6" >
    <Extension Code="ARROW_ID" Pos="1" Value="1" />
    <Extension Code="ARROW_ID" Pos="2" Value="2" />
    <Extension Code="ARROW_ID" Pos="3" Value="3" />
    <Extension Code="ARROW_ID" Pos="4" Value="4" />
    <Extension Code="ARROW_ID" Pos="5" Value="5" />
    <Extension Code="ARROW_ID" Pos="6" Value="6" />
  </ExtendedInfo>
  <ExtendedInfo Type="UI" Code="CURRENT_SETTB" Value="6" />
....

```

**Element: ExtendedInfos /SportDescription (0,1)**

Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes
Gender	M	CC @DisciplineGender	Gender code for the event unit
SubEventName	M	S(40)	EventUnit short name (not code) from Common Codes
UnitNum	O	S(6)	Match number

<b>Element: ExtendedInfos /VenueDescription (0,1)</b>			
<b>Venue Names in Text.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location short name (not code) from Common Codes

<b>Element: Result (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Rank	O	Text	Rank for the competitor in the event unit. To be send only when the result type is not IRM To be sent also for the DSQ (not doping)
RankEqual	O	S(1)	Send Y if the rank is equaled, else do not send.
Result	O	Numeric ###0	The result of the competitor in the event unit. Match score (set points) or Total points in the Ranking Round
IRM	O	SC @IRM	The invalid rank mark, in case it is assigned. Send just if ResultType is equal to IRM or IRM_SETS
WLT	O	SC @WLT	The code whether a competitor won, lost the match.
SortOrder	M	Numeric	Used to sort all the results of an event unit. According to the sport rules. Before the start of any event unit this will be the same as the StartSortOrder and is used as the primary sort except in the case where a Rank is available (from earlier event units) and in this case the SortOrder will consider Rank in the same way as if the competition had already started.  During the event unit any sort order change from the initial start list order for any competitor will be provided in this attribute regardless the competitor is ranked or not.
StartOrder	O	Numeric	Competitor's start order.
StartSortOrder	M	Numeric	Used to sort all start list competitors in an event unit.
ResultType	O	SC @ResultType	Type of the @Result attribute. Result type, either POINTS, IRM or SETS or IRM_SETS

<b>Element: Result /ExtendedResults /ExtendedResult (1,N)</b>			
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>
ER	ARROW	Numeric #0	Pos Description: Arrow number Element Expected: If available in team events.
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric #0 (score) or 'X' (inner ten)
	ValueType	O	SC @ResultType ValueType should be used to describe the type of data @Value
	Speed	O	Numeric ##0 Speed at this ExtendedResult. Send the speed of the arrow in km/h. Format.
	Unchecked	O	Y Send Y where the result @Value has not been appropriately validated (sport specific) else do not send.  Send "Y" if the arrow score is unsure. (Remove when sure)
ER	ARROW_TOT	N/A	Element Expected: Only after Ranking Round
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric ##0 Send the match cumulative score of the arrows (not including Shoot-Off)
ER	SET	Numeric 0	Pos Description: Set number Element Expected: Only after Ranking Round
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	O	Numeric 0 Score for this set (set points)
<b>Sub Element: Result /ExtendedResults /ExtendedResult /Extension</b>			
<b>Expected: Just for teams after Ranking Round</b>			
	<b>Attribute</b>	<b>Value</b>	<b>Description</b>
	Code	ARROW_TOT	
	Pos	N/A	N/A
	Value	Numeric ##0	Send the set cumulative score of the arrows

Element: Result /ExtendedResults /ExtendedResult (1,N)				
Type	Code	Pos	Description	
ER	TB_ARROW	Numeric #0	Pos Description: Arrow number  Element Expected: Only if applicable after Ranking Round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	
	Value	O	Numeric #0 (score) or 'X' (inner ten)	Arrow score for the tie-break shoot-off
	ValueType	O	SC @ResultType	ValueType should be used to describe the type of data @Value
	Speed	O	Numeric ##0	Speed at this ExtendedResult Send the speed of the arrow in km/h.
	Unchecked	O	S(1)	Send Y where the result @Value has not been appropriately validated else do not send.  Send "Y" if the arrow score is unsure. (Remove when sure)
<b>Sub Element: Result /ExtendedResults /ExtendedResult /Extension</b>				
<b>Expected: Send if equal score</b>				
<b>Attribute</b>	<b>Value</b>	<b>Description</b>		
Code	CLOSEST			
Pos	N/A	N/A		
Value	S(1)	Closest to centre. Send Y in case of equal score and this is the closet arrow		
ER	TEN_NUM	N/A	Element Expected: If applicable	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	
	Value	M	Numeric #0	
			Send the number of 10's for the competitor	
ER	TIE_BREAK	Numeric 0	Pos Description: Send the tie-break shoot-off series of arrows number (1 for 1st arrow/series of arrows, 2 for 2nd arrow/series of arrows, 3...).	
			Element Expected: If tie-break after Ranking Round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	
	Value	O	Numeric #0	
	ValueType	O	SC @ResultType	
			ValueType should be used to describe the type of data @Value	



Element: Result /ExtendedResults /ExtendedResult (1,N)				
Type	Code	Pos	Description	
<b>Sub Element: Result /ExtendedResults /ExtendedResult /Extension</b>				
<b>Expected: If applicable after Ranking Round for teams competition</b>				
	<b>Attribute</b>	<b>Value</b>	<b>Description</b>	
	Code	TB_SET		
	Pos	N/A	N/A	
	Value	Numeric #0	Send the set points for the tie-break.	
ER		TOSS	N/A	Element Expected: If applicable in the Ranking Round
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	S(1)	Send Y if, after a tie, disk toss is used to break the tie
ER		XS_NUM	N/A	Element Expected: If data exists
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric #0	Send the number of X's for the competitor

<b>Element: Result /ExtendedResults /ExtendedResult (1,N)</b>			
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>
ER	SECTOR	Numeric 0	Pos Description: Sector number Element Expected: Only for individual message for ranking round
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Value	O	Numeric ##0	Score for this sector
ValueType	O	SC @ResultType	ValueType should be used to describe the type of data @Value
Rank	O	Text	Rank of the competitor for this specific ExtendedResult. Send the rank of the competitor in this sector.
RankEqual	O	S(1)	Send Y where Rank at this specific ExtendResult is equalled else not sent.
<b>Sub Element: Result / ExtendedResults /ExtendedResult /Extension Expected: Only for ranking round</b>			
<b>Attribute</b>	<b>Value</b>	<b>Description</b>	
Code	TEN_NUM		
Pos	N/A	N/A	
Value	Numeric #0	Number of 10's within this sector	
<b>Sub Element: Result / ExtendedResults /ExtendedResult /Extension Expected: Only for ranking round</b>			
<b>Attribute</b>	<b>Value</b>	<b>Description</b>	
Code	XS_NUM		
Pos	N/A	N/A	
Value	Numeric #0	Number of X's within this sector	

**Sample**

```
<Result ResultType="SETS" Result="4" WLT="L" SortOrder="1" StartOrder="1" StartSortOrder="1">
  <ExtendedResults>
    <ExtendedResult Type="ER" Code="TEN_NUM" Value="7" />
    <ExtendedResult Type="ER" Code="XS_NUM" Value="4" />
    <ExtendedResult Type="ER" Code="ARROW_TOT" Value="216" />
    <ExtendedResult Type="ER" Code="SET" Pos="1" Value="2" >
      <Extension Code="ARROW_TOT" Value="55" />
    </ExtendedResult>
    <ExtendedResult Type="ER" Code="SET" Pos="2" Value="0" >
      <Extension Code="ARROW_TOT" Value="54" />
    </ExtendedResult>
    <ExtendedResult Type="ER" Code="SET" Pos="3" Value="2" >
      <Extension Code="ARROW_TOT" Value="57" />
    </ExtendedResult>
    <ExtendedResult Type="ER" Code="SET" Pos="4" Value="0" >
      <Extension Code="ARROW_TOT" Value="50" />
    </ExtendedResult>
    <ExtendedResult Type="ER" Code="ARROW" Pos="1" Value="10" ValueType="SETS" Speed="208" />
    <ExtendedResult Type="ER" Code="ARROW" Pos="2" Value="8" ValueType="SETS" Speed="211" />
    <ExtendedResult Type="ER" Code="ARROW" Pos="3" Value="9" ValueType="SETS" Speed="213" />
    <ExtendedResult Type="ER" Code="ARROW" Pos="4" Value="X" ValueType="SETS" Speed="212" />
    ...
    <ExtendedResult Type="ER" Code="ARROW" Pos="21" Value="10" ValueType="SETS" Speed="208" />
    <ExtendedResult Type="ER" Code="ARROW" Pos="22" Value="8" ValueType="SETS" Speed="211" />
    <ExtendedResult Type="ER" Code="ARROW" Pos="23" Value="9" ValueType="SETS" Speed="213" />
    <ExtendedResult Type="ER" Code="ARROW" Pos="24" Value="X" ValueType="SETS" Unchecked="Y"
Speed="212" />
    ...
  </ExtendedResults>
```

**Element: Result /RecordIndicators /RecordIndicator (1,N)**

**Result's record indicator.**

Attribute	M/O	Value	Description
Order	M	Numeric	The hierarchy (priority) for types of record from 1 to n. Can use the Order column from CC @RecordType for reference).
Code	M	CC @RecordCode	Code which describes the record broken.
RecordType	M	CC @RecordType	Code which specifies the level at which the record is broken. (e.g. "OR").
Equalled	O	S(1)	Send "Y" in the case that the record has been equalled else do not send.

<b>Element: Result /Competitor (1,1)</b>			
<b>Competitor related to the result of one event unit.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	S(20) with no leading zeroes or TBD or NOCOMP	Competitor's ID or TBD in case that the competitor is unknown at this time but will be available  NOCOMP is sent when there is no competitor (and will not come later)
Type	M	A	A for athlete
Bib	O	S(4)	Bib number
Organisation	O	CC @Organisation	Competitor's organisation

<b>Element: Result /Competitor /Description (0,1)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
TeamName	M	S(73)	Name of the team. Only applies for teams

<b>Element: Result /Competitor /EventUnitEntry (0,N)</b>			
<b>For team event information</b>			
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>
EUE	DESCRIPTION	N/A	Element Expected: Just if the Competitor @Code is equal to TBD
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	String
			<b>Description</b>
			Text to be placed instead of the competitor name when it is not known yet, i.e., when the competitor code is equal to TBD - 'Winner Match x '
EUE	RANK	N/A	Element Expected: Only send for Ranking Round
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	S(3)
			<b>Description</b>
			Send the team's World Archery Ranking
EUE	RANK_RND	N/A	Element Expected: Send for all units after Ranking Round
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	O	Numeric #0
			<b>Description</b>
			Send the team's ranking from the Ranking Round
EUE	TARGET	N/A	Element Expected: Do not send in case of ranking round event units
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric 0
			<b>Description</b>
			Team's target number

**Sample**

```
<EventUnitEntry Type="EUE" Code="TARGET" Value="1" />
<EventUnitEntry Type="EUE" Code="RANK" Value="5" />
```

<b>Element: Result /Competitor /Composition /Athlete (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	S(20) with no leading zeroes	Athlete's ID.
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".  In case of team members, it is used to specify the athlete letter (1 means A, 2 means B and 3 means C).
Bib	O	S(4)	Athlete Bib

<b>Element: Result /Competitor /Composition /Athlete /Description (1,1)</b>			
<b>Athletes extended information.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

<b>Element: Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)</b>				
<b>Individual athletes entry information.</b>				
Type	Code	Pos	Description	
EUE	DESCRIPTION	N/A	Element Expected: Just if the Athlete @Code is equal to TBD	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	String	Text to be placed instead of the competitor name when it is not known yet, i.e., when the competitor code is equal to TBD, e.g.: 'Winner 1/32 Group B'
EUE	RANK	N/A	Element Expected: Only send for Ranking Round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	S(3)	Send the competitors World Archery Ranking
EUE	RANK_RND	N/A	Element Expected: Send for all individual units after Ranking Round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	O	Numeric #0	Send the athlete's ranking from the Ranking Round
EUE	TARGET	N/A	Element Expected: Always, if available	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric ##0	Target number
EUE	TARGET_POS	N/A	Element Expected: Just in case of ranking round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	S(1)	Position (A, B, C or D) for ranking round

### Sample

```
<Competitor Code="1123070" Type="A" Organisation="SUI" >
  <Composition>
    <Athlete Code="1123070" Bib="59" Order="1">
      <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="SUI"
      BirthDate="1994-12-15" />
      <EventUnitEntry Type="EUE" Code="TARGET" Value="1" />
      <EventUnitEntry Type="EUE" Code="RANK_RND" Value="15" />
    </Athlete>
  </Composition>
</Competitor>
```

<b>Element: Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult (1,N)</b>				
<b>Team member's extended result.</b>				
<b>Type</b>	<b>Code</b>	<b>Pos</b>	<b>Description</b>	
ER	SCORE	N/A	Element Expected: Only for team members in the ranking round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	O	Numeric ##0	Send the individual score for a team member
	ValueType	O	SC @ResultType	ValueType should be used to describe the type of data @Value
	Rank	O	Text	Rank of the competitor for this specific ExtendedResult. Send the individual rank for a team member.
	RankEqual	O	Y	Send Y where Rank at this specific ExtendResult is equalled else not sent.
ER	TEN_NUM	N/A	Element Expected: Only for team members in the ranking round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric #0	Send the number of 10's for the athlete
ER	XS_NUM	N/A	Element Expected: Only for team members in the ranking round	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric #0	Send the number of X's for the competitor

### 2.2.4.5 Message Sort

Sort by Result @SortOrder

## 2.2.5 Brackets

### 2.2.5.1 Description

The brackets message contains the brackets information for one particular event. It is used in events where there is a necessity to know in advance how successive event units will be filled as the competition progresses. In the early stages of the competition, it indicates how each of the event units will be built from the winners/losers, or other competition rules of the previous event units.

### 2.2.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Full RSC of the event
DocumentType	DT_BRACKETS	Brackets message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: START_LIST (when the draw initially made) INTERMEDIATE (during the competition) OFFICIAL (when all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).  The end of the logical day is defined by default at 03:00 a.m.  For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction. Logical Date is expressed in the local time zone where the message was produced.
Source	SC @Source	Code indicating the system which generated the message.



### 2.2.5.3 Trigger and Frequency

This message should be sent at the very beginning of a competition, as soon as brackets are available.

Send when a match/event unit is completed, including Official status. Therefore it is triggered up to two times (with both status) for each event unit. The message should be updated including information on each competitor in the different bracket items. Note however if there is no change then the second message will not be sent as it would be a duplicate.

The @ResultStatus attribute will vary depending on the competition status.

- Send with ResultStatus = 'INTERMEDIATE' from an empty bracket until the last event unit (Gold Medal Match) is Unofficial (i.e. for all event units up until the Gold Medal match is completed for an event)
- Send with ResultStatus = 'OFFICIAL' when the last event unit for an event (Gold Medal match) has Official status.

Trigger also after any change.

### 2.2.5.4 Message Values

Element: ExtendedInfos /SportDescription (0,1)			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes.
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: ExtendedInfos /VenueDescription (0,1)			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue short name (not code) from Common Codes

Element: Bracket (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @Bracket	Bracket code to identify a bracket item (finals). There should be a different code for each bracket based on sport/ORIS presentation of the bracket. For example bronze bracket is a different code from that leading to gold (assuming there are matches played)

<b>Element: Bracket /BracketItems (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	SC @BracketItems	Bracket code to identify a set of bracket items. Each BracketItems should include all BracketItem grouped by their SC @BracketItems.

<b>Element: Bracket /BracketItems /BracketItem (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	O	Numeric or TBD	In general, it will be sent the bout number for each bracket item (e.g.: 17, 18, 19, 20 ..). However, it may include "TBD" for to be defined.
Order	M	Numeric	Sequential number inside of BracketItems to indicate the order, always start at 1
Date	O	Date	Date of match (example: YYYY-MM-DD). Must include if the data is available
Time	O	S(5)	Time of match (example HH:MM). Must include if the data is available.
Unit	O	CC @Unit	Full RSC of the unit for the BracketItem
Result	O	S(50)	Result of the match if the match is complete and formatted as in ORIS (separator & order, example 5-2). The format requested for the shootoff result is: 5T-4T (28*-28) as example. Also the result could include the IRM : 0(DSQ)-3 as example Must include if the data is available and the match is complete.
NextUnit	O	CC @Unit	Full RSC of the unit where the successful competitor will progress
NextUnitLoser	O	CC @Unit	Full RSC of the unit where the unsuccessful competitor will progress

**Element: Bracket /BracketItems /BracketItem /CompetitorPlace (1,N)**

- If the competitors are known, this element is used to place the competitors in the bracket.
- If they are not yet known, it contains some information (on the rule to access to this bracket...)

Attribute	M/O	Value	Description
Pos	M	Numeric ###	This attribute is a sequential number to place the different competitors in the bracket (1, 2 ...).
Code	O	SC @CompetitorPlace	Send when there is no competitor (BYE) or when it is not known yet (TBD).
Result	O	Numeric #0	Set score achieved by the competitor in the match
WLT	O	SC @WLT	Indicates the winner or loser of the bracket item. Always send when known.
IRM	O	SC @IRM	The invalid rank mark, if applicable

**Element: Bracket /BracketItems /BracketItem /CompetitorPlace /ExtCompPlaces /ExtCompPlace (1,N)**

Type	Code	Pos	Description
ECP	DESC	N/A	Element Expected: Just in case of the competitor is not known yet
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	S(n)
			<b>Description</b>
			Competitor's description. Examples: 'Winner Ranking Round No 3' or 'Loser Match 7' etc.

**Element: Bracket /BracketItems /BracketItem /CompetitorPlace /PreviousUnit (0,1)**

Previous event unit related to the CompetitorPlace@Pos competitor of the current bracket item. It is always informed except for the bracket items whose CompetitorPlace@Pos competitor do not have preceding event units in the bracket graph unless coming from a pool.

- CompetitorPlace /PreviousUnit should be informed in case of finals, semi-finals, quarterfinals, round of 16 and round of 32.

Attribute	M/O	Value	Description
Unit	O	CC @Unit Full RSC	Full RSC code of the previous event unit for the CompetitorPlace@Pos competitor of the bracket item. Must send if a winner/loser from a single unit.
Value	O	SC @Pool or S(2)	If the competitor in the current unit is unknown due to coming from pools or previous matches then fill this field with the code of the pool or the match number as appropriate.
WLT	O	SC @WLT	If the competitor in the current unit is unknown and coming from an earlier bracketitem then fill this field with the W or L indication winner or loser of the previous unit if the information is known. Do not send if competitor comes from a pool.

**Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor (0,1)**

CompetitorPlace @Pos competitor related to the bracket item. Only include if the competitor is known .

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team A for athlete
Seed	O	S(10)	Send the rank of the competitor in the ranking round.
Organisation	O	CC @Organisation	Competitors' organisation if known

**Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Description (0,1)**

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams

<b>Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /ExtBracketComps /ExtBracketComp (1,N)</b>				
<b>CompetitorPlace @Pos team competitor's extended bracket information, according to competitors' rules.</b>				
Type	Code	Pos	Description	
RES	ARROWS	N/A	Element Expected: Only for teams after each match	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	S(n)	Send the arrow score achieved by the team in the match as formatted in ORIS (for example 28,30,27,29,28-T10* in the case of tie-break )
RR	RECORD	N/A	Element Expected: Only for teams and only the first mention (furthest from final) this team appears in the bracket).	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	CC @RecordType	Send the record type related with the result of the ranking round. For the athletes who break both records OR and WR, only send the most relevant (WR if both).
RR	SCORE	N/A	Element Expected: Only for teams and only the first mention (furthest from final) this team appears in the bracket).	
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
	Value	M	Numeric ###0	Send the total score of the Team in the Ranking Round

<b>Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete (1,N)</b>				
Attribute	M/O	Value	Description	
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete	
Bib	O	S(4)	Athlete number	
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".	

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /ExtBracketAths /ExtBracketAth (1,N)			
CompetitorPlace @Pos team member's or individual athlete's extended bracket information, depending on whether Competitor @Type="T" or Competitor @Type="A" according to competitors' rules.			
Type	Code	Pos	Description
RES	ARROWS	N/A	Element Expected: Only for individual competition after each match
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	S(n)
	<b>Description</b>		Send the arrow score achieved by the athlete in the match as formatted in ORIS.
RR	RECORD	N/A	Element Expected: Only for individual event athletes and only the first mention (furthest from final) this athlete appears in the bracket).
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	CC @RecordType
	<b>Description</b>		Send the highest record type related with the result
RR	SCORE	N/A	Element Expected: Only for individual event athletes and only the first mention (furthest from final) this athlete appears in the bracket).
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric ###0
	<b>Description</b>		Send the total score of the athlete in the Ranking Round

### Sample

```
<Bracket Code="FNL">
  <BracketItems Code="SFL">
    <BracketItem Code="148" Order="1" Date="2012-08-12" Time="11:00" Unit="ARCMINDIVID-----SFNL000100--"
    " Result="6-2" NextUnit Unit=" ARCMINDIVID-----FNL-000100--" >
      <CompetitorPlace Pos="1" Result="6" WLT="W">
        <PreviousUnit Unit="ARCMINDIVID-----QFNL000300--" />
        <Competitor Code="1098720" Type="A" Organisation="SUI" >
          <Composition>
            <Athlete Code="1098720" Order="1" >
              <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="SUI"
              BirthDate="1996-12-15" />
              <ExtBracketAths>
                <ExtBracketAth Type="RES" Code="ARROWS" Value="(27,29,28,29,29)" />
              </ExtBracketAths>
            </Athlete>
          </Composition>
        </Competitor>
      </CompetitorPlace>
      <CompetitorPlace Pos="2" Result="2" WLT="L">
        <PreviousUnit Unit="ARCMINDIVID-----QFNL000400--" />
        <Competitor Code="1104827" Type="A" Organisation="ESP" >
          <Composition>
            <Athlete Code="1104827" Order="1" >
              <Description GivenName="Jack" FamilyName="Smith" Gender="M" Organisation="ESP"
              BirthDate="1996-12-16" />
              <ExtBracketAths>
                <ExtBracketAth Type="RES" Code="ARROWS" Value="(28,27,29,26,26)" />
              </ExtBracketAths>
            </Athlete>
          </Composition>
        </Competitor>
      </CompetitorPlace>
    </BracketItem>
  </BracketItems>
</Bracket>
```

### 2.2.5.5 Message Sort

The following order applies:

- \* Bracket @Code if more than one '@Code' is possible.
- \* BracketItems according to its @Code attribute.
- \* Then, the BracketItem /Unit @Unit are sorted according to their scheduled start time.

## 2.2.6 Records

### 2.2.6.1 Description

The message contains the list of all records from the start of the Games (events depending on header).

Special Situations - Not Established Records:

There are some situations where there are no records for a particular event. This can happen, for example, when the sport rules change (different weights or distances) or new events are introduced.

If this occurs then the NotEstablished flag is used to indicate this situation.

If a record is established for this event in the current competition then the NotEstablished flag and description will not be sent when a new record is established.

### 2.2.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (Discipline Level)	RSC of the discipline
DocumentSubcode	CC @RecordCode	If the message is sent as a result of a record being modified (broken, equalled or re-instated) then this attribute will be included and is the Record Event for the modification.
DocumentType	DT_RECORD	Records message
DocumentSubtype	FULL, PARTIAL	Send "FULL" if all records included. Send "PARTIAL" if only one record code is included.
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.



Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.6.3 Trigger and Frequency

The DT\_RECORD (without DocumentSubcode) message is sent as a full message (all records in a discipline) prior to the competition. Any new version of the DT\_RECORD message should replace all previous record information, either for the RecordCode specified in DocumentSubcode or all if no DocumentSubcode is specified.

Note: It is send by central systems before the competition with the historical records and during the competition if any record is broken.

### 2.2.6.4 Message Values

Element: ExtendedInfos /SportDescription (0,1)			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes

Element: Record (1,N)			
Attribute	M/O	Value	Description
Code	M	CC @RecordCode	<p>Record code. Send all record codes in the bulk message else this must match the DocumentSubcode, that is, only one per message.</p> <p>Send several record codes (different messages) in the case several record codes were broken for the current event unit.</p>

Element: Record /Description (1,1)			
Attribute	M/O	Value	Description
Name	M	S(40)	Record description (not code) from Common Codes

Element: Record /RecordType (1,N)			
It is possible to have more than one element with the same type (as in the case of National Records).			
Attribute	M/O	Value	Description
Order	M	Numeric #0	The hierarchy (priority) for types of record from 1 to n. (Can use the Order column from CC @RecordType to assist in case several records are broken, from high priority to low priority but must still use 1 to n).
RecordType	M	CC @RecordType	Record type.
Shared	M	S(1)	Y-There is more than one competitor sharing the record N-There is just one competitor holding the record
NotEstablished	O	S(1)	Send "Y" in the case there is no record in this category else do not send.
NotEstablishedLabel	O	S(25)	The description to be used in the case that NotEstablished="Y".

Element: Record /RecordType /RecordData (0,N)			
RecordData is not sent for NotEstablished Records unless a "standard" applies			
Attribute	M/O	Value	Description
Order	M	Numeric #0	In the case that a record (RecordType) is provided several times in the message, then Order is the chronological order for the records (1,N). 1 will be usually the historical record and for each record broken during the competition a new order value will be provided. Usually first time the record is broken will have Order="2", second time Order="3" etc. Send 1 for records (RecordType) not shared (historical records)
ResultType	M	SC @ResultType	Always POINTS
Result	M	Numeric ###0	Score Send always unless the record is not established. The performance of the competitor for the record.
Unit	O	CC @Unit	The full RSC of the unit in the current competition where the record was broken. Send always (Mandatory) in the case Historical="N".
Country	O	CC @Country	Send always unless the record is not established. Country code where the record was broken
Place	O	S(40)	Send always (when known) unless the record is not established. Place (town or city) where the record was broken (example: "Salt Lake City").

Element: Record /RecordType /RecordData (0,N)			
RecordData is not sent for NotEstablished Records unless a "standard" applies			
Attribute	M/O	Value	Description
Date	O	YYYY-MM-DD	Send always unless the record is not established. Date when the record was broken (for the current competition, the date will be assumed to be the date scheduled for the @Unit attribute)
Time	O	Time	Time the record was set. Send always (Mandatory) in the case of Historical="N".
Equalled	O	S(1)	Send "Y" if the existing record is equalled. Do not send if the record is not equalled.
Competition	O	S(40)	Send the text of the competition name where the record was broken (example: "2013 World Championships", "2012 Olympic Games", etc.).
Historical	M	S(1)	Send "Y" if the record for competitor was not achieved during the current competition. Send "N" if the record for the competitor was achieved during the current competition.
Current	O	S(1)	Send "Y" in the case that this is the current record else do not send (may be multiple in the case of a shared record).
ModificationIndicator	O	S(1)	The possible values are: "N" = New broken record (not provided in a previous message) "R" = This record is re-instated/re-established as the current record in this message (following an invalidation or similar). Do not send this attribute for other records included in the message (not broken or not re-instated)

Element: Record /RecordType /RecordData /Extension (0,N)			
Type	Code	Pos	Description
ER	XS_NUM	N/A	Element Expected: Send if applicable. For inner 10s
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric #0
			<b>Description</b>
			Number of inner 10s

**Element: Record /RecordType /RecordData /Competitor (0,1)**  
**Competitor to whom the record is assigned.**  
**Athlete's or team's information should be in DT\_PARTIC (Historic) if Competitor @Type="A" or DT\_PARTIC\_TEAMS (Historic) if Competitor @Type="T".**

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	"T" for team "A" for athlete
Organisation	O	CC @Organisation	Competitors' organisation if known

**Element: Record /RecordType /RecordData /Competitor /Description (0,1)**  
**Competitors extended information.**

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams / groups.

**Element: Record /RecordType /RecordData /Competitor /Composition /Athlete (1,N)**

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Numeric #0	Order attribute used to sort team members in a team if Competitor @Type="T" or 1 if Competitor @Type="A".

**Element: Record /RecordType /RecordData /Competitor /Composition /Athlete /Description (0,1)**  
**Athletes extended information.**

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

### 2.2.6.5 Message Sort

The following order applies:

- Record @Code
- RecordType @Order
- RecordData @Order

## 2.2.7 Event Final Ranking

### 2.2.7.1 Description

The event final ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a generic message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Rank Mark (disqualified, etc.), or both.

### 2.2.7.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC of the Event	
DocumentType	DT_RANKING	Event Final ranking message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Result status, indicates whether the data is official or partial. OFFICIAL PARTIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.7.3 Trigger and Frequency

This message is only triggered after a unit which affects the final ranking is official and that particular ranking is not subject to change.  
Trigger also after any change.

### 2.2.7.4 Message Values

Element: ExtendedInfos /SportDescription (0,1)			
Sport Description in text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes. Must be included if it is a single event
Gender	M	CC @DisciplineGender	Gender code for the event unit. Must be included if it is a single gender

Element: ExtendedInfos /VenueDescription (0,1)			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue short name (not code) from Common Codes

<b>Element: Result (1,N)</b>			
<b>For any event final ranking message, there should be at least one competitor being awarded a result for the event.</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Rank	O	Text	Final rank of the competitor in the corresponding event.
RankEqual	O	S(1)	Identifies if a rank has been equalled. Send Y if applicable
IRM	O	SC @IRM	The invalid rank mark, send if applicable.
SortOrder	M	Numeric	Unique sort order for all results based on rank to break rank ties.  This attribute is a sequential number with the order of the results for the particular event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out rank ties as well as results without rank.

<b>Element: Result /Competitor (1,1)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	S(20) with no leading zeroes, NOCOMP	Competitor's ID. "NOCOMP" in the case where there is no competitor in the rank due to IRM.
Type	M	S(1)	T for team A for athlete
Organisation	O	CC @Organisation	Competitors' organisation if known

<b>Element: Result /Competitor /Description (0,1)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
TeamName	M	S(73)	Name of the team. Only applies for teams / groups.

<b>Element: Result /Competitor /Composition /Athlete (1,N)</b>			
<b>Attribute</b>	<b>M/O</b>	<b>Value</b>	<b>Description</b>
Code	M	S(20) with no leading zeroes	Athlete's ID
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

### Sample (Sample)

```

<Result Rank="1" SortOrder="1">
  <Competitor Code="1106858" Type="A" Organisation="SUI" >
    <Composition>
      <Athlete Code="1106858" Order="1" >
        <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="SUI"
        BirthDate="1994-12-15" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
<Result SortOrder="2" IRM="DQB" >
  <Competitor Code="1090697" Type="A" Organisation="ESP" >
    <Composition>
      <Athlete Code="1090697" Order="1">
        <Description GivenName="James" FamilyName="Black" Gender="M" Organisation="ESP"
        BirthDate="1994-12-16" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
....

```

### 2.2.7.5 Message Sort

Sort by Result @SortOrder



## 2.2.8 Configuration

### 2.2.8.1 Description

The Configuration is a message containing general configuration.

The configuration should be provided before competition at event level only.

### 2.2.8.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	The DocumentCode will be at event level.
DocumentType	DT_CONFIG	Configuration message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

### 2.2.8.3 Trigger and Frequency

- Trigger one message for each event, send before other messages in the event.
- Trigger also after any change, but if it is resent then if any DT\_RESULT has been sent then the next version of DT\_RESULT must be sent immediately afterward.

### 2.2.8.4 Message Values

Element: Configs /Config (1,N)			
Attribute	M/O	Value	Description
Unit	O	CC @Event	Full RSC at event level

Element: Configs /Config /ExtendedConfig (1,N)			
Type	Code	Pos	Description
EC	BRACKET_SIZE	N/A	Element Expected: Always
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	SC @BracketItems
			Send the code for the first phase of the event
EC	TEAM_SIZE	N/A	Element Expected: Always
	<b>Attribute</b>	<b>M/O</b>	<b>Value</b>
	Value	M	Numeric 0
			Send the number of athletes in a team

#### Sample

```

....
<Configs>
  <Config Unit="ARCMINDIVID-----">
    <ExtendedConfig Type="EC" Code="BRACKET_SIZE" Value="R32" />
  </Config>
</Configs>

```

### 2.2.8.5 Message Sort

There is no general message sorting rule

### 3 Document Control

Version history		
Version	Date	Comments
v1.0	1 Aug 2017	First version

File Reference: ODF R-SOG-2020-ARC V1.0 SFR

Change Log		
Version	Status	Changes on version
v1.0	SFR	First version