

OLYMPIC DATA FEED

ODF Handball Data Dictionary

Tokyo 2020 - Games of the XXXII Olympiad

Technology and Information Department

© International Olympic Committee

ODF R-SOG-2020-HBL V1.1 SFA

3 January 2018

License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.

The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.

5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.

1 Introduction

1.1 This document

This document includes the ODF Handball Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for handball.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Handball Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the handball competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 2018 Youth Olympic Games

This document is to be applied for the 2018 Youth Olympic Games. All included concepts are applied except where noted below:

- DT_PARTIC: INTERNAT_PLAYED and INTERNAT_GOALS are not applicable
- DT_CURRENT: Message is not applicable
- DT_STATS: Message is not applicable

1.5 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies

1.6 Related Documents

Document Title	Document Description
ODF General Principles Document	The document explains the environment and general principles for ODF.
ODF General Messages Interface Document	The document describes the ODF General Messages
ODF Common Codes	The document describes the ODF Common codes used across all ODF documents.
ODF Sport Codes	The document describes the ODF Sport codes used across all ODF documents
ODF Header Values	The document details the header values which show which RSCs are used in which messages.

2 Messages

2.1 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in handball.

- The column “Message type” indicates the DocumentType that identifies a message
- The column “Message name” is the message name identified by the message type
- The column “Message extended” indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it should follow the general definition rules.

Message Type	Message Name	Message extended
DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule / update	X
DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / update	X
DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of teams / update	X
DT_MEDALS	Medal standings	
DT_MEDALLISTS_DAY	Medallists of the day	
DT_GLOBAL_GM	Global good morning	
DT_GLOBAL_GN	Global good night	
DT_RESULT	Event Unit Start List and Results	X
DT_PLAY_BY_PLAY	Play by Play	X
DT_CURRENT	Current Information	X
DT_POOL_STANDING	Pool Standings	X
DT_BRACKETS	Brackets	X
DT_STATS	Statistics	X
DT_RANKING	Event Final Ranking	X
DT_COMMUNICATION	Official Communication	
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_LOCAL_ON	Discipline/venue start transmission	
DT_KA	Keep Alive	

2.2 Messages

2.2.1 Competition schedule / Competition schedule update

2.2.1.1 Description

The Competition schedule is a bulk message provided for one particular discipline. As a general rule, it contains the complete schedule information for all event units needed to run a competition and excludes event units for activities such as unofficial training and press conferences.

This message contains the competition timetable for a complete discipline as well as status for each competition unit and is updated from OVR via the schedule update message.

All event units in codes which have the 'schedule' flag set to 'Y' are included in schedule messages (and have status UNSCHEDULED or SCHEDULED).

The arrival of the competition schedule message resets all the previous schedule information for one particular discipline.

To ensure there are no incorrectly ordered units then the start time must not be updated to the actual start time (there is an actual start time field to cater for this).

Competition schedule update:

Competition schedule update is an update message. It is not a complete schedule information message, but only the schedule data being modified.

The arrival of this message updates the previous schedule information for one particular event unit, but does not notify any other change for the rest of the event units except for those contained in the message.

The key of the information updated is Unit @Code. Therefore, any new unit, deleted unit or updated unit will be identified by this attribute.

It has to be understood that if one DT_SCHEDULE message arrives, then all previous DT_SCHEDULE_UPDATE messages should be discarded.

2.2.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	Full RSC at the discipline level
DocumentType	DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule bulk / update
Version	1...V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Refer to the ODF header definition
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.1.3 Trigger and Frequency

The competition schedule will be sent as a bulk message (DocumentType="DT_SCHEDULE") when available before the Games and then sent multiple times until a date to be confirmed after which only update messages will be sent (DocumentType="DT_SCHEDULE_UPDATE") by OVR. There is no automatic triggering and this (DT_SCHEDULE) message must not be sent after the transfer of control to OVR.

The competition schedule update message should be triggered at any time there has been a competition schedule modification for any previously sent competition schedule bulk message or update message including the addition of start list details (H2H).

Generally start list details for H2H should be sent immediately when known and usually soon after the preceding unit changes to Official.

The triggers for status changes are described in each sport data dictionary where differences are needed.

If any text descriptions change in a message (as opposed to the code) then this message is not resent to correct previous messages however the new data is to be used in future messages.

2.2.1.4 Message Values

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
SessionCode	M	S(5)	Format DDD00 where DDD is the discipline and 00 is the session number.
StartDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00
EndDate	O	DateTime	End date. Example: 2006-02-26T10:00:00+01:00
Leadin	O	m:ss	Amount of time from session start to first scheduled unit.
Venue	M	CC @VenueCode	Venue where the session takes place
VenueName	M	S(25)	Venue name
ModificationIndicator	O	S(1)	Attribute is mandatory in the DT_SCHEDULE_UPDATE message. N = New or U = Update.
SessionStatus	M	CC @ScheduleStatus	nly use CANCELLED if applicable. All other sessions are assumed to be scheduled. There is no change to running or finished.
SessionType	O	CC @SessionType	Session Type of the session

Element: Competition /Session /SessionName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Language of the Session Description
Value	O	S(40)	Name of the session. (if no other name then is session code)

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
SessionCode	M	S(5)	Code of the session which contains this event unit. Usually in the format DDD00 where DDD is the discipline and 00 is the session number within the discipline.
StartDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00
EndDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00
Leadin	O	m:ss	Amount of time from session start to first scheduled unit.
Venue	M	CC @VenueCode	Venue where the session takes place
VenueName	M	S(25)	Name of venue
ModificationIndicator	O	S(1)	Attribute is mandatory in the DT_SCHEDULE_UPDATE message. N = New or U = Update.
SessionStatus	O	CC @ScheduleStatus	Only use CANCELLED if applicable. All other sessions are assumed to be scheduled. There is no change to running or finished.
SessionType	O	CC @SessionType	Session type of the session

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Code	M	Full RSC for the unit	
PhaseType	M	CC @PhaseType	Phase type for the unit
UnitNum	O	S(6)	Match Number
ScheduleStatus	M	CC @ScheduleStatus	Unit Status

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
StartDate	O	DateTime	<p>Start date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED. For other statuses the StartDate is expected otherwise ordering is display is incorrect (including CANCELLED and POSTPONED).</p> <p>This is the scheduled Start date and time and will not be updated when an event unit starts (updated only with RESCHEDULED status)</p> <p>Example: 2006-02-26T10:00:00+01:00</p>
HideStartDate	O	S(1)	<p>Send 'Y' if StartDate (scheduled start time) should not be displayed. It may be an estimate or 'fake' time. Do not send if StartDate (scheduled start time) is to be displayed.</p> <p>Start times of some units depend on the finalisation of previous event units and therefore there is no fixed start time in these cases this field is set to 'Y'.</p> <p>When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed.</p>
EndDate	O	DateTime	<p>End date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED, POSTPONED or CANCELLED.</p> <p>Example: 2006-02-26T10:00:00+01:00</p>
HideEndDate	O	S(1)	<p>Send 'Y' if EndDate scheduled end time is not to be displayed.</p> <p>Some event units have a scheduled end time well bounded, however, some event units in some circumstances have a scheduled end time not quite variable (example, some press conferences or tennis matches, etc.) in these cases this field is set to 'Y' and should not be displayed.</p>
ActualStartDate	O	DateTime	<p>This attribute is expected once the event unit has started. Example: 2006-02-26T10:03:22+01:00</p>
ActualEndDate	O	DateTime	<p>This attribute is expected once the event unit has finished. Example: 2006-02-26T12:43:51+01:00</p>

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Order	O	Numeric ###0	Order of the units when displayed. This field is considered in two situations: 1. If HideStartDate = 'Y' then send at least for all Units in an affected session though it is suggested to be sent for all units in a discipline where the concept is used in the discipline. 2. If some units start at the same time and a particular order of the units is expected. It is generally recommended to start at 1 in each session each day though may be ordered independently by location starting at 1 for each location in each session (where the schedule is ordered by location) or using other numbers to ensure the order of two using starting at the same time are displayed in the appropriate order.
Medal	O	SC @UnitMedalType	Gold medal event unit or bronze medal event unit. Do not send if not a medal event unit
Venue	M	CC @VenueCode	VVenue where the unit takes place Use TBD if the Venue is not known yet (CC).
Location	M	CC @Location	Location where the unit takes place Use TBD if the Location is not known yet (CC) or a generic code for the discipline.
SessionCode	O	S(5)	Code of the session which contains this event unit.
ModificationIndicator	O	N, U	Attribute is mandatory in the DT_SCHEDULE_UPDATE message only N-New event unit U-Update event unit If ModificationIndicator='N', then include new event unit. It will be rarely used as most added units were available in "UNSCHEDULED" status. If ModificationIndicator="U", then update the event unit.

Element: Competition /Unit /StartText (0,N)			
This element is only used for Competition Schedules when HideStartDate is 'Y'. In this case, English Language is mandatory.			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
Value	M	S(20)	Text to be displayed in the case that StartDate is not to be displayed (e.g. "After M.1" or "Followed by") Using a code set or fixed text will also be directly displayed and allow end user translation.

Element: Competition /Unit /ItemName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
Value	M	S(40)	Item Name / Unit Description. For competition units show the short unit description from common codes which matches the RSC. As in all messages with a description only the ENG description is expected. For non-competition schedules (where the item description is not in common codes) then add the description.

Element: Competition /Unit /VenueDescription (1,1)			
Attribute	M/O	Value	Description
VenueName	M	S(25)	Venue name in first language. This is the CC value from unit/venue
LocationName	M	S(30)	Location name in first language. This is the CC value from unit/location.

Element: Competition /Unit /StartList /Start (1,N)			
StartList information is only sent in the case that the Unit type is one of HATH, HCOUP, HNOC or HTEAM and at least one of the competitors are known. (Sent as soon as known for applicable units)			
Attribute	M/O	Value	Description
StartOrder	O	Numeric	Competitor's start order
SortOrder	M	Numeric	Used to sort competitors in an event unit (for example, if there is no StartOrder). It is mainly used for display purposes.

Element: Competition /Unit /StartList /Start /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes, TBD or NOCOMP.	Competitor's ID, TBD in case that the competitor is not known at this time AND the other competitor is known. NOCOMP is sent when there is no competitor (and will not come later)
Type	M	T	T for team
Organisation	O	CC @Organisation	Should be sent when known

Element: Competition /Unit /StartList /Start /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Team Name where known, must send when available

2.2.1.5 Message Sort

The message is sorted by Unit@StartDate then by Unit@Order then Unit@Code.

In case of event unit with no Unit@StartDate defined (example, they are in an event unit status such as UNSCHEDULED), they will be listed at the end in Unit@Code order.

2.2.2 List of participants by discipline / List of participants by discipline update

2.2.2.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

List of participants by discipline (DT_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message can include a list of current athletes, officials, coaches, guides, technical officials, Reserves and historical athletes regardless of status.

List of participants by discipline update (DT_PARTIC_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

2.2.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	RSC at the discipline level
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	List of participants by discipline message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.2.3 Trigger and Frequency

The DT_PARTIC message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_UPDATE messages are sent.

The DT_PARTIC_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.

2.2.2.4 Message Values

Element: Participant (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	<p>Participant's ID.</p> <p>It identifies an athlete or an official and the holding participant's valid information for one particular period of time.</p> <p>It is used to link other messages to the participant's information.</p> <p>Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc.</p> <p>When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.</p>
Parent	M	S(20) with no leading zeroes	<p>Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent.</p> <p>The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.</p> <p>The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".</p>
Status	O	CC @ParticStatus	<p>Participant's accreditation status this attribute is Mandatory in the case of @Current="true" and it is optional in the case that @Current="false".</p> <p>To delete a participant, a specific value of the Status attribute is used.</p>
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)

Element: Participant (1,N)			
Attribute	M/O	Value	Description
PassportGivenName	O	S(25)	Passport Given Name (Uppercase)
PassportFamilyName	O	S(25)	Passport Family Name (Uppercase)
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth. This information may not be known at the very beginning, but it will be completed for all participants after successive updates
Height	O	S(3)	Height in centimetres. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
Weight	O	S(3)	Weight in kilograms. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC @Country	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC @Country	Country ID of Residence
Nationality	O	CC @Country	Participant's nationality. Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC @ResultsFunction	Main function In the Case of Current="true" this attribute is Mandatory.
Current	M	boolean	It defines if a participant is participating in the games (true) or is a Historical participant (false).

Element: Participant (1,N)			
Attribute	M/O	Value	Description
OlympicSolidarity	O	S(1)	'Y' or 'N' Flag to indicating if the participant participates in the Olympic Scholarship program.
ModificationIndicator	M	S(1)	'N' or 'U' Attribute is mandatory in the DT_PARTIC_UPDATE message only N-New participant (in the case that this information comes as a late entry) U-Update participant If ModificationIndicator='N', then include new participant to the previous bulk-loaded list of participants If ModificationIndicator='U', then update the participant to the previous bulk-loaded list of participants To delete a participant, a specific value of the Status attribute is used.

Element: Participant /Discipline (1,1)			
All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.			
Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the discipline
IFId	O	S(16)	IF ID (Competitor's federation number for the corresponding discipline)

Element: Participant /Discipline /RegisteredEvent (0,N)			
All accredited athletes will be assigned to one or more events. There is one exception: in some sports, substitutes may be accredited without any associated event. Historical athletes are not registered to any event.			
Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the event
Bib	O	S(2)	Shirt number. Although this attribute is optional, it will be updated and informed as soon as this information is known. Example: 1, 2,... (for athlete), A.E (for Team official)
Substitute	O	S(1)	Flag that indicates when the competitor is an alternate. Send "Y" if the competitor is an alternate player

Status	O	SC @AthleteStatus	Participant status (disqualified or replaced). Send if applicable else do not send.
--------	---	-------------------	---

Element: Participant /Discipline /RegisteredEvent /EventEntry (0,N)				
Type	Code	Pos	Description	
ENTRY	POSITION	N/A	Element Expected: If the information is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	M	CC @Position	Position Code in the Team
ENTRY	HAND	N/A	Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	M	SC @Hand	Handedness of the athlete
ENTRY	SHIRT_NAME	N/A	Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	O	S(25)	Shirt name
ENTRY	CLUB_NAME	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	M	S(25)	Club name
ENTRY	CLUB_CITY	N/A	Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	M	S(25)	Club City
ENTRY	CLUB_ORG	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	M	CC @Country	Club Country Code
ENTRY	INTERNAT_PLAYED	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	International games played

Element: Participant /Discipline /RegisteredEvent /EventEntry (0,N)			
Type	Code	Pos	Description
ENTRY	INTERNAT_GOALS	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).
Attribute	M/O	Value	Description
Value	M	Numeric ##0	International goals scored

Element: Participant /OfficialFunction (0,N)			
Send if the official has optional functions. Do not send, otherwise.			
Attribute	M/O	Value	Description
FunctionId	M	CC @ResultsFunction	Additional officials' function code

Sample (General)

```
<Discipline Code="HBL-----" IFId="203258" >
  <RegisteredEvent Event="HBLMTEAM7-----" >
    <EventEntry Type="ENTRY" Code="POSITION" Value="LB" />
    <EventEntry Type="ENTRY" Code="CLUB_NAME" Value="Badel 1862" />
    <EventEntry Type="ENTRY" Code="CLUB_CITY" Value="Zagreb" />
    <EventEntry Type="ENTRY" Code="CLUB_ORG" Value="CRO" />
    <EventEntry Type="ENTRY" Code="INTERNAT_PLAYED" Value="42" />
    <EventEntry Type="ENTRY" Code="INTERNAT_GOALS" Value="2" />
  </RegisteredEvent>
</Discipline>
```

2.2.2.5 Message Sort

The message is sorted by Participant @Code

2.2.3 List of teams / List of teams update

2.2.3.1 Description

DT_PARTIC_TEAMS contains the list of teams related to the current competition.

List of teams (DT_PARTIC_TEAMS) is a bulk message by discipline. The list is always complete. The arrival of this message resets all the previous participant teams' information for that discipline. It is assumed that all teams appearing in this list are valid, in the meaning that they are participating or they could participate in one event.

List of teams update (DT_PARTIC_TEAMS_UPDATE) is an update message. It is not a complete list of teams' information message. It only contains the data of a team being modified.

2.2.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	RSC at the discipline level
DocumentType	DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of participant teams message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.3.3 Trigger and Frequency

The DT_PARTIC_TEAMS message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_TEAMS_UPDATE messages are sent.

The DT_PARTIC_TEAMS_UPDATE message is triggered when there is a modification in the data for any team after the transfer of control to OVR.

2.2.3.4 Message Values

Element: Team (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Team's ID When the Team is an historical one, then this ID starts with "T".
Organisation	M	CC @Organisation	Team organisation's ID
Number	O	Numeric #0	Team's number. If there is not more than one team for one organisation participating in one event, it is 1. Otherwise, it will be incremental, 1 for the first organisation's team, 2 for the second organisation's team, etc. Required in the case of current teams.
Name	O	S(73)	Team's name.
TVTeamName	O	S(21)	TV Team Name
Gender	M	CC @DisciplineGender	Discipline Gender Code of the Team
Current	M	boolean	It defines if a team is participating in the games (true) or it is a Historical team (false)
ModificationIndicator	M	N, U, D	Attribute is mandatory in the DT_PARTIC_TEAMS_UPDATE message only N-New team (in the case that this information comes as a late entry) U-Update team D-Delete team If ModificationIndicator='N', then include new team to the previous bulk-loaded list of teams If ModificationIndicator='U', then update the team to the previous bulk-loaded list of teams If ModificationIndicator='D', then delete the team to the previous bulk-loaded list of teams

Element: Team /Composition /Athlete (0,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID of the listed team's member. Therefore, he/she makes part of the team's composition.
Order	O	Numeric	Team member order

Element: Team /TeamOfficials /Official (1,N)			
Send if there are specific officials for the team. Does not apply to historical teams.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Official's ID of the listed team's official. For all team officials
Function	M	CC @ResultsFunction	Official's function for the team.
Order	O	Numeric #0	Official's order in the team.

Element: Team /Discipline (0,1)			
Each team is assigned just to one discipline. Discipline is expected unless ModificationIndicator="D"			
Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the discipline

Element: Team /Discipline /RegisteredEvent (0,1)			
Each current team is assigned to one event. Historical teams will not be registered to any event.			
Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the event

Element: Team /Discipline /RegisteredEvent /EventEntry (0,N)				
Send if there are specific team's event entries.				
Type	Code	Pos	Description	
ENTRY	UNIFORM	Numeric 0	Pos Description: Send 1, 2, 3 to indicate the number of shirt Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	O	S(25)	Shirt Colour
ENTRY	SHORTS	Numeric 0	Pos Description: Send 1, 2, 3 to indicate the number of shorts Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	O	S(25)	Shorts colour
ENTRY	UNIFORM_GK	Numeric 0	Pos Description: Send 1, 2, 3 to indicate the number of goalkeeper shirt Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	O	S(25)	Shirt colour for Goalkeeper
ENTRY	SHORTS_GK	Numeric 0	Pos Description: Send 1, 2, 3 to indicate the number of shorts Element Expected: As soon as it is known (it can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	O	S(25)	Shorts colour for Goalkeeper
ENTRY	SEED	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	The position in which the team is seeded for the competition.
ENTRY	GROUP	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	O	S(1)	Team's Preliminary Group

Sample

```
<Team Code="HBLMTEAM7-----CAN01" Organisation="CAN" Number="1" Name="Canada" Gender="M"
Current="true">
  <Composition>
    <Athlete Code="1063192" Order="1"/>
    <Athlete Code="1063249" Order="2"/>
  ....
</Composition>
<TeamOfficials>
  <Official Code="7380750" Function="COACH" />
  <Official Code="7380751" Function="AST_COA" />
  <Official Code="7380752" Function="AST_COA" />
</TeamOfficials>
<Discipline Code="HBLM-----" >
  <RegisteredEvent Event="HBLMTEAM7-----" >
    <EventEntry Type="ENTRY" Code="UNIFORM" Pos="1" Value="White" />
    <EventEntry Type="ENTRY" Code="SHORTS" Pos="12" Value="Red" />
  ...
  </RegisteredEvent>
</Discipline>
</Team>
```

2.2.3.5 Message Sort

The message is sorted by Team @Code.

2.2.4 Event Unit Start List and Results

2.2.4.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports. The definition includes as much generic information as possible due to the fact that each discipline and event has its own format for the results information (example: score of a match, time in a race, distance in a throw...).

This is always a full message and all applicable elements and attributes are always sent.

2.2.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Full RSC of the event unit
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	Not used	Not used
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	It indicates whether the result is official or unofficial (or intermediate etc). START_LIST INTERMEDIATE (After each period) LIVE (used during the competition when nothing else applies). OFFICIAL UNOFFICIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.4.3 Trigger and Frequency

This message is sent with ResultStatus 'START_LIST' as soon as the expected information is available and any changes to the information. Possible information is:

- START LIST: As soon as the team/teams are known, before the match begins.
- START LIST: As soon as any of the line-up and starters are known and any change/addition to these only before the start of the match.

This message is then sent with ResultStatus 'LIVE' as soon as the unit starts and continues to be triggered on all updates.

- LIVE: At the beginning of each period.
- LIVE: After every change in any data (scores, substitute, DQ etc).

This message is also sent when the unit finishes and the results are still unofficial and again when the results become official. The message is sent as 'INTERMEDIATE' during extended breaks.

- INTERMEDIATE: After each period (if it is not the last period).
- UNOFFICIAL / OFFICIAL: After the unit.

Trigger also after any change.

2.2.4.4 Message Values

Element: ExtendedInfos /UnitDateTime (0,1)			
Attribute	M/O	Value	Description
StartDate	0	DateTime	Actual start date-time. Do not include until unit starts.

Element: ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	PERIOD	N/A	Element Expected: Beginning of each period. Remove when official.
Attribute	M/O	Value	Description
Value	O	SC @Period	Send current period
DISPLAY	CURRENT	Numeric #0	Pos Description: Send a unique number for each competitor on the court. Element Expected: When available when the unit is LIVE and only for those players on the court.
Attribute	M/O	Value	Description
Value	M	S(20) without leading zeroes	Send the competitor ID of the player.
DISPLAY	String	Numeric 0	Pos Description: Send a unique number to avoid duplication of codes. Code Description: Send the @Code of the last updated Result /Competitor /Stats /Stat or Result /Competitor /Composition /Athlete /Stats /Stat May be: SD, W, LD, PTY, FB, BT, ASSIST, TO, ST, BLC, YC, RC, TMS, EXC, SD_GK, W_GK, LD_GK, PTY_GK, FB_GK and BT_GK Pos Description: Sequential number within message Element Expected: When available and only when the unit is LIVE. Send multiple if applicable unit is LIVE. Send multiple if applicable
Attribute	M/O	Value	Description
Value	M	S(20)	Send the ID of the athlete/team who was updated

Sample

```
<ExtendedInfos>
  <ExtendedInfo Type="UI" Code="PERIOD" Value="1" />
  <ExtendedInfo Type= DISPLAY" Code="CURRENT" Pos="1" Value="1102201" />
  <ExtendedInfo Type= DISPLAY" Code="CURRENT" Pos="2" Value="1102199" />
  <ExtendedInfo Type= DISPLAY" Code="CURRENT" Pos="3" Value="1102203" />
  <ExtendedInfo Type= DISPLAY" Code="CURRENT" Pos="4" Value="1102213" />
  <ExtendedInfo Type= DISPLAY" Code="CURRENT" Pos="5" Value="1102198" />
  <ExtendedInfo Type= DISPLAY" Code="CURRENT" Pos="6" Value="1109414" />
  .....
  <ExtendedInfo Type="DISPLAY" Code="TO" Pos="1" Value="2518090" />
  ...
</ExtendedInfos>
```

Element: ExtendedInfos /SportDescription (0,1)			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes
Gender	M	CC @DisciplineGender	Gender code for the event unit
SubEventName	M	S(40)	EventUnit short name (not code) from Common Codes
UnitNum	O	S(6)	Match number

Element: ExtendedInfos /VenueDescription (0,1)			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location short name (not code) from Common Codes
Attendance	O	#####0	Total attendance (do not send if unknown)

Element: Officials /Official (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Official's code
Function	M	CC @ResultsFunction	Official's function. Send according to the codes, the referee etc.
Order	M	Numeric	Send by order for each official in each function, for example: Referee(s) followed by Reserve Referee(s), if more than one referees then sort by name.

Element: Officials /Official /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the official
Organisation	M	CC @Organisation	Officials' organisation
IFId	O	S(16)	International Federation ID

Element: Periods (0,1)			
Attribute	M/O	Value	Description
Home	M	S(20) with no leading zeroes	Home Competitor ID
Away	M	S(20) with no leading zeroes	Away Competitor ID

Element: Periods /Period (1,N)			
Period in which the event unit message arrives.			
Attribute	M/O	Value	Description
Code	M	SC @Period	Period code
HomeScore	M	Numeric ##0	Overall score of the home competitor at the end of the period.
AwayScore	M	Numeric ##0	Overall score of the away competitor at the end of the period.
HomePeriodScore	O	Numeric #0	Score of the home competitor for this period.
AwayPeriodScore	O	Numeric #0	Score of the away competitor for this period

Element: Result (1,N)			
For each Event Unit Results message, there must be at least one competitor with a result element in the event unit.			
Attribute	M/O	Value	Description
Result	O	Numeric ##0	Result of the Team for the particular event unit.
IRM	O	SC @IRM	The invalid rank mark, in case it is assigned. IRM of the Team for the particular event unit Send just in the case @ResultType both Points and IRM
WLT	O	SC @WLT	The code whether a competitor won, lost or tied
SortOrder	M	Numeric	This attribute is a sequential number with the order of the First named (1) and the Visitor (2)
StartOrder	M	Numeric	Send 1 for first named team, send 2 for second named team
StartSortOrder	M	Numeric	Same @StartOrder
ResultType	O	SC @ResultType	Type of the @Result attribute.

Element: Result /Competitor (1,1)			
Competitor related to the result of one event unit.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or TBD	Competitor's ID or TBD in case that the competitor is unknown at this time but will be available
Type	M	S(1)	T for team
Organisation	O	CC @Organisation	Competitor's organisation

Element: Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	O	S(73)	Name of the team

Element: Result /Competitor /Coaches /Coach (1,N)			
Competitor's Coach			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Official code.
Order	M	Numeric	Coach order (if more than one coach is needed). Send 1 if just one coach, sequential number if more than one
Function	M	CC @ResultsFunction	Coach functions

Element: Result /Competitor /Coaches /Coach /Description (1,1)
Coach extended information.

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the official
Nationality	M	CC @Country	Coach's nationality

Element: Result /Competitor /EventUnitEntry (0,N)

Type	Code	Pos	Description
EUE	HOME_AWAY	N/A	Element Expected: When available
	Attribute	M/O	Value
	Value	O	SC @Home

Sample

```
....
<EventUnitEntry Type="EUE" Code="HOME_AWAY" Value="AWAY" />
....
```

Element: Result /Competitor /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
ST	SD W LD PTY FB BT SHOT	SC @Period	Pos Description: Send the period. TOT for total of all periods Element Expected: Always, if the information is available
Attribute	M/O	Value	Description
Value	O	Numeric #0	Number of shots for each of 6 metres / Wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs and Total Shots / Penalties in the event unit.
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	BLC		
Pos	N/A	N/A	
Value	S(3)	Total Blocked. If doesn't apply send "N/A"	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	GOAL		
Pos	N/A	N/A	
Value	Numeric #0	Total goals.	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	MISS		
Pos	N/A	N/A	
Value	Numeric #0	Total Missed.	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	

Element: Result /Competitor /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
Value	Numeric ##0	Shooting percentage (%)	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	POST		
Pos	N/A	N/A	
Value	Numeric #0	Total Post.	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric #0	Total Saves.	
ST	TL ML BL TC MC BC TR MR BR	SC @Period	Pos Description: Send the period TOT for total of all periods Element Expected: Always, if the information is available
Attribute	M/O	Value	Description
Value	O	Numeric #0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots in the event unit.
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	GOAL		
Pos	N/A	N/A	
Value	Numeric #0	Total goals for this destination	

Element: Result /Competitor /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
ST	ASSIST TO ST BLC YC RC EXC TFT	SC @Period	Pos Description: Send the period TOT for total of all periods Element Expected: Always, if the information is available	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Total assists/ Turnovers /steals/blocked/ yellow cards/ red cards/Exclusions BenchTeam TOs in the event unit.
ST	TO_TEAM	N/A	Element Expected: Always, if the information is available	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Total turnovers bench/team in the event unit
ST	EXC_COACH RC_COACH YC_COACH	N/A	Element Expected: Always, if the information is available	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Yellow cards/Red cards/Exclusions for the Coach in the event unit.
ST	TMS_COACH	N/A	Element Expected: Always, if the information is available	
	Attribute	M/O	Value	Description
	Value	O	S(3)	2 Minute Suspensions for the Coach in the event unit. Send + for "2 minutes + 2 minutes suspensions".
ST	TMS	SC @Period	Pos Description: Send the period TOT for total of all periods Element Expected: Always, if the information is available	
	Attribute	M/O	Value	Description
	Value	O	S(3)	2 Minute Suspensions in the event unit. Send + for "2 minutes + 2 minutes suspensions"

Element: Result /Competitor /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
ST	ATC	SC @Period	Pos Description: Send the period Element Expected: Always, if the information is available
Attribute	M/O	Value	Description
Value	O	Numeric #0	Total Attacks for the team in the event unit.
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric ##0	Scoring Efficiency.	
ST	SHOT_GK SD_GK W_GK LD_GK PTY_GK FB_GK BT_GK (Only Goalkeepers)	SC @Period	Code Description: Only for Goalkeepers Pos Description: Send the period TOT for total of all periods Element Expected: Always, if the information is available
Attribute	M/O	Value	Description
Value	O	Numeric #0	Total shots / 6 metres / wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs shots for the Goalkeepers in the event unit.
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric #0	Efficiency (%).	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	

Element: Result /Competitor /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
Value	Numeric #0	Total saves.		
ST	TL_GK ML_GK BL_GK TC_GK MC_GK BC_GK TR_GK MR_GK BR_GK (Only Goalkeepers)	SC @Period	Code Description: Only for Goalkeepers Pos Description: Send the period TOT for total of all periods (only for Teams statistics) Element Expected: Always, if the information is available	
	Attribute	M/O	Value	Description
Value	O	Numeric #0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots for the Goalkeepers in the event unit.	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat				
Expected: Always, if the information is available				
Attribute	Value	Description		
Code	SAVE			
Pos	N/A	N/A		
Value	Numeric #0	Total save for this destination		

Element: Result /Competitor /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
BEACH	SHOT FIELD SPC INF SPN 6MP DGK	N/A	Pos Description: N/A Element Expected: Always, if the information is available for beach	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Number of shots for each of Total, Field, Specialist, In-Flight, Spin Shot, 6 metre Penalty, Goalkeeper Direct Goal
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available				
	Attribute	Value	Description	
	Code	GOAL		
	Pos	N/A	N/A	
	Value	Numeric #0	Goals (successful attempts)	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for total shots				
	Attribute	Value	Description	
	Code	PERCENT		
	Pos	N/A	N/A	
	Value	Numeric ##0	Shooting percentage (%) for total only	
BEACH	POINTS	N/A	Pos Description: N/A Element Expected: Always, if the information is available for beach	
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total goal points

Element: Result /Competitor /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
BEACH	SUS RC DR	N/A	Pos Description: N/A Element Expected: Always, if the information is available in beach	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Total suspensions, Red Cards and DQ with Report
BEACH	SUS_COACH RC_COACH DR_COACH	N/A	Element Expected: Always, if the information is available for beach	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Total suspensions, Red Cards and DQ with Report for the Bench or Team

Sample

```

....
<StatsItems>
  <StatsItem Type="ST" Code="LD" Pos="H1" Value="12">
    <ExtendedStat Code="GOAL" Value="4" />
    <ExtendedStat Code="SAVE" Value="2" />
    <ExtendedStat Code="MISS" Value="1" />
    <ExtendedStat Code="POST" Value="2" />
    <ExtendedStat Code="BLC" Value="2" />
    <ExtendedStat Code="PERCENT" Value="48" />
  </StatsItem >
....
  <StatsItem Type="ST" Code="ASSIST" Pos="H1" Value="16" />
  < StatsItem Type="ST" Code="TO" Pos="H1" Value="23" />
  <StatsItem Type="ST" Code="ST" Pos="H1" Value="3" />
  <StatsItem Type="ST" Code="BLC" Pos="H1" Value="4" />
  <StatsItem Type="ST" Code="YC" Pos="H1" Value="4" />
  <StatsItem Type="ST" Code="TMS" Pos="H1" Value="7" />
  <StatsItem Type="ST" Code="SHOT" Pos="H1" Value="24">
    <ExtendedStat Code="GOAL" Value="15" />
    <ExtendedStat Code="PERCENT" Value="63" />
  </StatsItem>
  <StatsItem Type="ST" Code="SD" Pos="H1" Value="1">
    <ExtendedStat Code="GOAL" Value="0" />
    <ExtendedStat Code="PERCENT" Value="0" />
  </StatsItem>
....

```


Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.
Order	M	Numeric #0	Order attribute used to sort team members in a team. Before the game starts it is the same as StartSortOrder, after the game starts then sort by Uniform number.
StartSortOrder	M	Numeric #0	Sort first goalkeepers by Uniform number then rest of the team by uniform number.
Bib	M	S(2)	Shirt number

Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)			
Individual athletes entry information.			
Type	Code	Pos	Description
EUE	STATUS	N/A	Element Expected: As soon as it is known
	Attribute	M/O	Value
	Value	O	SC @AthleteStatus Athlete's status in the team. When the athlete has been Suspended, replaced or disqualified.
EUE	POSITION	N/A	Element Expected: As soon as known
	Attribute	M/O	Value
	Value	O	CC @Position Position player in the team.

Sample

```
<Athlete Code="1125142" Bib="8" Order="4">
  <Description GivenName="Jane" FamilyName="Smith" Gender="F" Organisation="RSA" BirthDate="1992-12-15" />
  <EventUnitEntry Type="EUE" Code="POSITION" Value="GK" />
```

Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
ST	SHOT	N/A	Element Expected: Always, if the information is available team
Attribute	M/O	Value	Description
Value	O	Numeric #0	Total Shots/penalties on goals in the event unit.
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	BLC		
Pos	N/A	N/A	
Value	S(3)	Total Blocked. If doesn't apply send "N/A"	
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	GOAL		
Pos	N/A	N/A	
Value	Numeric #0	Total goals.	
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	MISS		
Pos	N/A	N/A	
Value	Numeric #0	Total Missed.	
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	PERCENT		

Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
Pos	N/A	N/A	
Value	Numeric ##0		Shooting percentage. Efficiency (%).
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	POST		
Pos	N/A	N/A	
Value	Numeric #0		Total Post.
ST	SD W LD PTY FB BT	N/A	Element Expected: Always, if the information is available
Attribute	M/O	Value	Description
Value	O	Numeric #0	Total 6 metres / Wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs in the event unit.
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for total			
Attribute	Value	Description	
Code	GOAL		
Pos	N/A	N/A	
Value	Numeric #0		Total goal.
ST	TL ML BL TC MC BC TR MR BR	N/A	Element Expected: Always, if the information is available
Attribute	M/O	Value	Description

Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
Value	O	Numeric #0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots in the event unit.	
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat				
Expected: Always, if the information is available				
Attribute	Value	Description		
Code	GOAL			
Pos	N/A	N/A		
Value	Numeric #0	Total goals for this destination		
ST	ASSIST TO ST BLC YC RC EXC	N/A	Element Expected: Always, if the information is available	
Attribute	M/O	Value	Description	
Value	O	Numeric #0	Total assists/ Turnovers /steals/blocked/ yellow cards/ red cards/Exclusions in the event unit.	
ST	TMS	N/A	Element Expected: Always, if the information is available	
Attribute	M/O	Value	Description	
Value	O	S(3)	2 Minute Suspensions in the event unit. Send + for "2 minutes + 2 minutes suspensions".	
ST	MINS	N/A	Element Expected: Always, if the information is available	
Attribute	M/O	Value	Description	
Value	O	m:ss	Time played for the athlete in the game.	
ST	SHOT_GK SD_GK W_GK LD_GK PTY_GK FB_GK BT_GK (For Goalkeepers)	N/A	Element Expected: Always, if the information is available (Only for Goalkeepers)	

Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
Attribute	M/O	Value	Description
Value	O	Numeric #0	Total shots / 6 metres / wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs shots for the Goalkeepers in the event unit.
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric #0	Efficiency (%)	
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric #0	Total saves.	
ST	TL_GK ML_GK BL_GK TC_GK MC_GK BC_GK TR_GK MR_GK BR_GK (For Goalkeepers)	N/A	Element Expected: Always, if the information is available for goalkeepers
Attribute	M/O	Value	Description
Value	O	Numeric #0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots for the Goalkeepers in the event unit.
Sub Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	

Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
Value	Numeric #0	Total save for this destination		
BEACH	SHOT FIELD SPC INF SPN 6MP DGK	N/A	Pos Description: N/A Element Expected: Always, if the information is available for beach	
Attribute	M/O	Value	Description	
Value	O	Numeric #0	Number of shots for each of Total, Field, Specialist, In-Flight, Spin Shot, 6 metre Penalty, Goalkeeper Direct Goal	
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available				
Attribute	Value	Description		
Code	GOAL			
Pos	N/A	N/A		
Value	Numeric #0	Goals (successful attempts)		
Sub Element: Result /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for total shots				
Attribute	Value	Description		
Code	PERCENT			
Pos	N/A	N/A		
Value	Numeric ##0	Shooting percentage (%) for total only		
BEACH	POINTS	N/A	Pos Description: N/A Element Expected: Always, if the information is available for beach	
Attribute	M/O	Value	Description	
Value	O	Numeric ##0	Goal points	

Element: Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
BEACH	SUS RC DR	N/A	Pos Description: N/A Element Expected: Always, if the information is available in beach	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Suspensions, Red Cards and DQ with Report

Sample

```

....
<StatsItems>
  <StatItems Type="ST" Code="LD" Value="12">
    <ExtendedStat Code="GOAL" Value="4" />
    <ExtendedStat Code="SAVE" Value="2" />
    <ExtendedStat Code="MISS" Value="1" />
    <ExtendedStat Code="POST" Value="2" />
    <ExtendedStat Code="BLC" Value="2" />
    <ExtendedStat Code="PERCENT" Value="48" />
  </StatItems>
</StatsItems>
...
  <StatItems Type="ST" Code="ASSIST" Value="1" />
  <StatItems Type="ST" Code="TO" Value="2" />
  <StatItems Type="ST" Code="ST" Value="3" />
  <StatItems Type="ST" Code="BLC" Value="4" />
  <StatItems Type="ST" Code="YC" Value="4" />
  <StatItems Type="ST" Code="SHOT" Value="4">
    <ExtendedStat Code="GOAL" Value="1" />
    <ExtendedStat Code="PERCENT" Value="63" />
  </StatItems>
  <StatItems Type="ST" Code="SD" Value="1">
    <ExtendedStat Type="SD" Code="GOAL" Value="0" />
    <ExtendedStat Type="SD" Code="PERCENT" Value="0" />
  </StatItems>

```

2.2.4.5 Message Sort

Sort by Result @SortOrder

2.2.5 Play by Play

2.2.5.1 Description

The Play by Play is a message containing official raw data from the results provider for each action.

The message contains a generic definition that can be used to provide results data of different nature as well as all of the actions in a unit.

2.2.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	RSC of the unit
DocumentSubcode	Not used	Not used
DocumentType	DT_PLAY_BY_PLAY	Play by Play message
DocumentSubtype	S(8)	Send "ACTION"
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Possible values are: START_LIST (only used if there are actions before the start) LIVE (used during the competition when nothing else applies) INTERMEDIATE UNOFFICIAL OFFICIAL (when results official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.5.3 Trigger and Frequency

This message is sent:

- LIVE: After every action
- LIVE: At the start of every period/extra time
- INTERMEDIATE: After each period (if it is not the last period)
- UNOFFICIAL/OFFICIAL: After the match (unit)

2.2.5.4 Message Values

Element: ExtendedInfos /SportDescription (0,1)			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes
SubEventName	M	S(40)	Text short description of the Event Unit, not code
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: ExtendedInfos /VenueDescription (0,1)			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location short name (not code) from Common Codes

Element: Actions (0,1)			
Attribute	M/O	Value	Description
Home	M	S(20) with no leading zeroes	Home Competitor ID
Away	M	S(20) with no leading zeroes	Away Competitor ID

Element: Actions /Action (1,N)			
Attribute	M/O	Value	Description
Id	M	S(36)	Unique identifier for the action within the message
PId	O	S(36)	If this is a related action then the ID of the original action appear here.
Period	M	SC @Period	Period of the action within the match
Order	M	Numeric	Unique sequential number for all of the actions from 1 to n. It is used to sort Action
Action	O	SC @Action	Actions in the game. Send one action code. The first action of each period should always be "STARTP". For GK substituted action send two Athlete Elements: 1st GK Out (ActionRole=OUT), 2nd GK In (ActionRole=IN).
ActionAdd	O	SC @DestType	Shot destination: Top Left, Top Right ..., and Bottom Left. In case of goal or shots saved. For shots only
When	O	mm:ss	Time in which the action occurred. Action's time in minutes and seconds Example (2:05). No leading zeros.
Result	O	SC @ResAction	Result of the Action for the player/team
ScoreH	O	Numeric ##0	Total Home Score of the game after the action Send if there is a score change for either team
ScoreA	O	Numeric ##0	Total Away Score of the game after the action Send if there is a score change for either team
LeadH	O	Numeric +/-#0	Points lead for the Home Team. Send if there is a score change for either team. (may be negative)
LeadA	O	Numeric +/-#0	Points lead for the Away Team. Send if there is a score change for either team. (may be negative)
SO_H	O	Numeric #0	Home Score in penalty shootout
SH_A	O	Numeric #0	Away Score in penalty shootout
Loc	O	SC @Res_Sub	Shot position (type of shot)
X	O	S(20)	X coordinate of the action location (only for shots)

Element: Actions /Action (1,N)			
Attribute	M/O	Value	Description
Y	O	S(20)	Y coordinate of the action location (only for shots)
TimeStamp	O	DateTime	Time of the action (for alignment to video)

Element: Actions /Action /Competitor (0,N) Competitor participating in the Action. Used when the Action is related to a competitor.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team
Order	O	Numeric	Order in which the competitor should appear for the action, if there is more than one competitor
Organisation	M	CC @Organisation	Competitors' organisation

Element: Actions /Action /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID (individual athlete or team member) related to the action
Order	O	Numeric	Order of the athletes. Used to order the athletes when there are more than one athlete related to the action.
Bib	O	S(2)	Shirt Number
Role	O	SC @ActionRole	Role of the player in the action, according to the available codes.

Element: Actions /Action /Competitor /Composition /Athlete /Description (1,1) Athletes extended information			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: UnitActions /UnitAction /Competitor /Coaches /Coach (1,N)			
Attribute	M/O	Value	Description
Code	O	S(20) with no leading zeroes	Official code. This code is normally expected though there may be rare exceptions.
Order	O	Numeric	Coach order (if more than one coach is needed).

Element: UnitActions /UnitAction /Competitor /Coaches /Coach /Description (1,1)			
Coach extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the official
Nationality	M	CC @Country	Coach's nationality

Sample

```
<Action Id="123456" Period="H1" Order="3" Action="SHOT" When="2:14" Result="SAVE" ActionAdd="ML"
LocA="LLD">
  <Competitor Code="HBLWTEAM7-----RSA01" Type="T" Organisation="RSA" Order="1">
    <Description TeamName="South Africa"/>
    <Composition>
      <Athlete Code="1106655" Order="1" Bib="17" >
        <Description GivenName="Jane" FamilyName="Smith" Gender="F" Organisation="RSA"
BirthDate="1993-05-12" />
      </Athlete>
    </Composition>
  </Competitor>
</Action>
```

2.2.5.5 Message Sort

Actions /Action @Order followed by @Pos

2.2.6 Current Information

2.2.6.1 Description

The Current message is a message containing the current information in a competition which is live. The message is used to send the latest applicable information and in team with a running clock, also the clock.

2.2.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	
DocumentSubcode	Not used	Not used
DocumentType	DT_CURRENT	Current message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.6.3 Trigger and Frequency

- At the start and end of every period (to start/stop clock)
- Immediately after every change in the score.
- Every time the clock starts and stops
- During play i.e. after start and not during breaks in play, every 30 seconds after the last DT_CURRENT message when there is no other activity triggering this message.

2.2.6.4 Message Values

Element: Clock (0,1)			
Attribute	M/O	Value	Description
Period	O	SC @Period	Current Period if the information is available automatically from the timing device.
Time	M	mm:ss	Value of the clock
Running	M	S(1)	Indicates if the clock is currently running. Y to indicate the clock is running; N to indicate the clock is stopped.

Element: Periods (0,1)			
Attribute	M/O	Value	Description
Home	M	S(20) with no leading zeroes	Home Competitor ID
Away	M	S(20) with no leading zeroes	Away Competitor ID

Element: Periods /Period (1,N)			
Period in which the event unit message arrives.			
Attribute	M/O	Value	Description
Code	M	SC @Period	Period code
HomeScore	M	Numeric ##0	Overall score of the home competitor (first named competitor) at the end of the period (or during if not finished)
AwayScore	M	Numeric ##0	Overall score of the away competitor (second named competitor) at the end of the period (or during if not finished)
HomePeriodScore	M	Numeric #0	Score of the home competitor (first named competitor) just for this period.
AwayPeriodScore	M	Numeric #0	Score of the away competitor (second named competitor) just for this period.

Sample

```
<Competition>  
  <Clock Period="H1" Time="1:34" Running="Y" />  
  <Periods Home="HBLWTEAM7---RSA01" Away="BKBWTEAM5-----NZL01" >  
    <Period Code="H1" AwayPeriodScore="13" HomePeriodScore="10" AwayScore="13" HomeScore="10"/>  
  </Periods>  
</Competition>
```

2.2.6.5 Message Sort

Sort by Period @Code.

2.2.7 Pool Standings

2.2.7.1 Description

The pool standings message contains the standings of a group in a competition. It is similar to the Phase Results message, except in the frequency and trigger. Here the message is triggered at the start of OVR operations and then after each event unit (match).

This report is sent independently for each of the groups / pools of the competition in a particular phase, and the group / pool can be determined from the message header (DocumentCode).

2.2.7.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (for the group)	RSC for the pool/group
DocumentType	DT_POOL_STANDING	Pool Standings message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: INTERMEDIATE (before and during the phase) UNOFFICIAL (if last match is unofficial) OFFICIAL (after all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.7.3 Trigger and Frequency

The general rule is that this message is sent:

- Before the start of the competition to build in the initial tables. The message has status INTERMEDIATE.
- When an event unit of the corresponding phase finishes (not waiting for official). The message has status INTERMEDIATE.
- When the phase finishes (there are no more event units/games to compete). The message has status OFFICIAL.

Trigger also after any change.

2.2.7.4 Message Values

Element: ExtendedInfos /ExtendedInfo (0,N)				
Type	Code	Pos	Description	
UI	LAST_UNIT	N/A	Element Expected: After at least one unit is complete.	
	Attribute	M/O	Value	Description
	Value	M	CC @Unit	Send the full RSC of the most recently unit made official for the pool included in this message.
UI	UNITS_TOTAL	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Total number of units (games) to be played in the pool included in the message.
UI	UNITS_COMPLETE	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Total number of units (games) which are official in the pool included in this message.

Element: ExtendedInfos /SportDescription (0,1) Sport Descriptions in Text.				
Attribute	M/O	Value	Description	
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes	
EventName	M	S(40)	Event name (not code) from Common Codes	
SubEventName	M	S(40)	Text short description of the Event Phase, not code	
Gender	M	CC @DisciplineGender	Gender code for the event unit	

Element: Result (1,N)			
For any message, there should be at least one competitor being awarded a result for the pool.			
Attribute	M/O	Value	Description
Rank	O	Text	Rank at the group. It is optional because the team can be disqualified
RankEqual	O	S(1)	Send "Y" if the Rank is equalled else do not send.
ResultType	M	SC @ResultType	Type of the @Result attribute, either points or IRM with points obtained by the competitor at all the games of the group
Result	O	Numeric or CANCELLED	Send the classification points a team has accrued during the pool stage. Optional as not available before the competition. Send "CANCELLED" in case of team disqualification during the Pool Round.
IRM	O	SC @IRM	The invalid rank mark, if applicable
SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the group, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified teams. Initially by Draw number, later when competition starts order by Rank Always starts at 1.
Won	O	Numeric #0	Number of games won by the team in the group. Do not send if the team has not played.
Lost	O	Numeric #0	Number of games lost by the team in the group. Do not send if the team has not played.
Tied	O	Numeric #0	Number of games tied by the team in the group. Do not send if the team has not played.
Played	O	Numeric #0	Number of games played by the team in the group Do not send if the team has not played.
For	O	Numeric #0	Total number of goals for (goal points in beach). Do not send if the team has not played.
Against	O	Numeric #0	Total number of goals against (goal points in beach). Do not send if the team has not played.
Diff	O	Numeric ##0 or -##0	Points difference, between goals for and goals against (goal points in beach)

Element: Result / ExtendedResults /ExtendedResult (1,N)			
Only applicable in Beach Handball			
Type	Code	Pos	Description
ER	PERIODS	N/A	Pos Description: Do not send anything Element Expected: When available
Sub Element: Result /ExtendedResults /ExtendedResult /Extension			
Expected: When available			
Attribute	Value	Description	
Code	LOST		
Pos	N/A	Do not send anything	
Value	Numeric ##0	Periods lost	
Sub Element: Result /ExtendedResults /ExtendedResult /Extension			
Expected: When available			
Attribute	Value	Description	
Code	DIFF		
Pos	N/A	Do not send anything	
Value	##0 or -##0	Different between periods won and periods lost.	
Sub Element: Result /ExtendedResults /ExtendedResult /Extension			
Expected: When available			
Attribute	Value	Description	
Code	WON		
Pos	N/A	Do not send anything	
Value	Numeric ##0	Periods won	

Element: Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team
Organisation	M	CC @Organisation	Competitor's organisation

Element: Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team.

Element: Result /Competitor /Opponent (0,N)				
Details of the opposing competitor in competitions within the pool. (The Opponent of the competitor in the Opponent @Pos column of the Pool)				
Type		Code	Pos	Description
T for team		S(20) with no leading zeroes	Numeric	Code Description: Competitor ID or TBD if unknown Pos Description: 1 to n. Normally expected to be the same as SortOrder for the same competitor. Element Expected: Always
Attribute	M/O	Value	Description	
Organisation	M	CC @Organisation	Competitors' organisation (code). Must include if the data is available	
Date	M	Date	Date of match between the competitor and opponent (example: YYYY-MM-DD). Must include if the data is available, send even after the match is complete.	
Time	O	S(5)	Time of match (example HH:MM) Must include if the data is available.	
Unit	O	CC @Unit	Full RSC of the Unit for the Pool Item	
HomeAway	O	S(1)	Home / Away indicator. Send H if the opponent is the home team, send A if the opponent is the away team.	
Result	O	S(50)	Result of the match if match is complete and formatted as in ORIS (separator & order, example 31-16). Must include if the data is available and the match is complete. The order of the result data is relative to the competitor and may be reversed for other competitor or depending on home/away display rules. May be "Cancelled" or other appropriate term.	

Element: Result /Competitor /Opponent /Description (0,1)				
Competitors extended information.				
Attribute	M/O	Value	Description	
TeamName	M	S(73)	Name of the opposition team.	

Sample

```
<Result Rank="3" ResultType="POINTS" Result="1" SortOrder="3" Played="2" Won="1" Tied="0" Lost="1"
For="63" Against="81" Diff="-38" >
  <Competitor Code="HBLMTEAM7-----EGY01" Type="T" Organisation="EGY">
    <Description TeamName="Egypt"/>
    <Opponent Code="HBLMTEAM7-----BRA01" Type="T" Pos="1" Organisation="BRA" Date="2012-07-27"
Time="14:00" Unit="HBLMTEAM7-----GPA-000200--" HomeAway="H" Result="42:40">
      <Description TeamName="Brazil"/>
    </Opponent>
    <Opponent Code="HBLMTEAM7-----BLR01" Type="T" Pos="2" Organisation="BLR" Date="2012-08-01"
Time="09:00" Unit="HBLMTEAM7-----GPA-000400--" HomeAway="A" >
      <Description TeamName="Belarus"/>
    </Opponent>
    <Opponent Code="HBLMTEAM7-----NZL01" Type="T" Pos="4" Organisation="NZL" Date="2012-07-29"
Time="09:00" Unit="HBLMTEAM7-----GPA-000500--" HomeAway="A" Result="21:41">
      <Description TeamName="New Zealand"/>
    </Opponent>
  </Competitor>
</Result>
```

2.2.7.5 Message Sort

The attribute used to sort the results is Result @SortOrder.

2.2.8 Brackets

2.2.8.1 Description

The brackets message contains the brackets information for one particular event. It is used in events where there is a necessity to know in advance how successive event units will be filled as the competition progresses. In the early stages of the competition, it indicates how each of the event units will be built from the winners/losers, or other competition rules of the previous event units.

2.2.8.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (event level)	Full RSC of the Event
DocumentType	DT_BRACKETS	Brackets message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: INTERMEDIATE (during the competition) UNOFFICIAL (when last match unofficial) OFFICIAL (when all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.8.3 Trigger and Frequency

- Before the competition.
- After every match in the preliminaries which determines a position in the bracket.
- After every match during final phases.
- Trigger after any change

2.2.8.4 Message Values

Element: ExtendedInfos /SportDescription (0,1) Sport Description in Text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes.
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: Bracket (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @Bracket	Bracket code to identify a bracket item. One for each individual bracket as defined in ORIS.

Element: Bracket /BracketItems (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @BracketItems	Bracket code to identify a set of bracket items. The quarterfinals, semifinals or finals phases etc.

Element: Bracket /BracketItems /BracketItem (1,N)			
Attribute	M/O	Value	Description
Code	O	Numeric #0	Bracket code to identify a bracket item. Unique identifier for the BracketItem. The game number for each bracket item (e.g.: 17, 18, 19, 20,...)
Order	M	Numeric	Sequential number inside of BracketItems to indicate the order, always start at 1
Date	O	Date	YYYY-MM-DD. Must be filled if known
Time	O	S(5)	HH:MM. Must be filled if known
Unit	O	CC @Unit	Full RSC of the unit for the BracketItem
Result	O	S(50)	Fill when match is complete, filled and formatted in the same format as in ORIS (example "26-27"). May include an IRM.
NextUnit	O	CC @Unit	Full RSC of the unit where the successful competitor will progress
NextUnitLoser	O	CC @Unit	Full RSC of the unit where the unsuccessful competitor will progress

Element: Bracket /BracketItems /BracketItem /CompetitorPlace (1,N)			
- If the competitors are known, this element is used to place the competitors in the bracket.			
- If they are not yet known, it contains some information (on the rule to access to this bracket...)			
Attribute	M/O	Value	Description
Pos	M	Numeric 0	This attribute is a sequential number to place the competitors in the bracket (1 or 2).
Code	O	SC @CompetitorPlace	Sent when there is no competitor team (BYE) or when it is not known yet (TBD).
WLT	O	SC @WLT	W or L, indicates the winner or loser of the bracket item. Always send when known.
Result	O	S(10)	The result (score) of the competitor in the event unit
IRM	O	SC @IRM	The invalid rank mark, if applicable

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /PreviousUnit (0,1)
Previous event unit related to the CompetitorPlace@Pos competitor of the current bracket item. It is always informed except for the bracket items whose CompetitorPlace@Pos competitor do not have preceding event units in the bracket graph unless coming from a pool.

Attribute	M/O	Value	Description
Unit	O	Full RSC at unit level	Full RSC code of the previous event unit for the CompetitorPlace@Pos competitor of the bracket item. Must send if a winner/loser from a single unit. Not sent when from group.
Value	O	SC @Pool	If there is no competitor team (TBD) and coming from Pool then send appropriate code.
WLT	O	S(1)	Send W or L for winner or loser of previous match (if not Pool) do not send if participant is unknown from a pool.

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor (0,1)
CompetitorPlace @Pos competitor related to the bracket item. Only include if the competitor is known .

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team
Organisation	O	CC @Organisation	Competitors' organisation if known

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Description (0,1)

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team.

Sample

```
<Bracket Code="FNL-">
  <BracketItems Code="SFNL">
    <BracketItem Code="33" Order="1" Date="2012-08-10" Time="15:00" Unit="HBLWTEAM7-----
SFNL000100--" Result="25-22" NextUnit=" HBLWTEAM7-----FNL-000100--" NextUnitLoser=" HBLWTEAM7---
-----FNL-000200--">
      <CompetitorPlace Pos="1" Result="25" WLT="W" >
        <Competitor Code="HBLWTEAM7-----NED01" Type="T" Organisation="NED">
          <Description TeamName="Netherlands"/>
        </Competitor>
      </CompetitorPlace>
      <CompetitorPlace Pos="2" Result="22" WLT="L" >
        <Competitor Code="HBLWTEAM7-----NZL01" Type="T" Organisation="NZL">
          <Description TeamName="New Zealand"/>
        </Competitor>
      </CompetitorPlace>
    </BracketItem>
```

2.2.8.5 Message Sort

Bracket @Code then BracketItems @Code then BracketItems /BracketItem /Unit @Phase and then BracketItem /Unit @Unit are sorted according to their scheduled start time.

2.2.9 Statistics

2.2.9.1 Description

The Statistics message contains a list of statistics for a competitor (could be an individual athlete or a team), that applies at a DocumentCode level, which could be for an event unit, a phase or an event.

There will be a separate message (identified by the header's DocumentSubtype and DocumentSubcode) for every table where multiple statistics apply.

2.2.9.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Depending on the statistics is could be at any level though is always full RSC.
DocumentSubcode	The DocumentSubcode is the NOC concatenated with the Team Number, e.g. BRA1.	Used for DocumentSubtype = CUM
DocumentType	DT_STATS	Statistics message
DocumentSubtype	CUM TEAM_RANKING IND_RANKING TOU	-CUM: For cumulative data of individual player statistics and team statistics. There will be one single message for each team. (see DocumentSubcode) -TEAM_RANKING: Ranking of team tournament statistics. -IND_RANKING: Ranking of individual tournament statistics, for the best athletes. -TOU: Tournament statistics.
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	It indicates whether the result is official or intermediate etc). LIVE (used during the competition when nothing else applies) INTERMEDIATE (used after the competition has started and is not finished but not currently live, typically between units) OFFICIAL (after the last unit which effects the statistics is official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.9.3 Trigger and Frequency

After each match

2.2.9.4 Message Values

Element: ExtendedInfos /ExtendedInfo (0,N)				
Type	Code	Pos	Description	
UI	LAST_UNIT	N/A	Element Expected: After at least one unit is complete in the CUM, IND_RANKING and TEAM_RANKING messages.	
	Attribute	M/O	Value	Description
	Value	M	CC @Unit	Send the RSC of the most recently unit made official. For CUM which only includes one team then it is the last unit for that team.
UI	UNITS_TOTAL	N/A	Element Expected: Always in the CUM, IND_RANKING and TEAM_RANKING messages.	
	Attribute	M/O	Value	Description

Element: ExtendedInfos /ExtendedInfo (0,N)				
	Type	Code	Pos	Description
	Value	M	Numeric ##0	Send the total number of units (games) to be played). For CUM which only includes one team then it is the total units for that team.
UI		UNITS_COMPLETE	N/A	Element Expected: Always in the CUM, IND_RANKING and TEAM_RANKING messages.
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Send the total number of units (games) which are official. For CUM which only includes one team then it is the total complete units for that team.

Element: ExtendedInfos /SportDescription (0,1)			
Sport Description in Text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes.
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: Stats (1,1)			
Attribute	M/O	Value	Description
Code	M	SC @Statistics	A code to identify the statistics being listed

Element: Stats /StatsItems /StatsItem (1,N)			
Type	Code	Pos	Description
ST	SHOT SD W LD PTY FB BT	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=TOU
	Attribute	M/O	Value
	Value	O	Numeric ##0
	Description		
	Total Shots / 6 metres / Wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs shots for team.		
	Sub Element: Stats /StatsItems /StatsItem /ExtendedStat		
	Expected: Always, if the information is available for the DocumentSubtype=TOU		
	Attribute	Value	Description
	Code	GOAL	
	Pos	N/A	N/A
	Value	Numeric ##0	Total goals.
	Sub Element: Stats /StatsItems /StatsItem /ExtendedStat		
	Expected: Always, if the information is available for the DocumentSubtype=TOU		
	Attribute	Value	Description
	Code	PERCENT	
	Pos	N/A	N/A
	Value	Numeric ##0	Shooting percentage Efficiency (%).
ST	ASSIST TO ST BLC YC RC EXC	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=TOU
	Attribute	M/O	Value
	Value	O	Numeric ##0
	Description		
	Total assists, turnovers / steals / blocked / yellow cards / red cards / Exclusions for the team.		

Element: Stats /StatsItems /StatsItem (1,N)				
Type	Code	Pos	Description	
ST	TMS	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=TOU	
	Attribute	M/O	Value	Description
	Value	O	S(3)	2 Minute Suspensions for the team. Send + for "2 minutes + 2 minutes suspensions"
ST	SHOT_GK SD_GK W_GK LD_GK PTY_GK FB_GK BT_GK	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=TOU	
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total shots / 6 metres / wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs for the Goalkeepers.
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype= TOU				
	Attribute	Value	Description	
	Code	PERCENT		
	Pos	N/A	N/A	
	Value	Numeric ##0	Efficiency (%).	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype= TOU				
	Attribute	Value	Description	
	Code	SAVE		
	Pos	N/A	N/A	
	Value	Numeric ##0	Total saves.	

Element: Stats /Competitor (0,N) Competitor of the statistics.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID to be assigned a specific type of statistic.
Type	M	S(1)	T for team
Order	M	Numeric ##0	Sort order for TEAM_RANKING: For each team: 1 -Rank, 2 -Team NOC code If teams share equal rank, present teams in alphabetical order by team NOC code Always show rank for each team
Organisation	O	CC @Organisation	Competitor's organisation if known

Element: Stats /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams / groups.

Element: Stats /Competitor /StatsItems /StatsItem (1,N) Team competitor's stats item, according to competitors' rules.			
Type	Code	Pos	Description
ST	SD W LD PTY FB BT SHOT	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM
	Attribute	M/O	Value
	Value	O	Numeric ##0
			Total 6 metres / Wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs / Total shots for the team.
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM			
	Attribute	Value	Description
	Code	BLC	
	Pos	N/A	N/A
	Value	S(3)	Total Blocked. If doesn't apply send "N/A"
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM			
	Attribute	Value	Description

Element: Stats /Competitor /StatsItems /StatsItem (1,N)			
Team competitor's stats item, according to competitors' rules.			
Type	Code	Pos	Description
Code	GOAL		
Pos	N/A	N/A	
Value	Numeric ##0		Total goal.
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	MISS		
Pos	N/A	N/A	
Value	Numeric ##0	Total Missed.	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric ##0	Shooting percentage (%).	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	POST		
Pos	N/A	N/A	
Value	Numeric ##0	Total Post.	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric ##0	Total Saves.	

Element: Stats /Competitor /StatsItems /StatsItem (1,N)			
Team competitor's stats item, according to competitors' rules.			
Type	Code	Pos	Description
ST	TOTAL	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=TEAM_RANKING
	Attribute	M/O	Value
	Value	O	Numeric ##0
	Rank	O	Numeric
	RankEqual	O	S(1)
	SortOrder	O	Numeric
ST	TL ML BL TC MC BC TR MR BR	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM
	Attribute	M/O	Value
	Value	O	Numeric #0
	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots for the teams.		
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available			
	Attribute	Value	Description
	Code	GOAL	
	Pos	N/A	N/A
	Value	Numeric #0	Total goals for this destination
ST	ASSIST ST BLC	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM
	Attribute	M/O	Value
	Value	O	Numeric ##0
	Total assists/ steals/ blocked for the team.		

Element: Stats /Competitor /StatsItems /StatsItem (1,N)				
Team competitor's stats item, according to competitors' rules.				
Type	Code	Pos	Description	
ST	TO YC RC EXC TFT	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total turnovers/ yellow cards/ red cards/ Exclusions for the team. Total turnovers bench/team
ST	TO_TEAM	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Total turnovers bench/team in the event unit
ST	EXC_COACH RC_COACH YC_COACH	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Yellow cards/Red cards/Exclusions for the Coach/Bench.
ST	TMS_COACH	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	
	Attribute	M/O	Value	Description
	Value	O	S(3)	2 Minute Suspensions for the Coach in the event unit. Send + for "2 minutes + 2 minutes suspensions".
ST	TMS	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	
	Attribute	M/O	Value	Description
	Value	O	S(3)	2 Minute Suspensions for the team. Send + for "2 minutes + 2 minutes suspensions"
ST	MP	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	

Element: Stats /Competitor /StatsItems /StatsItem (1,N)				
Team competitor's stats item, according to competitors' rules.				
Type	Code	Pos	Description	
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total match played for team.
ST	PTY_PTS	N/A	Element Expected: Always, if the information is available for the DocumentSubtype= TEAM_RANKING	
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Send Y in case the @Rank is an equalled
	Rank	O	String	Team's rank on penalty points.
	RankEqual	O	S(1)	Send Y in case the @Rank is an equalled rank else do not send
	SortOrder	O	Numeric	Sort Order for @Rank
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat				
Expected: Always, if the information is available for the DocumentSubtype= TEAM_RANKING				
	Attribute	Value	Description	
	Code	AVG		
	Pos	N/A	N/A	
	Value	Numeric #0.0	Average penalty points	
ST	SD_R_GRA SD_C_GRA SD_L_GRA W_R_GRA W_L_GRA LD_R_GRA LD_C_GRA LD_L_GRA PS_GRA FP_GRA BT_GRA	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM	
	Attribute	M/O	Value	Description
	Value	O	Numeric #0/#0	Right/Centre/Left 6 metres, Right/Left Wing, Right/Centre/Left 9 metres, 7 metres, Fast Breaks, Breakthroughs Goals/shots for the team.

Element: Stats /Competitor /StatsItems /StatsItem (1,N) Team competitor's stats item, according to competitors' rules.			
Type	Code	Pos	Description
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric #0/#0	Goals / saves.	
ST	SHOT_GK SD_GK W_GK LD_GK PTY_GK FB_GK BT_GK (For Goalkeepers)	N/A	Element Expected: Always for goalkeepers, if the information is available for the DocumentSubtype=CUM
Attribute	M/O	Value	Description
Value	O	Numeric ##0	Total shots / 6 metres / wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs shots for the Goalkeepers.
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric ##0	Efficiency (%).	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: For @Code: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric ##0	Total saves.	

Element: Stats /Competitor /StatsItems /StatsItem (1,N)			
Team competitor's stats item, according to competitors' rules.			
Type	Code	Pos	Description
ST	TL_GK ML_GK BL_GK TC_GK MC_GK BC_GK TR_GK MR_GK BR_GK (For Goalkeepers)	N/A	Element Expected: Always for goalkeepers, if the information is available for the DocumentSubtype=CUM
Attribute	M/O	Value	Description
Value	O	Numeric #0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Saves for the Goalkeepers.
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric #0	Total save for this destination	

Sample

```

<StatsItem Type="ST" Code="LD" Value="12">
  <ExtendedStat Code="GOAL" Value="4" />
  <ExtendedStat Code="SAVE" Value="2" />
  <ExtendedStat Code="MISS" Value="1" />
  <ExtendedStat Code="POST" Value="2" />
  <ExtendedStat Code="BLC" Value="2" />
  <ExtendedStat Code="PERCENT" Value="48" />
</StatsItem>
...
<StatsItem Type="ST" Code="ASSIST" Value="16" />
<StatsItem Type="ST" Code="TO" Value="23" />
<StatsItem Type="ST" Code="ST" Value="3" />
<StatsItem Type="ST" Code="BLC" Value="4" />
<StatsItem Type="ST" Code="YC" Value="4" />
<StatsItem Type="ST" Code="TMS" Value="7" />
<StatsItem Type="ST" Code="SHOT" Value="24">
  <ExtendedStat Code="GOAL" Value="15" />
  <ExtendedStat Code="PERCENT" Value="63" />
</StatsItem>
<StatsItem Type="ST" Code="SD" Value="1">
  <ExtendedStat Code="GOAL" Value="0" />
  <ExtendedStat Code="PERCENT" Value="0" />
</StatsItem>

```

Element: Stats /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Numeric ##0	Sort order for CUM: Uniform number or disqualification, family name , given name Sort order for IND_RANKING: 1 -Rank, 2 -family name, 3 -given name

Element: Stats /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)			
Team member's stats item according to competitors' rules.			
Type	Code	Pos	Description
ST	SHOT	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM and IND_RANKING
	Attribute	M/O	Value
	Value	O	Numeric ##0
	Rank	O	String
	RankEqual	O	S(1)
	SortOrder	O	Numeric
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM		
	Attribute	Value	Description
	Code	BLC	
	Pos	N/A	N/A
	Value	Numeric ##0	Total blocked.
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM and IND_RANKING		
	Attribute	Value	Description
	Code	GOAL	
	Pos	N/A	N/A

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)			
Team member's stats item according to competitors' rules.			
Type	Code	Pos	Description
Value	Numeric ##0		Total goals.
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	MISS		
Pos	N/A	N/A	
Value	Numeric ##0	Total misses.	
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM and IND_RANKING			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric ##0	Shooting percentage Efficiency (%).	
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM			
Attribute	Value	Description	
Code	POST		
Pos	N/A	N/A	
Value	Numeric ##0	Total post.	
ST	SD W LD PTY FB BT	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM. In the case of PTY also send when DocumentSubtype= IND_RANKING
Attribute	M/O	Value	Description
Value	O	Numeric ##0	Total 6 metres / Wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs shots for the athlete in the event unit.
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat			
Expected: Always, if the information is available for the DocumentSubtype=CUM. In the case of PTY also send when DocumentSubtype= IND_RANKING			

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Team member's stats item according to competitors' rules.				
Type	Code	Pos	Description	
ST	Attribute	Value	Description	
	Code	GOAL		
	Pos	N/A	N/A	
	Value	Numeric ##0	Total goals.	
		TL ML BL TC MC BC TR MR BR	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM
	Attribute	M/O	Value	Description
	Value	O	Numeric #0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots for the athlete
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat			
	Expected: Always, if the information is available			
	Attribute	Value	Description	
Code	GOAL			
Pos	N/A	N/A		
Value	Numeric #0	Total goals for this destination		
ST		ASSIST TO YC RC EXC	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM. In the case of ASSIST also send when DocumentSubtype= IND_RANKING
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total assists / turnovers / yellow cards / red cards / Exclusions for the athlete in the event unit.
	Rank	O	String	Athlete's rank on assists. Send for ASSIST only. (DocumentSubtype= IND_RANKING)

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Team member's stats item according to competitors' rules.				
	Type	Code	Pos	Description
	RankEqual	O	S(1)	Send Y in case the @Rank is an equalled rank else do not send. Send for ASSIST only. (DocumentSubtype= IND_RANKING)
	SortOrder	O	Numeric	Sort Order for @Rank Send for ASSIST only. (DocumentSubtype= IND_RANKING)
ST		ST BLC	N/A	Element Expected: Always, if the information is available for the DocumentSubtype= CUM and IND_RANKING
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total steals / blocked for the athlete in the event unit.
	Rank	O	String	Athlete's rank on steals/total blocked. (DocumentSubtype= IND_RANKING)
	RankEqual	O	S(1)	Send Y in case the @Rank is an equalled rank else do not send. (DocumentSubtype= IND_RANKING)
	SortOrder	O	Numeric	Sort Order for @Rank (DocumentSubtype= IND_RANKING)
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat			
	Expected: Always, if the information is available for the DocumentSubtype= IND_RANKING			
	Attribute	Value	Description	
	Code	AVG		
	Pos	N/A	N/A	
	Value	Numeric #0.0	Average.	
ST		TMS	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM and IND_RANKING
	Attribute	M/O	Value	Description
	Value	O	S(3)	2 Minute Suspensions for the athlete in the event unit. Send + for "2 minutes + 2 minutes suspensions"
ST		MINS	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM
	Attribute	M/O	Value	Description

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Team member's stats item according to competitors' rules.				
	Type	Code	Pos	Description
	Value	O	hh:mm:ss	Time played for the athlete in all games where the athlete was participated. Do not send leading zeros
ST		MP	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=CUM and IND_RANKING
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total matches played for athlete.
ST		GOAL_ASSIST	N/A	Element Expected: Always, if the information is available for the DocumentSubtype=IND_RANKING
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total goals shots + Assists.
	Rank	O	String	Athlete's rank on goals + assists.
	RankEqual	O	S(1)	Send Y in case the @Rank is an equalled rank else do not send.
	SortOrder	O	Numeric	Sort Order for @Rank
ST		PTY_PTS	N/A	Element Expected: Always, if the information is available for the DocumentSubtype= IND_RANKING
	Attribute	M/O	Value	Description
	Value	O	Numeric ##0	Total penalty points for the athlete.
	Rank	O	String	Athlete's rank on average penalty points.
	RankEqual	O	S(1)	Send Y in case the @Rank is an equalled rank else do not send.
	SortOrder	O	Numeric	Sort Order for @Rank
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat				
Expected: Always, if the information is available for the DocumentSubtype= IND_RANKING				
	Attribute	Value	Description	
	Code	AVG		
	Pos	N/A	N/A	
	Value	Numeric #0.0	Average.	

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N) Team member's stats item according to competitors' rules.			
Type	Code	Pos	Description
ST	SHOT_GK SD_GK W_GK LD_GK PTY_GK FB_GK BT_GK (For Goalkeepers)	N/A	Element Expected: Always for goalkeepers, if the information is available for the DocumentSubtype=CUM. In the case of SHOT_GK & PTY_GK also send when DocumentSubtype= IND_RANKING
Attribute	M/O	Value	Description
Value	O	Numeric #0	Total shots / 6 metres / wing / 9 metres / 7 metres / Fast Breaks / Breakthroughs for the Goalkeepers in the event unit.
Rank	O	String	Goalkeeper's rank on efficiency of saves for total shots/penalty saves. For SHOT_GK & PTY_GK only. (DocumentSubtype= IND_RANKING)
RankEqual	O	S(1)	Send Y in case the @Rank is an equalled rank else do not send. For SHOT_GK & PTY_GK only. (DocumentSubtype= IND_RANKING)
SortOrder	O	Numeric	Sort Order for @Rank. For SHOT_GK & PTY_GK only. (DocumentSubtype= IND_RANKING)
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM. In the case of SHOT_GK & PTY_GK also send when DocumentSubtype= IND_RANKING			
Attribute	Value	Description	
Code	PERCENT		
Pos	N/A	N/A	
Value	Numeric ##0	Efficiency (%).	
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available for the DocumentSubtype=CUM. In the case of SHOT_GK & PTY_GK also send when DocumentSubtype= IND_RANKING			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)
Team member's stats item according to competitors' rules.

Type	Code	Pos	Description
Value	Numeric ##0	Total saves.	
ST	TL_GK ML_GK BL_GK TC_GK MC_GK BC_GK TR_GK MR_GK BR_GK (For Goalkeepers)	N/A	Element Expected: Always for goalkeepers, if the information is available for the DocumentSubtype=CUM
Attribute	M/O	Value	Description
Value	O	Numeric ##0	Top/Middle/Bottom Left, Top/Middle/Bottom centre, Top/Middle/Bottom right: Total Shots for the Goalkeepers in the event unit.
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: Always, if the information is available			
Attribute	Value	Description	
Code	SAVE		
Pos	N/A	N/A	
Value	Numeric #0	Total save for this destination	

Sample

```
<StatsItem Type="ST" Code="LD" Value="12">
  <ExtendedStat Code="GOAL" Value="4" />
  <ExtendedStat Code="SAVE" Value="2" />
  <ExtendedStat Code="MISS" Value="1" />
  <ExtendedStat Code="POST" Value="2" />
  <ExtendedStat Code="BLC" Value="2" />
  <ExtendedStat Code="PERCENT" Value="48" />
</StatsItem>
...
<StatsItem Type="ST" Code="ASSIST" Value="1" />
<StatsItem Type="ST" Code="TO" Value="2" />
<StatsItem Type="ST" Code="ST" Value="3" />
<StatsItem Type="ST" Code="BLC" Value="4" />
<StatsItem Type="ST" Code="YC" Value="4" />
<StatsItem Type="ST" Code="SHOT" Value="4">
  <ExtendedStat Code="GOAL" Value="1" />
  <ExtendedStat Code="PERCENT" Value="63" />
</StatsItem>
<StatsItem Type="ST" Code="SD" Value="1">
  <ExtendedStat Type="SD" Code="GOAL" Value="0" />
  <ExtendedStat Type="SD" Code="PERCENT" Value="0" />
</StatsItem>
```

2.2.9.5 Message Sort

Sort according to the @Order attributes.

2.2.10 Event Final Ranking

2.2.10.1 Description

The event final ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Rank Mark (disqualified, etc.), or both.

2.2.10.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC of the Event	Full (34) RSC of the event
DocumentType	DT_RANKING	Event Final ranking message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Result status, indicates whether the data is official or partial. OFFICIAL PARTIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.10.3 Trigger and Frequency

This message is only triggered after a unit which affects the final ranking is official and that particular ranking is not subject to change.

- After each final position is known.

2.2.10.4 Message Values

Element: ExtendedInfos /SportDescription (0,1) Sport Description in text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Text short description, not code
Gender	M	CC @DisciplineGender	Gender code for the event unit.

Element: Result (1,N)			
For any event final ranking message, there should be at least one competitor being awarded a result for the event.			
Attribute	M/O	Value	Description
Rank	O	Text	Rank of the competitor in the result. It is optional because the team can be disqualified
RankEqual	O	S(1)	Send "Y" if the Rank is equaled else do not send.
Played	O	Numeric #0	Send number of matches played
Won	O	Numeric #0	Send number of matches won
Lost	O	Numeric #0	Send number of matches lost
Tied	O	Numeric #0	Send number of matches tied
IRM	O	SC @IRM	Send if the team has been disqualified
SortOrder	M	Numeric	This attribute is a sequential number with the order of the competitors at the end of the event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified teams.

Element: Result /Competitor (1,1)			
Competitor related to one final event result.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID. "NOCOMP" in the case where there is no competitor in the rank due to IRM.
Type	M	S(1)	T for team
Organisation	O	CC @Organisation	Organisation of the competitor

Element: Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team

Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to an individual athlete or a team member. Team members should be participating in the event.
Order	M	Numeric	Order attribute used to sort team members in a team
Bib	O	S(2)	Shirt number.

Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Sample

```
<Result Rank="1" SortOrder="1" Played="8" Won="8" Lost="0" >
  <Competitor Code="HBLMTEAM7-----CRO01" Type="T" Organisation="CRO">
    <Description TeamName="Croatia"/>
    <Composition>
      <Athlete Code="1085534" Order="1" Bib="12" >
```

2.2.10.5 Message Sort

Sort by Result @SortOrder

3 Document Control

Version history		
Version	Date	Comments
v1.0	25 Aug 2017	First version
V1.1	3 January 2017	Updated

File Reference: ODF R-SOG-2020-HBL V1.1 SFA

Change Log		
Version	Status	Changes in version
v1.0	SFR	First Version
V1.1	SFA	DT_PARTIC: Updated to add Passport names (CR15219)