

OLYMPIC DATA FEED

ODF Karate Data Dictionary

Tokyo 2020 - Games of the XXXII Olympiad

Technology and Information Department

© International Olympic Committee

ODF R-SOG-2020-KTE V1.2 SFA

3 January 2018

License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.
The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.
5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.

1 Introduction

1.1 This document

This document includes the ODF Karate Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for karate.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Karate Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the karate competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 2018 Youth Olympic Games

This document is to be applied for the 2018 Youth Olympic Games. All concepts are included with the exceptions of:

- DT_PARTIC
 - RANK_WLD is not applicable

1.5 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies

1.6 Related Documents

Document Title	Document Description
ODF General Principles Document	The document explains the environment and general principles for ODF.
ODF General Messages Interface Document	The document describes the ODF General Messages
ODF Common Codes	The document describes the ODF Common codes used across all ODF documents.
ODF Sport Codes	The document describes the ODF Sport codes used across all ODF documents

Document Title	Document Description
ODF Header Values	The document details the header values which show which RSCs are used in which messages.

2 Messages

2.1 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in karate .

- The column “Message type” indicates the DocumentType that identifies a message
- The column “Message name” is the message name identified by the message type
- The column “Message extended” indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it should follow the general definition rules.

Message Type	Message Name	Message extended
DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule / Competition schedule update	X
DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / List of participants by discipline update	X
DT_MEDALS	Medal standings	
DT_MEDALLISTS_DAY	Medallists of the day	
DT_GLOBAL_GM	Global good morning	
DT_GLOBAL_GN	Global good night	
DT_RESULT	Event Unit Start List and Results	X
DT_CURRENT	Current Information	X
DT_POOL_STANDING	Pool Standings	X
DT_BRACKETS	Brackets	X
DT_RANKING	Event Final Ranking	X
DT_COMMUNICATION	Official Communication	
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_LOCAL_ON	Discipline/venue start transmission	
DT_KA	Keep Alive	

2.2 Messages

2.2.1 Competition schedule / Competition schedule update

2.2.1.1 Description

The Competition schedule is a bulk message provided for one particular discipline. As a general rule, it contains the complete schedule information for all event units needed to run a competition and excludes event units for activities such as unofficial training and press conferences.

This message contains the competition timetable for a complete discipline as well as status for each competition unit and is updated from OVR via the schedule update message.

All event units in codes which have the 'schedule' flag set to 'Y' are included in schedule messages (and have status UNSCHEDULED or SCHEDULED).

The arrival of the competition schedule message resets all the previous schedule information for one particular discipline.

The StartList component of the message is only included in the case that the Unit Type is one of HATH, HCOUP, HNOC or HTEAM and at least one of the competitors are known.

The Composition component (i.e. listing athletes) is only included in the case that the Unit Type is one of HATH or HCOUP.

For reference the applicable unit types (from common codes) are:

HATH Individual Head to Head units (e.g. ARC, BDM, TEN etc)

HCOUP Pairs/Couples Head to Head units (e.g. BDM, TEN etc)

HNOC NOC Head to Head units (e.g. ARC)

HTEAM Teams Head to Head units (e.g. BKB, VBV, HOC etc)

Managing when start times are not known.

In some disciplines the start time of each unit is not known and the unit are managed by order rather than time.

In these disciplines usually only the time of the first unit (or first unit per location) is known and distributed. In this case all units should be sent with the same start time and those following units flagged as HideStartDate (and finish). To be able to correctly order these units then the Order attribute is used.

To ensure there are no incorrectly ordered units then the start time must not be updated to the actual start time (there is an actual start time field to cater for this).

If the discipline requires some text describing the order then StartText is used. Typical uses include 'Not before 17:00' or 'SUN 29 - 2nd match on CC' or 'Follows'.

Where HideStartDate='Y' is used then all start times for the units may be the same, usually the same as the

first unit in the session or location (which generally will not use HideStartDate='Y') but this is not mandatory and approximate start times may be used. The specific way this is managed in each sport is detailed in the specific sport data dictionary.

Advice for end users - how to sort event units and use DT_SCHEDULE:

- When displaying the schedule users must use the following sort order to display as intended:

1. By day (or filter by day)
2. By location if applicable (in a small number of sports)
3. By Time (regardless if HideStartDate='Y')
4. By Order

- The Order is sent for all units where HideStartDate='Y' else only sent if a particular event order is expected. Start with 1 each new session each day

- End users should display StartText if HideStartDate='Y'

Competition schedule update:

Competition schedule update is an update message. It is not a complete schedule information message, but only the schedule data being modified.

The arrival of this message updates the previous schedule information for one particular event unit, but does not notify any other change for the rest of the event units except for those contained in the message.

The key of the information updated is Unit @Code. Therefore, any new unit, deleted unit or updated unit will be identified by this attribute.

It has to be understood that if one DT_SCHEDULE message arrives, then all previous DT_SCHEDULE_UPDATE messages should be discarded.

2.2.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC at discipline level	
DocumentType	DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule bulk / update
Version	1...V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Refer to the ODF header definition
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.1.3 Trigger and Frequency

The competition schedule will be sent as a bulk message (DocumentType='DT_SCHEDULE') before the Games and then sent multiple times until a date to be confirmed after which only update messages will be sent (DocumentType='DT_SCHEDULE_UPDATE') by OVR. There is no automatic triggering and this (DT_SCHEDULE) message must not be sent after the transfer of control to OVR.

The competition schedule update message should be triggered at any time there has been a competition schedule modification for any previously sent competition schedule bulk message or update message including the addition of start list details (H2H).

Generally start list details for H2H should be sent immediately when known and usually soon after the preceding unit changes to Official.

If any text descriptions change in a message (as opposed to the code) then this message is not resent to correct previous messages however the new data is to be used in future messages.

2.2.1.4 Message Values

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
SessionCode	M	S(5)	Format DDD00 where DDD is the discipline and 00 is the session number.
StartDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
EndDate	O	DateTime	End date. Example: 2006-02-26T10:00:00+01:00
Leadin	O	m:ss	Amount of time from session start to first scheduled unit.
Venue	M	CC @VenueCode	Venue where the session takes place
VenueName	M	S(25)	Venue name
ModificationIndicator	O	S(1)	Attribute is mandatory in the DT_SCHEDULE_UPDATE message. N = New or U = Update.
SessionStatus	M	CC @ScheduleStatus	nly use CANCELLED if applicable. All other sessions are assumed to be scheduled. There is no change to running or finished.
SessionType	O	CC @SessionType	Session Type of the session

Element: Competition /Session /SessionName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Language of the Session Description
Value	O	S(40)	Name of the session. (if no other name then is session code)

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Code	M	Full RSC for the unit	
PhaseType	M	Phase type for the unit	
UnitNum	O	S(6)	Match / Game / Bout / Race Number or similar
ScheduleStatus	M	CC @ScheduleStatus	Unit Status
StartDate	O	DateTime	Start date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED. For other statuses the StartDate is expected otherwise ordering is display is incorrect (including CANCELLED and POSTPONED.) This is the scheduled Start date and time and will not be updated when an event unit starts (updated only with RESCHEDULED status) Where HideStartDate='Y' then this should be filled with the session start time or the start time of a group of units for all similar units and Order used for sorting. Example: 2006-02-26T10:00:00+01:00

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
HideStartDate	O	S(1)	<p>Send 'Y' if StartDate (scheduled start time) should not be displayed. It may be an estimate or 'fake' time. Do not send if StartDate (scheduled start time) is to be displayed.</p> <p>Start times of some units depend on the finalisation of previous event units and therefore there is no fixed start time in these cases this field is set to 'Y'.</p> <p>When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed.</p>
EndDate	O	DateTime	<p>End date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED, POSTPONED or CANCELLED.</p> <p>Example: 2006-02-26T10:00:00+01:00</p>
HideEndDate	O	S(1)	<p>Send 'Y' if EndDate scheduled end time is not to be displayed.</p> <p>Some event units have a scheduled end time well bounded, however, some event units in some circumstances have a scheduled end time not quite variable (example, some press conferences or tennis matches, etc.) in these cases this field is set to 'Y' and should not be displayed.</p>
ActualStartDate	O	DateTime	<p>This attribute is expected once the event unit has started. Example: 2006-02-26T10:03:22+01:00</p>
ActualEndDate	O	DateTime	<p>This attribute is expected once the event unit has finished. Example: 2006-02-26T12:43:51+01:00</p>
Order	O	Numeric ###0	<p>Order of the units when displayed. This field is considered in two situations:</p> <ol style="list-style-type: none"> 1. If HideStartDate = 'Y' then send at least for all Units in an affected session though it is suggested to be sent for all units in a discipline where the concept is used in the discipline. 2. If some units start at the same time and a particular order of the units is expected. <p>It is generally recommended to start at 1 in each session each day though may be ordered independently by location starting at 1 for each location in each session (where the schedule is ordered by location) or using other numbers to ensure the order of two using starting at the same time are displayed in the appropriate order.</p>

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Medal	O	SC @UnitMedalType	Gold medal event unit or bronze medal event unit. Do not send if not a medal event unit
Venue	M	CC @VenueCode	VVenue where the unit takes place Use TBD if the Venue is not known yet (CC).
Location	M	CC @Location	Location where the unit takes place Use TBD if the Location is not known yet (CC) or a generic code for the discipline.
SessionCode	O	S(5)	Code of the session which contains this event unit. Usually in the format DDD00 where DDD is the discipline and 00 is the session number within the discipline. For example ATH02 for the second session in Athletics.
ModificationIndicator	O	N, U	Attribute is mandatory in the DT_SCHEDULE_UPDATE message only N-New event unit U-Update event unit If ModificationIndicator='N', then include new event unit. It will be rarely used as most added units were available in "UNSCHEDULED" status. If ModificationIndicator="U", then update the event unit.

Element: Competition /Unit /StartText (0,N)			
This element is only used for Competition Schedules when HideStartDate is 'Y'. In this case, English Language is mandatory.			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
Value	M	S(20)	Text to be displayed in the case that StartDate is not to be displayed (e.g. "After M.1" or "Followed by") Using a code set or fixed text will also be directly displayed and allow end user translation.

Element: Competition /Unit /ItemName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
Value	M	S(40)	Item Name / Unit Description. For competition units show the short unit description from common codes which matches the RSC.

Element: Competition /Unit /VenueDescription (1,1)			
Attribute	M/O	Value	Description
VenueName	M	S(25)	Venue name in first language. This is the CC value from unit/venue
LocationName	M	S(30)	Location name in first language. This is the CC value from unit/location.

Element: Competition /Unit /StartList /Start (1,N)			
Attribute	M/O	Value	Description
StartOrder	O	Numeric	Competitor's start order
SortOrder	M	Numeric	Used to sort competitors in an event unit (for example, if there is no StartOrder). It is mainly used for display purposes.

Element: Competition /Unit /StartList /Start /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes, TBD or NOCOMP.	Competitor's ID, TBD in case that the competitor is not known at this time AND the other competitor is known. NOCOMP is sent when there is no competitor (and will not come later)
Type	M	S(1)	A for athlete
Organisation	O	CC @Organisation	Should be sent when known

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete (1,N)			
In case of the Competitor @Code='TBD' this element should not be sent.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID
Order	M	Numeric	Order attribute 1 if Competitor @Type="A".

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case). Send if not null.
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth.
IFId	O	S(16)	Athlete IF number, send if available, only for the current

			discipline.
--	--	--	-------------

2.2.1.5 Message Sort

The message is sorted by Unit@StartDate then by Unit@Order then Unit@Code.

In case of event unit with no Unit@StartDate defined (example, they are in an event unit status such as UNSCHEDULED), they will be listed at the end in Unit@Code order.

2.2.2 List of participants by discipline / List of participants by discipline update

2.2.2.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

This message includes historical athletes that do not participate in the current competition. Historical athletes will not be registered to any event.

It is important to note that all the sport messages that make references to athletes (start list, event unit results, etc.) will always match the athlete ID with the athlete ID in this message. The historical athletes will be used to match historical athlete information as it appears in the records message when sending the previous record information and this previous record was an historical record not being broken in the current competition.

List of participants by discipline (DT_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message can include a list of current athletes, officials, coaches, guides, technical officials, Reserves and historical athletes regardless of status.

List of participants by discipline update (DT_PARTIC_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

2.2.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC. Discipline level	RSC at discipline level
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	List of participants by discipline message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.

Attribute	Value	Comment
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.2.3 Trigger and Frequency

The DT_PARTIC message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_UPDATE messages are sent.

The DT_PARTIC_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.

2.2.2.4 Message Values

Element: Participant (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	<p>Participant's ID.</p> <p>It identifies an athlete or an official and the holding participant's valid information for one particular period of time.</p> <p>It is used to link other messages to the participant's information.</p> <p>Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc.</p> <p>When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.</p>
Parent	M	S(20) with no leading zeroes	<p>Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent.</p> <p>The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.</p> <p>The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".</p>
Status	O	CC @ParticStatus	<p>Participant's accreditation status this attribute is Mandatory in the case of @Current="true" and it is optional in the case that @Current="false".</p> <p>To delete a participant, a specific value of the Status attribute is used.</p>
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)
PassportGivenName	O	S(25)	Passport Given Name (Uppercase)

Element: Participant (1,N)			
Attribute	M/O	Value	Description
PassportFamilyName	O	S(25)	Passport Family Name (Uppercase)
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
LocalFamilyName	O	S(25)	Family name in the local language in the appropriate case for the local language (usually mixed case) Not for use in Rio 2016
LocalGivenName	O	S(25)	Given name in the local language in the appropriate case for the local language (usually mixed case). Not for use in Rio 2016
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth. This information may not be known at the very beginning, but it will be completed for all participants after successive updates
Height	O	S(3)	Height in centimetres. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
Weight	O	S(3)	Weight in kilograms. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC @Country	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC @Country	Country ID of Residence
Nationality	O	CC @Country	Participant's nationality. Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC @ResultsFunction	Main function In the Case of Current="true" this attribute is Mandatory.
Current	M	boolean	It defines if a participant is participating in the games (true) or is a Historical participant (false).

Element: Participant (1,N)			
Attribute	M/O	Value	Description
OlympicSolidarity	O	S(1)	'Y' or 'N' Flag to indicating if the participant participates in the Olympic Scholarship program.
ModificationIndicator	M	S(1)	'N' or 'U' Attribute is mandatory in the DT_PARTIC_UPDATE message only N-New participant (in the case that this information comes as a late entry) U-Update participant If ModificationIndicator='N', then include new participant to the previous bulk-loaded list of participants If ModificationIndicator='U', then update the participant to the previous bulk-loaded list of participants To delete a participant, a specific value of the Status attribute is used.

Element: Participant /Discipline (1,1)			
All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.			
Attribute	M/O	Value	Description
Code	M	CC @Discipline	It is the discipline code used to fill the OdfBody @DocumentCode attribute.
IFId	O	S(16)	IF unique identification (IF number)

Element: Participant /Discipline /RegisteredEvent (0,N)			
All accredited athletes will be assigned to one or more events. There is one exception: in some sports, substitutes may be accredited without any associated event. Historical athletes are not registered to any event.			
Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the event

Element: Participant /Discipline /RegisteredEvent /EventEntry (0,N)			
Send if there are specific athlete's event entries.			
Type	Code	Pos	Description
ENTRY	RANK_WLD	N/A	Description of @Pos: N/A Element's Expected: As soon as it is known (it can be sent in both messages)

Attribute	M/O	Value	Description
Value	M	S(3)	World Ranking

Element: Participant /OfficialFunction (0,N)

Send if the official has optional functions. Do not send, otherwise.

Attribute	M/O	Value	Description
FunctionId	M	CC @ResultsFunction	Additional officials' function code

2.2.2.5 Message Sort

The message is sorted by Participant @Code

2.2.3 Event Unit Start List and Results

2.2.3.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports. The definition includes as much generic information as possible due to the fact that each discipline and event has its own format for the results information (example: score of a match, time in a race, distance in a throw...).

This is always a full message and all applicable elements and attributes are always sent.

2.2.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	Not used	Not used
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	It indicates whether the result is official or unofficial (or intermediate etc). START_LIST OFFICIAL LIVE (used during the competition when nothing else applies). UNCONFIRMED (used after the competition is completed and before either UNOFFICIAL or OFFICIAL. It may be sent multiple times if modifications are required and the status has not changed)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.3.3 Trigger and Frequency

This message is sent with ResultStatus 'START_LIST' as soon as the expected information is available and any changes to the information. Possible information is:

- As soon as each competitor is known and any changes in start list data (START_LIST)
- When the contest starts and after every change in any data (LIVE)
- After the contest (UNOFFICIAL/OFFICIAL)

Trigger also after any change.

2.2.3.4 Message Values

Element: ExtendedInfos /UnitDateTime (0,1)			
Attribute	M/O	Value	Description
StartDate	O	DateTime	Actual start date-time. Do not include until unit starts.
Duration	O	m:ss	Match duration.

Element: ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	RES_CODE	N/A	Element Expected: When available and applicable.
	Attribute	M/O	Value
	Value	M	SC @ResultCode
			Description
			Decision for how the contest was won.

Sample

```
<ExtendedInfos>
  <UnitDateTime StartDate="2012-08-03T16:10:00+01:00" Duration="3:12" />
  <ExtendedInfo Type="UI" Code="RES_CODE" Value="POINTS" />
</ExtendedInfos>
```

Element: ExtendedInfos /SportDescription (0,1)			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes
Gender	M	CC @DisciplineGender	Gender code for the event unit
SubEventName	M	S(40)	EventUnit short name (not code) from Common Codes
UnitNum	O	S(6)	Bout number

Element: ExtendedInfos /VenueDescription (0,1)			
Venue Names in Text.			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location short name (not code) from Common Codes

Element: Officials /Official (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Official's code
Function	M	CC @ResultsFunction	Official's function (example: referee, etc.). Can be different from the function sent in the DT_PARTIC message.
Order	M	Numeric	Official's order. Send by order for each official in each function, example: 1 for Referee 2 for Judge 1 3 for Judge 2 ...

Element: Officials /Official /Description (1,1)			
Officials extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the official
Organisation	M	CC @Organisation	Officials' organisation
IFId	O	S(16)	International Federation ID

Sample

```
<Officials>
  <Official Code="7350035" Order="1" Function="RE" >
    <Description GivenName="Alexander" FamilyName="Zverkov" Gender="M" Organisation="RUS" />
  </Official>
  <Official Code="7350063" Order="2" Function="J1" >
    <Description GivenName="Artur" FamilyName="Bazaev" Gender="M" Organisation="RUS" />
  </Official>
```

Element: Result (1,N)			
Attribute	M/O	Value	Description
Result	O	Numeric #0	The result of the competitor in the event unit. Indicates the score of the competitor.
IRM	O	SC @IRM	The invalid rank mark, if applicable. IRM of the competitor for the particular event unit. Send if DNS before competition also.
WLT	O	SC @WLT	The code whether a competitor won (W), lost (L) or Tied (T) the bout.
SortOrder	M	Numeric	Used to sort all the results of an event unit. This attribute is a sequential number with the order of the competitor. Send 1 for Red competitor and 2 for Blue competitor
StartSortOrder	M	Numeric	Used to sort all start list competitors in an event unit. Send 1 for Red competitor and 2 for Blue competitor
ResultType	O	SC @ResultType	Type of the @Result attribute. Result type, either points or IRM for the corresponding event unit.

Element: Result /ExtendedResults /ExtendedResult (1,N)				
Type	Code	Pos	Description	
ER	y Where y = CC @PenaltyType	Numeric 0	Description of @code: Send the code for each type of penalty Description of @Pos: Send 1 for Category 1 Send 2 for Category 2 Element's Expected: Sent when applicable in Kumite	
	Attribute	M/O	Value	Description
	Value	M	S(1)	Send "Y" if applicable else do not send.
ER	z Where z = CC @ScoreType	N/A	Description of @code: Send the code for each SC @ScoreType Description of @Pos: Do not send Element's Expected: As soon as it is known in Kumite.	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Number of scores obtained by competitor during contest for given type

Sample

```
<Result ResultType="POINTS" Result="1" WLT="W" SortOrder="1" StartOrder="1" StartSortOrder="1">
  <ExtendedResults>
    <ExtendedResult Type="ER" Code="IP" Pos="1" Value="1" />
  </ExtendedResults>
</Result>
```

Element: Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or TBD	Competitor's ID or TBD in case that the competitor is unknown at this time but will be available
Type	M	S(1)	A for athlete
Organisation	O	CC @Organisation	Competitor's organisation

Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID.
Order	M	Numeric	Order attribute used to sort. Send 1 if Competitor @Type="A".

Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)			
Individual athletes entry information.			
Type	Code	Pos	Description
EUE	BODYWEIGHT	N/A	Description of @Pos: N/A Element's Expected: Always in Kumite.
	Attribute	M/O	Value
	Value	M	Numeric ##0.0
EUE	COLOUR	N/A	Description of @Pos: N/A Element's Expected: Always
	Attribute	M/O	Value
	Value	M	SC @Colour

Sample

```
<EventUnitEntry Type="EUE" Code="COLOUR" Value="RED" />
<EventUnitEntry Type="EUE" Code="BODYWEIGHT" Value="105.7" />
```

2.2.3.5 Message Sort

Sort by Result @SortOrder

2.2.4 Current Information

2.2.4.1 Description

The Current message is a message containing the current information in a competition which is live. The message is used to send the latest applicable and if applicable a clock.

2.2.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Full RSC of the unit.
DocumentSubcode	Not used	Not used
DocumentType	DT_CURRENT	Current message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.4.3 Trigger and Frequency

- At the start and end of every period (to start/stop clock)
- Every time the clock starts and stops during the unit.
- During the contest after start and not during breaks, every 30 seconds after the last DT_CURRENT message when there is no other activity triggering this message.

2.2.4.4 Message Values

Element: Clock (0,1)			
Attribute	M/O	Value	Description
Time	M	m:ss	Value of the clock
Running	M	S(1)	Indicates if the clock is currently running. Y to indicate the clock is running; N to indicate the clock is stopped.

2.2.4.5 Message Sort

N/A

2.2.5 Pool Standings

2.2.5.1 Description

The pool standings message contains the standings of a group in a competition. It is similar to the Phase Results message, except in the frequency and trigger. Here the message is triggered at the start of OVR operations and then after each event unit (game, match, etc.).

This report is sent independently for each of the groups / pools of the competition in a particular phase, and the group / pool can be determined from the message header (DocumentCode).

2.2.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (for the group)	RSC for the pool/group
DocumentType	DT_POOL_STANDING	Pool Standings message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: INTERMEDIATE (before and during the phase) UNOFFICIAL (if last match is unofficial) OFFICIAL (after all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.5.3 Trigger and Frequency

The general rule is that this message is sent:

- Before the start of the competition to build in the initial tables. The message has status INTERMEDIATE.
- When an event unit of the corresponding phase finishes (not waiting for official). The message has status INTERMEDIATE.
- When the phase finishes (there are no more event units/games to compete). The message has status OFFICIAL.

Trigger also after any change.

2.2.5.4 Message Values

Element: ExtendedInfos /ExtendedInfo (0,N)				
Type	Code	Pos	Description	
UI	LAST_UNIT	N/A	Element Expected: After at least one unit is complete.	
	Attribute	M/O	Value	Description
	Value	O	CC @Unit	Send the full RSC of the most recently unit made official for the pool included in this message.
UI	UNITS_TOTAL	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Total number of units (matches) to be played in the pool included in the message.
UI	UNITS_COMPLETE	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Total number of units (matches) which are official in the pool included in this message.

Element: ExtendedInfos /SportDescription (0,1) Sport Descriptions in Text.				
Attribute	M/O	Value	Description	
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes	
EventName	M	S(40)	Event name (not code) from Common Codes	

Element: ExtendedInfos /VenueDescription (0,1) Venue Names in Text. Only included where the phase is contested at a single venue				
Attribute	M/O	Value	Description	
Venue	M	CC @VenueCode	Venue Code	
VenueName	M	S(25)	Venue short name (not code) from Common Codes	

Element: Result (1,N) For any message, there should be at least one competitor being awarded a result for the pool.				
Attribute	M/O	Value	Description	
Rank	O	Text	Rank at the group.	
RankEqual	O	S(1)	Send "Y" if the Rank is 29qualed else do not send.	

Element: Result (1,N)			
For any message, there should be at least one competitor being awarded a result for the pool.			
Attribute	M/O	Value	Description
ResultType	M	SC @ResultType	Result type, either points or IRM with points obtained by the competitor in all matches in the group
Result	O	Numeric #0	Send the classification points the competitor has accrued during the pool stage. Optional as not available before the competition.
IRM	O	SC @IRM	IRM Send just in the case @ResultType is points and IRM (see codes section)
SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the group, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified competitors.
Won	O	Numeric #0	Number of matches won by the competitor in the group. Do not send if the competitor has not started.
Lost	O	Numeric #0	Number of matches lost by the competitor in the group. Do not send if the competitor has not started.
Tied	O	Numeric #0	Number of games tied by the team in the group. Do not send if the competitor has not started.
Played	O	Numeric #0	Number of matches played by the competitor in the group. Send 0 if played.
QualificationMark	O	SC @QualificationMark	Qualification indicator
For	O	Numeric #0	Total score for
Against	O	Numeric #0	Total score against
Diff	O	Numeric #0 or -#0	Points difference in Kata.

Element: Result / ExtendedResults /ExtendedResult (1,N)			
Type	Code	Pos	Description
ER	SCORE SCORE_AGAINST	N/A	Pos Description: Do not send anything Element Expected: Always after the first match for both score and score against.
Sub Element: Result /ExtendedResults /ExtendedResult /Extension Expected: When available			
Attribute	Value	Description	
Code	IPP		
Pos	N/A	Do not send anything	
Value	Numeric #0	Ippon Score	
Sub Element: Result /ExtendedResults /ExtendedResult /Extension Expected: When available			
Attribute	Value	Description	
Code	WAZ		
Pos	N/A	Do not send anything	
Value	Numeric #0	Waza-ari Score	
Sub Element: Result /ExtendedResults /ExtendedResult /Extension Expected: When available			
Attribute	Value	Description	
Code	YUK		
Pos	N/A	Do not send anything	
Value	Numeric #0	Yuko Score	

Element: Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	A for athlete
Organisation	M	CC @Organisation	Competitor's organisation

Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID.
Order	M	Numeric 0	Send 1 as only used for individual events.

Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Result /Competitor /Opponent (0,N)			
Details of the opposing competitor in competitions within the pool. (The Opponent of the competitor in the Opponent @Pos column of the Pool)			
Type	Code	Pos	Description
A for athlete	S(20) with no leading zeroes	Numeric #0	Code Description: Competitor ID or TBD if unknown Pos Description: 1 to n. Normally expected to be the same as SortOrder for the same competitor. Element Expected: Always
	Attribute	M/O	Value
	Organisation	M	CC @Organisation
	Date	M	Date
	Time	O	S(5)
	Unit	O	CC @Unit
	HomeAway	O	S(1)
	Result	O	S(50)
			Competitors' organisation (code). Must include if the data is available
			Date of match between the competitor and opponent (example: YYYY-MM-DD). Must include if the data is available, send even after the match is complete.
			Time of match (example HH:MM) Must include if the data is available and allowed to display.
			Full RSC of the Unit for the Pool Item
			Home / Away indicator. Send H if the opponent is the home competitor, send A if the opponent is the away competitor.
			Result of the match if match is complete and formatted as in ORIS (separator & order, example 5:2). Must include if the data is available and the match is complete. The order of the result data is relative to the competitor and may be reversed for other competitor or depending on home/away display rules.

Element: Result /Competitor /Opponent /Composition /Athlete (1,N) Only send composition if singles event.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID.
Order	M	Numeric 0	Send 1 as only used for individual events.

Element: Result /Competitor /Opponent /Composition /Athlete /Description (1,1) Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

2.2.5.5 Message Sort

The attribute used to sort the results is Result @SortOrder

2.2.6 Brackets

2.2.6.1 Description

The brackets message contains the brackets information for one particular event. It is used in events where there is a necessity to know in advance how successive event units will be filled as the competition progresses. In the early stages of the competition, it indicates how each of the event units will be built from the winners/losers, or other competition rules of the previous event units.

2.2.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Full RSC of the event
DocumentType	DT_BRACKETS	Brackets message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: START_LIST (when the draw initially made) INTERMEDIATE (during the competition) OFFICIAL (when all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2). The end of the logical day is defined by default at 03:00 a.m. For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction. Logical Date is expressed in the local time zone where the message was produced.
Source	SC @Source	Code indicating the system which generated the message.

2.2.6.3 Trigger and Frequency

This message should be sent at the very beginning of a competition, as soon as brackets are available after the draw.

Send when a match/event unit is completed, including Official status. Therefore it is triggered up to two times (with both status) for each event unit but only if there is a change from the previous version. The message should be updated including information on each competitor in the different bracket items.

The @ResultStatus attribute will vary depending on the competition status.

- Send with ResultStatus = 'INTERMEDIATE' until the last event unit (Gold Medal Match) is Unofficial (i.e. for all event units up until the Gold Medal match is completed for an event)
- Send with ResultStatus = 'OFFICIAL' when the last event unit for an event (Gold Medal match) has Official status.

Trigger also after any change.

2.2.6.4 Message Values

Element: ExtendedInfos /SportDescription (0,1)			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes.
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: ExtendedInfos /VenueDescription (0,1)			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue short name (not code) from Common Codes

Element: Bracket (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @Bracket	Bracket code to identify a bracket item (finals). There should be a different code for each bracket based on sport/ORIS presentation of the bracket.

Element: Bracket /BracketItems (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @BracketItems	Each BracketItems should include all BracketItem grouped by their SC @BracketItems.

Element: Bracket /BracketItems /BracketItem (1,N)			
Attribute	M/O	Value	Description
Code	O	S(3)	Unique identified for each bracket item. Use match number if it exists. However, it may include "TBD" for to be defined, if the contest number is not known.
Order	M	Numeric	Sequential number inside of BracketItems to indicate the order, always start at 1
Date	O	Date	Date of match (example: YYYY-MM-DD). Must include if the data is available
Time	O	S(5)	Time of match (example HH:MM). Must include if the data is available.
Unit	O	CC @Unit	Full RSC of the unit for the BracketItem
Result	O	S(50)	Result of the contest for the particular event unit. Indicates the final result with the ORIS format.
NextUnit	O	CC @Unit	Full RSC of the unit where the successful competitor will progress
NextUnitLoser	O	CC @Unit	Full RSC of the unit where the unsuccessful competitor will progress

Element: Bracket /BracketItems /BracketItem /ExtBracketItems /ExtBracketItem (1,N) ExtBracketItems /ExtBracketItem are optional elements according to competitors' rules.			
Type	Code	Pos	Description
EBI	DECISION	N/A	Element Expected: When available
	Attribute	M/O	Value
	Value	M	CC @ResultCode
			Description
			Decision of the contest

Element: Bracket /BracketItems /BracketItem /CompetitorPlace (1,N)			
- If the competitors are known, this element is used to place the competitors in the bracket. - If they are not yet known, it contains some information (on the rule to access to this bracket...)			
Attribute	M/O	Value	Description
Pos	M	Numeric ###	This attribute is a sequential number to place the different competitors in the bracket (1, 2 ...).
Code	O	SC @CompetitorPlace	Send when there is no competitor (BYE) or when it is not known yet (TBD).
WLT	O	SC @WLT	Indicates the winner or loser of the bracket item. Always send when known
Result	O	S(10)	The result (points) of the competitor in the event unit.
IRM	O	SC @IRM	The invalid rank mark, if applicable

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /PreviousUnit (0,1)			
Previous event unit related to the CompetitorPlace@Pos competitor of the current bracket item. It is always informed except for the bracket items whose CompetitorPlace@Pos competitor do not have preceding event units in the bracket graph unless coming from a pool.			
Attribute	M/O	Value	Description
Unit	O	CC @Unit Full RSC or S(2)	Full RSC code of the previous event unit for the CompetitorPlace@Pos competitor of the bracket item. Must send if a winner/loser from a single unit. Send the Pool code (A, B) is from a pool
Value	O	SC @Pool	If there is no competitor and coming from Pool then send appropriate code.
WLT	O	SC @WLT	If the competitor in the current unit is unknown and coming from an earlier bracketitem then fill this field with the W or L indication winner or loser of the previous unit if the information is known. Do not send if competitor comes from a pool.

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor (0,1)			
CompetitorPlace @Pos competitor related to the bracket item. Only include if the competitor is known .			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	A for athlete
Organisation	O	CC @Organisation	Competitors' organisation if known

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID
Order	M	Numeric	Order attribute use 1 if Competitor @Type="A".

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /ExtBracketAths /ExtBracketAth (1,N)				
Type	Code	Pos	Description	
EBA	STRIKE_OUT	N/A	Description of @Pos: N/A Element's Expected: Send always and when there is a competitor with the IRM DNS or DSQ	
	Attribute	M/O	Value	Description
	Value	M	S(1)	Send Y when the athlete is DSQ or DNS. Otherwise do not send.

Sample

```
....
<BracketItem Code="131" Order="2" Date="2016-08-09" Time="01:20" Unit="KTEM54KG-----SFNL0001----"
Result="1:0" NextUnit Unit=" KTEM54KG-----FNL-0001----" >
  <CompetitorPlace Pos="1" WLT="W" Result="1" >
    <PreviousUnit Unit=" KTE54KG-----QFNL0001----" />
    <Competitor Code="1066978" Type="A" Seed="4" Organisation="ESP" >
      <Composition>
        <Athlete Code="1066978" Order="1" >
          <Description FamilyName="Black" GivenName="John" Gender="M" Organisation="ESP"
BirthDate="1991-12-16" />
        </Athlete>
      </Composition>
    </CompetitorPlace>
  </BracketItem>

```

2.2.6.5 Message Sort

The following order applies:

- * Bracket @Code if more than one '@Code'.
- * BracketItems according to its @Code attribute.
- * Then, the BracketItem /Unit @Unit are sorted according to their scheduled start time.

2.2.7 Event Final Ranking

2.2.7.1 Description

The event final ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a generic message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Rank Mark (disqualified, etc.), or both.

2.2.7.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC of the Event	
DocumentType	DT_RANKING	Event Final ranking message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Result status, indicates whether the data is official or partial. OFFICIAL PARTIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2). The end of the logical day is defined by default at 03:00 a.m. For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction. Logical Date is expressed in the local time zone where the message was produced.
Source	SC @Source	Code indicating the system which generated the message.

2.2.7.3 Trigger and Frequency

This message is only triggered after a unit which affects the final ranking is official and that particular ranking is not subject to change. For the lower ranked athletes it can be sent after the morning session and then each match in the afternoon.

Trigger also after any change.

2.2.7.4 Message Values

Element: ExtendedInfos /SportDescription (0,1)			
Sport Description in text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes. Must be included if it is a single event
Gender	M	CC @DisciplineGender	Gender code for the event unit. Must be included if it is a single gender

Element: ExtendedInfos /VenueDescription (0,1)			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue short name (not code) from Common Codes

Element: Result (1,N)			
For any event final ranking message, there should be at least one competitor being awarded a result for the event.			
Attribute	M/O	Value	Description
Rank	O	Text	Final rank of the competitor in the corresponding event.
RankEqual	O	S(1)	Identifies if a rank has been equalled. Send Y if applicable else do not send.
IRM	O	SC @IRM	The invalid rank mark, send if applicable.
SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the particular event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out rank ties as well as results without rank.

Element: Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes, NOCOMP	Competitor's ID. "NOCOMP" in the case where there is no competitor in the rank due to IRM.
Type	M	S(1)	A for athlete
Organisation	O	CC @Organisation	Competitors' organisation if known

Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID
Order	M	Numeric	Order attribute. Send 1 when Competitor @Type="A".

Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Sample

```

<Result Rank="1" SortOrder="1">
  <Competitor Code="1106858" Type="A" Organisation="SUI" >
    <Composition>
      <Athlete Code="1106858" Order="1" >
        <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="SUI" BirthDate="1994-12-15" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
<Result SortOrder="2" IRM="DQB" >
  <Competitor Code="1090697" Type="A" Organisation="ESP" >
    <Composition>
      <Athlete Code="1090697" Order="1">
        <Description GivenName="James" FamilyName="Black" Gender="M" Organisation="ESP" BirthDate="1994-12-16" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
....

```

2.2.7.5 Message Sort

Sort by Result @SortOrder

3 Document Control

Version history		
Version	Date	Comments
v1.0	15 September 2017	First version
V1.1	4 December 2017	Updated with feedback
V1.2	3 January 2018	Updated

File Reference: ODF R-SOG-2020-KTE V1.2 SFA

Change Log		
Version	Status	Changes on version
v1.0	SFR	First version
V1.1	SFR	DT_CONFIG message removed as does not add value. SF is always the start of the bracket. DT_RESULT: Remove option of both athletes receiving L for WLT. DT_RESULT: Corrected StartDate to not be mandatory DT_RESULT: Change Result to numeric. DT_CURRENT: Message added DT_POOL_STANDING: Modify the structure of score extensions.
V1.2	SFA	DT_PARTIC: Updated to add Passport names (CR15219)