



INTERNATIONAL
OLYMPIC
COMMITTEE

ODF R-SOG-2020-TTE V2.1 SFA

OLYMPIC DATA FEED

ODF Table Tennis Data Dictionary

Tokyo 2020 - Games of the XXXII Olympiad

Technology and Information Department

© International Olympic Committee

ODF R-SOG-2020-TTE V2.1 SFA

25 February 2019

License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.

The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.

5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.

1 Introduction

1.1 This document

This document includes the ODF Table Tennis Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for table tennis.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Table Tennis Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the table tennis competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies

1.5 Related Documents

Document Title	Document Description
ODF General Principles Document	The document explains the environment and general principles for ODF.
ODF General Messages Interface Document	The document describes the ODF General Messages
ODF Common Codes	The document describes the ODF Common codes used across all ODF documents.
ODF Sport Codes	The document describes the ODF Sport codes used across all ODF documents
ODF Header Values	The document details the header values which show which RSCs are used in which messages.

2 Messages

2.1 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in table tennis.

- The column “Message type” indicates the DocumentType that identifies a message
- The column “Message name” is the message name identified by the message type
- The column “Message extended” indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it should follow the general definition rules.

Message Type	Message Name	Message extended
DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule / update	X
DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / update	X
DT_PARTIC_NAME	Participant Names	
DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of teams / update	X
DT_MEDALS	Medal standings	
DT_RESULT	Event Unit Start List and Results	X
DT_PLAY_BY_PLAY	Play by Play	X
DT_POOL_STANDING	Pool Standings	X
DT_BRACKETS	Brackets	X
DT_STATS	Statistics	X
DT_RANKING	Event Final Ranking	X
DT_COMMUNICATION	Official Communication	
DT_CONFIG	Configuration	X
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_LOCAL_ON	Discipline/venue start transmission	
DT_KA	Keep Alive	

2.2 Messages

2.2.1 Competition schedule / Competition schedule update

2.2.1.1 Description

The Competition schedule is a bulk message provided for one discipline. As a general rule, it contains the complete schedule information for all event units needed to run a competition and excludes event units for activities such as unofficial training and press conferences.

This message contains the competition timetable for a complete discipline as well as status for each competition unit and is updated from OVR via the schedule update message.

All event units in codes which have the 'schedule' flag set to 'Y' are included in schedule messages regardless of status (those without status must be sent as UNSCHEDULED if the schedule flag is 'Y').

The arrival of the competition schedule message resets all the previous schedule information for one discipline.

The StartList component of the message is only included in the case that the Unit Type is one of HATH, HCOUP, HNOC or HTEAM and at least one of the competitors are known.

The Composition component (i.e. listing athletes) is only included in the case that the Unit Type is one of HATH or HCOUP.

For reference the applicable unit types (from common codes) are:

HATH Individual Head to Head units (e.g. ARC, BDM, TEN, SBD etc)

HCOUP Pairs/Couples Head to Head units (e.g. BDM, TEN etc)

HNOC NOC Head to Head units (e.g. ARC, ALP)

HTEAM Teams Head to Head units (e.g. BKB, VBV, HBL, CUR, IHO etc)

Managing when start times are not known.

In some disciplines the start time of each unit is not known and the unit are managed by order rather than time.

In these disciplines only the time of the first unit (or first unit per location) is known and distributed. In this case all units should be sent with the same start time and those following units flagged as HideStartDate (and finish). To be able to correctly order these units then the Order attribute is used (and must be sent from the venue).



To ensure there are no incorrectly ordered units then the start time must not be updated to the actual start time (there is an actual start time field to cater for this). For example:

Start Time in message	To Display	Unit	HideStartDate	Location	Order
12:00	12:00	Unit 1	N	Court 2	1
12:00	Match 2 Court 2	Unit 2	Y	Court 2	2
12:00	Match 3 Court 2	Unit 3	Y	Court 2	3
16:30	Not before 16:30	Unit 4	Y	Court 2	4

If the discipline requires some text describing the order then StartText is used. Typical uses include "Not before 17:00" or "SUN 29 - 2nd match on CC" or "Follows".

Advice for end users - how to sort event units and use DT_SCHEDULE:

- When displaying the schedule users must use the following sort order to display as intended:

1. By day (or filter by day)
2. By location if applicable (in a small number of sports, when EventOrder = LOC in Discipline codes)
3. By Time (regardless if HideStartDate="Y")
4. By Order

- The Order is sent for all units where HideStartDate="Y" or if special ordering is required else not sent.

Start with 1 each new session each day

- End users should display StartText if HideStartDate="Y"

If a StartText value of "Not before hh:mm" is used then it is expected that the StartDate sent is the same hh:mm.

Competition schedule update:

Competition schedule update is an update message. It is not a complete schedule information message, but only the schedule data being modified.

The arrival of this message updates the previous schedule information for one particular event unit(s) or session(s), but does not notify any other change for the rest of the event units/sessions except for those contained in the message.

The key of the information updated is Unit @Code. Therefore, any new unit, deleted unit or updated unit will be identified by all this attribute.

It has to be understood that if one DT_SCHEDULE message arrives, then all previous DT_SCHEDULE_UPDATE messages should be discarded.

When message is sent from Competition Schedule application in advance of the Games the element ExtendedInfos/EntendedInfo will contain following information:

- Type=CS, Code=VERSION, the attribute Value will indicate the version details from the competition schedule application

- Type=CS, Code=STATUS the attribute Value will indicate the status details from the competition schedule application

2.2.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	Full RSC at the discipline level
DocumentType	DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule bulk / update
Version	1...V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Refer to the ODF header definition
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.1.3 Trigger and Frequency

The competition schedule will be sent as a bulk message (DocumentType="DT_SCHEDULE") when available before the Games and then sent multiple times until a date to be confirmed after which only update messages will be sent (DocumentType="DT_SCHEDULE_UPDATE") by OVR. There is no automatic triggering and this (DT_SCHEDULE) message must not be sent after the transfer of control to OVR.

The competition schedule update message should be triggered at any time there has been a competition schedule modification for any previously sent competition schedule bulk message or update message including the addition of start list details (H2H).

Generally start list details for H2H should be sent immediately when known and usually soon after the preceding unit changes to Official.

The triggers for status changes are described in each sport data dictionary where differences are needed.

If any text descriptions change in a message (as opposed to the code) then this message is not resent to correct previous messages however the new data is to be used in future messages.

2.2.1.4 Message Values

Element: Competition /Session (0,N)			
Attribute	M/O	Value	Description
SessionCode	M	S(5)	Code of the sports competition session which contains this event unit. Usually in the format DDD00. DDD is the discipline and 00 is the session number within the discipline. For example ARC02 for the second session in Archery.
StartDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00
EndDate	M	DateTime	End date. Example: 2006-02-26T10:00:00+01:00
Leadin	O	m:ss	Amount of time from session start to first scheduled unit.
Venue	M	CC @VenueCode	Venue where the session takes place
VenueName	M	S(25)	Name of venue
ModificationIndicator	O	S(1)	Attribute is mandatory in the DT_SCHEDULE_UPDATE message. N = New or U = Update.
SessionStatus	O	CC @ScheduleStatus	Only use CANCELLED if applicable. All other sessions are assumed to be scheduled. There is no change to running or finished.
SessionType	O	CC @SessionType	Session type of the Session.



Element: Competition /Session /SessionName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Language of the Session Description
Value	O	S(40)	Name of the sports competition session

Sample

```
<Session Code="ATH01" StartDate="2016-08-12T10:00:00+01:00" EndDate="2016-08-12T14:00:00+05:00" LeadIn="5:00" Venue="STA" VenueName="Olympic Stadium" >
  <SessionName Language="ENG" Value="Athletics Session 1" />
</Session>
<Session Code="ATH02" StartDate="2016-08-12T18:00:00+01:00" EndDate="2016-08-12T21:00:00+05:00" LeadIn="5:00" Venue="STA" VenueName="Olympic Stadium" >
  <SessionName Language="ENG" Value="Athletics Session 2" />
</Session>
```

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Code	M	Full RSC for the unit	
PhaseType	M	CC @PhaseType	Phase type for the unit
UnitNum	O	S(15)	Match / Game / Bout / Race Number or similar
ScheduleStatus	M	CC @ScheduleStatus	Unit Status
StartDate	O	DateTime	<p>Start date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED. For other statuses the StartDate is expected otherwise ordering is display is incorrert (including CANCELLED and POSTPONED.</p> <p>This is the scheduled Start date and time and will not be updated when an event unit starts (updated only with RESCHEDULED status)</p> <p>Where HideStartDate="Y" then this should be filled with the session start time or the start time of a group of units for all similar units and Order used for sorting. This method is not used in team sports where HideStartDate="Y" is only used temporarily to remove times.</p> <p>Example: 2006-02-26T10:00:00+01:00</p>



Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
HideStartDate	O	S(1)	<p>Send 'Y' if StartDate (scheduled start time) should not be displayed. It may be an estimate or 'fake' time. Do not send if StartDate (scheduled start time) is to be displayed.</p> <p>Start times of some units depend on the finalisation of previous event units and therefore there is no fixed start time in these cases this field is set to 'Y'.</p> <p>When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed.</p>
EndDate	O	DateTime	<p>End date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED, POSTPONED or CANCELLED.</p> <p>Example: 2006-02-26T10:00:00+01:00</p>
HideEndDate	O	S(1)	<p>Send 'Y' if EndDate scheduled end time is not to be displayed.</p> <p>Some event units have a scheduled end time well bounded, however, some event units in some circumstances have a scheduled end time not quite variable (example, some press conferences or tennis matches, etc.) in these cases this field is set to 'Y' and should not be displayed.</p>
ActualStartDate	O	DateTime	<p>This attribute is expected once the event unit has started.</p> <p>Example: 2006-02-26T10:03:22+01:00</p>
ActualEndDate	O	DateTime	<p>This attribute is expected once the event unit has finished.</p> <p>Example: 2006-02-26T12:43:51+01:00</p>



Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Order	O	Numeric ###0	<p>Order of the units when displayed. This field is considered in two situations:</p> <ol style="list-style-type: none"> 1. If HideStartDate = 'Y' then send at least for all Units in an affected session though it is suggested to be sent for all units in a discipline where the concept is used in the discipline. 2. If some units start at the same time and a particular order of the units is expected. <p>It is generally recommended to start at 1 in each session each day though may be ordered independently by location starting at 1 for each location in each session (where the schedule is ordered by location) or using other numbers to ensure the order of two using starting at the same time are displayed in the appropriate order.</p>
Medal	O	SC @UnitMedalType	<p>Medal indicator. Do not send if not a medal event unit</p>
Venue	O	CC @VenueCode	<p>Venue where the unit takes place Mandatory unless UNSCHEDULED Can use TBD if the Venue is not known yet (CC).</p>
Location	O	CC @Location	<p>Location where the unit takes place Mandatory unless UNSCHEDULED Can use TBD if the Location is not known yet (CC) or a generic code for the discipline.</p>
MediaAccess	O	S(6)	<p>Only applicable for non-competition. If unit is open to media send "Open", if the unit is closed then send "Closed".</p>
SessionCode	O	S(5)	<p>Code of the sports competition session which contains this event unit. Usually in the format DDD00. DDD is the discipline and 00 is the session number within the discipline. For example ARC02 for the second session in Archery.</p>



Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
ModificationIndicator	O	N, U	<p>Attribute is mandatory in the DT_SCHEDULE_UPDATE message only</p> <p>N-New event unit U-Update event unit</p> <p>If ModificationIndicator='N', then include new event unit. It will be rarely used as most added units were available in "UNSCHEDULED" status.</p> <p>If ModificationIndicator="U", then update the event unit.</p>

Element: Competition /Unit /StartText (0,N)			
This element is only used for Competition Schedules when HideStartDate is 'Y'. In this case, English Language is mandatory.			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
Value	M	S(20) or a code set to be defined discipline by discipline	<p>Text to be displayed in the case that StartDate is not to be displayed (e.g. "After M.1" or "Followed by")</p> <p>Using a code set or fixed text will also be directly displayed and allow end user translation.</p>

Element: Competition /Unit /ItemName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
Value	M	S(40)	<p>Item Name / Unit Description.</p> <p>For competition units show the short unit description from common codes which matches the RSC. As in all messages with a description only the ENG description is expected.</p> <p>For non-competition schedules (where the item description is not in common codes) then add the description.</p>

Element: Competition /Unit /ItemDescription (0,N)			
Attribute	M/O	Value	Description
Language	M	CC @Language	Code Language of the @Value
-	M	Free Text	Item Description for non-competition schedule



Element: Competition /Unit /VenueDescription (1,1)			
Attribute	M/O	Value	Description
VenueName	M	S(25)	Venue name in first language. This is the CC value from unit/venue
LocationName	M	S(30)	Location name in first language. This is the CC value from unit/location.

Element: Competition /Unit /StartList /Start (1,N)			
StartList information is only sent in the case that the Unit type is one of HATH, HCOUP, HNOC or HTEAM and at least one of the competitors are known. (Sent as soon as known for applicable units)			
Attribute	M/O	Value	Description
StartOrder	O	Numeric	Competitor's start order
SortOrder	M	Numeric	Used to sort competitors in an event unit (for example, if there is no StartOrder). It is mainly used for display purposes.
PreviousWLT	O	S(1)	W or L for winner of loser of a particular previous unit plays in this unit. This attribute is only filled if the competitors are 100% confirmed as participating at this time and not subject to change depending on TV times etc. Further, the data is removed when the real teams are known.
PreviousUnit	O	S(34)	The full RSC of the unit where this competitor came from. This attribute is only filled if the competitors are 100% confirmed as participating at this time and not subject to change depending on TV times etc. Further, the data is removed when the real teams are known.

Element: Competition /Unit /StartList /Start /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes, TBD or NOCOMP.	Competitor's ID, TBD in case that the competitor is not known at this time AND the other competitor is known. NOCOMP is sent when there is no competitor (and will not come later)
Type	M	S(1)	T for team A for athlete
Organisation	O	CC @Organisation	Should be sent when known



Element: Competition /Unit /StartList /Start /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Team Name where known, must send when available
IFId	O	S(16)	Team IF number, send if available

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete (1,N)			
Only send in the case that the Unit type is one of HATH (AR, BD, TE etc) or HCOUP (BD, TE etc), In case of the Competitor @Code='TBD' this element should not be sent.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete in the event unit.
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case). Send if not null.
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth.
IFId	O	S(16)	Athlete IF number, send if available, only for the current discipline.

2.2.1.5 Message Sort

Sort by Session @SessionCode.

The message is sorted by Unit@StartDate then by Unit@Order then Unit@Code.

In case of event unit with no Unit@StartDate defined (example, they are in an event unit status such as UNSCHEDULED), they will be listed at the end in Unit@Code order.

2.2.2 List of participants by discipline / List of participants by discipline update

2.2.2.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

It is important to note that all the sport messages that make references to athletes (start list, event unit results, etc.) will always match the athlete ID with the athlete ID in this message. The historical athletes will be used to match historical athlete information as it appears in the records message when sending the previous record information and this previous record was an historical record not being broken in the current competition.

List of participants by discipline (DT_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message can include a list of current athletes, officials, coaches, guides, technical officials, Reserves and historical athletes regardless of status.

List of participants by discipline update (DT_PARTIC_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

2.2.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	RSC at the discipline level
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	List of participants by discipline message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.



Attribute	Value	Comment
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.2.3 Trigger and Frequency

The DT_PARTIC message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_UPDATE messages are sent.

The DT_PARTIC_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.



2.2.2.4 Message Values

Element: Participant (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	<p>Participant's ID.</p> <p>It identifies an athlete or an official and the holding participant's valid information for one particular period of time.</p> <p>It is used to link other messages to the participant's information.</p> <p>Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc.</p> <p>When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.</p>
Parent	M	S(20) with no leading zeroes	<p>Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent.</p> <p>The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.</p> <p>The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".</p>
Status	O	CC @ParticStatus	<p>Participant's accreditation status this attribute is Mandatory in the case of @Current="true" and it is optional in the case that @Current="false".</p> <p>To delete a participant, a specific value of the Status attribute is used.</p>
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)



Element: Participant (1,N)			
Attribute	M/O	Value	Description
PassportGivenName	O	S(25)	Passport Given Name (Uppercase)
PassportFamilyName	O	S(25)	Passport Family Name (Uppercase)
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
TVFamilyName	M	S(25)	TV family name
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth. This information may not be known at the very beginning, but it will be completed for all participants after successive updates
Height	O	S(3)	Height in centimetres. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
Weight	O	S(3)	Weight in kilograms. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC @Country	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC @Country	Country ID of Residence
Nationality	O	CC @Country	Participant's nationality. Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC @ResultsFunction	Main function In the Case of Current="true" this attribute is Mandatory.
Current	M	boolean	It defines if a participant is participating in the games (true) or is a Historical participant (false).



Element: Participant (1,N)			
Attribute	M/O	Value	Description
OlympicSolidarity	O	S(1)	'Y' or 'N' Flag to indicating if the participant participates in the Olympic Scholarship program.
ModificationIndicator	M	S(1)	'N' or 'U' Attribute is mandatory in the DT_PARTIC_UPDATE message only N-New participant (in the case that this information comes as a late entry) U-Update participant If ModificationIndicator='N', then include new participant to the previous bulk-loaded list of participants If ModificationIndicator='U', then update the participant to the previous bulk-loaded list of participants To delete a participant, a specific value of the Status attribute is used.

Element: Participant /Discipline (1,1)			
All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.			
Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the discipline
IFId	O	S(16)	IF ID (Competitor's federation number for the corresponding discipline)

Element: Participant /Discipline /RegisteredEvent (0,N)			
All accredited athletes will be assigned to one or more events. Historical athletes are not registered to any event.			
Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the event
Class	O	CC @SportClass	This attribute is required in competitions including athletes with disabilities.



Element: Participant /Discipline /RegisteredEvent /EventEntry (0,N) Send if there are specific athlete's event entries.				
Type	Code	Pos	Description	
ENTRY	QUAL_TYPE	N/A	Element Expected: If applicable (this information can be sent in both messages). Send for Individual and Team events.	
	Attribute	M/O	Value	Description
	Value	M	SC @QualifyingType	Qualification method
ENTRY	RANK_WLD	N/A	Element Expected: If applicable (this information can be sent in both messages). Only for Individual events.	
	Attribute	M/O	Value	Description
	Value	M	S(4)	Player's world ranking
ENTRY	HAND	N/A	Element Expected: As soon as this information is available (this information can be sent in both messages). Send for Individual and Team events	
	Attribute	M/O	Value	Description
	Value	M	SC @Hand	Handedness
ENTRY	GRIP	N/A	Element Expected: As soon as this information is known (this information only will be sent in the update message). Send for Individual and Team events	
	Attribute	M/O	Value	Description
	Value	M	SC @Grip	Grip
ENTRY	SEED	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	The position in which the competitor is seeded for the competition.



Sample

```
<Discipline Code="TTE-----" IFId="203258" >  
  <RegisteredEvent Event="TTEMSINGLES-----" >  
    <EventEntry Type="ENTRY" Code="GRIP" Value="xx" />  
    <EventEntry Type="ENTRY" Code="HAND" Value="L" />  
    <EventEntry Type="ENTRY" Code="RANK_WLD" Value="7" />  
  </RegisteredEvent>  
</Discipline>
```

2.2.2.5 Message Sort

The message is sorted by Participant @Code

2.2.3 List of teams / List of teams update

2.2.3.1 Description

DT_PARTIC_TEAMS contains the list of teams related to the current competition.

A team is a type of competitor, being a group of two or more individual athletes participating together in one event. Pairs are also defined as team of two competitors. One team participates in one event of one discipline. When one team participates in multiple events, there will be one team for each event for the same group. Also when the same organisation participates in the same event twice, there will be different teams. Table tennis has two types of teams, pairs and “team” in the team competition.

List of teams (DT_PARTIC_TEAMS) is a bulk message by discipline. The list is always complete. The arrival of this message resets all the previous participant teams' information for that discipline. It is assumed that all teams appearing in this list are valid, in the meaning that they are participating or they could participate in one event.

List of teams update (DT_PARTIC_TEAMS_UPDATE) is an update message. It is not a complete list of teams' information message. It only contains the data of a team being modified.

2.2.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (discipline level)	RSC at the discipline level
DocumentType	DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of participant teams message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.3.3 Trigger and Frequency

The DT_PARTIC_TEAMS message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_TEAMS_UPDATE messages are sent.

The DT_PARTIC_TEAMS_UPDATE message is triggered when there is a modification in the data for any team after the transfer of control to OVR.

2.2.3.4 Message Values

Element: Team (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Team's ID When the Team is an historical one, then this ID starts with "T".
Organisation	M	CC @Organisation	Team organisation's ID
Number	O	Numeric #0	Team's number. If there is not more than one team for one organisation participating in one event, it is 1. Otherwise, it will be incremental, 1 for the first organisation's team, 2 for the second organisation's team, etc. Required in the case of current teams.
Name	O	S(73)	Team's name.



Element: Team (1,N)			
Attribute	M/O	Value	Description
TVTeamName	O	S(21)	TV Team Name
Gender	M	CC @DisciplineGender	Discipline Gender Code of the Team
Current	M	boolean	It defines if a team is participating in the games (true) or it is a Historical team (false)
ModificationIndicator	M	N, U, D	Attribute is mandatory in the DT_PARTIC_TEAMS_UPDATE message only N-New team (in the case that this information comes as a late entry) U-Update team D-Delete team If ModificationIndicator='N', then include new team to the previous bulk-loaded list of teams If ModificationIndicator='U', then update the team to the previous bulk-loaded list of teams If ModificationIndicator='D', then delete the team to the previous bulk-loaded list of teams

Element: Team /Composition /Athlete (0,N)			
In the case of current teams the number of athletes is 2 or more.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID of the listed team's member. Therefore, he/she makes part of the team's composition.
Order	O	Numeric	Team member order

Element: Team /Discipline (0,1)			
Each team is assigned just to one discipline. Discipline is expected unless ModificationIndicator="D"			
Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the discipline

Element: Team /Discipline /RegisteredEvent (0,1)			
Each current team is assigned to one event. Historical teams will not be registered to any event.			
Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the event



Element: Team /Discipline /RegisteredEvent /EventEntry (0,N) Send if there are specific team's event entries.				
Type	Code	Pos	Description	
ENTRY	RANK_WLD	N/A	Element Expected: If available (this information can be sent in both messages)	
	Attribute	M/O	Value	Description
	Value	M	S(4)	Team Ranking
ENTRY	SEED	N/A	Element Expected: As soon as it is known (this information can be sent in both messages).	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	The position in which the team is seeded for the competition.

Sample (General)

```
<Team Code="TTEMTEAM-----CAN01" Organisation="CAN" Number="1" Name="Canada" Gender="M"
Current="true">
  <Composition>
    <Athlete Code="1063192" Order="1"/>
    <Athlete Code="1063249" Order="2"/>
    <Athlete Code="1067349" Order="3"/>
  ....
</Composition>
<Discipline Code="TTE-----" >
  <RegisteredEvent Event="TTEMTEAM-----" >
    <EventEntry Type="ENTRY" Code="RANK_WLD" Value="3" />
  </RegisteredEvent>
</Discipline>
</Team>
```

2.2.3.5 Message Sort

The message is sorted by Team @Code.

2.2.4 Event Unit Start List and Results

2.2.4.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports. The definition includes as much generic information as possible due to the fact that each discipline and event has its own format for the results information (example: score of a match, time in a race, distance in a throw...).

This is always a full message and all applicable elements and attributes are always sent.

2.2.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Full RSC of the event unit
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	Not used	Not used
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	It indicates whether the result is official or unofficial (or intermediate etc.). START_LIST LIVE (used during the competition when nothing else applies). INTERMEDIATE (used after the competition has started and is not finished but not currently live) UNOFFICIAL OFFICIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.4.3 Trigger and Frequency

This message is sent with ResultStatus 'START_LIST' as soon as the start list (competitors) are known and any changes to the information.

This message is then sent with ResultStatus 'LIVE' as soon as the unit starts and continues to be triggered on all updates.

For individual match in Singles or Doubles (in team event or not):

- As soon as each competitor is known and any changes in start list data (START_LIST)
- When the unit starts and after every change in any data (LIVE)
- At the end of each game (INTERMEDIATE)
- After the unit is over (UNOFFICIAL / OFFICIAL)

(For team match in Team events):

- As soon as each competitor is known and any changes in start list data of team match (START_LIST)
- When the unit starts and after every change in any data (LIVE)
- After a sub-match is finished (within the team match), except for the last one (INTERMEDIATE)
- After the unit is over (UNOFFICIAL / OFFICIAL)

Note: during a team match when the first sub-match finishes for example (the sub-match status is UNOFFICIAL), and the status of DT_RESULT for team match is still LIVE (just an INTERMEDIATE message will be sent after a sub-match), until the team match finishes (UNOFFICIAL / OFFICIAL).



2.2.4.4 Message Values

Element: ExtendedInfos /UnitDateTime (0,1)			
Attribute	M/O	Value	Description
StartDate	O	DateTime	Actual start date-time. Do not include until unit starts.
Duration	O	h:mm	Match duration It will not be sent for DSQ before the match or WO. In case of team events: duration of the team match.

Element: ExtendedInfos /ExtendedInfo (0,N)				
Type	Code	Pos	Description	
UI	FINAL_RESULT	N/A	Element Expected: At the end of the match/sub-match. For singles and team events (for team match also at the end of each sub-match, when INTERMEDIATE)	
	Attribute	M/O	Value	Description
	Value	M	String	Match final result in the display format. Examples: -for singles events - match, or, for team events - sub-match: "4-1 DSQ", or "4-1", or "4-0 WO" -for team events - Team match (and sub-matches in brackets). After a sub-match, there is no closing bracket in the final result of the team match while the match is not finished. (team match - after first sub-match): "1-0 (3:0 " (team match finished): "3-0 (3:1,3:1,3:0)", or "0-3 (0:3,0-3WO,1:3)", or "3-2 (0:3,3:2,0:3,3:0,3:1)"
UI	RALLY_MAX	N/A	Element Expected: At the end of the match. For singles events match, and, for team events singles/doubles matches and team match.	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Send the longest rally (number of strokes) in the match (in case of singles/doubles matches) or in the team match (in case of team events).



Element: ExtendedInfos /ExtendedInfo (0,N)				
Type	Code	Pos	Description	
UI	RALLY_AVG	N/A	Element Expected: At the end of the match. For singles events match, and, for team events singles/doubles matches and team match.	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Send the average rally (number of strokes) in the match (in case of singles/doubles matches) or in the team match (in case of team events)
UI	TABLE	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	S(2)	Send table number
UI	SERVE	Numeric 0	Pos Description: Send 1 or 2 for the pair's athlete, to indicate which athlete is serving in the doubles match in teams events (only send in doubles match, else do not send) Element Expected: When available when LIVE	
	Attribute	M/O	Value	Description
	Value	M	S(1)	Serve Indicator, for the competitor with the NEXT serve Send H for Home Send A for Away
UI	CARD	S(1)	Pos Description: Send H (for Home) Send A (for Away) to indicate the competitor who receives the card. Element Expected: When LIVE (if applicable) in singles and doubles matches (not overall team)	
	Attribute	M/O	Value	Description
	Value	M	SC @Card	Send the penalty card code (for the most recent card the competitor has received in the match) (e.g.: Y, YR1 ...)



Element: ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	CURRENT	N/A	Element Expected: When applicable when LIVE For singles events match, and, for team events singles/doubles matches.
Attribute	M/O	Value	Description
Value	M	Numeric 0	Send the current game number within the match (singles & doubles matches, not team match).
TEAM	MATCH	Numeric 0	Pos Description: Send the match number in the team match. (1, 2...) Element Expected: Just for team events
Attribute	M/O	Value	Description
Value	M	CC @Unit	Send the full RSC of the singles/doubles subunit within the team match
Sub Element: ExtendedInfos /ExtendedInfo /Extension Expected: Just for team events, if available			
Attribute	Value	Description	
Code	AWAY		
Pos	Numeric 0	Send 1 in case of singles matches in the team match. Send 1..2 for doubles matches in the team match (one for each team player at the match for the team with team order 2)	
Value	S(20) with no leading zeroes or TBD or NOCOMP	Send the player ID for each player (for the team with team order 2) at the match in the team match (if known) or TBD (for To Be Defined) or NOCOMP (if no player)	
Sub Element: ExtendedInfos /ExtendedInfo /Extension Expected: Just for team events, if available			
Attribute	Value	Description	
Code	HOME		
Pos	Numeric 0	Send 1 in case of singles matches in the team match. Send 1..2 for doubles matches in the team match (one for each team player at the match for the team with team order 1)	



Element: ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
Value	S(20) with no leading zeroes or TBD or NOCOMP		Send the player ID for each player (for the team with team order 1) at the match in the team match if known or TBD (for To Be Defined) or NOCOMP (if no player)
Sub Element: ExtendedInfos /ExtendedInfo /Extension Expected: Just for team events			
Attribute	Value	Description	
Code	TYPE		
Pos	N/A	N/A	
Value	SC @MatchType	Send S for singles match and D for doubles match in the team match	

Sample (singles)

```
<ExtendedInfos>
  <UnitDateTime StartDate="2012-07-28T16:00:00+01:00" Duration="29" />
  <ExtendedInfo Type="UI" Code="RALLY_MAX" Value="13" />
  <ExtendedInfo Type="UI" Code="RALLY_AVG" Value="6" />
  <ExtendedInfo Type="UI" Code="FINAL_RESULT" Value="4-0 DSQ" />
  <ExtendedInfo Type="UI" Code="TABLE" Value="4" />
</ExtendedInfos>
```

Sample (team event, singles/doubles match)

```
<ExtendedInfos>
  <UnitDateTime StartDate="2012-07-28T16:00:00+01:00" Duration="29" />
  <ExtendedInfo Type="UI" Code="RALLY_MAX" Value="13" />
  <ExtendedInfo Type="UI" Code="RALLY_AVG" Value="7" />
  <ExtendedInfo Type="UI" Code="FINAL_RESULT" Value="0-3" />
  <ExtendedInfo Type="UI" Code="TABLE" Value="1" />
</ExtendedInfos>
```



Sample (team event, team match)

```

<ExtendedInfos>
  <UnitDateTime StartDate="2012-07-28T16:00:00+01:00" Duration="2:29" />
  <ExtendedInfo Type="UI" Code="RALLY_MAX" Value="16" />
  <ExtendedInfo Type="UI" Code="RALLY_AVG" Value="9" />
  <ExtendedInfo Type="UI" Code="FINAL_RESULT" Value="0-3 (0:3,2:3,2:3)" />
  <ExtendedInfo Type="UI" Code="TABLE" Value="4" />
  <ExtendedInfo Type="TEAM" Code="MATCH" Pos="1" Value="TTEM.....">
    <Extension Code="TYPE" Value="S" />
    <Extension Code="HOME" Pos="1" Value="4123456" />
    <Extension Code="AWAY" Pos="1" Value="5654321" />
  </ExtendedInfo>
  <ExtendedInfo Type="TEAM" Code="MATCH" Pos="2" Value="TTEM.....">
    <Extension Code="TYPE" Value="S" />
    <Extension Code="HOME" Pos="1" Value="4362698" />
    <Extension Code="AWAY" Pos="1" Value="5436276" />
  </ExtendedInfo>
  <ExtendedInfo Type="TEAM" Code="MATCH" Pos="3" Value="TTEM.....">
    <Extension Code="TYPE" Value="D" />
    <Extension Code="HOME" Pos="1" Value="TBD" />
    <Extension Code="HOME" Pos="2" Value="TBD" />
    <Extension Code="AWAY" Pos="1" Value="TBD" />
    <Extension Code="AWAY" Pos="2" Value="TBD" />
  </ExtendedInfo>
  ....
</ExtendedInfos>

```

Element: ExtendedInfos /SportDescription (0,1)

Sport Descriptions in Text.

Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes
Gender	M	CC @DisciplineGender	Gender code for the event unit
SubEventName	M	S(40)	EventUnit short name (not code) from Common Codes
UnitNum	O	S(6)	Match number In the case of singles/doubles matches in a team match, it is followed by: 1, 2, 3 etc. in brackets (to indicate the current sub-match, while the team match is not finished) (e.g.: "12", "32(2)", ...)



Element: ExtendedInfos /VenueDescription (0,1) Venue Names in Text.			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location short name (not code) from Common Codes

Element: Officials /Official (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Official's code
Function	M	CC @ResultsFunction	Send the umpires
Order	M	Numeric 0	Order of the Officials According to the sport rules

Element: Officials /Official /Description (1,1) Officials extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the official
Organisation	M	CC @Organisation	Officials' organisation
IFId	O	S(16)	International Federation ID

Sample

```
<Officials>
  <Official Code="1138266" Function="UM" Order="1">
    <Description GivenName="Jane" FamilyName="Smith" Gender="F" Organisation="SUI" />
  </Official>
  <Official Code="1105079" Function="UM" Order="2">
    <Description GivenName="Ann" FamilyName="Jones" Gender="F" Organisation="ESP" />
  </Official>
</Officials>
```



Element: Periods (0,1)			
Attribute	M/O	Value	Description
Home	M	S(20) with no leading zeroes	Home Competitor ID
Away	M	S(20) with no leading zeroes	Away Competitor ID

Element: Periods /Period (1,N)			
Period in which the event unit message arrives.			
Only send for singles and doubles matches (not team match).			
Attribute	M/O	Value	Description
Code	M	SC @Period	Game number in case of singles and doubles matches
HomeScore	M	Numeric #0	Home competitor score up (number of games won) at the end of this game (@Code period). Cumulative games won by competitor with order 1 at the game (game number at the Period Code: G1..Gn) in the match.
AwayScore	M	Numeric #0	Away competitor score up (number of games) at the end of this game (@Code period). Cumulative games won by competitor with order 2 at the game (game number at the Period Code: G1..Gn) in the match.
HomePeriodScore	O	Numeric #0	Home competitor points just for this game (@Code period). Points won by competitor with order 1 just for this game (game number at the Period Code: G1..Gn) in the match
AwayPeriodScore	O	Numeric #0	Away competitor points just for this game (@Code period). Points won by competitor with order 2 just for this game (game number at the Period Code: G1..Gn) in the match
Duration	O	mm	Duration (minutes) of the game (game number at the Period Code: G1..Gn) in the match

Element: Periods /Period /ExtendedPeriods /ExtendedPeriod (1,N)			
ExtendedPeriod information.			
Type	Code	Pos	Description
EP	RALLY_MAX	N/A	Element Expected: Always in singles and doubles matches
	Attribute	M/O	Value
	Value	M	Numeric #0
	Description		
	Send the longest rally (number of strokes) for the corresponding game.		
EP	RALLY_AVG	N/A	Element Expected: Always in singles and doubles matches
	Attribute	M/O	Value
	Value	M	Numeric #0
	Description		
	Send the average rally (number of strokes) for the corresponding game.		



Sample

```
<Periods>
  <Period Code="G1" HomeScore="1" AwayScore="0" HomePeriodScore="14" AwayPeriodScore="12"
Duration="8">
    <ExtendedPeriods>
      <ExtendedPeriod Type="EP" Code="RALLY_MAX" Value="16" />
      <ExtendedPeriod Type="EP" Code="RALLY_AVG" Value="4" />
    </ExtendedPeriods>
  </Period>
  <Period Code="G2" HomeScore="2" AwayScore="0" HomePeriodScore="11" AwayPeriodScore="2"
Duration="4">
    <ExtendedPeriods>
      <ExtendedPeriod Type="EP" Code="RALLY_MAX" Value="11" />
      <ExtendedPeriod Type="EP" Code="RALLY_AVG" Value="4" />
    </ExtendedPeriods>
  </Period>
  ....
  <Period Code="G6" HomeScore="3" AwayScore="3" HomePeriodScore="15" AwayPeriodScore="17"
Duration="14">
    <ExtendedPeriods>
      <ExtendedPeriod Type="EP" Code="RALLY_MAX" Value="12" />
      <ExtendedPeriod Type="EP" Code="RALLY_AVG" Value="5" />
    </ExtendedPeriods>
  </Period>
  <Period Code="G7" HomeScore="4" AwayScore="3" HomePeriodScore="11" AwayPeriodScore="8"
Duration="6">
    <ExtendedPeriods>
      <ExtendedPeriod Type="EP" Code="RALLY_MAX" Value="10" />
      <ExtendedPeriod Type="EP" Code="RALLY_AVG" Value="5" />
    </ExtendedPeriods>
  </Period>
</Periods>
```



Element: Result (1,N) For each Event Unit Results message, there must be at least one competitor with a result element in the event unit.			
Attribute	M/O	Value	Description
Result	O	Numeric #0	Games won in the match for singles/doubles (stand-alone or part of the team event) If the opponent retires (RET) or is disqualified (DSQ) after the match was started, it will be 4 for the winner. Or Matches won in the team match for Team events. If the opponent retires (RET) or is disqualified (DSQ) after the team match was started, it will be 3 for the winner.
IRM	O	SC @IRM	Invalid result mark (if applicable). Only send it if ResultType is equal to IRM_POINTS
WLT	O	SC @WLT	Indicate if the competitor won (W), lost (L) or tied (T). Only included (mandatory) at the end of the match/sub-match.
SortOrder	M	Numeric	Used to sort all start list competitors in an event unit. Send 1 for Home and 2 for Away.
StartSortOrder	M	Numeric	Same @SortOrder
ResultType	O	SC @ResultType	Type of the @Result attribute. Result type, either POINTS or IRM_POINTS for the corresponding match Only included (mandatory) at the end of the match/sub-match.

Element: Result /ResultItems /ResultItem (1,N) Only applicable in Team Matches ResultItem /Result will be for one particular subunit in the team match			
Attribute	M/O	Value	Description
Unit	M	CC @Unit	Full phase level RSC of the subunit.
Order	M	Numeric #0	Logical order of the subunits, usually schedule order.



Element: Result /ResultItems /ResultItem /Result (1,1)			
Attribute	M/O	Value	Description
ResultType	O	SC @ResultType	Type of the @Result attribute
Result	O	Numeric #0	Games won in the sub-match
IRM	O	SC @IRM	Invalid result mark (if applicable). Only send it if ResultType is equal to IRM_POINTS
WLT	O	SC @WLT	Indicate if the competitor won (W) or lost (L) Only included (mandatory) at the end of the sub-match.
SortOrder	M	Numeric 0	One for the first named competitor in the subunit, 2 for the second named competitor.

Element: Result /Competitor (1,1)			
Competitor related to the result of one event unit.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or TBD or NOCOMP	Competitor's ID (if known): -For Competitor @Type=T, it will be: Team's ID -Otherwise, Athlete's ID (for Competitor @Type=A) (for singles). Or, TBD (for To Be Determined) in case that the competitor is unknown at this time but will be available. NOCOMP is sent when there is no competitor (and will not come later).
Type	M	S(1)	T for team A for athlete
Organisation	O	CC @Organisation	Competitor's organisation

Element: Result /Competitor /Description (0,1)			
Competitors extended information (for Team events, when competitor known).			
Attribute	M/O	Value	Description
TeamName	O	S(73)	Name of the team. Only applies for teams.



Element: Result /Competitor /EventUnitEntry (0,N)				
Team entry information.				
Type	Code	Pos	Description	
EUE	SEED	N/A	Element Expected: Always when applicable in doubles and team matches	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Competitor seed

Element: Result /Competitor /StatsItems /StatsItem (1,N)				
Only send for Doubles/Team events.				
Type	Code	Pos	Description	
ST	PTS_WON	SC @Period or S(3)	Pos Description: Send the period or TOT for full match in doubles Send the match number or TOT for full team match Element Expected: After period or sub-match starts	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Points won by the competitor in the related @Pos
ST	LEAD_MAX	SC @Period or S(3)	Pos Description: Send the period or TOT for full match in doubles Send the match number or TOT for full team match Element Expected: After period or sub-match starts	
	Attribute	M/O	Value	Description
	Value	M	S(2)	Biggest lead by the competitor in the related @Pos. If competitor never had the lead, use “-”
ST	PTS_SERVICE_WON	SC @Period or S(3)	Pos Description: Send the period or TOT for full match in doubles Send the match number or TOT for full team match Element Expected: After period or sub-match starts	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Number of points won on own serve by the competitor in the related @Pos
ST	PTS_SERVICE_LOST	SC @Period or S(3)	Pos Description: Send the period or TOT for full match in doubles Send the match number or TOT for full team match Element Expected: After period or sub-match starts	



Element: Result /Competitor /StatsItems /StatsItem (1,N) Only send for Doubles/Team events.				
Type	Code	Pos	Description	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Number of points lost on own serve by the competitor in the related @Pos
ST	PTS_CONSEC	SC @Period or S(3)		Pos Description: Send the period or TOT for full match in doubles Send the match number or TOT for full team match Element Expected: After period or sub-match starts
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	The most consecutive points won by the competitor in the related @Pos
ST	DEF_OVC_MAX	SC @Period or S(3)		Pos Description: Send the period or TOT for full match in doubles Send the match number or TOT for full team match Element Expected: After period or sub-match starts
	Attribute	M/O	Value	Description
	Value	M	S(2)	The greatest deficit overcome by the competitor in the period. If competitor never had deficit overcome, use "-".



Sample (Doubles)

```
<StatsItems>
  <StatsItem Type="ST" Code="PTS_WON" Pos="TOT" Value="80" />
  <StatsItem Type="ST" Code="LEAD_MAX" Pos="TOT" Value="9" />
  <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="TOT" Value="42" />
  <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="TOT" Value="35" />
  <StatsItem Type="ST" Code="PTS_CONSEC" Pos="TOT" Value="8" />
  <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="TOT" Value="3" />
  <StatsItem Type="ST" Code="PTS_WON" Pos="G1" Value="14" />
  <StatsItem Type="ST" Code="LEAD_MAX" Pos="G1" Value="3" />
  <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="G1" Value="6" />
  <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="G1" Value="7" />
  <StatsItem Type="ST" Code="PTS_CONSEC" Pos="G1" Value="5" />
  <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="G1" Value="2" />
  <StatsItem Type="ST" Code="PTS_WON" Pos="G2" Value="11" />
  <StatsItem Type="ST" Code="LEAD_MAX" Pos="G2" Value="9" />
  <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="G2" Value="5" />
  <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="G2" Value="1" />
  <StatsItem Type="ST" Code="PTS_CONSEC" Pos="G2" Value="8" />
  <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="G2" Value="-" />
  <StatsItem Type="ST" Code="PTS_WON" Pos="G3" Value="7" />
  <StatsItem Type="ST" Code="LEAD_MAX" Pos="G3" Value="1" />
  <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="G3" Value="3" />
  <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="G3" Value="7" />
  <StatsItem Type="ST" Code="PTS_CONSEC" Pos="G3" Value="2" />
  <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="G3" Value="-" />
  <StatsItem Type="ST" Code="PTS_WON" Pos="G4" Value="9" />
  <StatsItem Type="ST" Code="LEAD_MAX" Pos="G4" Value="-" />
  <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="G4" Value="6" />
  <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="G4" Value="4" />
  <StatsItem Type="ST" Code="PTS_CONSEC" Pos="G4" Value="4" />
  <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="G4" Value="-" />
</StatsItems>
```

Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.
Order	M	Numeric #0	If Competitor @Type="T" then order attribute used to sort team members in a team. Where the unit is doubles (or doubles within a team match) then the order used is 1,2 for the two players) For Team events, only those members that participate in this sub-match will be included If Competitor @Type="A" then 1



Element: Result /Competitor /Composition /Athlete /Description (1,1)

Athletes extended information.

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID
Class	O	CC @SportClass	This attribute is required in competitions including athletes with disabilities.



Element: Result /Competitor /Composition /Athlete /EventUnitEntry (0,N) Individual athletes entry information.				
Type	Code	Pos	Description	
EUE	TS	N/A	Element Expected: Just for team events, if available	
	Attribute	M/O	Value	Description
	Value	M	S(1) A, B, C, X, Y or Z	<p>Team sequence for each player. For the first two singles matches within the team match:</p> <ul style="list-style-type: none"> - the team with team order 1 uses team sequence A and B in matches 1 and 2 respectively - the team with team order 2 uses team sequence X and Y <p>For the doubles match within the team match, for each pair in the match:</p> <ul style="list-style-type: none"> - for the known player in the pair: the team with team order 1 uses team sequence C and the team with team order 2 uses team sequence Z - for the second player in the pair: the team with team order 1 uses team sequence A or B respectively and the team with team order 2 uses team sequence X or Y <p>For the fourth match in the team match:</p> <ul style="list-style-type: none"> - for team order 1: before the team match : blank, after teams have indicated the doubles paring: A or B - for team order 2: Z <p>For the fifth match in the team match:</p> <ul style="list-style-type: none"> - for team order 1: C - for team order 2: before the team match: blank, after teams have indicated the doubles paring: X or Y <p>In the Paralympics the team sequence for each team player is different, Team events will be best of 3 matches and the doubles match will be the first)</p>
EUE	GRIP	N/A	Element Expected: Always when available in singles and doubles matches	
	Attribute	M/O	Value	Description
	Value	M	SC @Grip	Grip of the player
EUE	HAND	N/A	Element Expected: Always when available in singles and doubles matches	
	Attribute	M/O	Value	Description
	Value	M	SC @Hand	Handedness of the athlete



Element: Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)
Individual athletes entry information.

Type	Code	Pos	Description	
EUE	SEED	N/A	Element Expected: Always when applicable in singles matches	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Athlete seed

Sample (singles or doubles)

```
<EventUnitEntry Type="EUE" Code="HAND" Value="R" />
<EventUnitEntry Type="EUE" Code="GRIP" Value="P" />
```

Element: Result /Competitor /Composition /Athlete /StatsItems /Stat (1,N)
For individual athletes statistics.

Type	Code	Pos	Description	
ST	PTS_WON	SC @Period or TOT	Pos Description: Send the period or TOT for full match Element Expected: For singles matches	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Points won by the competitor in the @Pos
ST	LEAD_MAX	SC @Period or TOT	Pos Description: Send the period or TOT for full match Element Expected: For singles matches	
	Attribute	M/O	Value	Description
	Value	M	S(2)	Biggest lead by the competitor in the @Pos. If competitor never had the lead, use "-"
ST	PTS_SERVICE_WON	SC @Period or TOT	Pos Description: Send the period or TOT for full match Element Expected: For singles matches	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Number of points won on own serve by the competitor in the @Pos
ST	PTS_SERVICE_LOST	SC @Period or TOT	Pos Description: Send the period or TOT for full match Element Expected: For singles matches	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Number of points lost on own serve by the competitor in the @Pos



Element: Result /Competitor /Composition /Athlete /StatsItems /Stat (1,N) For individual athletes statistics.				
Type	Code	Pos	Description	
ST	PTS_CONSEC	SC @Period or TOT	Pos Description: Send the period or TOT for full match Element Expected: For singles matches	
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	The most consecutive points won by the competitor in the @Pos
ST	DEF_OVC_MAX	SC @Period or TOT	Pos Description: Send the period or TOT for full match Element Expected: For singles matches	
	Attribute	M/O	Value	Description
	Value	M	S(2)	The greatest deficit overcome by the competitor in the @Pos. If competitor never had deficit overcome, use "-".

Sample (singles)

```
<Athlete Code="1086788" Order="1">
  <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="NZL" BirthDate="1992-12-15" />
  <EventUnitEntry Type="EUE" Code="HAND" Value="R" />
  <EventUnitEntry Type="EUE" Code="GRIP" Value="P" />
  <StatsItems>
    <StatsItem Type="ST" Code="PTS_WON" Pos="TOT" Value="80" />
    <StatsItem Type="ST" Code="LEAD_MAX" Pos="TOT" Value="9" />
    <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="TOT" Value="42" />
    <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="TOT" Value="35" />
    <StatsItem Type="ST" Code="PTS_CONSEC" Pos="TOT" Value="8" />
    <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="TOT" Value="3" />
    <StatsItem Type="ST" Code="PTS_WON" Pos="G1" Value="14" />
    <StatsItem Type="ST" Code="LEAD_MAX" Pos="G1" Value="3" />
    <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="G1" Value="6" />
    <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="G1" Value="7" />
    ....
    <StatsItem Type="ST" Code="PTS_WON" Pos="G7" Value="11" />
    <StatsItem Type="ST" Code="LEAD_MAX" Pos="G7" Value="3" />
    <StatsItem Type="ST" Code="PTS_SERVICE_WON" Pos="G7" Value="6" />
    <StatsItem Type="ST" Code="PTS_SERVICE_LOST" Pos="G7" Value="4" />
    <StatsItem Type="ST" Code="PTS_CONSEC" Pos="G7" Value="5" />
    <StatsItem Type="ST" Code="DEF_OVC_MAX" Pos="G7" Value="2" />
  </StatsItems>
</Athlete>
```

2.2.4.5 Message Sort

Sort by Result @SortOrder



INTERNATIONAL
OLYMPIC
COMMITTEE

ODF R-SOG-2020-TTE V2.1 SFA

2.2.5 Play by Play

2.2.5.1 Description

The Play by Play is a message containing official raw data from the results provider for each action.

The message contains a generic definition that can be used to provide results data of different nature as well as all of the actions in a unit.

2.2.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	RSC of the unit
DocumentSubcode	Not used	Not used
DocumentType	DT_PLAY_BY_PLAY	Play by Play message
DocumentSubtype	S(8)	Send "ACTION"
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Possible values are: START_LIST (only used if there are actions before the start) LIVE (used during the competition when nothing else applies) INTERMEDIATE UNOFFICIAL OFFICIAL (when results official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.5.3 Trigger and Frequency

The message is sent after every point in all units (except overall team match).

2.2.5.4 Message Values

Element: ExtendedInfos /SportDescription (0,1) Sport Descriptions in Text.			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes
SubEventName	M	S(40)	Text short description of the Event Unit, not code
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: ExtendedInfos /VenueDescription (0,1) Venue Names in Text.			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location short name (not code) from Common Codes



Element: Actions (0,1)			
Attribute	M/O	Value	Description
Home	M	S(20) with no leading zeroes	Home Competitor ID
Away	M	S(20) with no leading zeroes	Away Competitor ID

Element: Actions /Action (1,N)			
Attribute	M/O	Value	Description
Id	M	S(36)	Unique identifier for the action within the message
Period	M	SC @Period	Period of the action within the match
Order	M	Numeric	Unique sequential number for all of the actions from 1 to n. It is used to sort Action
Action	O	S(2)	Server indicator (for next serves) H or A for Home / Away In doubles follow H/A with 1 or 2 indicating player 1 or 2 to serve
ScoreH	O	Numeric #0	Total Home Score of the game after the action Send if there is a score change for either team
ScoreA	O	Numeric #0	Total Away Score of the game after the action Send if there is a score change for either team

Sample

```
<Actions Home="123456" Away="234567" >
....
  <UnitAction Id="123456" Period="G1" Order="3" ScoreH="2" ScoreA="2" Value="H" />
  <UnitAction Id="123457" Period="G1" Order="4" ScoreH="2" ScoreA="3" Value="A" />
....
</UnitActions>
```

2.2.5.5 Message Sort

Actions /Action @Order

2.2.6 Pool Standings

2.2.6.1 Description

The pool standings message contains the standings of a group in a competition. It is similar to the Phase Results message, except in the frequency and trigger. Here the message is triggered at the start of OVR operations and then after each event unit (game, match, etc.).

This report is sent independently for each of the groups / pools of the competition in a particular phase, and the group / pool can be determined from the message header (DocumentCode).

This message is only for use in the Paralympic Games.

2.2.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (for the group)	RSC for the pool/group
DocumentType	DT_POOL_STANDING	Pool Standings message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: INTERMEDIATE (before and during the phase) UNOFFICIAL (if last match is unofficial) OFFICIAL (after all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.



Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.6.3 Trigger and Frequency

The general rule is that this message is sent:

- Before the start of the competition to build in the initial tables. The message has status INTERMEDIATE.
- When an event unit of the corresponding phase finishes (not waiting for official). The message has status INTERMEDIATE.
- When the phase finishes (there are no more event units/games to compete). The message has status OFFICIAL.

Trigger also after any change.

2.2.6.4 Message Values

Element: ExtendedInfos /Progress (0,1)			
Attribute	M/O	Value	Description
LastUnit	O	CC @Unit	Send the full RSC of the most recently unit made official for the pool included in this message.
UnitsTotal	O	Numeric ##0	Total number of units (matches) to be played in the pool included in the message.
UnitsComplete	O	Numeric ##0	Total number of units (matches) which are official in the pool included in this message.



Element: ExtendedInfos /SportDescription (0,1)			
Sport Descriptions in Text.			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes

Element: ExtendedInfos /VenueDescription (0,1)			
Venue Names in Text. Only included where the phase is contested at a single venue			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue short name (not code) from Common Codes

Element: Result (1,N)			
For any message, there should be at least one competitor being awarded a result for the pool.			
Attribute	M/O	Value	Description
Rank	O	Text	Rank at the group. It is optional because the team can be disqualified
RankEqual	O	S(1)	Send "Y" if the Rank is equaled else do not send.
ResultType	M	SC @ResultType	Result type, either points or IRM with points obtained by the competitor at all the games of the group
Result	O	Numeric #0	Send the classification/match points the competitor has accrued during the pool stage. Optional as not available before the competition.
IRM	O	SC @IRM	IRM Send just in the case @ResultType is points and IRM (see codes section)
QualificationMark	O	S(1)	Send "Q" for individuals qualified for next round
SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the group, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified teams.

Element: Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	A for athlete, T for team
Organisation	M	CC @Organisation	Competitor's organisation



Element: Result /Competitor /Description (0,1)

Competitors extended information.

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team if a team.

Element: Result /Competitor /Composition /Athlete (1,N)

Only send composition if singles event.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.
Order	M	Numeric 0	Send 1 as only used for individual events.

Element: Result /Competitor /Composition /Athlete /Description (1,1)

Athletes extended information.

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID
Class	O	CC @SportClass	This attribute is required in competitions including athletes with disabilities.



Element: Result /Competitor /Opponent (0,N)

Details of the opposing competitor in competitions within the pool. (The Opponent of the competitor in the Opponent @Pos column of the Pool)

Type	Code	Pos	Description
T for team or A for athlete	S(20) with no leading zeroes	Numeric #0	Code Description: Competitor ID or TBD if unknown Pos Description: 1 to n. Normally expected to be the same as SortOrder for the same competitor. Element Expected: Always
Attribute	M/O	Value	Description
Organisation	M	CC @Organisation	Competitors' organisation (code). Must include if the data is available
Date	M	Date	Date of match between the competitor and opponent (example: YYYY-MM-DD). Must include if the data is available, send even after the match is complete.
Time	O	S(5)	Time of match (example HH:MM) Must include if the data is available and allowed to display.
Unit	O	CC @Unit	Full RSC of the Unit for the Pool Item
HomeAway	O	S(1)	Home / Away indicator. Send H if the opponent is the home team, send A if the opponent is the away team.
Result	O	S(50)	Result of the match if match is complete and formatted as in ORIS (separator & order, example 5-2). Must include if the data is available and the match is complete. The order of the result data is relative to the competitor and may be reversed for other competitor or depending on home/away display rules.

Element: Result /Competitor /Opponent /Description (0,1)

Competitors extended information.

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the opposition team if a team

Element: Result /Competitor /Opponent /Composition /Athlete (1,N)

Only send composition if singles event.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.
Order	M	Numeric 0	Send 1 as only used for individual events.



Element: Result /Competitor /Opponent /Composition /Athlete /Description (1,1)			
Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

2.2.6.5 Message Sort

The attribute used to sort the results is Result @SortOrder.

2.2.7 Brackets

2.2.7.1 Description

The brackets message contains the brackets information for one particular event. It is used in events where there is a necessity to know in advance how successive event units will be filled as the competition progresses. In the early stages of the competition, it indicates how each of the event units will be built from the winners/losers, or other competition rules of the previous event units.

2.2.7.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC (event level)	Full RSC of the Event
DocumentType	DT_BRACKETS	Brackets message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Status of the message. Expected statuses are: INTERMEDIATE (during the competition) UNOFFICIAL (when last match unofficial) OFFICIAL (when all matches official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.



Attribute	Value	Comment
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2). The end of the logical day is defined by default at 03:00 a.m. For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction. Logical Date is expressed in the local time zone where the message was produced.
Source	SC @Source	Code indicating the system which generated the message.

2.2.7.3 Trigger and Frequency

This message should be sent at the very beginning of a competition, as soon as brackets are available.

Send when a match/event unit is completed, including Unofficial and Official status. Therefore it is triggered up to three times (with both status) for each event unit (if unofficial is used). The message should be updated including information on each competitor in the different bracket items.

The @ResultStatus attribute will vary depending on the competition status.

- Send with ResultStatus = 'INTERMEDIATE' until the last event unit (Gold Medal Match) is Unofficial (i.e. for all event units up until the Gold Medal match is completed for an event)
- Send with ResultStatus = 'UNOFFICIAL' when the last event unit for an event (Gold Medal match) has Unofficial status.
- Send with ResultStatus = 'OFFICIAL' when the last event unit for an event (Gold Medal match) has Official status.

Trigger also after any change.



2.2.7.4 Message Values

Element: ExtendedInfos /SportDescription (0,1) Sport Description in Text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Event name (not code) from Common Codes.
Gender	M	CC @DisciplineGender	Gender code for the event unit

Element: ExtendedInfos /VenueDescription (0,1) Venue Names in text.			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue short name (not code) from Common Codes

Element: Bracket (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @Bracket	Bracket code to identify a bracket item. One for each individual bracket Note for example Gold and Bronze are different brackets.

Element: Bracket /BracketItems (1,N)			
Attribute	M/O	Value	Description
Code	M	SC @BracketItems	Bracket code to identify a set of bracket items. The quarterfinals, semifinals or finals phases etc.



Element: Bracket /BracketItems /BracketItem (1,N)			
Attribute	M/O	Value	Description
Code	O	S(6)	Bracket code to identify a bracket item. Unique identifier for the BracketItem. Where available it should be the match number or team match number.
Order	M	Numeric	Sequential number inside of BracketItems to indicate the order, always start at 1 and include all items of the current phase even if both competitors of this BracketItem are BYEs
Position	M	Numeric #0	Bracket position when drawing the bracket. For example, a quarter final has 4 items, with positions 1, 2, 3 and 4 from the top. Use the appropriate number to draw the position.
Date	O	Date	YYYY-MM-DD. Must be filled if known
Time	O	S(5)	HH:MM. Must be filled if known
Unit	O	CC @Unit	Full RSC of the unit for the BracketItem
Result	O	S(50)	Result of the match if match is complete and formatted as in ORIS (example 4-1 (11:4 11:7 11:4 1:11 11:1)). Must include if the data is available and the match is complete.

Element: Bracket /BracketItems /BracketItem /CompetitorPlace (1,N)			
- If the competitors are known, this element is used to place the competitors in the bracket.			
- If they are not yet known, it contains some information (on the rule to access to this bracket...)			
Attribute	M/O	Value	Description
Pos	M	Numeric 0	This attribute is a sequential number to place the competitors in the bracket (1 or 2).
Code	O	SC @CompetitorPlace or SC @IRM	Code for the first competitor of the BracketItem, usually to indicate the rule to access to the bracket item and appearing as first competitor. When there is no competitor send BYE or when not known yet send TBD or if an Invalid Result Mark (for example, DSQ). Send as appropriate.
WLT	O	SC @WLT	W or L, indicates the winner or loser of the bracket item. Always send when known.
Result	O	S(10)	The result (score) of the competitor in the event unit
IRM	O	SC @IRM	The invalid rank mark, if applicable
StrikeOut	O	S(1)	If the competitor should be struck out in this bracket item send Y, usually only used for DQB.



Element: Bracket /BracketItems /BracketItem /CompetitorPlace /PreviousUnit (0,1)
 Previous event unit related to the CompetitorPlace@Pos competitor of the current bracket item. It is always informed except for the bracket items whose CompetitorPlace@Pos competitor do not have preceding event units in the bracket graph unless coming from a pool.

Attribute	M/O	Value	Description
Unit	O	CC @Unit	Full RSC code of the previous event unit for the CompetitorPlace@Pos competitor of the bracket item. Must send if a winner/loser from a single unit. If from a pool then this is the RSC of the pool.
Value	O	SC @Pool or S(6)	If the competitor in the current unit is unknown due to coming from a pool or previous matches then fill this field with the pool code or the match number as appropriate.
WLT	O	SC @WLT	Send W or L for winner or loser of previous match (if not Pool) do not send if participant is unknown from a pool.

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor (0,1)
 CompetitorPlace @Pos competitor related to the bracket item. Only include if the competitor is known .

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team or A for athlete
Seed	O	Numeric #0	The seed of the competitor or equivalent information Always when it exists
Organisation	O	CC @Organisation	Competitors' organisation if known

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Description (0,1)

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams/doubles (Organisation)

Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete (1,N)

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".



Element: Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFld	O	S(16)	International Federation ID
Class	O	CC @SportClass	This attribute is required in competitions including athletes with disabilities.

Sample

```

<Bracket Code="FNL">
  <BracketItems Code="QFL">
    <BracketItem Order="1" >
      <CompetitorPlace Pos="1" Code="BYE"/>
      <CompetitorPlace Pos="2" Code="BYE"/>
    </BracketItem>
    <BracketItem Order="2" Position="2" Result="4-1 (11:4 11:7 11:4 1:11 11:1)" Unit="TTEMSINGLES-----QFNL000100--" >
      <CompetitorPlace Pos="1" WLT="W">
        <Competitor Code="1126413" Type="A" Seed="2" Organisation="ESP" >
          <Composition>
            <Athlete Code="1126413" Order="1" >
              <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="ESP" BirthDate="1994-12-15" />
            </Athlete>
          </Composition>
        </Competitor>
      </CompetitorPlace>
      <CompetitorPlace Pos="2" WLT="L">>
        <Competitor Code="1093294" Type="A" Organisation="SUI" >
          <Composition>
            <Athlete Code="1093294" Order="1" >
              <Description GivenName="John" FamilyName="Black" Gender="M" Organisation="SUI" BirthDate="1992-12-13" />
            </Athlete>
          </Composition>
        </Competitor>
      </CompetitorPlace>
    </BracketItem>
  </BracketItems>
</Bracket>

```



2.2.7.5 Message Sort

Bracket @Code then BracketItems @Code then BracketItems /BracketItem /Unit @Unit are sorted according to their scheduled start time.

2.2.8 Statistics

2.2.8.1 Description

The Statistics message contains a list of statistics for a competitor (could be an individual athlete or a team), that applies at a DocumentCode level, which could be for an event unit, a phase or an event.

There will be a separate message (identified by the header's DocumentSubtype and DocumentSubcode) for every table where multiple statistics apply.

2.2.8.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Depending on the statistics is could be at any level though is always full RSC.
DocumentSubcode	Date	For TOU the DocumentSubcode with the day (in case of daily statistics) will be informed for some tournament statistics.
DocumentType	DT_STATS	Statistics message
DocumentSubtype	CUM TOU	In the case of CUM it will indicate singles, teams (singles in teams) or all matches. In the case of TOU it will indicate event GSINGLES, GTEAM where G = M, W or O. Moreover, header attribute DocumentSubtype will be informed, categorizing different types of statistics reports. We will have the following different DocumentSubtype header attributes: * CUM: For cumulative statistics for individuals. * TOU: For Tournament statistics.
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	It indicates whether the result is official or intermediate etc). LIVE (used during the competition when nothing else applies) INTERMEDIATE (used after the competition has started and is not finished but not currently live, typically between units) OFFICIAL (after the last unit which effects the statistics is official)
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.

Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.8.3 Trigger and Frequency

This message is sent with CUM and TOU after each match.

2.2.8.4 Message Values

Element: ExtendedInfos /Progress (0,1)			
Attribute	M/O	Value	Description
LastUnit	O	CC @Unit	Send the RSC of the most recently unit made official.
UnitsTotal	O	Numeric ##0	The total number of units (games) to be played
UnitsComplete	O	Numeric ##0	The total number of units (games) which are official.

Element: ExtendedInfos /SportDescription (0,1)			
Sport Description in Text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	O	S(40)	Event name (not code) from Common Codes.
Gender	O	CC @DisciplineGender	Gender code for the event unit



Element: Stats (1,1)			
Attribute	M/O	Value	Description
Code	M	SC @Statistics	A code to identify the statistics being listed

Element: Stats /StatsItems /StatsItem (1,N) Statistics for the event unit / phase or event – depending on the headers' DocumentCode. (information sent in the messages with TOU at the DocumentSubtype header)			
Type	Code	Pos	Description
ST	MATCHES_TEAM	Numeric 0	Pos Description: Send phase number for the statistics of each phase. "1" for finals "2" for Semifinals "3" for Quarterfinals ... and "0" for total statistics. Element Expected: Just for team events. It must include statistics for each phase (send phase number in Pos) and total statistics (send 0 in Pos). Only send Pos=0 for Daily message.
	Attribute	M/O	Value
	Value	M	Numeric #0
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
	Attribute	Value	Description
	Code	DURATION	
	Pos	N/A	N/A
	Value	hh:mm	Duration of team matches played
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
	Attribute	Value	Description
	Code	DURATION_AVG	
	Pos	N/A	N/A
	Value	hh:mm	Average duration of team matches played



Element: Stats /StatsItems /StatsItem (1,N) Statistics for the event unit / phase or event – depending on the headers' DocumentCode. (information sent in the messages with TOU at the DocumentSubtype header)			
Type	Code	Pos	Description
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	DURATION_MAX		
Pos	N/A	N/A	
Value	hh:mm	Duration of the longest team match	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	DURATION_MIN		
Pos	N/A	N/A	
Value	hh:mm	Duration of the shortest team match	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	MARGIN		
Pos	SC @Margin	Send 5 for 3:0, 6 for 3:1, 7 for 3:2 match margin and 8 for IRM. In the Paralympics Send 5 for 2:0, 6 for 2:1 match margin, and 8 for IRM	
Value	Numeric #0	Number of team matches won for each match margin (indicated at the @Pos number)	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	MARGIN_PERCENT		
Pos	SC @Margin	Send 5 for 3:0, 6 for 3:1, 7 for 3:2 match margin and 8 for IRM. In the Paralympics Send 5 for 2:0, 6 for 2:1 match margin, and 8 for IRM	
Value	Numeric ##0	Percentage of team matches won for each match margin (indicated at the @Pos number)	



Element: Stats /StatsItems /StatsItem (1,N) Statistics for the event unit / phase or event – depending on the headers' DocumentCode. (information sent in the messages with TOU at the DocumentSubtype header)			
Type	Code	Pos	Description
ST	MATCHES	Numeric #0	Pos Description: Send phase number for the statistics of each phase. "1" for finals "2" for Semifinals "3" for Quarterfinals ... and "0" for total statistics. Element Expected: For singles and team events. It must include statistics for each phase (send phase number in Pos) and total statistics (send 0 in Pos). Only send Pos=0 for Daily message.
	Attribute	M/O	Value
	Value	M	Numeric ##0
	Sub Element: Stats /StatsItems /StatsItem /ExtendedStat		
	Expected: Always		
	Attribute	Value	Description
	Code	DURATION	
	Pos	N/A	N/A
	Value	hh:mm	Total duration
	Sub Element: Stats /StatsItems /StatsItem /ExtendedStat		
	Expected: Always		
	Attribute	Value	Description
	Code	DURATION_AVG	
	Pos	N/A	N/A
	Value	hh:mm	Average match duration
	Sub Element: Stats /StatsItems /StatsItem /ExtendedStat		
	Expected: Always		
	Attribute	Value	Description
	Code	DURATION_MAX	
	Pos	N/A	N/A



Element: Stats /StatsItems /StatsItem (1,N)

**Statistics for the event unit / phase or event – depending on the headers' DocumentCode.
(information sent in the messages with TOU at the DocumentSubtype header)**

Type	Code	Pos	Description
Value	hh:mm		Duration of the longest match
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			
Attribute	Value	Description	
Code	DURATION_MIN		
Pos	N/A		N/A
Value	hh:mm		Duration of the shortest match
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			
Attribute	Value	Description	
Code	MARGIN		
Pos	SC @Margin		Send 1 for 4:0, 2 for 4:1, 3 for 4:2, 4 for 4:3, 5 for 3:0, 6 for 3:1, 7 for 3:2 game margin and 8 for IRM In the Paralympics. Send 1 for 3:0, 2 for 3:1, 3 for 3:2 match margin and 8 for IRM
Value	Numeric #0		Number of matches won for each game margin (indicated at the @Pos number)
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			
Attribute	Value	Description	
Code	MARGIN_PERCENT		
Pos	SC @Margin		Send 1 for 4:0, 2 for 4:1, 3 for 4:2, 4 for 4:3, 5 for 3:0, 6 for 3:1, 7 for 3:2 game margin and 8 for IRM. In the Paralympics. Send 1 for 3:0, 2 for 3:1, 3 for 3:2 match margin and 8 for IRM
Value	Numeric #0		Percentage of matches won for each game margin (indicated at the @Pos number)



Element: Stats /StatsItems /StatsItem (1,N) Statistics for the event unit / phase or event – depending on the headers' DocumentCode. (information sent in the messages with TOU at the DocumentSubtype header)				
Type	Code	Pos	Description	
ST	GAMES	Numeric 0	Pos Description: Send phase number for the statistics of each phase. "1" for finals "2" for Semifinals "3" for Quarterfinals ... and "0" for total statistics. Element Expected: For singles and team events. It must include statistics for each phase (send phase number in Pos) and total statistics (send 0 in Pos). Only send Pos=0 for Daily message.	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Total games played
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always				
	Attribute	Value	Description	
	Code	DURATION		
	Pos	N/A	N/A	
	Value	hh:mm	Total duration	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always				
	Attribute	Value	Description	
	Code	DURATION_AVG		
	Pos	N/A	N/A	
	Value	hh:mm	Average game duration	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always				
	Attribute	Value	Description	
	Code	DURATION_MAX		
	Pos	N/A	N/A	



Element: Stats /StatsItems /StatsItem (1,N) Statistics for the event unit / phase or event – depending on the headers' DocumentCode. (information sent in the messages with TOU at the DocumentSubtype header)			
Type	Code	Pos	Description
Value	hh:mm		Duration of the longest game
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	DURATION_MIN		
Pos	N/A		N/A
Value	hh:mm		Duration of the shortest game
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	MARGIN		
Pos	SC @PointMargin		Send 1 for 11 point margin, 2 for 10 point margin... 10 for 2 point margin and 11 for IRM
Value	Numeric #0		Number of games won for each point margin (indicated at the @Pos number)
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat Expected: Always			
Attribute	Value	Description	
Code	MARGIN_PERCENT		
Pos	SC @PointMargin		Send 1 for 11 point margin, 2 for 10 point margin... 10 for 2 point margin and 11 for IRM
Value	Numeric #0		Percentage of games won for each point margin (indicated at the @Pos number)



Element: Stats /StatsItems /StatsItem (1,N) Statistics for the event unit / phase or event – depending on the headers' DocumentCode. (information sent in the messages with TOU at the DocumentSubtype header)			
Type	Code	Pos	Description
ST	PTS	Numeric 0	Pos Description: Send phase number for the statistics of each phase. "1" for finals "2" for Semifinals "3" for Quarterfinals ... and "0" for total statistics. Element Expected: For singles and team events. It must include statistics for each phase (send phase number in Pos) and total statistics (send 0 in Pos). Only send Pos=0 for Daily message.
Attribute	M/O	Value	Description
Value	M	Numeric ###0	Total points scored
Avg	O	Numeric #0.00	Average of points scored per game
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			
Attribute	Value	Description	
Code	CONS_WON_MAX		
Pos	N/A	N/A	
Value	Numeric #0	Send the most consecutive points won	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			
Attribute	Value	Description	
Code	DEF_OVC_MAX		
Pos	N/A	N/A	
Value	Numeric #0	Send the greatest deficit overcome	
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			



Element: Stats /StatsItems /StatsItem (1,N)

**Statistics for the event unit / phase or event – depending on the headers' DocumentCode.
(information sent in the messages with TOU at the DocumentSubtype header)**

Type	Code	Pos	Description
Attribute	Value	Description	
Code	RALLY_AVG		
Pos	N/A	N/A	
Value	Numeric #0		Send the average rally (number of strokes)
Sub Element: Stats /StatsItems /StatsItem /ExtendedStat			
Expected: Always			
Attribute	Value	Description	
Code	RALLY_MAX		
Pos	N/A	N/A	
Value	Numeric #0		Send the longest rally (number of strokes)



Sample

```
<StatsItems>
  <StatsItem Type="ST" Code="MATCHES_TEAM" Pos="0" Value="12" >
    <ExtendedStat Code="MARGIN" Pos="5" Value="9" />
    <ExtendedStat Code="MARGIN" Pos="6" Value="3" />
    <ExtendedStat Code="MARGIN" Pos="7" Value="0" />
    <ExtendedStat Code="MARGIN" Pos="8" Value="0" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="5" Value="75" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="6" Value="25" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="7" Value="0" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="8" Value="0" />
    <ExtendedStat Code="DURATION" Value="19:18" />
    <ExtendedStat Code="DURATION_MAX" Value="2:42" />
    <ExtendedStat Code="DURATION_MIN" Value="0:58" />
    <ExtendedStat Code="DURATION_AVG" Value="1:37" />
  </StatsItem>
  <StatsItem Type="ST" Code="MATCHES" Pos="0" Value="39" >
    <ExtendedStat Code="MARGIN" Pos="5" Value="26" />
    <ExtendedStat Code="MARGIN" Pos="6" Value="10" />
    <ExtendedStat Code="MARGIN" Pos="7" Value="3" />
    <ExtendedStat Code="MARGIN" Pos="8" Value="0" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="5" Value="67" />
  ...
  </StatsItem>
  <StatsItem Type="ST" Code="GAMES" Pos="0" Value="133" >
    <ExtendedStat Code="MARGIN" Pos="1" Value="0" />
    <ExtendedStat Code="MARGIN" Pos="2" Value="1" />
    <ExtendedStat Code="MARGIN" Pos="3" Value="7" />
    ...
    <ExtendedStat Code="MARGIN" Pos="11" Value="0" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="1" Value="0" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="2" Value="1" />
    ...
    <ExtendedStat Code="MARGIN_PERCENT" Pos="10" Value="23" />
    <ExtendedStat Code="MARGIN_PERCENT" Pos="11" Value="0" />
    <ExtendedStat Code="DURATION" Value="13:38" />
    <ExtendedStat Code="DURATION_MAX" Value="0:13" />
    <ExtendedStat Code="DURATION_MIN" Value="0:03" />
    <ExtendedStat Code="DURATION_AVG" Value="0:06" />
  </StatsItem>
  <StatsItem Type="ST" Code="PTS" Pos="0" Value="2435" Avg="18.31" >
    <ExtendedStat Code="CONS_WON_MAX" Value="9" />
    <ExtendedStat Code="DEF_OVC_MAX" Value="5" />
    <ExtendedStat Code="RALLY_MAX" Value="93" />
    <ExtendedStat Code="RALLY_AVG" Value="6" />
  </StatsItem>
  ....
```




Element: Stats /Competitor (0,N) Competitor of the statistics.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID to be assigned a specific type of statistic. The competitor should be participating in the event / phase / event unit depending on the DocumentCode in the message's header.
Type	M	S(1)	T for team A for athlete
Order	M	Numeric ##0	Order of the competitor in the statistics
Organisation	O	CC @Organisation	Competitor's organisation if known

Element: Stats /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams

Element: Stats /Competitor /StatsItems /StatsItem (1,N) For Mixed Team only (information sent in the messages with CUM at the DocumentSubtype header attribute)			
Type	Code	Pos	Description
ST	MATCHES	N/A	Element Expected: For the team
	Attribute	M/O	Value
	Attempt	O	Numeric #0
	Value	M	Numeric #0
	Percent	O	Numeric ##0
	Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available		
	Attribute	Value	Description
	Code	LOST	
	Pos	N/A	N/A
	Value	Numeric #0	Number of matches lost
ST	DURATION	N/A	Element Expected: For athletes or team members



Element: Stats /Competitor /StatsItems /StatsItem (1,N) For Mixed Team only (information sent in the messages with CUM at the DocumentSubtype header attribute)					
Type	Code	Pos	Description		
	Attribute	M/O	Value	Description	
	Value	M	hh:mm	Duration of all matches for the team	
	Avg	O	hh:mm	Average match duration	
ST	GAMES	N/A	Element Expected: If available		
	Attribute	M/O	Value	Description	
	Attempt	O	Numeric ##0	Number of games played by the team	
	Value	M	Numeric ##0	Number of games won	
	Percent	O	Numeric ##0	Percentage of games won	
	Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available				
	Attribute	Value	Description		
	Code	LOST			
	Pos	N/A	N/A		
	Value	Numeric ##0	Number of games lost		
	ST	PTS	N/A	Element Expected: For the team	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available					
Attribute	Value	Description			
Code	CONS_LOST_MAX				
Pos	N/A	N/A			
Value	Numeric ##0	Most consecutive points lost			
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available					
Attribute	Value	Description			
Code	CONS_WON_MAX				
Pos	N/A	N/A			
Value	Numeric ##0	Most consecutive points won			



**Element: Stats /Competitor /StatsItems /StatsItem (1,N)
For Mixed Team only (information sent in the messages with CUM at the DocumentSubtype header attribute)**

Type	Code	Pos	Description
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	DEF_OVC_MAX		
Pos	N/A	N/A	
Value	Numeric #0	Greatest deficit overcome	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LEAD_LOST_MAX		
Pos	N/A	N/A	
Value	Numeric #0	Greatest lead lost	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LOST		
Pos	N/A	N/A	
Value	Numeric ##0	Total points lost	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LOST_OPP_SERVE		
Pos	N/A	N/A	
Value	Numeric ##0	Total points lost in opponent's serve	
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LOST_OWN_SERVE		
Pos	N/A	N/A	



Element: Stats /Competitor /StatsItems /StatsItem (1,N)			
For Mixed Team only (information sent in the messages with CUM at the DocumentSubtype header attribute)			
Type	Code	Pos	Description
Value	Numeric ##0		Total points lost in own serve
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: If available			
Attribute	Value	Description	
Code	WON		
Pos	N/A		N/A
Value	Numeric ##0		Total points won
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: If available			
Attribute	Value	Description	
Code	WON_OPP_SERVE		
Pos	N/A		N/A
Value	Numeric ##0		Total points won in opponent's serve
Sub Element: Stats /Competitor /StatsItems /StatsItem /ExtendedStat			
Expected: If available			
Attribute	Value	Description	
Code	WON_OWN_SERVE		
Pos	N/A		N/A
Value	Numeric ##0		Total points won in own serve
ST	IRM	N/A	Element Expected: If applicable
Attribute	M/O	Value	Description
Value	M	SC @IRM	Team's invalid result mark for the tournament

Element: Stats /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Numeric #0	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".



Element: Stats /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID
Class	O	CC @SportClass	This attribute is required in competitions including athletes with disabilities.

Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Team member's or individual athlete's stats item, depending on whether Competitor @Type="T" or Competitor @Type="A" according to competitors' rules. (information sent in the messages with CUM at the DocumentSubtype header attribute)				
Type	Code	Pos	Description	
ST	MATCHES	N/A	Element Expected: For athletes or team members	
	Attribute	M/O	Value	Description
	Attempt	O	Numeric #0	Number of matches played by the athlete
	Value	M	Numeric #0	Number of matches won by the athlete
	Percent	O	Numeric ##0	Percentage of matches won
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available				
	Attribute	Value	Description	
	Code	LOST		
	Pos	N/A	N/A	
	Value	Numeric #0	Number of matches lost by the athlete	
ST	DURATION	N/A	Element Expected: For athletes or team members	
	Attribute	M/O	Value	Description
	Value	M	hh:mm	Duration of all matches for the player
	Avg	O	hh:mm	Average match duration for the player



Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N) Team member's or individual athlete's stats item, depending on whether Competitor @Type="T" or Competitor @Type="A" according to competitors' rules. (information sent in the messages with CUM at the DocumentSubtype header attribute)			
Type	Code	Pos	Description
ST	GAMES	N/A	Element Expected: If available
	Attribute	M/O	Value
	Attempt	O	Numeric ##0
	Value	M	Numeric ##0
	Percent	O	Numeric ##0
	Description Number of games played by the player		
	Description Number of games won by the player		
	Description Percentage of games won by the player		
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available		
	Attribute	Value	Description
	Code	LOST	
	Pos	N/A	N/A
	Value	Numeric ##0	Number of games lost by the player
ST	PTS	N/A	Element Expected: For athletes or team members
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available		
	Attribute	Value	Description
	Code	CONS_LOST_MAX	
	Pos	N/A	N/A
	Value	Numeric ##0	Most consecutive points lost by the player
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available		
	Attribute	Value	Description
	Code	CONS_WON_MAX	
	Pos	N/A	N/A
	Value	Numeric ##0	Most consecutive points won by the player
	Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available		



Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)
Team member's or individual athlete's stats item, depending on whether Competitor @Type="T" or Competitor @Type="A" according to competitors' rules.
(information sent in the messages with CUM at the DocumentSubtype header attribute)

Type	Code	Pos	Description
Attribute	Value	Description	
Code	DEF_OVC_MAX		
Pos	N/A	N/A	
Value	Numeric #0		Greatest deficit overcome by the player
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LEAD_LOST_MAX		
Pos	N/A	N/A	
Value	Numeric #0		Greatest lead lost by the player
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LOST		
Pos	N/A	N/A	
Value	Numeric ##0		Total points lost by the player
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LOST_OPP_SERVE		
Pos	N/A	N/A	
Value	Numeric ##0		Total points lost by the player in opponent's serve
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat Expected: If available			
Attribute	Value	Description	
Code	LOST_OWN_SERVE		
Pos	N/A	N/A	
Value	Numeric ##0		Total points lost by the player in own serve



Type	Code	Pos	Description	
Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Team member's or individual athlete's stats item, depending on whether Competitor @Type="T" or Competitor @Type="A" according to competitors' rules.				
(information sent in the messages with CUM at the DocumentSubtype header attribute)				
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat				
Expected: If available				
Attribute	Value	Description		
Code	WON			
Pos	N/A	N/A		
Value	Numeric ##0	Total points won by the player		
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat				
Expected: If available				
Attribute	Value	Description		
Code	WON_OPP_SERVE			
Pos	N/A	N/A		
Value	Numeric ##0	Total points won by the player in opponent's serve		
Sub Element: Stats /Competitor /Composition /Athlete /StatsItems /StatsItem /ExtendedStat				
Expected: If available				
Attribute	Value	Description		
Code	WON_OWN_SERVE			
Pos	N/A	N/A		
Value	Numeric ##0	Total points won by the player in own serve		
ST	HAND	N/A	Element Expected: For athletes or team members, if available	
	Attribute	M/O	Value	Description
	Value	M	SC @Hand	Handedness of the player
ST	GRIP	N/A	Element Expected: For athletes or team members, if available	
	Attribute	M/O	Value	Description
	Value	M	SC @Grip	Grip of the player
ST	IRM	N/A	Element Expected: If applicable	
	Attribute	M/O	Value	Description
	Value	M	SC @IRM	Player's invalid result mark for the tournament



Sample

```
<StatsItems>
  <StatsItem Type="ST" Code="MATCHES" Attempt="2" Value="2" Percent="100" >
    <ExtendedStat Code="LOST" Value="0" />
  </StatsItem>
  <StatsItem Type="ST" Code="DURATION" Value="0:50" Avg="0:25" >
  <StatsItem Type="ST" Code="GAMES" Attempt="6" Value="6" Percent="100" >
    <ExtendedStat Code="LOST" Value="0" />
  </StatsItem>
  <StatsItem Type="ST" Code="PTS">
    <ExtendedStat Code="WON" Value="67" />
    <ExtendedStat Code="LOST" Value="44" />
    <ExtendedStat Code="WON_OWN_SERVE" Value="30" />
    <ExtendedStat Code="LOST_OWN_SERVE" Value="27" />
    <ExtendedStat Code="WON_OPP_SERVE" Value="37" />
    <ExtendedStat Code="LOST_OPP_SERVE" Value="17" />
    <ExtendedStat Code="CONS_WON_MAX" Value="6" />
    <ExtendedStat Code="CONS_LOST_MAX" Value="5" />
    <ExtendedStat Code="DEF_OVC_MAX" Value="4" />
    <ExtendedStat Code="LEAD_LOST_MAX" Value="0" />
  </StatsItem>
  <StatsItem Type="ST" Code="HAND" Value="R" />
  <StatsItem Type="ST" Code="GRIP" Value="S" />
</StatsItems>
```

2.2.8.5 Message Sort

Sort according to the @Order attributes.

2.2.9 Event Final Ranking

2.2.9.1 Description

The event final ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a generic message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Rank Mark (disqualified, etc.), or both.

Depending on the sport rules include all competitors in the competition as all can be ranked (as in Marathon) or only include those with a final ranking as other are unranked.

2.2.9.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC of the Event	Full (34) RSC of the event
DocumentType	DT_RANKING	Event Final ranking message
Version	1..V	Version number associated to the message's content. Ascendant number
ResultStatus	SC @ResultStatus	Result status, indicates whether the data is official or partial. OFFICIAL PARTIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.



Attribute	Value	Comment
LogicalDate	Date	<p>Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight.</p> <p>If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2).</p> <p>The end of the logical day is defined by default at 03:00 a.m.</p> <p>For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction.</p> <p>Logical Date is expressed in the local time zone where the message was produced.</p>
Source	SC @Source	Code indicating the system which generated the message.

2.2.9.3 Trigger and Frequency

This message is only triggered after a unit which affects the final ranking is official and that particular ranking is not subject to change.

- After the event is finished (OFFICIAL)
- After any final ranking is known (PARTIAL)

2.2.9.4 Message Values

Element: ExtendedInfos /SportDescription (0,1) Sport Description in text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline name (not code) from Common Codes
EventName	M	S(40)	Text short description, not code
Gender	M	CC @DisciplineGender	Gender code for the event unit.

Element: ExtendedInfos /VenueDescription (0,1) Venue Names in text			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue short name (not code) from Common Codes



Element: Result (1,N)			
For any event final ranking message, there should be at least one competitor being awarded a result for the event.			
Attribute	M/O	Value	Description
Rank	O	Text	Rank of the competitor in the result. It is optional because the team can be disqualified
RankEqual	O	S(1)	Send "Y" if the Rank is 84qualified else do not send.
IRM	O	SC @IRM	Send just if the competitor has been disqualified
SortOrder	M	Numeric #0	Unique sort order for all results based on rank to break rank ties. This attribute is a sequential number with the order of the competitors at the end of the event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified teams.

Element: Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes, organisation ID	Competitor's ID. If organisation the Organisation ID. "NOCOMP" in the case where there is no competitor in the rank due to IRM.
Type	M	S(1)	A for athlete T for team
Organisation	O	CC @Organisation	Organisation of the competitor

Element: Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams

Element: Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to an individual athlete or a team member. Team members should be participating in the event.
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".



Element: Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID
Class	O	CC @SportClass	This attribute is required in competitions including athletes with disabilities.

Element: Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult (1,N)			
Team member's extended result (only for Team events)			
Type	Code	Pos	Description
ER	IRM	N/A	Element Expected: As soon as this information is available and only for individuals in a team if applicable
	Attribute	M/O	Value
	Value	M	SC @IRM
			Description
			Send invalid result mark, in case it is assigned to a team member.

Sample



```
<Result Rank="1" SortOrder="1" >
  <Competitor Code="1078935" Type="A" Organisation="ESP" >
    <Composition>
      <Athlete Code="1102342" Order="1">
        <Description GivenName="John" FamilyName="Black" Gender="M" Organisation="ESP"
BirthDate="1994-12-15" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
<Result Rank="2" SortOrder="2" >
  <Competitor Code="1126413" Type="A" Organisation="USA" >
    <Composition>
      <Athlete Code="1102342" Order="1">
        <Description GivenName="Pat" FamilyName="Smith" Gender="M" Organisation="USA"
BirthDate="1992-12-15" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
```

2.2.9.5 Message Sort

Sort by Result @SortOrder

2.2.10 Configuration

2.2.10.1 Description

The Configuration is a message containing general configuration.

Ideally the configuration should be provided before competition.

2.2.10.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	Full RSC	Sent this message for each event.
DocumentType	DT_CONFIG	Configuration message
Version	1..V	Version number associated to the message's content. Ascendant number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. If an event unit continues after midnight (24:00), all messages produced will be considered as happening at the logical date on which the event unit began (e.g. for a session which began at 21:00 on Aug 2 and ended at 1:20 on Aug 3, the message will all be dated Aug 2). The end of the logical day is defined by default at 03:00 a.m. For messages corrections, like invalidating medals or Records, it will be the LogicalDate of the day of the correction. Logical Date is expressed in the local time zone where the message was produced.
Source	SC @Source	Code indicating the system which generated the message.

2.2.10.3 Trigger and Frequency

- Send for all events, one message per event. Send as soon as the bracket size is known (regardless of the competition starts with pools or not).

2.2.10.4 Message Values

Element: Configs /Config (1,N)			
Attribute	M/O	Value	Description
Unit	M	CC @Event	Full RSC of the event

Element: Configs /Config /ExtendedConfig (1,N)				
Type	Code	Pos	Description	
EC	BRACKET_SIZE (send by event)	N/A	Element Expected: When available	
	Attribute	M/O	Value	Description
	Value	M	SC @BracketItems	Send the code for the first bracket phase of the event

Sample

```
....
<Config Unit="TTEMSINGLES-----" >
  <ExtendedConfig Type="EC" Code="BRACKET_SIZE" Value="R128" />
</Config>
```

2.2.10.5 Message Sort

There is no general message sorting rule.



3 Document Control

Version history		
Version	Date	Comments
v1.0	23 November 2016	First version
V1.1	9 January 2017	SFA
V1.2	2 March 2017	Updated
V1.3	24 March 2017	Updated
V1.4	21 May 2017	Error correction
V1.5	1 August 2017	Adapt for YOG
V2.0	4 January 2019	Updated
V2.1	25 February 2019	Updated

File Reference: ODF R-SOG-2020-TTE V2.1 SFA

Change Log		
Version	Status	Changes in version
v1.0	SFR	First Version
V1.1	SFA	Remove reference to Bib in DT_PARTIC (typo) Updated to SFA
V1.2	APP	DT_RESULT: Remove StartListMod in the header 1.4 Add note regarding the RANK_WLD for Commonwealth Games DT_POOL_STANDING: Remove DocumentSubtype in the header
V1.3	APP	DT_RESULT: Note that CARD is for singles and doubles matches, not overall team. Clarify that doubles always uses 1,2 for team order. And only those in a sub-match are included.
V1.4	APP	DT_RESULT: Correct error in the use of duration in ExtendedInfos. Should be an attribute.
V1.5	APP	DT_POOL_STANDING: Add Result/For, Result/Against, GAMES/WON and GAMES/LOST



Change Log		
Version	Status	Changes in version
V2.0	SFA	<p>DT_PARTIC: Updated to add Passport names (CR15219)</p> <p>DT_PARTIC: Delete ENTRY/SEED (not required in ORIS)</p> <p>DT_PARTIC_TEAMS: Add ENTRY/SEED</p> <p>DT_RESULTS: Updated ExtendedInfos for teams to be clearer.</p> <p>Add Class where applicable for use in Paralympic Games</p> <p>Removed reference to 2018 Commonwealth Games</p> <p>Removed reference to 2018 Youth Olympics</p> <p>CR 15039: Add DT_PARTIC_NAME to applicable messages.</p> <p>CR 16671: Add TVFamilyName in DT_PARTIC message.</p> <p>CR16537: Add ExtendedInfos/Progress to pool standings and statistics to replace the previous extensions.</p> <p>CR 16628: DT_BRACKETS: Add attributes to remove some extensions. Clarify previous unit.</p> <p>CR 16928: DT_STATS: Add Value & Avg @ ST/PTS @Stats/StatsItems/StatsItem, remove extensions & simplify stats @ Stats /Competitor /Composition /Athlete /StatsItems /StatsItem with Percent and Avg.</p>
V2.1	SFA	<p>DT_PARTIC: Removed Substitute and Status as not applicable.</p> <p>DT_PARTIC: Add ENTRY/SEED</p> <p>DT_RESULT: Add EUE/SEED for teams and athletes.</p>