



International
Olympic
Committee

EG-2024-TEQ-1.0 SFA

Olympic Data Feed

Teqball

ODF Data Dictionary

Technology and Information Department
© International Olympic Committee

EG-2024-TEQ-1.0 SFA
1 November 2022

License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.

The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.

5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.

1	Introduction.....	5
1.1	This document	5
1.2	Objective.....	5
1.3	Main Audience.....	5
1.4	Glossary	5
1.5	Related Documents	5
2	Messages	5
2.1	Teqball Overview	5
2.2	Applicable Messages	6
2.3	Messages	8
2.3.1	List of participants by discipline / List of participants by discipline update	8
2.3.1.1	Description.....	8
2.3.1.2	Header Values.....	8
2.3.1.3	Trigger and Frequency	9
2.3.1.4	Message Structure	9
2.3.1.5	Message Values	10
2.3.1.6	Message Sort	12
2.3.2	List of teams / List of teams update	13
2.3.2.1	Description.....	13
2.3.2.2	Header Values.....	13
2.3.2.3	Trigger and Frequency	13
2.3.2.4	Message Structure.....	14
2.3.2.5	Message Values	14
2.3.2.6	Message Sort	16
2.3.3	Event Unit Start List and Results.....	17
2.3.3.1	Description.....	17
2.3.3.2	Header Values.....	17
2.3.3.3	Trigger and Frequency	17
2.3.3.4	Message Structure.....	18
2.3.3.5	Message Values	20
2.3.3.6	Message Sort	24

2.3.4	Pool Standings	25
2.3.4.1	Description.....	25
2.3.4.2	Header Values.....	25
2.3.4.3	Trigger and Frequency	25
2.3.4.4	Message Structure.....	26
2.3.4.5	Message Values	28
2.3.4.6	Message Sort	31
2.3.5	Brackets	32
2.3.5.1	Description.....	32
2.3.5.2	Header Values.....	32
2.3.5.3	Trigger and Frequency	32
2.3.5.4	Message Structure.....	33
2.3.5.5	Message Values	34
2.3.5.6	Message Sort	37
2.3.6	Event Final Ranking.....	38
2.3.6.1	Description.....	38
2.3.6.2	Header Values.....	38
2.3.6.3	Trigger and Frequency	38
2.3.6.4	Message Structure.....	38
2.3.6.5	Message Values	39
2.3.6.6	Message Sort	42
3	Document Control.....	43



1 Introduction

1.1 This document

This document includes the ODF Teqball Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for this discipline.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Teqball Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies

1.5 Related Documents

Document Title	Document Description
ODF Foundation Principles	The document explains the environment & general principles for ODF
ODF General Messages Interface	The document describes the ODF General Messages
Common Codes	The document describes the ODF Common codes
ODF Header Values	The document details the header values which shows which RSCs are used in which messages.
ORIS Sports Document	The document details the sport specific requirements

2 Messages

2.1 Teqball Overview

MESSAGES IN EACH EVENT



- * All events (individual and pairs) have a single DT_RESULT, DT_PLAY_BY_PLAY for each unit (match).
- * For events which start with a groups phase then DT_POOL_STANDING is also provided.
- * There is also a DT_BRACKET message for the progression in each event.

SCHEDULE

- * The DT_SCHEDULE/DT_SCHEDULE_UPDATE message will include each unit (schedule=Y) only which is aligned with the same RSC for DT_RESULT.
- * The detailed schedule is not known until a few days before each day of competition. A series of temporary units will be scheduled (all identified by using phase = TMRY). The units will all be removed when the schedule is published.

2.2 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in this discipline.

- The column “Message type” indicates the MessageType that identifies a message
- The column “Message name” is the message name identified by the message type
- The column “Message extended” indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it follows the general definition rules.
- Message responsibilities appears in the ODF General Document.

Message Type	Message Name	Message extended
DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule / Competition schedule update	
DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / List of participants by discipline update	X
DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of teams / List of teams update	X
DT_RESULT	Event Unit Start List and Results	X
DT_POOL_STANDING	Pool Standings	X
DT_BRACKETS	Brackets	X
DT_RANKING	Event Final Ranking	X
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_MEDALS	Medal standings	
DT_COMMUNICATION	Communication	
DT_PRESENTER	Medal Presenters	
DT_LOCAL_ON	Discipline/venue start transmission	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_KA	Keep Alive	
DT_ALERT	Alert	
DT_BCK	Background Document	
DT_BIO_PAR	Participant Biography	
DT_NEWS	News Document	
DT_PIC	Pictures	
DT_PDF	PDF Message	



2.3 Messages

2.3.1 List of participants by discipline / List of participants by discipline update

2.3.1.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

It is important to note that all the sport messages that make references to athletes (event unit start list and results, phase results, medallists etc.) will always match the athlete ID with the athlete ID in this message.

List of participants by discipline (DT_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message includes a list of current athletes, officials, coaches, guides, technical officials, reserves and historical athletes regardless of their status.

List of participants by discipline update (DT_PARTIC_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

2.3.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Discipline	Full RSC at the discipline level
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	/ List of participants by discipline message
DocumentSubtype	S(20)	HISTORICAL if the message is from the historical results provider and only includes historic athletes else the attribute is not included. Never included in _UPDATE message.
Version	1..V	Version number associated to the message's content. Ascending number
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.



2.3.1.3 Trigger and Frequency

The DT_PARTIC message is sent as a bulk message prior to the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_UPDATE messages are sent.

The DT_PARTIC_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.

2.3.1.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6
Competition (0,1)					
	Gen				
	Sport				
	Codes				
	Participant (1,N)				
		Code			
		Parent			
		Status			
		GivenName			
		FamilyName			
		PassportGivenName			
		PassportFamilyName			
		PrintName			
		PrintInitialName			
		TVName			
		TVInitialName			
		TVFamilyName			
		LocalFamilyName			
		LocalGivenName			
		Gender			
		Organisation			
		BirthDate			
		PlaceofBirth			
		CountryofBirth			
		PlaceofResidence			
		CountryofResidence			
		Nationality			
		MainFunctionId			
		Current			
		OlympicSolidarity			
		ModificationIndicator			
		Discipline (1,1)			



	Code
	IFld
	RegisteredEvent (0,N)
	Event
	Substitute
	EventEntry (0,N)
	Type
	Code
	Pos
	Value

2.3.1.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Sample (General)

<Competition Gen="SOG-2020-1.10" Sport="SOG-2020-TEQ-1.10" Codes="SOG-2020-1.20" >

Element: Competition /Participant (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	<p>Participant's ID.</p> <p>It identifies an athlete or an official and the holding participant's valid information for one particular period of time.</p> <p>It is used to link other messages to the participant's information.</p> <p>Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc.</p> <p>When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.</p>
Parent	M	S(20) with no leading zeroes	<p>Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent.</p> <p>The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.</p>



			The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".
Status	O	CC @ParticStatus	Participant's accreditation status this attribute is Mandatory in the case of @Current="true" and it is optional in the case that @Current="false". To delete a participant, a specific value of the Status attribute is used.
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
PassportGivenName	O	S(25)	Passport Given Name (Uppercase).
PassportFamilyName	O	S(25)	Passport Family Name (Uppercase).
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
TVFamilyName	M	S(25)	TV family name
LocalFamilyName	O	S(25)	Family name in the local language in the appropriate case for the local language (usually mixed case)
LocalGivenName	O	S(25)	Given name in the local language in the appropriate case for the local language (usually mixed case)
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth. Expected for athletes, not expected for all groups of officials.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC @Country	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC @Country	Country ID of Residence
Nationality	O	CC @Country	Participant's nationality. Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC @ResultsFunction	Main function In the Case of Current="true" this attribute is Mandatory.
Current	M	boolean	It defines if a participant is participating in the games (true) or is a Historical participant (false).
OlympicSolidarity	O	S(1)	Send Y if the participant is a member of the Solidarity / Scholarship Program else not sent.
ModificationIndicator	M	S(1)	'N' or 'U' Attribute is mandatory in the DT_PARTIC_UPDATE message only N-New participant (in the case that this information comes as a late entry)



			U-Update participant If ModificationIndicator='N', then include new participant to the previous bulk-loaded list of participants If ModificationIndicator='U', then update the participant to the previous bulk-loaded list of participants To delete a participant, a specific value of the Status attribute is used.
--	--	--	---

Element: Competition /Participant /Discipline (1,1)

All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.

Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the Discipline. It is the discipline code used to fill the OdfBody @DocumentCode attribute.
IFld	O	S(16)	Competitor's federation number for the corresponding discipline.

Element: Competition /Participant /Discipline /RegisteredEvent (0,N)

All accredited athletes will be assigned to one or more events. There is one exception: in some sports, substitutes may be accredited without any associated event. Historical athletes are not registered to any event.

Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the Event
Substitute	O	S(1)	Flag that indicates when the competitor is an alternate. Send "Y" if the competitor is an alternate player.

Element: Competition /Participant /Discipline /RegisteredEvent /EventEntry (0,N)

Send if there are specific athlete's event entries.

Type		Code	Pos	Description
ENTRY		RANK_PTS	N/A	Element Expected: If available (this information can be sent in both messages).
	Attribute	M/O	Value	Description
	Value	M	Numeric #####0	Send the athlete's World Teqball Ranking Points.
ENTRY		RANK_WLD	N/A	Element Expected: If applicable (this information can be sent in both messages).
	Attribute	M/O	Value	Description
	Value	M	S(4)	Player's world ranking.

2.3.1.6 Message Sort

The message is sorted by Participant @Code

2.3.2 List of teams / List of teams update

2.3.2.1 Description

The List of teams message contains the list of teams related to the current competition.

A team is a type of competitor, being a group of two or more individual athletes participating together in one event. Pairs are also defined as team of two competitors. One team participates in one event of one discipline. When one team participates in multiple events, there will be one team for each event for the same group. Also when the same organisation participates in the same event twice, there will be different teams. Teqball has two types of teams, pairs and "team" in the team competition.

List of teams (DT_PARTIC_TEAMS) is a bulk message by discipline. The list is always complete. The arrival of this message resets all the previous participant teams' information for that discipline. It is assumed that all teams appearing in this list are valid, in the meaning that they are participating or they could participate in one event.

List of teams update (DT_PARTIC_TEAMS_UPDATE) is an update message. It is not a complete list of teams' information message. It only contains the data of a team being modified.

2.3.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Discipline	Full RSC at the discipline level
DocumentType	DT_PARTIC_TEAMS DT_PARTIC_TEAMS_UPDATE	List of participant teams message
DocumentSubtype	S(20)	HISTORICAL if the message is from the historical results provider and only includes historic teams else the attribute is not included. Never included in _UPDATE message.
Version	1..V	Version number associated to the message's content. Ascending number
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.2.3 Trigger and Frequency

The DT_PARTIC_TEAMS message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_TEAMS_UPDATE messages are sent.

The DT_PARTIC_TEAMS_UPDATE message is triggered when there is a modification in the data for any team after the transfer of control to OVR.



2.3.2.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6
Competition (0,1)					
	Gen				
	Sport				
	Codes				
	Team (1,N)				
		Code			
		Organisation			
		Number			
		Name			
		ShortName			
		TVTeamName			
		Gender			
		Current			
		TeamType			
		ModificationIndicator			
		Composition (0,1)			
			Athlete (0,N)		
				Code	
				Order	
		Discipline (0,1)			
			Code		
			RegisteredEvent (0,1)		
				Event	
				EventEntry (0,N)	
					Type
					Code
					Pos
					Value

2.3.2.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message



Element: Competition /Team (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Team's ID. When the Team is an historical one, then this ID starts with "T".
Organisation	M	CC @Organisation	Team organisation's ID
Number	O	Numeric #0	Team's number. If there is not more than one team for one organisation participating in one event, it is 1. Otherwise, it will be incremental, 1 for the first organisation's team, 2 for the second organisation's team, etc. Required in the case of current teams.
Name	M	S(73)	Team name
ShortName	M	S(40)	Team Short Name
TVTeamName	M	S(21)	TV Team Name
Gender	M	CC @SportGender	Gender Code of the Team
Current	M	boolean	It defines if a team is participating in the games (true) or it is a Historical team (false)
TeamType	M	SC @TeamType	Send the team type. This is how the name is constructed to allow clients to build in other languages.
ModificationIndicator	M	N, U, D	Attribute is mandatory in the DT_PARTIC_TEAMS_UPDATE message only N-New team (in the case that this information comes as a late entry) U-Update team D-Delete team If ModificationIndicator='N', then include new team to the previous bulk-loaded list of teams If ModificationIndicator='U', then update the team to the previous bulk-loaded list of teams If ModificationIndicator='D', then delete the team to the previous bulk-loaded list of teams

Element: Competition /Team /Composition /Athlete (0,N)			
In the case of current teams the number of athletes is 2 or more.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete ID of the listed team member.
Order	O	Numeric	Team member order (same as defined in ORIS)

Element: Competition /Team /Discipline (0,1)			
Each team is assigned just to one discipline. Discipline is expected unless ModificationIndicator="D"			
Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the Discipline

Element: Competition /Team /Discipline /RegisteredEvent (0,1)			
Each current team is assigned to one event. Historical teams will not be registered to any event.			
Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the Event

2.3.2.6 Message Sort

The message is sorted by Team @Code.



2.3.3 Event Unit Start List and Results

2.3.3.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports. The definition includes as much generic information as possible due to the fact that each discipline and event has its own format for the results information (example: score of a match, time in a race, distance in a throw...).

This is always a full message and all applicable elements and attributes are always sent.

2.3.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Unit	Full RSC of the event unit
DocumentSubcode	N/A	N/A
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	N/A	N/A
Version	1..V	Version number associated to the message's content. Ascending number
ResultStatus	CC @ResultStatus	It indicates whether the result is official or unofficial (or intermediate etc.). START_LIST LIVE (used during the competition when nothing else applies). INTERMEDIATE (used after the competition has started and is not finished but not currently live) UNOFFICIAL OFFICIAL
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.3.3 Trigger and Frequency

This message is sent with ResultStatus 'START_LIST' as soon as the start list (competitors) are known and any changes to the information.

This message is then sent with ResultStatus 'LIVE' as soon as the unit starts and continues to be triggered on all updates.

For each match:

- As soon as each competitor is known and any changes in start list data (START_LIST)
- When the unit starts and after every change in any data (LIVE)
- At the end of each set (INTERMEDIATE)



- After the unit is over (UNOFFICIAL / OFFICIAL)

2.3.3.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
Competition (0,1)							
	Gen						
	Sport						
	Codes						
	ExtendedInfos (0,1)						
	UnitDateTime (0,1)						
	StartDate						
	Duration						
	ExtendedInfo (0,N)						
	Type						
	Code						
	Pos						
	Value						
	SportDescription (0,1)						
	DisciplineName						
	EventName						
	Gender						
	SubEventName						
	UnitNum						
	VenueDescription (0,1)						
	Venue						
	VenueName						
	Location						
	LocationName						
	Periods (0,1)						
	Home						
	Away						
	Period (1,N)						
	Code						
	HomeScore						
	AwayScore						
	HomePeriodScore						
	AwayPeriodScore						
	Duration						
	Result (1,N)						
	Result						



	IRM	
	WLT	
	SortOrder	
	StartSortOrder	
	ResultType	
	Competitor (1,1)	
	Code	
	Type	
	Organisation	
	Description (0,1)	
	TeamName	
	EventUnitEntry (0,N)	
	Type	
	Code	
	Pos	
	Value	
	StatsItems (0,1)	
	StatsItem (1,N)	
	Type	
	Code	
	Pos	
	Value	
	Composition (0,1)	
	Athlete (0,N)	
	Code	
	Order	
	Description (1,1)	
	GivenName	
	FamilyName	
	Gender	
	Organisation	
	BirthDate	
	IFId	
	EventUnitEntry (0,N)	
	Type	
	Code	
	Pos	
	Value	
	StatsItems (0,1)	
	StatsItem (1,N)	
	Type	



	Code
	Pos
	Value

2.3.3.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /UnitDateTime (0,1)			
Actual times. Include when the unit starts.			
Attribute	M/O	Value	Description
StartDate	M	DateTime	Actual start date and time.
Duration	O	mm	Match duration. Duration of the Match in minutes. Update with each message after the start of the match.

Element: Competition /ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	RES_CODE	N/A	Element Expected: Always when available
	Attribute	M/O	Value
	Value	M	SC @ResultCode
			Description
			Send the Result Code of the Match. Used only for Bye or W/O.
UI	CURRENT_SET	N/A	Element Expected: Always when LIVE
	Attribute	M/O	Value
	Value	M	SC @Period
			Description
			Current Set
UI	SERVE	SC @Home	Pos Description: If home or away have serve Element Expected: When available when LIVE. Updated for the server after each point for the next point.
	Attribute	M/O	Value
	Value	M	S(20) with no leading zeroes
			Description
			Competitor ID of the server
UI	MATCH_POINT	N/A	Element Expected: If applicable for the current point when triggered at the end of the point.
	Attribute	M/O	Value
	Value	M	SC @Home
			Description
			Next match point indicator:
UI	SET_POINT	Numeric 0	Element Expected: If applicable for the current point when triggered at the end of the point.



Attribute	M/O	Value	Description
Value	M	SC @Home	Next set point indicator

Element: Competition /ExtendedInfos /SportDescription (0,1)

Sport Descriptions in Text.

Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline ENG Description (not code) from Common Codes
EventName	M	S(40)	Event ENG Description (not code) from Common Codes.
Gender	M	CC @SportGender	Gender code for the event unit
SubEventName	M	S(40)	EventUnit ENG Description (not code) from Common Codes
UnitNum	O	S(15)	Match number as appropriate

Element: Competition /ExtendedInfos /VenueDescription (0,1)

Venue Names in Text.

Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue ENG Description (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location ENG Description (not code) from Common Codes

Element: Competition /Periods (0,1)

Attribute	M/O	Value	Description
Home	M	S(20) with no leading zeroes	Home Competitor ID
Away	M	S(20) with no leading zeroes	Away Competitor ID

Element: Competition /Periods /Period (1,N)

Attribute	M/O	Value	Description
Code	M	SC @Period	Set code, do not send TOT.
HomeScore	M	Numeric 0	Home competitor score up (number of sets won) at the end of this set (@Code period). Cumulative sets won by competitor with order 1 Send when the match starts
AwayScore	M	Numeric 0	Away competitor score up (number of sets won) at the end of this set (@Code period). Cumulative sets won by competitor with order 2 Send when the match starts
HomePeriodScore	O	Numeric #0	Home competitor points just for this set (@Code period). Points won by competitor with order 1 just for this set
AwayPeriodScore	O	Numeric #0	Away competitor points just for this set (@Code period). Points won by competitor with order 2 just for this set
Duration	O	mm	Duration (minutes) of the set



Sample (General)

```
<Periods Home="123456" Away="234567" >  
  <Period Code="S1" HomeScore="1" AwayScore="0" HomePeriodScore="12" AwayPeriodScore="8" Duration="15"/>  
  </Period>  
  <Period Code="S2" HomeScore="1" AwayScore="0" HomePeriodScore="6" AwayPeriodScore="2" Duration="10"/>  
</Periods>
```

Element: Competition /Result (1,N)

For each Event Unit Results message, there must be at least one competitor with a result element in the event unit.

Attribute	M/O	Value	Description
Result	O	Numeric 0	The result of the competitor in the event unit, i.e. the number of sets won in the match. Send either in the case @ResultType is points or IRM with points.
IRM	O	SC @IRM	Invalid Result Mark for the event unit, in case it is assigned. Send just in the case @ResultType is both IRM and Points for some period; the match will have finished.
WLT	O	SC @WLT	The code whether a competitor won (W) or lost (L) the match. Only included at the end of the unit
SortOrder	M	Numeric 0	Used to sort all start list competitors in an event unit. Send 1 for Home and 2 for Away.
StartSortOrder	M	Numeric	Same @SortOrder
ResultType	O	SC @ResultType	Result type, either points or IRM for the corresponding match.

Element: Competition /Result /Competitor (1,1)

Competitor related to the result of one event unit.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or NOCOMP	Competitor's ID (if known): -For Competitor @Type=T, it will be: Team's ID -Otherwise, Athlete's ID (for Competitor @Type=A) (for singles). NOCOMP is sent when there is no competitor (and will not come later).
Type	M	S(1)	T for team A for athlete
Organisation	O	CC @Organisation	Competitor's organisation

Element: Competition /Result /Competitor /Description (0,1)

Competitors extended information (for Team events, when competitor known).

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for doubles.



Element: Competition /Result /Competitor /EventUnitEntry (0,N)				
For team event information				
Type		Code	Pos	Description
EUE		SEED	N/A	Element Expected: Always, as soon as this information is known and this team has a Seed Number.
	Attribute	M/O	Value	Description
	Value	M	Numeric ##	Seed Number (for team)

Sample (doubles)

```
<EventUnitEntry Type="EUE" Code="SEED" Value="4" />
```

Element: Competition /Result /Competitor /StatsItems /StatsItem (1,N)				
Only applicable for doubles matches.				
Type		Code	Pos	Description
ST		PTS_PLAYED	SC @Period	Pos Description: Send the Period, not "TOT" Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Total Points Played
ST		PTS_WON	SC @Period	Pos Description: Send the Period, not "TOT" Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Total Points Won

Sample (General)

```
<StatsItems>  
  <StatsItem Type="ST" Code="PTS_PLAYED" Pos="G1" Value="25" />  
  <StatsItem Type="ST" Code="PTS_WON" Pos="G1" Value="21" />  
  ...  
</StatsItems>
```

Element: Competition /Result /Competitor /Composition /Athlete (0,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.
Order	M	Numeric #0	If Competitor @Type="T" then order attribute used to sort team members in a team. If Competitor @Type="A" then 1



Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Competition /Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)				
Individual athletes entry information.				
Type		Code	Pos	Description
EUE		SEED	N/A	Element Expected: Always, as soon as this information is known and this athlete has Seed Number.
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Seed Number (for athlete)

Sample (singles)

<EventUnitEntry Type="EUE" Code="SEED" Value="5" />

Element: Competition /Result /Competitor /Composition /Athlete /StatsItems /StatsItem (1,N)				
Only applicable for single matches.				
Type		Code	Pos	Description
ST		PTS_PLAYED	SC @Period	Pos Description: Send the Period, not "TOT" Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Total Points Played
ST		PTS_WON	SC @Period	Pos Description: Send the Period, not "TOT" Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Total Points Won

2.3.3.6 Message Sort

Sort by Result @SortOrder

2.3.4 Pool Standings

2.3.4.1 Description

The Pool Standings message contains the standings of a group in a competition. It is similar to the Phase Results message, except in the frequency and trigger. Here the message is triggered at the start of OVR operations and then after each event unit (game, match, etc.).

This report is sent independently for each of the groups / pools of the competition in a particular phase, and the group / pool can be determined from the message header (DocumentCode).

2.3.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Phase	Full RSC for the pool/group (phase)
DocumentSubcode	N/A	N/A
DocumentType	DT_POOL_STANDING	Pool Standings message
DocumentSubtype	N/A	N/A
Version	1..V	Version number associated to the message's content. Ascending number
ResultStatus	CC @ResultStatus	Status of the message. Expected statuses are: START_LIST (before the start of competition) INTERMEDIATE (during the phase) UNOFFICIAL (if last match is unofficial) OFFICIAL (after all matches official)
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.4.3 Trigger and Frequency

The general rule is that this message is sent:

- Before the start of the competition to build in the initial tables. The message has status START_LIST.
- When an event unit of the corresponding phase finishes (not waiting for official). The message has status INTERMEDIATE.
- When the phase finishes (there are no more event units/games to compete). The message has status OFFICIAL.

Trigger also after any change.



2.3.4.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
Competition (0,1)							
	Gen						
	Sport						
	Codes						
	ExtendedInfos (0,1)						
		ExtendedInfo (0,N)					
			Code				
			Pos				
			Value				
		Progress (0,1)					
			LastUnit				
			UnitsTotal				
			UnitsComplete				
		SportDescription (0,1)					
			DisciplineName				
			EventName				
			Gender				
		VenueDescription (0,1)					
			Venue				
			VenueName				
	Result (1,N)						
		Rank					
		RankEqual					
		ResultType					
		Result					
		IRM					
		QualificationMark					
		SortOrder					
		Won					
		Lost					
		Played					
		For					
		Against					
		Diff					
		ExtendedResults (0,1)					
			ExtendedResult (1,N)				
				Type			
				Code			



Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
				Pos			
				Value			
				Diff			
				Extension (0,N)			
		Competitor (1,1)					
			Code				
			Type				
			Organisation				
			Description (0,1)				
				TeamName			
			Composition (0,1)				
				Athlete (1,N)			
					Code		
					Order		
					Description (1,1)		
						GivenName	
						FamilyName	
						Gender	
						Organisation	
						BirthDate	
						IFId	
			Opponent (0,N)				
				Code			
				Type			
				Pos			
				Organisation			
				Date			
				Time			
				Unit			
				HomeAway			
				Result			
				Description (0,1)			
					TeamName		
				Composition (0,1)			
					Athlete (1,N)		
						Code	
						Order	
						Description (1,1)	
							GivenName
							FamilyName



Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
							Gender
							Organisation
							BirthDate
							IFId

2.3.4.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	QUAL_RULE	N/A	Element Expected: Always
Attribute	M/O	Value	Description
Value	M	SC @QualRule	Send the code for the qualification rule.

Element: Competition /ExtendedInfos /Progress (0,1)			
Attribute	M/O	Value	Description
LastUnit	O	CC @Unit	Send the full RSC of the most recently unit made official for the pool included in this message.
UnitsTotal	O	Numeric ##0	Total number of units (matches) to be played in the pool included in the message.
UnitsComplete	O	Numeric ##0	Total number of units (matches) which are official in the pool included in this message.

Element: Competition /ExtendedInfos /SportDescription (0,1)			
Sport Descriptions in Text.			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline ENG Description (not code) from Common Codes
EventName	M	S(40)	Event ENG Description (not code) from Common Codes.
Gender	M	CC @SportGender	Gender code for the event unit

Element: Competition /ExtendedInfos /VenueDescription (0,1)			
Venue Names in Text. Only included where the phase is contested at a single venue			
Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue ENG Description (not code) from Common Codes



Element: Competition /Result (1,N)			
For any message, there should be at least one competitor being awarded a result for the pool.			
Attribute	M/O	Value	Description
Rank	O	Text	Rank at the group.
RankEqual	O	S(1)	Send "Y" if the Rank is equalled else do not send.
ResultType	M	SC @ResultType	Type of the @Result attribute, either points or IRM obtained by the competitor at all the games of the group
Result	O	Numeric	Send the classification points a team has accrued during the pool stage.
IRM	O	SC @IRM	The invalid result mark, if applicable
QualificationMark	O	SC @QualificationMark	The code which gives an indication on the qualification of the competitor for the next round of the competition.
SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the group, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified competitors.
Won	O	Numeric #0	Number of matches won by the competitor in the group. Do not send if the competitor has not played.
Lost	O	Numeric #0	Number of matches lost by the competitor in the group. Do not send if the competitor has not played.
Played	O	Numeric #0	Number of matches played by the competitor in the group. Send 0 if not played.
For	O	Numeric ###0	Total number of points won. Do not send if the competitor has not played.
Against	O	Numeric ###0	Total number of points lost. Do not send if the competitor has not played.
Diff	O	+/-Numeric +##0 or -##0 or 0	Points difference, between points won and lost. Do not send if the competitor has not played.

Element: Competition /Result /ExtendedResults /ExtendedResult (1,N)			
Type	Code	Pos	Description
ER	SETS	N/A	Element Expected: If available
	Attribute	M/O	Value
	Value	M	Numeric #0
	Diff	M	+/-Numeric +/-#0 or 0
Sub Element: Competition /Result /ExtendedResults /ExtendedResult /Extension Expected If available			
	Attribute	Value	Description
	Code	LOST	
	Pos	N/A	
	Value	Numeric #0	Number of sets lost. Do not send anything in case of IRM.



Element: Competition /Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team A for athlete
Organisation	M	CC @Organisation	Competitor's organisation

Element: Competition /Result /Competitor /Description (0,1)			
Competitors extended information.			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team, if a team.

Element: Competition /Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Numeric 0	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A". (same order as defined in ORIS)

Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Competition /Result /Competitor /Opponent (0,N)			
Details of the opposing competitor in competitions within the pool. (The Opponent of the competitor in the Opponent @Pos column of the Pool)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor ID
Type	M	S(1)	A for athlete, T for team
Pos	M	Numeric #0	1 to n. Normally expected to be the same as SortOrder for the same competitor.
Organisation	M	CC @Organisation	Competitor's organisation (code). Must include if the data is available
Date	M	Date	Date of match between the competitor and opponent (example: YYYY-MM-DD). Must include if the data is available, send even after the match is complete.
Time	O	S(5)	Time of match (example HH:MM) Must include if the data is available and allowed to display, send even after the match is complete.
Unit	O	CC @Unit	Full RSC of the Unit for the Pool Item



HomeAway	O	S(1)	Home / Away indicator. Send H if the opponent is the home team, send A if the opponent is the away team.
Result	O	S(50)	Result of the match if match is complete and formatted as in ORIS (separator & order). Must include if the data is available and the match is complete. The order of the result data is relative to the competitor and may be reversed for other competitor or depending on home/away display rules. In case of withdrawn then send "No match"

Element: Competition /Result /Competitor /Opponent /Description (0,1)

Competitors extended information.

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the opposition team, if a team

Element: Competition /Result /Competitor /Opponent /Composition /Athlete (1,N)

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athletes ID, corresponding to either a team member or an individual athlete
Order	M	Numeric 0	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Competition /Result /Competitor /Opponent /Composition /Athlete /Description (1,1)

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

2.3.4.6 Message Sort

The attribute used to sort the results is Result @SortOrder.



2.3.5 Brackets

2.3.5.1 Description

The brackets message contains the brackets information for one particular event. It is used in events where there is a necessity to know in advance how successive event units will be filled as the competition progresses. In the early stages of the competition, it indicates how each of the event units will be built from the winners/losers, or other competition rules of the previous event units.

2.3.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Event	Full RSC of the Event
DocumentType	DT_BRACKETS	Brackets message
Version	1..V	Version number associated to the message's content. Ascending number
ResultStatus	CC @ResultStatus	Status of the message. Expected statuses are: START_LIST (before any unit is complete) INTERMEDIATE (during the competition) UNOFFICIAL (when last match unofficial) OFFICIAL (when all matches official)
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.5.3 Trigger and Frequency

This message should be sent at the very beginning of a competition, as soon as brackets are available.

Send when a match/event unit is completed is UNOFFICIAL. Send again when OFFICIAL in the case that the content changed, else do not trigger again. The message should be updated including information on each competitor in the different bracket items.

The @ResultStatus attribute will vary depending on the competition status.

- * Send with ResultStatus = 'START_LIST' before the competition with the empty bracket
- * Send with ResultStatus = 'INTERMEDIATE' after every match in the preliminaries which determines a position in the bracket
- * Send with ResultStatus = 'INTERMEDIATE' until the last event unit is Unofficial (i.e. for all event units up until the Gold Medal match is completed for an event)
- * Send with ResultStatus = 'UNOFFICIAL' when the last event unit for an event has Unofficial status.
- * Send with ResultStatus = 'OFFICIAL' when the last event unit for an event has Official status.

Trigger also after any change.



2.3.5.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9	Level 10	Level 11
Competition (0,1)										
	Gen									
	Sport									
	Codes									
	ExtendedInfos (0,1)									
	SportDescription (0,1)									
	DisciplineName									
	EventName									
	Gender									
	VenueDescription (0,1)									
	Venue									
	VenueName									
	Bracket (1,N)									
	Code									
	BracketItems (1,N)									
	Code									
	BracketItem (1,N)									
	Code									
	Order									
	Position									
	Date									
	Time									
	Unit									
	Result									
	CompetitorPlace (1,N)									
	Pos									
	Code									
	WLT									
	Result									
	ResultType									
	IRM									
	StrikeOut									
	PreviousUnit (0,1)									
	Unit									
	WLT									
	Competitor (0,1)									



	Code
	Type
	Seed
	Organisation
	Description (0,1)
	TeamName
	Composition (0,1)
	Athlete (1,N)
	Code
	Order
	Description (1,1)
	GivenName
	FamilyName
	Gender
	Organisation
	BirthDate
	IFId
	ExtBracketAths (0,1)
	ExtBracketAth (1,N)
	Type
	Code
	Pos
	Value

2.3.5.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /SportDescription (0,1)			
Sport Description in Text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline ENG Description (not code) from Common Codes
EventName	M	S(40)	Event ENG Description (not code) from Common Codes.
Gender	M	CC @SportGender	Gender code for the event unit

Element: Competition /ExtendedInfos /VenueDescription (0,1)			
Venue Names in text.			



Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue ENG Description (not code) from Common Codes

Element: Competition /Bracket (1,N)

Attribute	M/O	Value	Description
Code	M	SC @Bracket	Bracket code to identify a bracket item. One for each individual bracket Note for example Gold and Bronze are different brackets.

Element: Competition /Bracket /BracketItems (1,N)

Attribute	M/O	Value	Description
Code	M	SC @BracketItems	Bracket code to identify a set of bracket items. It usually refers to the round in the brackets, for example quarterfinals, semifinals or finals phases, etc.

Element: Competition /Bracket /BracketItems /BracketItem (1,N)

Attribute	M/O	Value	Description
Code	M	S(15)	Bracket code to identify a bracket item.
Order	M	Numeric ##0	Sequential number inside of BracketItems to indicate the order, always start at 1
Position	M	Numeric ##0	Bracket position when drawing the bracket. For example a quarter final has 4 items, with positions 1, 2, 3 and 4 from the top. Use the appropriate number to draw the position. If there is only 3 items in a quarterfinal and the fourth is not displayed and would logically be the first then the positions are 2, 3, 4.
Date	O	Date	Date of match (example: YYYY-MM-DD). Must be filled if known.
Time	O	S(5)	Time of match (example HH:MM). Must be filled if known.
Unit	O	CC @Unit	Full RSC of the unit for the BracketItem
Result	O	S(50)	Result of the match if the match is complete and formatted as appropriate (example: 2-0 (12-10, 12-8)). Must include if the data is available and the match is complete.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace (1,N)

- If the competitors are known, this element is used to place the competitors in the bracket.
- If they are not yet known, it contains some information (on the rule to access to this bracket...)

Attribute	M/O	Value	Description
Pos	M	Numeric 0	This attribute is a sequential number to place the different competitors in the bracket (1 or 2).
Code	O	SC @CompetitorPlace or SC @IRM	When there is no competitor send BYE or when not known yet send TBD or if an Invalid Result Mark (for example, DSQ). Send as appropriate.
WLT	O	SC @WLT	W or L, indicates the winner or loser of the bracket item. Always send when known.
Result	O	S(10)	The result (score) of the competitor in the event unit. This is sets won.
ResultType	O	SC @ResultType	Type of the @Result attribute.



IRM	O	SC @IRM	The invalid result mark, send DQB if applicable
StrikeOut	O	S(1)	If the competitor should be struck out in this bracket item send Y, usually only used for DQB.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /PreviousUnit (0,1)

Previous event unit related to the CompetitorPlace@Pos competitor of the current bracket item. It is always informed except for the bracket items whose CompetitorPlace@Pos competitor do not have preceding event units in the bracket graph unless coming from a pool.

Attribute	M/O	Value	Description
Unit	O	CC @Unit	Full RSC code (unit level) of the previous event unit for the CompetitorPlace@Pos competitor of the bracket item. Must send if a winner/loser from a single unit. If from a pool then this is the RSC of the pool.
Value	O	SC @Pool or S(6)	If the competitor in the current unit is unknown due to coming from a pool or previous matches then fill this field with the pool code or the match number as appropriate.
WLT	O	SC @WLT	If the competitor in the current unit is unknown and coming from an earlier bracketitem then fill this field with the W or L indication winner or loser of the previous unit if the information is known. Do not send if competitor comes from a pool.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor (0,1)

CompetitorPlace @Pos competitor related to the bracket item. Only include if the competitor is known.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	T for team A for athlete
Seed	O	Numeric #0	The seed of the competitor or equivalent information. Always when it exists.
Organisation	O	CC @Organisation	Competitors' organisation if known.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Description (0,1)

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for doubles.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete (1,N)

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /Description (1,1)

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete



Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFld	O	S(16)	International Federation ID

Sample (singles)

```
<BracketItem Code="122" Order="1" Position="1" Date="2020-08-05" Time="08:30" Unit="..." >
  <ExtBracketItems>
    <CompetitorPlace Pos="1">
      <Competitor Code="1126413" Type="A" Organisation="ESP" >
        <Composition>
          <Athlete Code="1126413" Order="1" >
            <Description GivenName="John" FamilyName="Smith" Gender="M" Organisation="ESP" BirthDate="1994-12-15" />
          </Athlete>
        </Composition>
      </Competitor>
    </CompetitorPlace>
    <CompetitorPlace Pos="2">
      <Competitor Code="1093294" Type="A" Organisation="SUI" >
        <Composition>
          <Athlete Code="1093294" Order="1" >
            <Description GivenName="John" FamilyName="Black" Gender="M" Organisation="SUI" BirthDate="1992-12-13" />
          </Athlete>
        </Composition>
      </Competitor>
    </CompetitorPlace>
  </BracketItem>
```

2.3.5.6 Message Sort

Bracket @Code (using order in sport codes) then Bracket/BracketItems @Code (descending, using order in sport codes) then Bracket/BracketItems/BracketItem @Position.

2.3.6 Event Final Ranking

2.3.6.1 Description

The Event Final Ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a generic message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Result Mark (disqualified, etc.), or both.

2.3.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Event	Full RSC of the Event
DocumentType	DT_RANKING	Event Final ranking message
Version	1..V	Version number associated to the message's content. Ascending number
ResultStatus	CC @ResultStatus	Result status, indicates whether the data is official or partial. PARTIAL OFFICIAL
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.6.3 Trigger and Frequency

This message is only triggered after a unit which affects the final ranking is official and that particular ranking is not subject to change.

- After any final ranking is known (PARTIAL)
- After the event is finished (OFFICIAL)

Trigger also after any major change.

2.3.6.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
Competition (0,1)							
	Gen						
	Sport						
	Codes						



ExtendedInfos (0,1)	
SportDescription (0,1)	
DisciplineName	
EventName	
Gender	
VenueDescription (0,1)	
Venue	
VenueName	
Result (1,N)	
Rank	
RankEqual	
IRM	
SortOrder	
Competitor (1,1)	
Code	
Type	
Organisation	
Description (0,1)	
TeamName	
Composition (1,1)	
Athlete (0,N)	
Code	
Order	
Description (1,1)	
GivenName	
FamilyName	
Gender	
Organisation	
BirthDate	
IFId	
ExtendedResults (0,1)	
ExtendedResult (1,N)	
Type	
Code	
Pos	
Value	

2.3.6.5 Message Values

Element: Competition (0,1)



Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /SportDescription (0,1)

Sport Description in text

Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline ENG Description (not code) from Common Codes
EventName	M	S(40)	Event ENG Description (not code) from Common Codes. Must be included if it is a single event
Gender	M	CC @SportGender	Gender code for the event unit. Must be included if it is a single gender

Element: Competition /ExtendedInfos /VenueDescription (0,1)

Venue Names in text

Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue code
VenueName	M	S(25)	Venue ENG Description (not code) from Common Codes

Element: Competition /Result (1,N)

For any event final ranking message, there should be at least one competitor being awarded a result for the event.

Attribute	M/O	Value	Description
Rank	O	Text	Final rank of the competitor in the corresponding event. It is optional because the competitor be disqualified.
RankEqual	O	S(1)	Identifies if a rank has been equalled. Send "Y" only if applicable.
IRM	O	SC @IRM	The invalid result mark, in case it is assigned.
SortOrder	M	Numeric #0	Unique sort order for all results based on rank to break rank ties. This attribute is a sequential number with the order of the results for the particular event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out rank ties as well as results without rank.

Element: Competition /Result /Competitor (1,1)

Competitor related to one final event result.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or SC @CompetitorPlace	Competitor's ID or another indicator (SC @CompetitorPlace) in the case where there is no competitor in the rank due to IRM.
Type	M	S(1)	A for athlete T for team
Organisation	O	CC @Organisation	Competitor's organisation if known



Element: Competition /Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams.

Element: Competition /Result /Competitor /Composition /Athlete (0,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to an individual athlete or a team member. Team members should be participating in the event.
Order	M	Numeric	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A". (same order as defined in ORIS)

Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Competition /Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult (1,N)				
Team member's extended result (only for Team events).				
Type		Code	Pos	Description
ER		IRM	N/A	Element Expected: As soon as this information is available and only for individuals in a team if applicable.
	Attribute	M/O	Value	Description
	Value	M	SC @IRM	Send invalid result mark, in case it is assigned to a team member.

Sample (singles)



```
<Result Rank="1" SortOrder="1" >
  <Competitor Code="1078935" Type="A" Organisation="ESP" >
    <Composition>
      <Athlete Code="1102342" Order="1">
        <Description GivenName="John" FamilyName="Black" Gender="M" Organisation="ESP" BirthDate="1994-12-15" IFId="51690" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
<Result Rank="2" SortOrder="2" >
  <Competitor Code="1126413" Type="A" Organisation="USA" >
    <Composition>
      <Athlete Code="1102342" Order="1">
        <Description GivenName="Pat" FamilyName="Smith" Gender="M" Organisation="USA" BirthDate="1992-12-15" IFId="48962" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
```

2.3.6.6 Message Sort

Sort by Result @SortOrder



3 Document Control

Version history		
Version	Date	Comments
V1.0	2 Nov 2022	First Version

File Reference: EG-2024-TEQ-1.0 SFA

Change Log		
Version	Status	Changes on version
V1.0	SFA	First Version