



International
Olympic
Committee

WYOG-2024-NCB-3.0 SFA

Olympic Data Feed

Nordic Combined

ODF Data Dictionary

Technology and Information Department
© International Olympic Committee

WYOG-2024-NCB-3.0 SFA
5 May 2023



License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.

The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.

5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.



1	Introduction.....	4
1.1	This document	4
1.2	Objective.....	4
1.3	Main Audience.....	4
1.4	Glossary	4
1.5	Related Documents	5
2	Messages	5
2.1	Nordic Combined Overview.....	5
2.2	Applicable Messages	5
2.3	Messages	6
2.3.1	List of participants by discipline / List of participants by discipline update	6
2.3.1.1	Description.....	6
2.3.1.2	Header Values.....	7
2.3.1.3	Trigger and Frequency	7
2.3.1.4	Message Structure.....	7
2.3.1.5	Message Values	8
2.3.1.6	Message Sort	11
2.3.2	List of teams / List of teams update	12
2.3.2.1	Description.....	12
2.3.2.2	Header Values.....	12
2.3.2.3	Trigger and Frequency	12
2.3.2.4	Message Structure.....	13
2.3.2.5	Message Values	13
2.3.2.6	Message Sort	14
2.3.3	Event Unit Start List and Results.....	15
2.3.3.1	Description.....	15
2.3.3.2	Header Values.....	15
2.3.3.3	Trigger and Frequency	15
2.3.3.4	Message Structure.....	16
2.3.3.5	Message Values	18
2.3.3.6	Message Sort	27
2.3.4	Image	28
2.3.4.1	Description.....	28
2.3.4.2	Header Values.....	28
2.3.4.3	Trigger and Frequency	28
2.3.4.4	Message Structure.....	28
2.3.4.5	Message Values	29
2.3.4.6	Message Sort	31
2.3.5	Event Final Ranking.....	32
2.3.5.1	Description.....	32
2.3.5.2	Header Values.....	32
2.3.5.3	Trigger and Frequency	32
2.3.5.4	Message Structure.....	32



2.3.5.5	Message Values	33
2.3.5.6	Message Sort	35
2.3.6	Configuration	36
2.3.6.1	Description.....	36
2.3.6.2	Header Values.....	36
2.3.6.3	Trigger and Frequency	36
2.3.6.4	Message Structure.....	36
2.3.6.5	Message Values	37
2.3.6.6	Message Sort	40
3	Document Control.....	41

1 Introduction

1.1 This document

This document includes the ODF Nordic Combined Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for this discipline.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Nordic Combined Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies



1.5 Related Documents

Document Title	Document Description
ODF Foundation Principles	The document explains the environment & general principles for ODF
ODF General Messages Interface	The document describes the ODF General Messages
Common Codes	The document describes the ODF Common codes
ODF Header Values	The document details the header values which shows which RSCs are used in which messages.
ORIS Sports Document	The document details the sport specific requirements

2 Messages

2.1 Nordic Combined Overview

Note: All messages related to the ski jumping component of nordic combined are defined in the ski jumping document, this includes DT_RESULT, DT_CURRENT, DT_WEATHER and DT_CONFIG.

MESSAGES IN EACH EVENT

All jumps are always detailed in a single unit.

Individual Events

* There will be a DT_RESULT for each jump in trial/training and competition in as well as a DT_CURRENT. There will also be a DT_RESULT for the cross country which contains the final results.

Team Events

* There will be a DT_RESULT for each jump in trial/training (individual message format) and competition in as well as a DT_CURRENT. There will also be a DT_RESULT for the cross country which contains the final results.

TRAINING AND TRIALS

* Note that jumping trials in teams events are sent as individual results, not as team message.

SCHEDULE

* The DT_SCHEDULE/DT_SCHEDULE_UPDATE message will include the competition jump and the cross country separately (Y). DT_RESULTS is at jump / cross country.

2.2 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in this discipline.

- The column "Message type" indicates the DocumentType that identifies a message
- The column "Message name" is the message name identified by the message type
- The column "Message extended" indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it follows the general definition rules.
- Message responsibilities appears in the ODF General Document.

Message Type	Message Name	Message extended
DT_SCHEDULE DT_SCHEDULE_UPDATE	/ Competition schedule / Competition schedule update	



DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / List of participants by discipline update	X
DT_PARTIC_NAME	Participant Names	
DT_PARTIC_TEAMS DT_PARTIC_TEAMS_UPDATE	/ List of teams / List of teams update	X
DT_RESULT	Event Unit Start List and Results	X
DT_CURRENT	Current Information	
DT_IMAGE	Image	X
DT_RANKING	Event Final Ranking	X
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_MEDALS	Medal standings	
DT_CONFIG	Configuration	X
DT_COMMUNICATION	Communication	
DT_PRESENTER	Medal Presenters	
DT_LOCAL_ON	Discipline/venue start transmission	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_KA	Keep Alive	
DT_ALERT	Alert	
DT_BIO_PAR	Participant Biography	
DT_PIC	Pictures	
DT_PDF	PDF Message	

2.3 Messages

2.3.1 List of participants by discipline / List of participants by discipline update

2.3.1.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

It is important to note that all the sport messages that make references to athletes (start list, event unit results, etc.) will always match the athlete ID with the athlete ID in this message.

List of participants by discipline (DT_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message can include a list of current athletes, officials, coaches, guides, technical officials, Reserves and historical athletes regardless of status.



List of participants by discipline update (DT_PARTIC_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

2.3.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Discipline	Full RSC at the discipline level
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	/ List of participants by discipline message
DocumentSubtype	S(20)	HISTORICAL if the message is from the historical results provider and only includes historic athletes else the attribute is not included. Never included in _UPDATE message.
Version	1..V	Version number associated to the message's content. Ascending number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.1.3 Trigger and Frequency

The DT_PARTIC message is sent as a bulk message prior to the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_UPDATE messages are sent.

The DT_PARTIC_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.

2.3.1.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5
Competition (0,1)				
	Gen			
	Sport			
	Codes			
	Participant (1,N)			
		Code		
		Parent		
		Status		



	GivenName
	FamilyName
	PassportGivenName
	PassportFamilyName
	PrintName
	PrintInitialName
	TVName
	TVInitialName
	TVFamilyName
	LocalFamilyName
	LocalGivenName
	Gender
	Organisation
	BirthDate
	Height
	PlaceofBirth
	CountryofBirth
	PlaceofResidence
	CountryofResidence
	Nationality
	MainFunctionId
	Current
	OlympicSolidarity
	ModificationIndicator
	Discipline (1,1)
	Code
	IFId
	RegisteredEvent (0,N)
	Event

2.3.1.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Sample (Participants)

<Competition Gen="SOG-2020-1.10" Sport="SOG-2020-NCB-1.10" Codes="SOG-2020-1.20" >

Element: Competition /Participant (1,N)



Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	<p>Participant's ID.</p> <p>It identifies an athlete or an official and the holding participant's valid information for one particular period of time.</p> <p>It is used to link other messages to the participant's information.</p> <p>Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc.</p> <p>When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.</p>
Parent	M	S(20) with no leading zeroes	<p>Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent.</p> <p>The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.</p> <p>The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".</p>
Status	O	CC @ParticStatus	<p>Participant's accreditation status this attribute is Mandatory in the case of @Current="true" and it is optional in the case that @Current="false".</p> <p>To delete a participant, a specific value of the Status attribute is used.</p>
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
PassportGivenName	O	S(25)	Passport Given Name (Uppercase).
PassportFamilyName	O	S(25)	Passport Family Name (Uppercase).
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
TVFamilyName	M	S(25)	TV family name
LocalFamilyName	O	S(25)	Family name in the local language in the appropriate case for the local language (usually mixed case)
LocalGivenName	O	S(25)	Given name in the local language in the appropriate case for the local language (usually mixed case)
Gender	M	CC @PersonGender	Participant's gender
Organisation	M	CC @Organisation	Organisation ID



BirthDate	O	YYYY-MM-DD	Date of birth. This information may not be known at the very beginning, but it will be completed for all participants after successive updates
Height	O	S(3)	Height in centimetres. It will be included if this information is available. This information is not needed in the case of officials/referees. "-" may be used where the data is not available.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC @Country	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC @Country	Country ID of Residence
Nationality	O	CC @Country	Participant's nationality. Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC @ResultsFunction	Main function In the Case of Current="true" this attribute is Mandatory.
Current	M	boolean	It defines if a participant is participating in the games (true) or is a Historical participant (false).
OlympicSolidarity	O	S(1)	Send Y if the participant is a member of the Solidarity / Scholarship Program else not sent.
ModificationIndicator	M	S(1)	'N' or 'U' Attribute is mandatory in the DT_PARTIC_UPDATE message only N-New participant (in the case that this information comes as a late entry) U-Update participant If ModificationIndicator='N', then include new participant to the previous bulk-loaded list of participants If ModificationIndicator='U', then update the participant to the previous bulk-loaded list of participants To delete a participant, a specific value of the Status attribute is used.

Element: Competition /Participant /Discipline (1,1)

All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.

Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the Discipline. It is the discipline code used to fill the OdfBody @DocumentCode attribute.
IFId	O	S(16)	IF ID (competitor's federation number for the discipline).

Element: Competition /Participant /Discipline /RegisteredEvent (0,N)

All accredited athletes will be assigned to one or more events. There is one exception: in some sports, substitutes may be accredited without any associated event.

Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the Event

		In the Olympic Games the athletes are initially only assigned to a single generic event at discipline level. This generic event should be removed on an athlete by athlete basis as soon as the athlete is inscribed in a competition event.
--	--	--

2.3.1.6 Message Sort

The message is sorted by Participant @Code

2.3.2 List of teams / List of teams update

2.3.2.1 Description

DT_PARTIC_TEAMS contains the list of teams related to the competition.

A team is a type of competitor, being a group of two or more individual athletes participating together in one event. One team participates in one event of one discipline. When one team participates in multiple events, there will be one team for each event for the same group. Also when the same organisation participates in the same event twice, there will be different teams.

List of teams (DT_PARTIC_TEAMS) is a bulk message by discipline. The list is always complete. The arrival of this message resets all the previous participant teams' information for that discipline. It is assumed that all teams appearing in this list are valid, in the meaning that they are participating or they could participate in one event.

List of teams update (DT_PARTIC_TEAMS_UPDATE) is an update message. It is not a complete list of teams' information message. It only contains the data of a team being modified.

2.3.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Discipline	Full RSC at the discipline level
DocumentType	DT_PARTIC_TEAMS DT_PARTIC_TEAMS_UPDATE	List of participant teams message
DocumentSubtype	S(20)	HISTORICAL if the message is from the historical results provider and only includes historic teams else the attribute is not included. Never included in _UPDATE message.
Version	1..V	Version number associated to the message's content. Ascending number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.2.3 Trigger and Frequency

There is no DT_PARTIC_TEAMS message in this discipline.

The teams are created in OVR and sent as DT_PARTIC_TEAMS_UPDATE to create the teams.

The DT_PARTIC_TEAMS_UPDATE message is triggered when there is a modification in the data for any team after the transfer of control to OVR.



2.3.2.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5
Competition (0,1)				
	Gen			
	Sport			
	Codes			
	Team (1,N)			
		Code		
		Organisation		
		Number		
		Name		
		ShortName		
		TVTeamName		
		Gender		
		Current		
		TeamType		
		ModificationIndicator		
		Composition (0,1)		
			Athlete (0,N)	
				Code
				Order
		Discipline (0,1)		
			Code	
			IFId	
			RegisteredEvent (0,1)	
				Event

2.3.2.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /Team (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Team's ID
Organisation	M	CC @Organisation	Team organisation's ID
Number	O	Numeric #0	Team's number.



			If there is not more than one team for one organisation participating in one event, it is 1. Otherwise, it will be incremental, 1 for the first organisation's team, 2 for the second organisation's team, etc. Required in the case of current teams.
Name	M	S(73)	Team name
ShortName	M	S(40)	Team Short Name
TVTeamName	M	S(21)	TV Team Name
Gender	M	CC @SportGender	Gender Code of the Team
Current	M	boolean	It defines if a team is participating in the games (true) or it is a Historical team (false)
TeamType	M	SC @TeamType	Send the team type. This is how the name is constructed to allow clients to build in other languages. Always use ORG in this discipline.
ModificationIndicator	M	N, U, D	Attribute is mandatory in the DT_PARTIC_TEAMS_UPDATE message only N-New team (in the case that this information comes as a late entry) U-Update team D-Delete team If ModificationIndicator='N', then include new team to the previous bulk-loaded list of teams If ModificationIndicator='U', then update the team to the previous bulk-loaded list of teams If ModificationIndicator='D', then delete the team to the previous bulk-loaded list of teams

Element: Competition /Team /Composition /Athlete (0,N)

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID of the listed team's member. Therefore, he/she makes part of the team's composition.
Order	O	Numeric 0	Team member order

Element: Competition /Team /Discipline (0,1)

Discipline is expected unless ModificationIndicator="D"

Attribute	M/O	Value	Description
Code	M	CC @Discipline	Full RSC of the Discipline
IFld	O	S(16)	Competitor's federation number for the corresponding discipline.

Element: Competition /Team /Discipline /RegisteredEvent (0,1)

Each current team is assigned to one event.

Attribute	M/O	Value	Description
Event	M	CC @Event	Full RSC of the Event

2.3.2.6 Message Sort

The message is sorted by Team @Code.



2.3.3 Event Unit Start List and Results

2.3.3.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports.

This is always a full message and all applicable elements and attributes are always sent.

2.3.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Unit	Full RSC at unit level, one message per race.
DocumentSubcode	N/A	N/A
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	N/A	N/A
Version	1..V	Version number associated to the message's content. Ascending number
ResultStatus	CC @ResultStatus	Indicates whether the result is official or unofficial (or intermediate, live, etc). Expected statuses are (though any in GEN are possible): START_LIST (as soon as the start list is available and any changes [inc. IRMs]) LIVE (when the unit starts and after every update [intermediates etc.]). INTERMEDIATE (used after the competition has started and is not finished but not currently live, only for exceptional circumstances) UNCONFIRMED (used after the competition is completed and before either UNOFFICIAL or OFFICIAL. It may be sent multiple times if modifications are required and the status has not changed) UNOFFICIAL OFFICIAL PROTESTED
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.3.3 Trigger and Frequency

This message is sent:

- * As soon as the start list is available and any changes [inc. IRMs] (START_LIST)
- * Send with all updates during the unit (LIVE)
- * Send after each athlete (with all intermediate data and judge data) completes the course (and has all data) (LIVE)



* After the unit is finished (UNCONFIRMED / UNOFFICIAL / OFFICIAL) as applicable.

* After any change (status as appropriate)

2.3.3.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
Competition (0,1)							
	Gen						
	Sport						
	Codes						
	ExtendedInfos (0,1)						
	UnitDateTime (0,1)						
	StartDate						
	ExtendedInfo (0,N)						
	Type						
	Code						
	Pos						
	Value						
	SportDescription (0,1)						
	DisciplineName						
	EventName						
	Gender						
	SubEventName						
	VenueDescription (0,1)						
	Venue						
	VenueName						
	Location						
	LocationName						
	Officials (0,1)						
	Official (1,N)						
	Code						
	Function						
	Order						
	Description (1,1)						
	GivenName						
	FamilyName						
	Gender						
	Organisation						
	Result (1,N)						
	Rank						
	RankEqual						



	Result	
	IRM	
	SortOrder	
	StartOrder	
	StartSortOrder	
	ResultType	
	Diff	
	ExtendedResults (0,1)	
	ExtendedResult (1,N)	
	Type	
	Code	
	Pos	
	Value	
	Value2	
	Rank	
	RankEqual	
	SortOrder	
	Diff	
	Move	
	Competitor (1,1)	
	Code	
	Type	
	Bib	
	Organisation	
	Description (0,1)	
	TeamName	
	EventUnitEntry (0,N)	
	Type	
	Code	
	Pos	
	Value	
	Composition (0,1)	
	Athlete (0,N)	
	Code	
	Order	
	Bib	
	Description (1,1)	
	GivenName	
	FamilyName	
	Gender	
	Organisation	



	BirthDate
	IFld
EventUnitEntry (0,N)	
	Type
	Code
	Pos
	Value
ExtendedResults (0,1)	
ExtendedResult (1,N)	
	Type
	Code
	Pos
	Value
	Value2
	IRM
	Rank
	RankEqual
	SortOrder
	Diff

2.3.3.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /UnitDateTime (0,1)			
Actual start date and time / end date and time. (do not include until unit starts)			
Attribute	M/O	Value	Description
StartDate	M	DateTime	Actual start date-time. Do not include until unit starts.

Element: Competition /ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	STARTERS	N/A	Element Expected: Always
Attribute	M/O	Value	Description
Value	M	Numeric ##0	Send the number of competitors on the start list.
Sub Element: Competition /ExtendedInfos /ExtendedInfo /Extension Expected Always where status is not START_LIST and at least one competitor has completed the unit without IRM.			
Attribute	Value	Description	



	Code	COMPLETE		
	Pos	N/A		
	Value	Numeric ##0	Send the number of competitors whose event unit is completed (includes IRMs).	
Sub Element: Competition /ExtendedInfos /ExtendedInfo /Extension Expected Always after the first competitor passed the @Pos Intermediate point in individual events.				
	Attribute	Value	Description	
	Code	PASSED		
	Pos	S(2)	Intermediate point in the unit (1, 2...F).	
	Value	Numeric ##0	Send the number of competitors who have passed this intermediate point IRMs should also be included in the number. At the end this number will equal STARTERS.	
DISPLAY		INT_x	Numeric #0	Code Description: x = overall Intermediate Point, not LEG. Pos Description: Send a unique number for each competitor included (that is if two competitors updated send 1 & 2). Element Expected: When available and only when the unit is LIVE. Each competitor is only sent once at each intermediate (athlete in team events).
	Value	O	S(20) without leading zeroes	Send the competitor ID of the last competitor(s) to reach the intermediate point (including F) to enable highlighting of recent changes.
LEADER		CURRENT	S(2)	Pos Description: Most recent intermediate point reached by the first competitor (1,2,3,..F). Finish line is considered as an intermediate point. The value should be according to the Pos defined in the INTERMEDIATES of the DT_CONFIG message. For Relays it starts with 1 in leg 1, and finish with F in the last intermediate of the last leg. Element Expected: Always
	Attribute	M/O	Value	Description
	Value	M	S(20) without leading zeroes.	Send the competitor ID of the first competitor to reach the intermediate point (including F).
DISPLAY		NEXT	N/A	Element Expected: In all NCB cross country
	Attribute	M/O	Value	Description
	Value	M	S(20) without leading zeroes	Send the competitor ID of the next competitor to start.
DISPLAY		STARTED	N/A	Element Expected: Always, send only once for each competitor.
	Attribute	M/O	Value	Description
	Value	M	S(20) without leading zeroes	Send the competitor ID of the competitor most recently started.
DISPLAY		CURR_LEG	N/A	Element Expected:



Attribute	M/O	Value	Relay events. Description
Value	M	Numeric 0	Current Leg reached by the leading competitor updated at the exchange.

Sample (Individual)

```
<ExtendedInfos>  
<UnitDateTime StartDate="2012-08-07T11:01:00+01:00" />  
<ExtendedInfo Type="UI" Code="STARTERS" Value="27" >  
<Extension Code="COMPLETE" Value="9" />  
<ExtendedInfo Type="DISPLAY" Code="INT_2" Pos="1" Value="123456" />  
</ExtendedInfo>
```

Element: Competition /ExtendedInfos /SportDescription (0,1)

Sport Descriptions in Text.

Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline ENG Description (not code) from Common Codes
EventName	M	S(40)	Event ENG Description (not code) from Common Codes.
Gender	M	CC @SportGender	Gender code for the event unit
SubEventName	M	S(40)	EventUnit ENG Description (not code) from Common Codes

Element: Competition /ExtendedInfos /VenueDescription (0,1)

Venue Names in Text.

Attribute	M/O	Value	Description
Venue	M	CC @VenueCode	Venue Code
VenueName	M	S(25)	Venue ENG Description (not code) from Common Codes
Location	M	CC @Location	Location code
LocationName	M	S(30)	Location ENG Description (not code) from Common Codes

Element: Competition /Officials /Official (1,N)

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Official's code
Function	M	CC @ResultsFunction	Official's function. Can be different from the function sent in the DT_PARTIC message.
Order	M	Numeric #0	Order of officials.

Element: Competition /Officials /Official /Description (1,1)

Officials extended information.

Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the official
Organisation	M	CC @Organisation	Official's organisation



Element: Competition /Result (1,N)			
For each Event Unit Results message, there must be at least one competitor with a result element in the event unit.			
Attribute	M/O	Value	Description
Rank	O	S(3)	Rank of the competitor in the event unit
RankEqual	O	S(1)	Identifies if a rank has been equalled. Send Y if applicable else not sent.
Result	O	h:mm:ss.f or string	Time for the competitor. Do not send hours if not applicable or any leading zeros. LAP is a Result Mark (RM), not IRM. LAP competitors receive a Rank. LAP value may be sent when @ResultType is TIME.
IRM	O	SC @IRM	IRM for the event unit Send only in the case @ResultType is IRM or IRM_TIME
SortOrder	M	Numeric ##0	This attribute is a sequential number with the order of the results for the event unit, if they were to be presented. It is mostly based on the rank, but it should be used to sort out rank ties as well as results without rank. Prior to the unit the order is the same as StartSortOrder. Updated during the race with the current order.
StartOrder	O	Numeric ##0	Start Order
StartSortOrder	M	Numeric ##0	Unique number for sorting the start list.
ResultType	O	SC @ResultType	Type of the @Result attribute.
Diff	O	+m:ss.f or 0.0	Time behind the leader. Send 0.0 for the leader.

Element: Competition /Result /ExtendedResults /ExtendedResult (1,N)				
Type	Code	Pos	Description	
ER	STATUS	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	SC @CompetitorStatus	Race status for the competitor
ER	CURRENT	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	S(2)	Intermediate point where the competitor has most recently passed If the competitor has an IRM: 1. In case the DNS or the competitor has an IRM before crossing the first intermediate point: send 0. 2. In other cases, send the Intermediate point that was crossed most recently. (Starting by 1. Start point (0) not considered if competitor athlete does not receive an IRM)
PROGRESS	INTERMEDIATE	S(2)	Pos Description: Intermediate point where the intermediate time is recorded (1, 2...F). Element Expected: When data is available for individual events.	
	Attribute	M/O	Value	Description



	Value	M	h:mm:ss.f	Cumulative time at the intermediate point in the current race. Do not send hours or minutes if zero.
	Rank	M	S(2)	Send the rank of the competitor at the intermediate point.
	RankEqual	O	S(1)	Send 'Y' if rank is equalled, otherwise do not send.
	SortOrder	M	Numeric #0	Index based on the Rank to sort the competitor considering equals and IRMs.
	Diff	M	+h:mm:ss.f or 0.0	Send the time behind the leader in the unit at the point. Do not send hours or minutes if zero.
	Move	O	Numeric [+/-]#0	Send the rank progression in the current intermediate compared to the previous intermediate (i.e: "+2", "0", "-1", etc) + means improved position
PROGRESS		SECTION	S(2)	Pos Description: Intermediate point where the section ends (1, 2, 3...F). A section is between two intermediate points. For example 1 is from the start to intermediate 1. Element Expected: When data is available for individual events
	Attribute	M/O	Value	Description
	Value	M	h:mm:ss.f	Section time at the intermediate point in the current race. Do not send hours or minutes if zero.
	Rank	O	S(2)	Send the rank of the competitor in the section.
	RankEqual	O	S(1)	Send 'Y' if rank is equalled, otherwise do not send.
	SortOrder	M	Numeric #0	Index based on the Rank to sort the competitor considering equals and IRMs.
	Diff	O	+m:ss.f or 0.0	Send the time behind the leader for the section (not race leader). Do not send minutes if zero.
ER		PHOTO	N/A	Element Expected: If applicable
	Attribute	M/O	Value	Description
	Value	M	S(1)	To know if the competitor's final result was decided by photo. Send E for Evaluated, P for Pending, otherwise do not send. If pending then those pending competitors will not have rank but will still be sorted in the correct place (as well as is known). For example: Rank = 1,,,4... and SortOrder = 1,2,3,4 ...
ER		RAW	N/A	Element Expected: Individual events
	Attribute	M/O	Value	Description
	Value	M	h:mm:ss.f	Raw total time (without start behind time, i.e. the different between finishing time and start behind time). Do not send leading zeros.
	Rank	M	S(2)	Send the rank of the competitor based on @Value.



	RankEqual	O	S(1)	Send 'Y' if rank is equalled, otherwise do not send.
	SortOrder	M	Numeric	Index based on the Rank to sort the competitor considering equals and IRMs.
	Diff	O	+m:ss.f or 0.0	Send the time behind. Do not send minutes if zero.
ER		POT_DSQ	N/A	Element Expected: If applicable
	Attribute	M/O	Value	Description
	Value	M	S(1)	Send 'Y' if the competitor is a potential disqualification, time adjustment or protest in this unit else do not send.
ER		IRM_RULE	N/A	Element Expected: If applicable
	Attribute	M/O	Value	Description
	Value	M	String	Send rule number if disqualified.
	Value2	O	String	Send rule description if disqualified.

Sample (Individual)

```
<Result SortOrder="1" ResultType="TIME" Rank="1" Result="1:08:15.4" StartOrder="12" StartSortOrder="12" Diff="0.0">
  <ExtendedResults>
    <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="1" Value="3:56.3" Diff="+5.1" Rank="11" RankEqual="Y"
SortOrder="12" />
    <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="2" Value="9:11.6" Diff="+1.5" Rank="5" SortOrder="5" />
    <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="3" Value="13:02.3" Diff="+3.0" Rank="7" SortOrder="7" />
    ...
    <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="F" Value="1:08:15.4" Diff="0.0" Rank="1" SortOrder="1" />
    ...
    <ExtendedResult Type="PROGRESS" Code="SECTION" Pos="F" Value="4:55.9" Diff="0.0" Rank="1" SortOrder="1" />
  <Competitor Code="2040363" Type="A" Organisation="NED" >
    <Composition>
      <Athlete Code="2040363" Bib="21" Order="1">
        <Description GivenName="Jon" FamilyName="Brown" Gender="M" Organisation="NED" BirthDate="1994-11-15" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
```

Element: Competition /Result /Competitor (1,1)

Competitor related to the result of one event unit.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	S(1)	A for athlete, T for team
Bib	O	S(5)	Bib number for the team
Organisation	M	CC @Organisation	Competitor's organisation

Element: Competition /Result /Competitor /Description (0,1)

Used in Team events only

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team.



Element: Competition /Result /Competitor /EventUnitEntry (0,N)				
For team event only				
Type	Code	Pos	Description	
EUE	LANE	N/A	Element Expected: Team Events	
Attribute	M/O	Value	Description	
Value	M	Numeric #0	Lane number for the competitor	
EUE	WAVE	N/A	Element Expected: If the competitor is in a wave start	
Attribute	M/O	Value	Description	
Value	M	m:ss	Time of the wave start for the competitor if applicable.	
EUE	HCP_TIME	N/A	Element Expected: Always in team event	
Attribute	M/O	Value	Description	
Value	M	m:ss	Handicap time or start behind time.	
EUE	SJP	S(3)	Pos Description: Rank of the team in ski jump. Element Expected: Team event only	
Attribute	M/O	Value	Description	
Value	M	Numeric ###0.0	Result (points) of the team in ski jump	
EUE	PERFORM	S(3)	Pos Description: Send SJP for Ski Jump performance Send CCS for Cross Country Performance Element Expected: Always when available in Nordic Combined Teams competition for the Team.	
Attribute	M/O	Value	Description	
Value	M	Numeric #0	Numeric value 0-10	

Element: Competition /Result /Competitor /Composition /Athlete (0,N)				
Attribute	M/O	Value	Description	
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.	
Order	M	Numeric 0	Order attribute used to sort team members in a team (if Competitor @Type="T") on the results or 1 if Competitor @Type="A".	
Bib	O	S(5)	Bib number Numeric for individuals. ##0-0 for team members.	



Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Element: Competition /Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)				
Individual athletes entry information.				
Type		Code	Pos	Description
EUE		LANE	N/A	Element Expected: Individual events
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Lane number for the competitor
EUE		WAVE	N/A	Element Expected: If the athlete is in a wave start in the individual event
	Attribute	M/O	Value	Description
	Value	M	m:ss	Time of the wave start for the competitor if applicable
EUE		HCP_TIME	N/A	Element Expected: Always in individual event
	Attribute	M/O	Value	Description
	Value	M	m:ss	Handicap time or start behind time
EUE		SJP	S(3)	Pos Description: Rank of the athlete in ski jump. Only include for individual event. Element Expected: Always
	Attribute	M/O	Value	Description
	Value	M	Numeric ###0.0	Result of the athlete in ski jump (team and individual as appropriate)
EUE		LEG_BIB	N/A	Element Expected: Team Events
	Attribute	M/O	Value	Description
	Value	M	Numeric 0	Leg number of the Team member. For Relay should be 1,2,3,4
EUE		COLOUR	N/A	Element Expected: Team events
	Attribute	M/O	Value	Description
	Value	M	SC @BibColour	Bib colour ("b", "g", "r" or "y")
EUE		PERFORM	S(3)	Pos Description: Send SJP for Ski Jump performance



			Send CCS for Cross Country Performance Element Expected: Always when available in both team and individual events
Attribute	M/O	Value	Description
Value	M	Numeric #0	Numeric value 0-10

Element: Competition /Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult (1,N)

Team member extended result.

Type	Code	Pos	Description
PROGRESS	INTERMEDIATE	S(2)	Pos Description: Intermediate point where the intermediate time is recorded (1, 2...F). This is the overall intermediate, not per leg. Element Expected: When data is available in team events.
Attribute	M/O	Value	Description
Value	M	h:mm:ss.f	Cumulative time at the intermediate point in the current race. Do not send hours or minutes if zero.
Value2	O	m:ss.ff	Time from the start of the leg ending at the intermediate point @Pos
Rank	M	S(2)	Send the rank of the competitor at the intermediate point
RankEqual	O	S(1)	Send 'Y' if rank is equalled, otherwise do not send.
SortOrder	M	Numeric #0	Index based on the Rank to sort the competitor considering equals and IRMs.
Diff	O	+h:mm:ss.f or 0.0	Send the time behind the leader in the unit at the point. Do not send hours or minutes if zero.
PROGRESS	LEG_SPLIT	S(2)	Pos Description: Identifies the leg or round, from 1 to the total number of legs (1-4). Element Expected: When data is available in team events.
Attribute	M/O	Value	Description
Value	O	m:ss.f	Leg time in the @Pos leg for the team member in the leg. It is not cumulative.
IRM	O	SC @IRM	IRM if applicable
Rank	M	S(2)	Rank @Pos in the leg for the team member in the leg.
RankEqual	O	S(1)	Send 'Y' if rank is equalled, otherwise do not send.
SortOrder	M	Numeric #0	Index based on the Rank to sort the team member in the leg (relay) or round (team sprint) considering equals and IRMs.
Diff	M	+m:ss.f or 0.0	Send the time behind the leader in the unit at the split.



Sample (Team)

```
<Result SortOrder="1" ResultType="TIME" Rank="1" Result="53:02.7" Diff="0.0" StartOrder="10" StartSortOrder="10" >
  <Competitor Code="NCBMNH4X5KM---SWE01" Bib="2" Type="T" Organisation="SWE" >
    <Description TeamName="Sweden" />
    <Composition>
      <Athlete Bib="2-2" Code="2019490" Order="2">
        <Description GivenName="John" FamilyName="Brown" Gender="M" Organisation="NED" BirthDate="1994-11-15" />
        <ExtendedResults>
          <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="5" Value="18:21.3" Value2="4:23.3" Diff="+1.3"
Rank="5" SortOrder="5" />
          <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="6" Value="20:44.1" Value2="6:26.8" Diff="+1.3"
Rank="7" SortOrder="7" />
          <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="7" Value="25:18.4" Value2="11:29.6" Diff="+0.4"
Rank="2" SortOrder="2" />
          <ExtendedResult Type="PROGRESS" Code="INTERMEDIATE" Pos="8" Value="28:21.6" Value2="14:29.8" Diff="+4.3"
Rank="3" SortOrder="3" />
          <ExtendedResult Type="PROGRESS" Code="LEG_SPLIT" Pos="1" Value="14:29.8" Diff="+4.3" Rank="3" SortOrder="3" />
        </ExtendedResults>
      </Athlete>
      <Athlete Bib="2-2" Code="2014836" Order="2">
```

2.3.3.6 Message Sort

Sort by Result @SortOrder



2.3.4 Image

2.3.4.1 Description

The Image message is a message containing an image or images file(s) in .jpg or .png format encapsulated in a XML message.

Each message contains only one photofinish picture.

Multiple messages may be sent for the same DocumentCode (a single race [RSC]) when more than one photofinish cases/photos occur in the same race depending on the circumstances of the unit/race.

2.3.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Unit	Full RSC of the unit
DocumentSubcode	Numeric #0	Picture number This value is a sequential number for each picture provided in a unit (RSC). The value will be 1, 2, 3 ... Where there is only one image related to the DocumentCode then the value 1 is sent. 2, 3 etc. are used if additional images (ranks to be resolved) are sent for the same DocumentCode.
DocumentType	DT_IMAGE	Image message
DocumentSubtype	S(20)	Send PHOTOFINISH
Version	1..V	Version number associated to the message's content. Ascending number. Values beyond 1 are only used if a message needs to be resent for a second or subsequent image/result with the same DocumentSubcode to replace the original image (to resolve the same rank).
ResultStatus	CC @ResultStatus	Only applicable status is OFFICIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.4.3 Trigger and Frequency

Trigger when image available and after any change.

2.3.4.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8
Competition (0,1)							
	Gen						



	Sport	
	Codes	
	Image (1,N)	
	Pos	
	Version	
	Revision	
	ImageType	
	Result (0,N)	
	Result	
	Rank	
	StartOrder	
	SortOrder	
	Competitor (1,1)	
	Code	
	Type	
	Organisation	
	Description (0,1)	
	TeamName	
	Composition (0,1)	
	Athlete (1,N)	
	Code	
	Order	
	Bib	
	Description (1,1)	
	GivenName	
	FamilyName	
	ImageData (1,1)	
	-	

2.3.4.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message



Element: Competition /Image (1,N)			
Always only one image per message			
Attribute	M/O	Value	Description
Pos	M	Numeric #0	Always send 1
Version	M	Numeric #0	Document Version
Revision	M	Numeric #0	Document Revision
ImageType	M	S(3)	Image type extension, jpg or png

Element: Competition /Image /Result (0,N)			
This element should always appear and must only include the information of those competitors appearing in the image.			
Attribute	M/O	Value	Description
Result	O	S(20)	Result of the competitor in the image at the end of the unit. Formatted in the same way as associated DT_RESULT. Use IRM code if appropriate.
Rank	O	S(10)	Rank of the competitor at the end of the unit
StartOrder	O	S(4)	Start or lane position This value is expected if it is included in DT_RESULT
SortOrder	M	Numeric ###0	This attribute is a sequential number with the order of the competitors in the image.

Element: Competition /Image /Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID (Team or individual) If it is possible to send the ID it should be included.
Type	M	S(1)	A for athlete or T for team. If it is possible to send the type it should be included.
Organisation	M	CC @Organisation	Competitor's organisation

Element: Competition /Image /Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the Team.

Element: Competition /Image /Result /Competitor /Composition /Athlete (1,N)			
Only sent in the case of individual events. Team members are not sent in team events.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. If it is possible to send the ID it should be included.
Order	M	Numeric 0	Value is 1
Bib	M	S(5)	Bib



Element: Competition /Image /Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name (Photofinish Name)
FamilyName	M	S(25)	Family name (Photofinish Name)

Element: Competition /Image /ImageData (1,1)			
Attribute	M/O	Value	Description
-	M	Free Text	The ImageData element has a body consisting of one Base64-encoded report (a jpeg or png file)

Sample (Image)

```
<Image Pos="1" Version="1" Revision="0" ImageType="jpg" >
  <Result Result="3:26.23" Rank="1" StartOrder="5" SortOrder="1" >
    <Competitor Code="1234567" Type="T" Organisation="GBR" >
      <Description TeamName="Great Britain"/>
    </Competitor>
  </Result>
  <Result Result="3:26.26" Rank="2" StartOrder="3" SortOrder="2" >
    <Competitor Code="1234444" Type="T" Organisation="ESP" >
      <Description TeamName="Spain"/>
    </Competitor>
  </Result>
  <ImageData>/9j/4AAQSkZJRgABAQEAAAAAAAAA ETC ETC //2Q==</ImageData>
</Image>
```

2.3.4.6 Message Sort

Sort by Competition /Image /Pos and SortOrder within image.



2.3.5 Event Final Ranking

2.3.5.1 Description

The event final ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a generic message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Rank Mark (disqualified, etc.), or both.

Depending on the sport rules include all competitors in the competition as all can be ranked (as in Marathon) or only include those with a final ranking as others are unranked. All those who are in the start list in ski jumping are expected to be included.

2.3.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Event	Full RSC of the event, sent for all competition events.
DocumentType	DT_RANKING	Event Final ranking message
Version	1..V	Version number associated to the message's content. Ascending number
ResultStatus	CC @ResultStatus	Result status, indicates that the data is official. OFFICIAL
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.5.3 Trigger and Frequency

The message is expected only at the end of the Event.
Trigger also after any change.

2.3.5.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7
Competition (0,1)						
	Gen					
	Sport					
	Codes					
	ExtendedInfos (0,1)					
		SportDescription (0,1)				



		DisciplineName
		EventName
		Gender
	Result (1,N)	
	Rank	
	RankEqual	
	ResultType	
	Result	
	Diff	
	IRM	
	SortOrder	
	Competitor (1,1)	
		Code
		Type
		Organisation
		Description (0,1)
		TeamName
		Composition (1,1)
		Athlete (0,N)
		Code
		Order
		Description (1,1)
		GivenName
		FamilyName
		Gender
		Organisation
		BirthDate
		IFId

2.3.5.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message



Element: Competition /ExtendedInfos /SportDescription (0,1)			
Sport Description in text			
Attribute	M/O	Value	Description
DisciplineName	M	S(40)	Discipline ENG Description (not code) from Common Codes
EventName	M	S(40)	Event ENG Description (not code) from Common Codes. Must be included if it is a single event
Gender	M	CC @SportGender	Gender code for the event unit. Must be included if it is a single gender

Element: Competition /Result (1,N)			
For any event final ranking message, there should be at least one competitor being awarded a result for the event.			
Attribute	M/O	Value	Description
Rank	O	S(3)	Final rank of the competitor in the corresponding event.
RankEqual	O	S(1)	Identifies if a rank has been equalled. Send Y if applicable else not sent.
ResultType	O	SC @ResultType	Result type, for the corresponding event, mandatory if Result or IRM is included.
Result	O	h:mm:ss.f	Time for the competitor. Do not send leading zeros or hours unless applicable.
Diff	O	+m:ss.f or 0.0 for winner	Time behind the leader when available.
IRM	O	SC @IRM	Send if the competitor has an IRM.
SortOrder	M	Numeric	This attribute is a sequential number with the order of the results for the event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out rank ties as well as results without rank.

Element: Competition /Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID. "NO_AWARD" in the case where there is no competitor in the rank due to IRM.
Type	M	S(1)	A for athlete, T for team
Organisation	O	CC @Organisation	Competitor's organisation if known

Element: Competition /Result /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team. Only applies for teams.

Element: Competition /Result /Competitor /Composition /Athlete (0,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to an individual athlete or a team member.
Order	M	Numeric #0	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".



Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC @PersonGender	Gender of the athlete
Organisation	M	CC @Organisation	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID

Sample (Individual)

```
<Result SortOrder="2" ResultType="TIME" Rank="2" Result="23:15.8" Diff="2.6" >
  <Competitor Code="2000691" Type="A" Organisation="RUS" >
    <Composition>
      <Athlete Code="2000691" Order="1" >
        <Description GivenName="John" FamilyName="Brown" Gender="M" Organisation="RUS" BirthDate="1994-11-15" />
      </Athlete>
    </Composition>
  </Competitor>
</Result>
```

2.3.5.6 Message Sort

Sort by Result @SortOrder

2.3.6 Configuration

2.3.6.1 Description

The Configuration is a message containing general configuration.

Ideally the configuration should be provided before competition.

2.3.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC @Competition	Unique ID for competition
DocumentCode	CC @Unit	Full RSC. Send one message per unit with the unit level DocumentCode.
DocumentType	DT_CONFIG	Configuration message
Version	1..V	Version number associated to the message's content. Ascending number
FeedFlag	"P"-Production "T"-Test	Test message or production message.
Date	Date	Date when the message is generated, expressed in the local time zone where the message was produced.
Time	Time	Time up to milliseconds when the message is generated, expressed in the local time zone where the message was produced.
LogicalDate	Date	Logical Date of events. This is the same as the physical day except when the unit or message transmission extends after midnight. See full explanation in ODF Foundation.
Source	SC @Source	Code indicating the system which generated the message.

2.3.6.3 Trigger and Frequency

The message is sent prior to any ODF results message.

Trigger also any change, but considering that, if possible, the configuration for one event unit must be provided before the start list.

If a DT_CONFIG message is sent after a DT_RESULT in a related unit then the next version of DT_RESULT must be sent immediately.

2.3.6.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5
Competition (0,1)				
	Gen			
	Sport			
	Codes			
	Configs (1,1)			
		Config (1,N)		
			Unit	



ExtendedConfig (1,N)	
Type	
Code	
Pos	
Value	

2.3.6.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /Configs /Config (1,N)			
Attribute	M/O	Value	Description
Unit	M	CC @Unit	Full RSC of the Unit. The applies to cross country, not ski jumping.

Element: Competition /Configs /Config /ExtendedConfig (1,N)				
Type	Code	Pos	Description	
FIS	CODEX	N/A	Element Expected: When available	
	Attribute	M/O	Value	Description
	Value	M	String	FIS Codex
COURSE	NAME	Numeric 0	Pos Description: If there is more than one course send 1 for the first course and 2 for the second. Do not include @Pos unless multiple courses. Element Expected: When available	
	Attribute	M/O	Value	Description
	Value	M	String	Name of the course in ENG
COURSE	ALTITUDE	N/A	Element Expected: When available	
	Attribute	M/O	Value	Description
	Value	M	Numeric ###0	Send the altitude of the stadium(start/finish) in metres
COURSE	HEIGHT_DIFF	Numeric 0	Pos Description: If there is more than one course in the race(skiathlon & relay) send 1 for the first course and 2 for the second. Do not include @Pos unless multiple courses. Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Numeric ##0	Send the total difference in height from the low point to the highest point. (metres)



COURSE	LENGTH		Numeric 0	Pos Description: If there is more than one course in the race send 1 for the first course and 2 for the second. Do not include @Pos unless multiple courses. Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	Numeric ####0	Send the total length of the course in meters.
COURSE	LAP		Numeric 0	Pos Description: If there is more than one course send 1 for the first course and 2 for the second. Do not include @Pos unless multiple courses. Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	Numeric ####0	Send the lap length in metres
Sub Element: Competition /Configs /Config /ExtendedConfig /ExtendedConfigItem Expected When available				
	Attribute	Value	Description	
	Code	NUM		
	Pos	N/A		
	Value	Numeric #0	Number of laps for each athlete.	
COURSE	CLIMB		Numeric 0	Pos Description: If there is more than one course send 1 for the first course and 2 for the second. Do not include @Pos unless multiple courses. Element Expected: Always
	Attribute	M/O	Value	Description
	Value	M	Numeric ####0	Course Total Climb in metres
Sub Element: Competition /Configs /Config /ExtendedConfig /ExtendedConfigItem Expected Always				
	Attribute	Value	Description	
	Code	MAX		
	Pos	N/A		
	Value	Numeric ####0	Course maximum climb in metres	
EC	INTERMEDIATE		S(2)	Pos Description: Send the value that identifies the intermediate point, 1 to n for intermediates along the course and F for the finish point. Element Expected: Always
	Attribute	M/O	Value	Description
	Value	M	Numeric #0.0#	Distance from the start in km for the intermediate.
Sub Element: Competition /Configs /Config /ExtendedConfig /ExtendedConfigItem Expected Team events only				



	Attribute	Value	Description	
	Code	LEG		
	Pos	Numeric 0	Send the leg number of the team.	
	Value	S(2)	Send the INTERMEDIATE within the leg 1..F. If Pos = 2 and Value=F then it is the start point for leg 3 and the end point for leg 2 This makes the relationship between overall intermediates and legs.	
EC		INTERMEDIATES_NUM	N/A	Element Expected: Always
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Send the total number of intermediate points where the time is recorded including F.
EC		LEG	S(2)	Pos Description: Send the value that identifies the leg in the team event, 1 to n for each leg. Element Expected: Relay Events
	Attribute	M/O	Value	Description
	Value	M	Numeric #0.0#	Distance from the start of the race in km to the end of the leg.
Sub Element: Competition /Configs /Config /ExtendedConfig /ExtendedConfigItem Expected Always				
	Attribute	Value	Description	
	Code	INTERMEDIATE		
	Pos	S(2)	Send the value that identifies the intermediate point, 1,2.. to F for intermediates in the leg, including the end.	
	Value	Numeric #0.0#	Distance from the start of the leg in km for the intermediate	
EC		LEGS_NUM	N/A	Element Expected: Team events
	Attribute	M/O	Value	Description
	Value	M	Numeric #0	Number of legs

Sample (Individual)

```

<Configs>
  <Config Unit="NCBWNH10KM-----FNL-0001CC--">
    <ExtendedConfig Type="COURSE" Code="NAME" Pos="1" Value="2.5 km Red" />
    <ExtendedConfig Type="COURSE" Code="HEIGHT_DIFF" Pos="1" Value="35" />
    <ExtendedConfig Type="COURSE" Code="LAP" Pos="1" Value="2500" >
      <ExtendedConfigItem Code="NUM" Value="4" />
    </ExtendedConfig>
    <ExtendedConfig Type="COURSE" Code="CLIMB" Pos="1" Value="280" >
      <ExtendedConfigItem Type="COURSE" Code="MAX" Value="42" />
    </ExtendedConfig>
    <ExtendedConfig Type="EC" Code="INTERMEDIATES_NUM" Value="5" />
    <ExtendedConfig Type="EC" Code="INTERMEDIATE" Pos="1" Value="1.7" />
    <ExtendedConfig Type="EC" Code="INTERMEDIATE" Pos="2" Value="3.75" />
    <ExtendedConfig Type="EC" Code="INTERMEDIATE" Pos="3" Value="5.4" />
    <ExtendedConfig Type="EC" Code="INTERMEDIATE" Pos="5" Value="7.5" />
    <ExtendedConfig Type="EC" Code="INTERMEDIATE" Pos="F" Value="10.0" />
  </Config>

```

Sample (Teams)

```
<ExtendedConfig Type="EC" Code="LEGS_NUM" Value="4" />
  <ExtendedConfigItem Type="EC" Code="LEG" Pos="1" Value="5.0" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="1" Value="1.7" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="2" Value="2.5" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="3" Value="4.2" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="F" Value="5.0" />
  <ExtendedConfig Type="EC" Code="LEG" Pos="2" Value="10.0" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="1" Value="1.7" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="2" Value="2.5" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="3" Value="4.2" />
    <ExtendedConfigItem Code="INTERMEDIATE" Pos="F" Value="5.0" />
</ExtendedConfig>
```

2.3.6.6 Message Sort

There is no message sorting rule.



3 Document Control

Version history		
Version	Date	Comments
V0.1	29 Aug 2019	First version
V0.2	27 Feb 2020	Updated
V0.3	10 Jul 2020	Updated to align with CCS & PT0 review
V0.4	4 Aug 2020	Updated
V0.5	18 Sep 2020	Updated
V1.0	16 Oct 2020	Approved
V1.1	27 Nov 2020	Updated
V1.2	19 Feb 2021	Updated with CR
V1.3	14 May 2021	Updated with CR022136 [DT_IMAGE only]
V1.4	12 Nov 2021	Updated with CR
V3.0	5 May 2023	First version for Gangwon

Change Log		
Version	Status	Changes on version
V0.1	SFR	First version
V0.2	SFR	DT_RESULT: Add PROGRESS/INTERMEDIATE/Move @ Result /ExtendedResults /ExtendedResult DT_RESULT: Add clarifications in intermediates DT_RESULT: Update IRM_RULE for consistency with SJP
V0.3	SFA	Applicable messages: Add note regarding the use of ski jumping document. Applicable Message: Updated list DT_PARTIC: Delete Participant/Weight DT_PARTIC: Update Participant /Discipline /RegisteredEvent /Event DT_PARTIC: Update to clarify no historical athletes DT_PARTIC: Remove Participant /Discipline /RegisteredEvent /Bib DT_PARTIC_TEAM: Add Team/ShortName and Team/TeamType [CR19497] DT_RESULT: Update ResultStatus options in header values DT_RESULT: Update UI/STARTERS at ExtendedInfos /ExtendedInfo DT_RESULT: Add UI/STARTERS/PASSED at ExtendedInfos /ExtendedInfo DT_RESULT: Add LEADER/CURRENT at ExtendedInfos /ExtendedInfo DT_RESULT: Add DISPLAY/NEXT, STARTED & CURR_LEG at ExtendedInfos /ExtendedInfo DT_RESULT: Update Result/Result DT_RESULT: Add ER/STATUS at Result /ExtendedResults /ExtendedResult DT_RESULT: Update expected PROGRESS/INTERMEDIATE at Result /ExtendedResults /ExtendedResult DT_RESULT: Delete IRM and Value2, update Value and Diff at PROGRESS/INTERMEDIATE at Result /ExtendedResults /ExtendedResult DT_RESULT: Add PROGRESS/SECTION at Result /ExtendedResults /ExtendedResult DT_RESULT: Update Pos and expected description for PROGRESS/INTERMEDIATE at Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult DT_RESULT: Delete IRM, update Value and Diff at PROGRESS/INTERMEDIATE at Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult DT_RESULT: Update Value2 at PROGRESS/INTERMEDIATE at Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult DT_RESULT: Update Pos description for PROGRESS/LEG_SPLIT at Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult DT_RESULT: Remove IRM at PROGRESS/LEG_SPLIT at Result /Competitor /Composition /Athlete /EventUnitEntry DT_RESULT: Update Expected at Result /Competitor /EventUnitEntry DT_RESULT: Update Expected at EUE/PERFORM at Result /Competitor /Composition /Athlete /EventUnitEntry DT_RESULT: Update Expected at EUE/WAVE at Result /Competitor /Composition /Athlete /EventUnitEntry DT_CURRENT: Message removed



		DT_RANKING: Remove PARTIAL as possible value for ResultStatus in the header values DT_RANKING: Clarify who to include in the description of the message. DT_CONFIG: Update description DT_CONFIG: Update @Pos description throughout for clarity DT_CONFIG: Update expected for EC/INTERMEDIATE at Configs /Config /ExtendedConfig DT_CONFIG: Remove EC/LEG/CUMULATIVE at Configs /Config /ExtendedConfig Review and update M/O as needed Editorial improvements throughout DT_PARTIC_TEAMS: Update Triggering DT_PARTIC_TEAMS: Remove Team /Discipline /RegisteredEvent /Bib DT_RESULT: Add ER/CURRENT at Result /ExtendedResults /ExtendedResult DT_RESULT: Update M/O DT_RANKING: Correct typo in sample DT_RANKING: Update Result /Competitor /Code DT_CONFIG: Update DocumentCode in the Header
V0.4	SFA	Section 2.1 (Overview) added DT_RESULT: Remove ExtendedInfos /ExtendedInfo /Competitor
V0.5	SFA	DT_RESULT: Update EUE/COLOUR to use codes in Value at Result /Competitor /Composition /Athlete /EventUnitEntry (does not change the value sent, added for language purposes) DT_RESULT: Add EUE/SJP at Result /Competitor /EventUnitEntry DT_RESULT: Add EUE/SJP at Result /Competitor /Composition /Athlete /EventUnitEntry
V1.0	APP	No changes, status changed to Approved
V1.1	APP	Timeline added
V1.2	APP	DT_WEATHER: Update triggering [CR021512] DT_WEATHER: Update Weather/Conditions/Code to add HIGH and LOW [CR021512]
V1.3	APP	DT_IMAGE: Update message description [CR022136] DT_IMAGE: Update DocumentSubcode & Version in header [CR022136] DT_IMAGE: Update expected in Competition/Image [CR022136] DT_IMAGE: Update expected and attributes in Competition/Image/Result [CR022136]
V1.4	APP	DT_RESULT: Add IRM for PROGRESS/LEG_SPLIT at Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult [CR024294]
V3.0	SFA	Remove DT_WEATHER