



Olympic Data Feed



Bowls and Para Bowls ODF Data Dictionary

Technology and Information Department
© International Olympic Committee

SCOG-2026-LBO-1.7 SFR
23 July 2026

License

The document accompanying this license and the information contained therein (the Document), whether in a paper or electronic format, is made available to you subject to the terms stated below. By using and/or copying all or part of the Document, you (the licensee) agree that you will comply with the following terms and conditions.

1. You may, on a non-exclusive basis, use the Document only on the condition that you abide by the terms of this license. Subject to this condition and other terms and restrictions contained herein, the Document and the information contained therein may be used (i) to further develop the standards described in the Document for use in relation with the Olympic and Paralympic Games and/or (ii) to develop similar standards for other events than the Olympic and Paralympic Games (both (i) and (ii) are hereinafter designated as the Permitted Use, and works further developing these standards for the Olympic and Paralympic Games or developing similar standards for other events are hereinafter referred to as Derivative Works), and copies of the Document or of Derivative Works may be made and distributed for the purpose of the Permitted Use, PROVIDED THAT the COPYRIGHT and references to the IOC appearing in the Document and the TERMS OF THIS LICENSE are included on ALL such COPIES, and further PROVIDED THAT you do not charge any fee or any other monetary compensation for the distribution of the Document to others. The copyright and other intellectual property rights in the Document remain vested in the IOC and the IOC remains entitled to assert his copyright or other intellectual property rights in the Document against any person or entity who does not comply with the terms of this License.
2. A copy of any Derivative Work shall be provided to the IOC free of charge. Moreover, the IOC is granted a worldwide, perpetual, unrestricted, royalty-free non-exclusive license to use any Derivative Work for the further development of the standards made by or for the IOC in relation to the Olympic and Paralympic Games (these standards and the documents describing them are hereinafter referred to as Further Standards) and to make or have made all kinds of exploitation of the Further Standards, with the right to grant sub-licenses.
3. Except if reproduced in the Document, the use of the name and trademarks of the IOC is strictly prohibited, including, without limitation, for advertising, publicity, or in relation to products or services and their names. Any use of the name or trademarks of the IOC, whether registered or not, shall require the specific written prior permission of the IOC.
4. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THE DOCUMENT. The Document and the information contained herein are provided on an "as is" basis. THE IOC DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL THE IOC BE LIABLE TO ANYONE FOR DAMAGES OF ANY KIND ARISING FROM OR RELATING TO YOUR ACQUISITION, USE, DUPLICATION, DISTRIBUTION, OR EXPLOITATION OF THE DOCUMENT OR ANY PORTION THEREOF, INCLUDING BUT NOT LIMITED TO, COMPENSATORY DAMAGES, LOST PROFITS, LOST DATA OR ANY FORM OF SPECIAL, INCIDENTAL, DIRECT, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES, WHETHER BASED ON BREACH OF CONTRACT OR WARRANTY, TORT OR OTHERWISE. THE IOC FURTHER DISCLAIMS ANY LIABILITY FOR ANY DAMAGE CAUSED WHEN THE DOCUMENT IS USED IN A DERIVATIVE WORK. The IOC further disclaims any liability regarding the existence or inexistence of any intellectual property or other rights that might be claimed by third parties with respect to the implementation or use of the technology or information described in the Document.

The same conditions as those described in this Section shall apply mutatis mutandis to the license granted to the IOC on the Derivative Works in Section 2 above.

5. This License is perpetual subject to your conformance to its terms and conditions. The IOC may terminate this License immediately upon your breach of any of its terms and, upon such termination you will cease all use, duplication, distribution, and/or exploitation in any manner of the Document.
6. This License is governed by the laws of Switzerland. You agree that any disputes arising from or relating to this License will be resolved in the courts of Lausanne, Switzerland.

IF YOU DO NOT AGREE TO THESE TERMS YOU MUST CEASE ALL USE OF THE DOCUMENT NOW.



1	Introduction	5
1.1	This document.....	5
1.2	Objective	5
1.3	Main Audience.....	5
1.4	Glossary	5
1.5	Related Documents.....	5
2	Messages.....	6
2.1	Bowls Overview.....	6
2.2	Applicable Messages	6
2.3	Messages	8
2.3.1	Competition schedule / Competition schedule update.....	8
2.3.1.1	Description	8
2.3.1.2	Header Values.....	9
2.3.1.3	Trigger and Frequency.....	10
2.3.1.4	Message Structure	10
2.3.1.5	Message Values.....	12
2.3.1.6	Message Sort	17
2.3.2	List of participants by discipline / List of participants by discipline update	18
2.3.2.1	Description	18
2.3.2.2	Header Values.....	18
2.3.2.3	Trigger and Frequency.....	19
2.3.2.4	Message Structure	19
2.3.2.5	Message Values.....	20
2.3.2.6	Message Sort	22
2.3.3	List of teams / List of teams update	23
2.3.3.1	Description	23
2.3.3.2	Header Values.....	23
2.3.3.3	Trigger and Frequency.....	23
2.3.3.4	Message Structure	23
2.3.3.5	Message Values.....	24
2.3.3.6	Message Sort	25
2.3.4	List of Entries by Event.....	26
2.3.4.1	Description	26
2.3.4.2	Header Values.....	26
2.3.4.3	Trigger and Frequency.....	26
2.3.4.4	Message Structure	26
2.3.4.5	Message Values.....	27
2.3.4.6		29
2.3.4.7	Message Sort	29
2.3.5	Event Unit Start List and Results	30
2.3.5.1	Description	30
2.3.5.2	Header Values.....	30
2.3.5.3	Trigger and Frequency.....	30
2.3.5.4	Message Structure	31
2.3.5.5	Message Values.....	33
2.3.5.6	Message Sort	37
2.3.6	Pool Standings	38
2.3.6.1	Description	38
2.3.6.2	Header Values.....	38
2.3.6.3	Trigger and Frequency.....	38
2.3.6.4	Message Structure	38



2.3.6.5	Message Values	41
2.3.6.6	Message Sort	45
2.3.7	Brackets	46
2.3.7.1	Description	46
2.3.7.2	Header Values	46
2.3.7.3	Trigger and Frequency	46
2.3.7.4	Message Structure	46
2.3.7.5	Message Values	48
2.3.7.6	Message Sort	51
2.3.8	Event Final Ranking	52
2.3.8.1	Description	52
2.3.8.2	Header Values	52
2.3.8.3	Trigger and Frequency	52
2.3.8.4	Message Structure	52
2.3.8.5	Message Values	53
2.3.8.6	Message Sort	55
2.3.9	Configuration	56
2.3.9.1	Description	56
2.3.9.2	Header Values	56
2.3.9.3	Trigger and Frequency	56
2.3.9.4	Message Structure	56
2.3.9.5	Message Values	57
2.3.9.6	Message Sort	57
3	Message Timeline	58
3.1	Preparation Phase	58
3.2	Before competition	58
3.3	During competition	58
3.4	After competition	58
4	Document Control	61



1 Introduction

1.1 This document

This document includes the ODF Bowls Data Dictionary. This Data Dictionary refines the messages described in the ODF General Messages Interface Document specifically for this discipline.

1.2 Objective

The objective of this document is to provide a complete and formal definition of the ODF Bowls Data Dictionary, with the intention that the information message producer and the message consumer can successfully interchange the information as the competition is run.

1.3 Main Audience

The main audience of this document is the IOC as the ODF promoter, ODF users such as the World News Press Agencies, Rights Holding Broadcasters and International Sports Federations.

1.4 Glossary

The following abbreviations are used in this document.

Acronym	Description
IF	International Federation
IOC	International Olympic Committee
NOC	National Olympic Committee
ODF	Olympic Data Feed
RSC	Results System Codes
WNPA	World News Press Agencies

1.5 Related Documents

Document Title	Document Description
ODF Foundation Principles	The document explains the environment & general principles for ODF
ODF General Messages Interface	The document describes the ODF General Messages
Common Codes	The document describes the ODF Common codes
ODF Header Values	The document details the header values which shows which RSCs are used in which messages.
ORIS Sports Document	The document details the sport specific requirements



2 Messages

2.1 Bowls Overview

MESSAGES IN EACH EVENT

All games have the same messages sent and all games are managed independently. Each game has a DT_RESULT message with the current standing of the match.

After the match in pool rounds a DT_POOL_STANDING is used to send the current pool ranking. In elimination phases the DT_BRACKET is used to inform about the current bracket updates.

SCHEDULE

The DT_SCHEDULE/DT_SCHEDULE_UPDATE message will include each game (schedule=Y) only which is aligned with the same RSC for DT_RESULT.

BRACKET

There is only one bracket with the code FNL available for all H2H Bowls competitions. The bronze medal match is included in that FNL bracket in the final phase after the gold medal match with Position=2.

2.2 Applicable Messages

The following table is a full list of all ODF messages and describes the list of messages used in this discipline.

- The column "Message type" indicates the DocumentType that identifies a message
- The column "Message name" is the message name identified by the message type
- The column "Message extended" indicates whether a particular message has extended definition in regards to those that are general for all sports. If one particular message is not extended, then it follows the general definition rules.
- Message responsibilities appears in the ODF General Document.

Message Type	Message Name	Message\nextended
DT_SCHEDULE / DT_SCHEDULE_UPDATE	Competition schedule / Competition schedule update	X
DT_PARTIC / DT_PARTIC_UPDATE	List of participants by discipline / List of participants by discipline update	X
DT_PARTIC_TEAMS / DT_PARTIC_TEAMS_UPDATE	List of teams / List of teams update	X
DT_ENTRIES	List of Entries by Event	X
DT_RESULT	Event Unit Start List and Results	X
DT_POOL_STANDING	Pool Standings	X
DT_BRACKETS	Brackets	X
DT_RANKING	Event Final Ranking	X
DT_MEDALLISTS	Event's Medallists	
DT_MEDALLISTS_DISCIPLINE	Medallists by discipline	
DT_MEDALS	Medal standings	
DT_COMMUNICATION	Communication	
DT_WEATHER	Weather conditions	X
DT_PRESENTER	Medal Presenters	



DT_LOCAL_ON	Discipline/venue start transmission	
DT_LOCAL_OFF	Discipline/venue stop transmission	
DT_KA	Keep Alive	
DT_ALERT	Alert	
DT_BCK	Background Document	
DT_BIO_PAR	Participant Biography	
DT_BIO_TEA	Team Biography	
DT_NEWS	News Document	
DT_PIC	Pictures	
DT_PDF	PDF Message	



2.3 Messages

2.3.1 Competition schedule / Competition schedule update

2.3.1.1 Description

The Competition schedule is a bulk message provided for one discipline. As a general rule, it contains the complete schedule information for all event units needed to run a competition and excludes event units for activities such as unofficial training and press conferences.

This message contains the competition timetable for a complete discipline as well as status for each competition unit and is updated from OVR via the schedule update message.

All event units in codes which have the 'schedule' flag set to 'Y' or 'S' are included in schedule messages regardless of status (those without status must be sent as UNSCHEDULED if the schedule flag is 'Y' or 'S').

The arrival of the competition schedule message resets all the previous schedule information for one discipline.

The StartList component of the message is only included in the case that the Unit Type is one of HATH, HCOUP or HTEAM and at least one of the competitors are known.

The Composition component (i.e. listing athletes) is only included in the case that the Unit Type is one of HATH or HCOUP.

For reference the applicable unit types (from common codes) are:

HATH Individual Head to Head units (e.g. ARC, BDM, TEN, SBD etc)
HCOUP Pairs/Couples Head to Head units (e.g. BDM, TEN etc)
HTEAM Teams Head to Head units (e.g. BKB, VBV, HBL, CUR, IHO etc)

Managing when start times are not known.

In some disciplines the start time of each unit is not known and the unit are managed by order rather than time.

In these disciplines only the time of the first unit (or first unit per location) is known and distributed. In this case all units should be sent with the same start time and those following units flagged as HideStartDate (and finish). To be able to correctly order these units then the Order attribute is used (and must be sent from the venue).

To ensure there are no incorrectly ordered units then the start time must not be updated to the actual start time (there is an actual start time field to cater for this). For example:

Start Time	Display	Unit	HideStartDate	Location	Order
in message					
12:00	12:00	Unit 1	N	Court 2	1
12:00	Match 2	Court 2	Unit 2	Y	Court 2 2
12:00	Match 3	Court 2	Unit 3	Y	Court 2 3
16:30	Not before 16:30	Unit 4	Y	Court 2	4

If the discipline requires some text describing the order then StartText is used. Typical uses include "Not before 17:00" or "SUN 29 - 2nd match on CC" or "Follows".

Advice for end users - how to sort event units and use DT_SCHEDULE:

- When displaying the schedule users must use the following sort order to display as intended:

Olympic Data Feed - © IOC

Document Control

Technology and Information Department

23 July 2026

Where the discipline is defined as LOC:

1. By day (or filter by day)
2. Session Code
3. By location
4. By Time (regardless if HideStartDate="Y")
5. By Order

Where the discipline is defined as SESSION OR DATE:

1. By day (or filter by day)
2. Session Code
3. By Time (regardless if HideStartDate="Y")
4. By Order

- The Order can be match number for simplicity and show correct order for two matches at the same time.
- End users should display StartText if HideStartDate="Y"

If a StartText value of "Not before hh:mm" is used then it is expected that the StartDate sent is the same hh:mm.

Competition schedule update:

Competition schedule update is an update message. It is not a complete schedule information message, but only the schedule data being modified.

The arrival of this message updates the previous schedule information for one particular event unit(s) or sessions(s), but does not notify any other change for the rest of the event units/sessions except for those contained in the message.

The key of the information updated is Unit @Code. Therefore, any new unit, deleted unit or updated unit will be identified by all this attribute.

It has to be understood that if one DT_SCHEDULE message arrives, then all previous DT_SCHEDULE_UPDATE messages should be discarded.

When message is sent from Competition Schedule application in advance of the Games the element ExtendedInfos/EntendedInfo will contain following information:

- Type=CS, Code=VERSION, the attribute Value will indicate the version details from the competition schedule application
- Type=CS, Code=STATUS the attribute Value will indicate the status details from the competition schedule application

2.3.1.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC@DISCIPLINE Code	Full RSC at the discipline level
DocumentSubcode	N/A	N/A
DocumentType	DT_SCHEDULE DT_SCHEDULE_UPDATE	/ Competition schedule bulk / update
DocumentSubtype	SYNC N/A	SYNC if the message is for re-synchronisation for ODF clients. Only sent once the control is transferred to OVR.



		DocumentSubtype is not applicable for _UPDATE messages.
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	N/A	N/A
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.1.3 Trigger and Frequency

The competition schedule will be sent as a bulk message (DocumentType="DT_SCHEDULE") when available before the Games and then sent multiple times until a date to be confirmed after which only update messages will be sent (DocumentType="DT_SCHEDULE_UPDATE") by OVR. There is no automatic triggering and this (DT_SCHEDULE) message must not be sent after the transfer of control to OVR.

The competition schedule update message should be triggered at any time there has been a competition schedule modification for any previously sent competition schedule bulk message or update message including the addition of start list details (H2H).

Generally start list details for H2H units should be sent immediately when officially known, which should be as soon as possible after the preceding unit changes to official.

The triggers for status changes are described in each sport data dictionary where differences are needed.

If any text descriptions change in a message (as opposed to the code) then this message is not resent to correct previous messages however the new data is to be used in future messages.

2.3.1.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9	Level 10
Competition (0,1)									
	Gen								
	Sport								
	Codes								
	Session (0,N)								
		SessionCode							
		StartDate							
		HideStartDate							
		EndDate							
		HideEndDate							
		Leadin							



	Venue
	VenueName
	SessionStatus
	SessionType
	Medal
	FOP
	SessionName (1,N)
	Language
	Value
Unit (0,N)	
	Code
	PhaseType
	UnitNum
	HideUnitNum
	ScheduleStatus
	StartDate
	HideStartDate
	EndDate
	HideEndDate
	ActualStartDate
	ActualEndDate
	Order
	Medal
	Venue
	Location
	SessionCode
	StartText (0,N)
	Language
	Value
	ItemName (1,N)
	Language
	Value
	ItemDescription (0,N)
	Language
	-
	VenueDescription (0,1)
	VenueName
	LocationName
	StartList (0,1)



Start (1,N)	
StartOrder	
SortOrder	
PreviousUnit(0,1)	
Unit	
Value	
WLT	
Competitor (1,1)	
Code	
Type	
Organisation	
Bib	
Description (0,1)	
TeamName	
IFId	
Composition (0,1)	
Athlete (1,N)	
Code	
Order	
Bib	
Description (1,1)	
GivenName	
FamilyName	
Gender	
Organisation	
BirthDate	
IFId	
Class	

2.3.1.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /Session (0,N)			
-------------------------------------	--	--	--



Attribute	M/O	Value	Description
SessionCode	M	S(10)	Code of the sports competition session which contains this event unit. Usually in the format DDD00. DDD is the discipline and 00 is the session number within the discipline. For example ARC02 for the second session in Archery.
StartDate	M	DateTime	Start date. Example: 2006-02-26T10:00:00+01:00
HideStartDate	O	Y	Y only if StartDate (scheduled start time) should not be displayed. Applicable only in the early stages of the DT_Schedule (Schedule by Date), while the schedule is still under definition and approval and details are under embargo. When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed.
EndDate	M	DateTime	End date. Example: 2006-02-26T10:00:00+01:00
HideEndDate	O	Y	Y only if EndDate (scheduled end time) should not be displayed. Applicable only in the early stages of the DT_Schedule (Schedule by Date), while the schedule is still under definition and approval and details are under embargo. When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed
Leadin	O	m:ss	Amount of time from session start to first scheduled unit.
Venue	M	CC@VENUE Id	Venue where the session takes place
VenueName	M	CC@VENUE ENG Description	Venue ENG Description (not code) from Common Codes
SessionStatus	O	CC@SCHEDULESTATUS Id	Only use CANCELLED if applicable. All other sessions are assumed to be scheduled. There is no change to running or finished.
SessionType	O	CC@SESSION_TYPE Id	Session type of the Session.
Medal	O	#0	Send the number of gold medals planned to be determined in this session. [this is a calculation based on the units assigned to the session].
FOP	O	#0	The number of fields of play planned to be used in this session. This data is only included in the message in the pre-Games period before the schedule is known. Do not include in data to or from OVR during the Games period.

Element: Competition /Session /SessionName (1,N)			
Attribute	M/O	Value	Description
Language	M	CC@LANGUAGE Id	Language of the Session Description
Value	M	S(40)	Name of the sports competition session

Sample (General)



```
<Session Code="ATH01" StartDate="2016-08-12T10:00:00+01:00" EndDate="2016-08-12T14:00:00+05:00" LeadIn="5:00" Venue="STA" VenueName="Olympic Stadium" >
<SessionName Language="ENG" Value="Athletics Session 1" />
</Session>
<Session Code="ATH02" StartDate="2016-08-12T18:00:00+01:00" EndDate="2016-08-12T21:00:00+05:00" LeadIn="5:00" Venue="STA" VenueName="Olympic Stadium" >
<SessionName Language="ENG" Value="Athletics Session 2" />
</Session>
```

Element: Competition /Unit (0,N)			
Attribute	M/O	Value	Description
Code	M	CC@EVENT_UNIT Code	Full RSC for the unit
PhaseType	M	CC@PHASE_TYPE Id	Phase type for the unit
UnitNum	O	S(15)	Match / Game / Bout / Race Number or similar
HideUnitNum	O	Y	Y only if the UnitNum should not be displayed (example the Gold medal match schedule details are not confirmed yet and shall not be displayed)
ScheduleStatus	M	CC@SCHEDULESTATUS Id	Unit Status
StartDate	O	DateTime	Start date. This attribute may not be sent when the @ScheduleStatus is UNSCHEDULED. For other statuses the StartDate is expected otherwise ordering is display is incorrert (including CANCELLED and POSTPONED). This is the scheduled Start date and time and will not be updated when an event unit starts, that is, do not change to actual (updated only with RESCHEDULED status) Where HideStartDate="Y" then this should be filled with the session start time or the start time of a group of units for all similar units and Order used for sorting. This method is not used in team sports where HideStartDate="Y" is only used temporarily to remove times. Example: 2006-02-26T10:00:00+01:00
HideStartDate	O	Y	Send 'Y' if StartDate (scheduled start time) should not be displayed. It may be an estimate or 'fake' time. Do not send if StartDate (scheduled start time) is to be displayed. Start times of some units depend on the finalisation of previous event units and therefore there is no fixed start time in these cases this field is set to 'Y'. When the flag is set to 'Y' then the time is used for sorting purposes but should not be displayed.
EndDate	O	DateTime	This is the scheduled end date and time and will not be updated when an event unit ends, that is, do not change to actual (updated only with RESCHEDULED status relative to StartDate) This attribute is not required when the @ScheduleStatus is UNSCHEDULED or CANCELLED. Example: 2006-02-26T10:00:00+01:00
HideEndDate	O	Y	Send 'Y' if EndDate scheduled end time is not to be displayed.



			Some event units have a scheduled end time well bounded, however, some event units in some circumstances have a scheduled end time not quite variable (example, some press conferences or tennis matches, etc.) in these cases this field is set to 'Y' and should not be displayed.
ActualStartDate	O	DateTime	This attribute is expected once the event unit has started. Example: 2006-02-26T10:03:22+01:00
ActualEndDate	O	DateTime	This attribute is expected once the event unit has finished. Example: 2006-02-26T12:43:51+01:00
Order	O	Positive Integer	Order of the units when displayed. This field is considered in two situations: 1. If HideStartDate = 'Y' then send at least for all Units in an affected session though it is suggested to be sent for all units in a discipline where the concept is used in the discipline. 2. If some units start at the same time and a particular order of the units is expected. Can use match number so the units are displayed in the correct order when at the same time.
Medal	O	SCGEN@UnitMedalType Code	Indicator of medal awarded for this unit.
Venue	O	CC@VENUE Id	Venue where the unit takes place Mandatory unless UNSCHEDULED Can use TBD if the Venue is not known yet (see CC).
Location	O	CC@LOCATION Id	Location where the unit takes place. Mandatory unless UNSCHEDULED. Can use TBD if the Location is not known yet or a generic code for the discipline (see CC).
SessionCode	O	S(10)	Code of the sports competition session which contains this event unit. Usually in the format DDD00. DDD is the discipline and 00 is the session number within the discipline. For example ARC02 for the second session in Archery.

Element: Competition /Unit /StartText (0,N)

This element is only used for Competition Schedules when HideStartDate is 'Y'. In this case, English Language is mandatory.

Attribute	M/O	Value	Description
Language	M	CC@LANGUAGE Id	Code Language of the @Value
Value	M	S(20) or SC@StartText Code	Text to be displayed in the case that StartDate is not to be displayed. Use available codes or free text if appropriate is not available

Element: Competition /Unit /ItemName (1,N)

Attribute	M/O	Value	Description
Language	M	CC@LANGUAGE Id	Code Language of the @Value
Value	M	CC@EVENT_UNIT ENG Short Description	Item Name / Unit Description. For competition units show the unit Description from common codes which matches the RSC. As in all messages with a description. Only the ENG description is expected.



			For non-competition schedules (where the item description is not in common codes) then add the description.
--	--	--	---

Element: Competition /Unit /ItemDescription (0,N)			
Attribute	M/O	Value	Description
Language	M	CC@LANGUAGE Id	Code Language of the @Value
-	M	Free Text	Item Description for non-competition schedule

Element: Competition /Unit /VenueDescription (0,1)			
Mandatory when Unit/Venue is included			
Attribute	M/O	Value	Description
VenueName	M	CC@VENUE ENG Description	Venue ENG Description (not code) from Common Codes
LocationName	M	CC@LOCATION ENG Description	Location ENG Description (not code) from Common Codes

Element: Competition /Unit /StartList /Start (1,N)			
StartList information is only sent in the case that the Unit type is one of HATH, HCOUP or HTEAM and at least one of the competitors are known. (Sent as soon as known for applicable units)			
Attribute	M/O	Value	Description
StartOrder	O	Positive Integer	Competitor's start order
SortOrder	M	Positive Integer	Used to sort competitors in an event unit (for example, if there is no StartOrder). It is mainly used for display purposes.

Element: Competition /Unit /StartList /Start /PreviousUnit (0,N)			
Previous Event Unit related to the Start@SortOrder for the current unit. It is only sent in the case that the Unit type is one of HATH, HCOUP or HTEAM. Include only if the real competitors are not known.			
Attribute	M/O	Value	Description
Unit	O	CC@EVENT_UNIT Code	The full RSC of the unit where this competitor came from. This attribute is only filled if the progression of the competitors are 100% confirmed as participating at this time and not subject to change depending on TV times etc. Further, the data is removed when the real competitors are known.
Value	O	Integer	Rank in the pool, if the previous phase is the pool phase.
WLT	O	SC@WLT Code	W or L for winner of loser of a particular previous unit plays in this unit. This attribute is only filled if the competitors are 100% confirmed as participating at this time and not subject to change depending on TV times etc. Further, the data is removed when the real competitors are known.

Element: Competition /Unit /StartList /Start /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or SC@CompetitorPlace Code	Competitor's ID, TBD in case that the competitor is not known at this time AND the other competitor is known. NOCOMP is sent when there is no competitor (and will not come later)
Type	M	A, T	A for athlete, T for team



Organisation	O	CC@ORGANISATION Id	Should be sent when known
--------------	---	-----------------------	---------------------------

Element: Competition /Unit /StartList /Start /Competitor /Description (0,1)			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Team Name where known, must send when available
IFId	O	S(16)	Team IF number, send if available

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete (1,N)			
Only send in the case that the Unit type is one of HATH (ARC, BDM, TEN etc) or HCOUP (BDM, TEN etc), In case of the Competitor @Code='TBD' the Competitor element should not be sent.			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeros	Athlete's ID, corresponding to either a team member or an individual athlete in the event unit.
Order	M	Positive Integer	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".
Bib	O	S(5)	Individual athlete's bib number (if Competitor @Type="A") or team member's bib number (if Competitor @Type="T").

Element: Competition /Unit /StartList /Start /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Preferred Given Name
FamilyName	M	S(25)	Preferred Family Name
Gender	M	CC@PERSON_GENDER Id	Participant's gender
Organisation	M	CC@ORGANISATION Id	Organisation ID
BirthDate	O	YYYY-MM-DD	Date of birth.
IFId	O	S(16)	Athlete IF number, send if available, only for the current discipline.
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games). This attribute is optional because it is not used in events without such athletes.

2.3.1.6 Message Sort

Sort by Session @SessionCode.

The message is sorted by Unit@StartDate then by Unit@Order then Unit@Code.

In case of event unit with no Unit@StartDate defined (example, they are in an event unit status such as UNSCHEDULED), they will be listed at the end in Unit@Code order.

2.3.2 List of participants by discipline / List of participants by discipline update

2.3.2.1 Description

A participant is considered to be any individual (type athlete, participating or not in the current games) or any official in one or several disciplines or a competitor being part of a team (team member).

Although the participant may participate in more than one event or more than one discipline, this message just contains the information for the discipline of the message, listing the information of all the events for that discipline.

List of participants by discipline (DT_PARTIC) is a bulk message, provided for each discipline. It is a complete participant information message for one particular discipline. The arrival of this message resets all the previous participants' information for one particular discipline. This message can include a list of current athletes, officials, coaches, guides, technical officials, Reserves and historical athletes regardless of status.

List of participants by discipline update (DT_PARTIC_UPDATE) is an update message. It is not a complete list of participants' information by discipline message, only the participant data being modified, i.e. if some data of one participant changes, the element Participant for it with all its children and attributes must be sent.

The key of the information updated consists of the following attribute: Participant @Code. Therefore, any new or updated Participant Discipline-Event will be identified by all these attributes.

2.3.2.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC_DISCIPLINE Code	Discipline RSC
DocumentSubcode	N/A	N/A
DocumentType	DT_PARTIC DT_PARTIC_UPDATE	/ List of participants by discipline message
DocumentSubtype	SYNC HISTORICAL N/A	SYNC if the message is for re-synchronisation for ODF clients. Only sent once the control is transferred to OVR. HISTORICAL if the message is from the historical results provider and includes only historic data. The message is not sent to external clients. DocumentSubtype is not applicable for _UPDATE messages.
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	N/A	N/A
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.



2.3.2.3 Trigger and Frequency

The DT_PARTIC message is sent as a bulk message prior to the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_UPDATE messages are sent.

The DT_PARTIC_UPDATE message is triggered when there is a modification in the data for any individual after the transfer of control to OVR.

2.3.2.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6
Competition (0,1)					
	Gen				
	Sport				
	Codes				
	Participant (1,N)				
		Code			
		Parent			
		Status			
		GivenName			
		FamilyName			
		PassportGivenName			
		PassportFamilyName			
		PrintName			
		PrintInitialName			
		TVName			
		TVInitialName			
		TVFamilyName			
		LocalFamilyName			
		LocalGivenName			
		PSCBName			
		PSCBShortName			
		PSCBLongName			
		Gender			
		Organisation			
		Height			
		BirthDate			
		PlaceofBirth			
		CountryofBirth			
		PlaceofResidence			
		CountryofResidence			
		Nationality			
		MainFunctionId			



	Current
	OlympicSolidarity
	Discipline (1,1)
	Code
	IFId
	DisciplineEntry (0,1)
	Type
	Code
	Pos
	Value

2.3.2.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Sample (General)

<Competition Gen="SOG-2020-1.10" Sport="SOG-2020-BK3-1.10" Codes="SOG-2020-1.20" >

Element: Competition /Participant (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Participant's ID. It identifies an athlete or an official and the holding participant's valid information for one particular period of time. It is used to link other messages to the participant's information. Participant's information (example @Organisation) will not be the latest for the athlete/official, unless the @Code attribute is the same as the @Parent attribute. However, this information could be the one being valid in the particular moment of a start list, event unit results, etc. When the participant is an historical one, then this ID will start with "A" when it is an Athlete, "C" when Coach and "O" when Official.
Parent	M	S(20) with no leading zeroes	Participant's parent ID, which is used to link to the latest valid information for one participant. @Parent attribute should be linked to the latest participant's information, by retrieving that Athlete/Official whose @Code attribute is the same as @Parent. The participant containing @Code attribute being the same as the @Parent attribute will be the one with the latest information for the participant.



			The @Parent attribute will only be different from @Code in the case that critical personal information has changed from previous competitions. The typical examples are Organisation (for change of country) or Name (particularly for women changing their name at marriage). Further to be clear, @Parent and @Code can only be different if Current = "false".
Status	M	CC@PARTICIPANT_STATUS Id	Participant's sport entry status. To delete a participant, a specific value of the Status attribute is used.
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
PassportGivenName	O	S(25)	Passport Given Name (Uppercase).
PassportFamilyName	O	S(25)	Passport Family Name (Uppercase).
PrintName	M	S(35)	Print name (family name in upper case + given name in mixed case)
PrintInitialName	M	S(18)	Print Initial name (for the given name it is sent just the initial, without dot)
TVName	M	S(35)	TV name
TVInitialName	M	S(18)	TV initial name
TVFamilyName	M	S(25)	TV family name
LocalFamilyName	O	S(25)	Family name in the local language in the appropriate case for the local language (usually mixed case)
LocalGivenName	O	S(25)	Given name in the local language in the appropriate case for the local language (usually mixed case)
PSCBName	O	S(50)	Public Scoreboard Name created by OVR.
PSCBShortName	O	S(50)	Public Scoreboard Short Name created by OVR.
PSCBLongName	O	S(50)	Public Scoreboard Long Name created by OVR.
Gender	M	CC@PERSON_GENDER Id	Participant's gender
Organisation	M	CC@ORGANISATION Id	Organisation ID
Height	O	S(3)	Height in centimetres. It will be included if this information is available. This information is not needed in the case of officials/referees. "." may be used where the data is not available.
BirthDate	O	YYYY-MM-DD	Date of birth. Expected for athletes, not expected for all groups of officials.
PlaceofBirth	O	S(75)	Place of Birth
CountryofBirth	O	CC@COUNTRY Id	Country ID of Birth
PlaceofResidence	O	S(75)	Place of Residence
CountryofResidence	O	CC@COUNTRY Id	Country ID of Residence
Nationality	O	CC@COUNTRY ID	Participant's nationality. Although this attribute is optional, in very exceptional situations it will not be known, and for this reason not ready to be sent.
MainFunctionId	O	CC@DISCIPLINE_FUNCTION Id	Main function In the Case of Current="true" this attribute is Mandatory.



OlympicSolidarity	O	Y	Send Y if the participant is a member of the Solidarity / Scholarship Program else not sent.
-------------------	---	---	--

Element: Competition /Participant /Discipline (1,1)

All participating athletes will be assigned at least one discipline, it could be more. Each accredited official will be assigned at least one discipline, but it could be more. If an athlete or official is assigned to more than one discipline, it will be included in the participant message of both disciplines.

Attribute	M/O	Value	Description
Code	M	CC@DISCIPLINE Id	Full RSC of the Discipline. It is the discipline code used to fill the OdfBody @DocumentCode attribute.
IFId	O	S(16)	IF ID (Competitor's federation number for the corresponding discipline)

Element: Competition /Participant /Discipline /DisciplineEntry (0,1)

Send if there are specific athlete's discipline entries.

Type	Code	Pos	Description
ENTRY	RANK_WLD	N/A	Element Expected: If the information is known (this information can be sent in both messages).
	Attribute	M/O	Value
	Value	M	S(4)
ENTRY	RANK_PTS	N/A	Element Expected: If the information is known (this information can be sent in both messages).
	Attribute	M/O	Value
	Value	M	#####0
ENTRY	FIBA_ID	N/A	Element Expected: If known
	Attribute	M/O	Value
	Value	M	S(40)

2.3.2.6 Message Sort

The message is sorted by Participant @Code

2.3.3 List of teams / List of teams update

2.3.3.1 Description

DT_PARTIC_TEAMS contains the list of teams related to the current competition.

List of teams (DT_PARTIC_TEAMS) is a bulk message by discipline. The list is always complete. The arrival of this message resets all the previous participant teams' information for that discipline. It is assumed that all teams appearing in this list are valid, in the meaning that they are participating or they could participate in one event.

List of teams update (DT_PARTIC_TEAMS_UPDATE) is an update message. It is not a complete list of teams' information message. It only contains the data of a team being modified.

2.3.3.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC@DISCIPLINE Code	Discipline RSC
DocumentSubcode	N/A	N/A
DocumentType	DT_PARTIC_TEAMS DT_PARTIC_TEAMS_UPDATE	List of participant teams message
DocumentSubtype	SYNC HISTORICAL N/A	SYNC if the message is for re-synchronisation for ODF clients. Only sent once the control is transferred to OVR. HISTORICAL if the message is from the historical results provider and includes only historic data. The message is not sent to external clients. DocumentSubtype is not applicable for _UPDATE messages.
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	N/A	N/A
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.3.3 Trigger and Frequency

The DT_PARTIC_TEAMS message is sent as a bulk message before the Games. It is sent several times up to the date of transfer of control to OVR after which only DT_PARTIC_TEAMS_UPDATE messages are sent.

The DT_PARTIC_TEAMS_UPDATE message is triggered when there is a modification in the data for any team after the transfer of control to OVR.

2.3.3.4 Message Structure

The following table defines the structure of the message.



Level 1	Level 2	Level 3	Level 4	Level 5	Level 6
Competition (0,1)					
	Gen				
	Sport				
	Codes				
	Team (1,N)				
		Code			
		Status			
		Organisation			
		Name			
		ShortName			
		TVTeamName			
		PSCBName			
		PSCBShortName			
		PSCBLongName			
		Gender			
		TeamType			
		Discipline (1,1)			
			Code		
			IFld		

2.3.3.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /Team (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Team's ID
Status	M	CC@PARTICIPANT_STATUS Id	Team's entry status. This attribute is Mandatory always To delete a team, a specific value of the Status attribute is used.
Organisation	M	CC@ORGANISATION Id	Team organisation's ID
Name	M	S(73)	Team name.
ShortName	M	S(40)	Team Short Name
TVTeamName	M	S(21)	Team's TV Name.
PSCBName	O	S(50)	Public Scoreboard Name created by OVR.
PSCBShortName	O	S(50)	Public Scoreboard Short Name created by OVR.
PSCBLongName	O	S(50)	Public Scoreboard Long Name created by OVR.



Gender	M	CC@DISCIPLINE_GENDER Gender	Gender Code of the Team
TeamType	M	SCGEN@TeamType Code	Send the team type. This is how the name is constructed to allow clients to build in other languages. Use ORG

Element: Competition /Team /Discipline (0,1)

A team is assigned just to one discipline.

Attribute	M/O	Value	Description
Code	M	CC@DISCIPLINE Code	Full RSC of the Discipline
IFId	O	S(16)	International Federation Id

2.3.3.6 Message Sort

The message is sorted by Team @Code.

2.3.4 List of Entries by Event

2.3.4.1 Description

This message contains the entry information for a specific event within a discipline with the specific event entry information of the participant.

It is always a full message and any new message received resets all the previous participants' entry information for the event. This message includes the list of athletes, guides, reserves, teams including the team composition (if known) that have been entered to an event.

2.3.4.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC@EVENT Code	Event RSC
DocumentSubcode	N/A	N/A
DocumentType	DT_ENTRIES	List of entries by event message
DocumentSubtype	N/A	N/A
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	N/A	N/A
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.4.3 Trigger and Frequency

The DT_ENTRIES message is sent as a bulk message prior to the Games. It is sent several times up to the date of transfer of control to OVR after which the entries information is updated at the venue and the bulk message is triggered by the OVR.

2.3.4.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9
Competition (0,1)								
	Gen							
	Sport							
	Codes							
	Entry (1,N)							
		Code						
		Type						



	Organisation
	SortOrder
	EntryStatus
	Description (0,1)
	TeamName
	ExtendedEntry (0,N)
	Type
	Code
	Pos
	Value
	Composition (0,1)
	Athlete (0,N)
	Code
	Order
	EntryStatus
	Description (1,1)
	GivenName
	FamilyName
	Gender
	Organisation
	BirthDate
	IFId
	Class
	ExtendedEntry (0,N)
	Type
	Code
	Pos
	Value

2.3.4.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	M	S(20)	Version of the General Data Dictionary applicable to the message
Sport	M	S(35)	Version of the Sport Data Dictionary applicable to the message
Codes	M	S(20)	Version of the Codes applicable to the message

Element: Competition /Entry (1,N)



Attribute	M/O	Value	Description
Code	M	S(20) without leading zeros	Team's ID.
Type	M	T	T for team
Organisation	M	CC@ORGANISATION Id	Competitor's organisation
SortOrder	M	Positive Integer	Order used to sort the competitors within an event following the entry list requirements for the event referenced in the message header.
EntryStatus	O	SC@AthleteStatus Code	Team's Event participation status

Element: Competition /Entry /Description (0,1)

Used in Team event only

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team

Element: Competition /Entry /ExtendedEntry (0,N)

Element: Competency, Knowledge, Skill, Ability (C/K/S/A)				
Type		Code	Pos	Description
ENTRY		GROUP	N/A	Element Expected: as soon as it is known
	Attribute	M/O	Value	Description
	Value	M	S(1)	Athlete's and Team's Preliminary Group
ENTRY		SEED	N/A	Element Expected: as soon as it is known
	Attribute	M/O	Value	Description
	Value	M	Positive Integer	Seed number

Element: Competition /Entry /Composition /Athlete (0,N)

Attribute	M/O	Value	Description
Code	M	S(20) without leading zeros	Athlete's ID
Order	M	Positive Integer	1 in individual events (if Competitor @Type="A"), or athlete starting order (1..n) within the team (if Competitor @Type="T").
EntryStatus	O	SC@AthleteStatus Code	Athlete's Event participation status

Element: Competition /Entry /Composition /Athlete /Description (1,1)

Attribute	M/O	Value	Description
GivenName	O	S(25)	Preferred Given Name
FamilyName	M	S(25)	Preferred Family Name
Gender	M	CC@PERSON_GENDER Id	Gender of the athlete
Organisation	M	CC@ORGANISATION Id	Athletes' organisation
BirthDate	O	YYYY-MM-DD	Date of Birth, must be included if the data is available
IFId	O	S(16)	International Federation ID
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games).



Element: Competition /Entry /Composition /Athlete /ExtendedEntry (0,N)				
Type		Code	Pos	Description
ENTRY		POSITION	N/A	Element Expected: when available
	Attribute	M/O	Value	Description
	Value	M	CC@POSITION PositionCode	Position in the Team

Sample:

```
<Entry Code="LBOMTEAM2--BEL01" Type="T" Organisation="BEL" SortOrder="1">
  <Description TeamName="Belgium"/>
  <Composition>
    <Athlete Code="8548555" Order="1" >
      <Description GivenName="Bret" FamilyName="Casillas" Gender="M" Organisation="BEL" BirthDate="1983-11-22"
      IFId="WCFBELM500666"/>
      <ExtendedEntry Type="ENTRY" Code="POSITION" Value="1"/>
    </Athlete>
    <Athlete Code="8548554" Order="2">
      <Description GivenName="Grady" FamilyName="Winchester" Gender="M" Organisation="BEL" BirthDate="1992-02-01"
      IFId="WCFBELM215160"/>
      <ExtendedEntry Type="ENTRY" Code="POSITION" Value="S"/>
    </Athlete>
  </Composition>
</Entry>
```

2.3.4.6

2.3.4.7 Message Sort

Sort by Entry @SortOrder



2.3.5 Event Unit Start List and Results

2.3.5.1 Description

The Event Unit Start List and Results is a message containing both the start list and results information of the competitors in one (individual or team) event unit.

The Event Unit Start List and Results is a mandatory message for all sports. The definition includes as much generic information as possible due to the fact that each discipline and event has its own format for the results information (example: score of a match, time in a race, distance in a throw...).

This is always a full message and all applicable elements and attributes are always sent.

2.3.5.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC@EVENT_UNIT Code	Event Unit RSC
DocumentSubcode	N/A	N/A
DocumentType	DT_RESULT	Event Unit Start List and Results message
DocumentSubtype	N/A	N/A
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	CC@ResultStatus Code	It indicates whether the result is official or unofficial (or intermediate etc). START_LIST LIVE (used during the competition when nothing else applies). INTERMEDIATE (only if there is an unscheduled break in play) UNOFFICIAL OFFICIAL PROVISIONAL
FeedFlag	"P" - Production "T" - Test	Test message or production message.
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.5.3 Trigger and Frequency

This message is sent with ResultStatus 'START_LIST' as soon as the expected information is available and any changes to the information. Possible information is:

- * START LIST: As soon as the team/teams are known, before the unit begins.
- * START LIST: As soon as any of the line-up and starters are known and any change/addition to these only before the start of the match.

This message is then sent with ResultStatus 'LIVE' as soon as the unit starts and continues to be triggered on all updates.

- * LIVE: At the beginning of each period.
- * LIVE: After every change in any data (scores, rebounds etc.).



This message is also sent when the unit finishes and the results are still unofficial and again when the results become official. The message is sent as 'INTERMEDIATE' during extended breaks.

* INTERMEDIATE: Only if there is an unscheduled break in play.

* UNOFFICIAL / OFFICIAL: After the unit.

Trigger also after any change.

2.3.5.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9
Competition (0,1)								
	Gen							
	Sport							
	Codes							
	ExtendedInfos (0,1)							
	UnitDateTime (0,1)							
	StartDate							
	EndDate							
	Duration							
	ExtendedInfo (0,N)							
	Type							
	Code							
	Pos							
	Value							
	SportDescription (0,1)							
	DisciplineName							
	EventName							
	Gender							
	SubEventName							
	UnitNum							
	VenueDescription (0,1)							
	Venue							
	VenueName							
	Location							
	LocationName							
	Attendance							
	Periods (0,1)							
	Home							
	Away							
	Period (1,N)							
	Code							
	HomeScore							



		AwayScore
		ExtendedPeriods (0,1)
		ExtendedPeriod (1,N)
		Type
		Code
		Pos
		Value
	Result (1,N)	
	Result	
	IRM	
	WLT	
	SortOrder	
	StartOrder	
	StartSortOrder	
	ResultType	
	ExtendedResults (0,1)	
		ExtendedResult (1,N)
		Type
		Code
		Pos
		Value
	Competitor (1,1)	
	Code	
	Type	
	Organisation	
	Description (0,1)	
		TeamName
		IFId
		EventUnitEntry (0,N)
		Type
		Code
		Pos
		Value
		Composition (0,1)
		Athlete (0,N)
		Code
		Order
		StartSortOrder
		Bib
		Description (1,1)
		GivenName



	FamilyName
	Gender
	Organisation
	BirthDate
	IFId
	EventUnitEntry (0,N)
	Type
	Code
	Pos
	Value

2.3.5.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /UnitDateTime (0,1)			
Actual times. Include when the unit starts.			
Attribute	M/O	Value	Description
StartDate	M	DateTime	Actual start date and time.
EndDate	O	DateTime	Actual end date-time
Duration	O	h:mm	Match duration

Element: Competition /ExtendedInfos /ExtendedInfo (0,N)			
Type	Code	Pos	Description
UI	PERIOD	N/A	Element Expected: Always after the start of the unit, remove, when official
Attribute	M/O	Value	Description
Value	M	SC@Period Code SC@GameState Code	Send current period or the GameState Use SC@Period unless some GameState applies

Element: Competition /ExtendedInfos /SportDescription (0,1)			
Sport Descriptions in Text.			
Attribute	M/O	Value	Description
DisciplineName	M	CC@DISCIPLINE ENG Description	Discipline ENG Description (not code) from Common Codes
EventName	M	CC@EVENT ENG Description	Event ENG Description (not code) from Common Codes.



Gender	M	CC@DISCIPLINE_GENDER Gender	Gender code for the event unit
SubEventName	M	CC@EVENT_UNIT ENG ShortDescription	EventUnit ENG Description (not code) from Common Codes
UnitNum	O	S(15)	Match number

Element: Competition /ExtendedInfos /VenueDescription (0,1)

Venue Names in Text.

Attribute	M/O	Value	Description
Venue	M	CC@VENUE Id	Venue Code
VenueName	M	CC@VENUE ENG Description	Venue ENG Description (not code) from Common Codes
Location	M	CC@LOCATION Id	Location code
LocationName	M	CC@LOCATION ENG Description	Location ENG Description (not code) from Common Codes
Attendance	O	Positive Integer	Total attendance (do not send if unknown)

Element: Competition /Periods (0,1)

Attribute	M/O	Value	Description
Home	O	S(20) with no leading zeroes	Home Competitor ID
Away	O	S(20) with no leading zeroes	Away Competitor ID

Element: Competition /Periods /Period (1,N)

Period in which the event unit message arrives.

Attribute	M/O	Value	Description
Code	M	SC@Period Code	Period's code for the set
HomeScore	M	0.0	Overall score of the home competitor at the end of the period (set score)
AwayScore	M	0.0	Overall score of the away competitor at the end of the period (set score)
HomePeriodScore	O	#0	Home competitor period score just for this set.
AwayPeriodScore	O	#0	Away competitor period score just for this set.

Element: Competition /Periods /Period /ExtendedPeriods /ExtendedPeriod (1,N)

ExtendedPeriod information.

Type	Code	Pos	Description
END	HOME AWAY	#0	Pos: Number of end inside the set Element Expected: Always in singles and doubles matches.
Attribute	M/O	Value	Description
Value	M	#0	Send the running score achieved for HOME and AWAY in the set



EP	Attribute	M/O	Value	Description
	Value	O	H/A/T	Winner of the period once known (H=HOME or A=AWAY, T=TIE in case of no winner)

Element: Competition /Result (1,N)

For each Event Unit Results message, there must be at least one competitor with a result element in the event unit.

Attribute	M/O	Value	Description
Result	O	#0.#	Result of the competitor for the particular event unit. Set Scores for the game
IRM	O	SC@IRM Code	The invalid rank mark, in case it is assigned. IRM of the competitor for the event unit
WLT	O	SC@WLT Code	The code whether a competitor won or lost
SortOrder	M	Positive Integer	This attribute is a sequential number with the order of the First named (1) and the Visitor (2)
StartOrder	M	Positive Integer	Send 1 for first named team, send 2 for second named team
StartSortOrder	M	Positive Integer	Same @StartOrder
ResultType	O	SC@ResultType Code	Type of the @Result attribute. Result type, either points or IRM with points for the corresponding event unit

Element: Competition /Result /Competitor (1,1)

Competitor related to the result of one event unit.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or SC@CompetitorPlace Code	Competitor's ID or TBD in case that the competitor is unknown at this time but will be available NOCOMP is sent when there is no competitor (and will not come later)
Type	M	A, T	T for team
Organisation	O	CC@ORGANISATION Id	Competitor's organisation

Element: Competition /Result /Competitor /Description (0,1)

Competitors extended information.

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team in team events

Element: Competition /Result /Competitor /EventUnitEntry (0,N)

For team event information

Type	Code	Pos	Description
EUE	HOME_AWAY	N/A	Element Expected: When available
Attribute	M/O	Value	Description
Value	M	SC@Home Code	Send Home or Away designator



EUE		UNIFORM	N/A	Element Expected: If available
Attribute	M/O	Value	Description	
Value	M	SC@UNIFORM_COLOR Code	Red or Blue for color of the balls the team is playing.	

Sample (General)

```
<EventUnitEntry Type="EUE" Code="HOME_AWAY" Value="AWAY" />  
<EventUnitEntry Type="EUE" Pos="2" Code="UNIFORM" Value="BLUE" />  
....
```

Element: Competition /Result /Competitor /Composition /Athlete (0,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID. Can belong to a team member or an individual athlete.
Order	M	Positive Integer	Order attribute used to sort team members in a team. Before the competition this will be the same as the StartSortOrder and is used as the primary sort. During competition the competitors should be sorted as on the Match Result in ORIS.
StartSortOrder	M	Positive Integer	Order attribute used to sort team members in a team on the start list. Order defined as in ORIS.

Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Athletes extended information.			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC@PERSON_GENDER Id	Gender of the athlete
Organisation	M	CC@ORGANISATION Id	Athletes' organisation
BirthDate	O	YYYY-MM-DD	Birth date (example: YYYY-MM-DD). Must include if the data is available
IFId	O	S(16)	International Federation ID
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games).

Element: Competition /Result /Competitor /Composition /Athlete /EventUnitEntry (0,N)			
Individual athletes entry information.			
Type	Code	Pos	Description
EUE	STATUS	N/A	Element Expected: Send just for those suspended players
Attribute	M/O	Value	Description
Value	O	SC@AthleteStatus Code	Athlete's status in the team. When the athlete has been Suspended
EUE	POSITION	N/A	Element Expected: As soon as it is known
Attribute	M/O	Value	Description



	Value	O	CC@POSITION Id	Position of the player in the team.
EUE		UNIFORM	N/A	Element Expected: If available
	Attribute	M/O	Value	Description
	Value	M	SC@UNIFORM_COLOR Code	Red or Blue for color of the balls the team is playing.
EUE		HOME_AWAY	N/A	Element Expected: When available
	Attribute	M/O	Value	Description
	Value	M	SC@Home Code	Send Home or Away designator

Element: Competition /Result /Competitor /Composition /Athlete /ExtendedResults /ExtendedResult (0,N)

Individual athletes entry information.

Type	Code	Pos	Description
ER	STATUS	N/A	Element Expected: Send just for those players suspended during the match
	Attribute	M/O	Value
	Value	O	SC@AthleteStatus Code
			Athlete's status in the team. When the athlete has been Suspended

Sample (General)

```
<Athlete Code="1125142" Bib="8" Order="4">
<Description GivenName="Jane" FamilyName="Smith" Gender="F" Organisation="RSA" BirthDate="1992-12-15" />
<EventUnitEntry Type="EUE" Code="STARTER" Value="Y" />
<EventUnitEntry Type="EUE" Code="AGE" Value="22" />
```

2.3.5.6 Message Sort

Sort by Result @SortOrder



2.3.6 Pool Standings

2.3.6.1 Description

The pool standings message contains the standings of a group in a competition. Here the message is triggered at the start of OVR operations and then after each event unit (match).

This report is sent independently for each of the groups / pools of the competition in a particular phase, and the group / pool can be determined from the message header (DocumentCode).

2.3.6.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Unique ID for competition
DocumentCode	CC@Phase Code	Full Phase level RSC (Pool)
DocumentSubcode	N/A	N/A
DocumentType	DT_POOL_STANDING	Pool Standings message
DocumentSubtype	N/A	N/A
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	CC@RESULTSTATUS Code	Expected statuses are: START_LIST INTERMEDIATE UNOFFICIAL (if last match in pool is unofficial) OFFICIAL PROVISIONAL
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.6.3 Trigger and Frequency

The general rule is that this message is sent:

- * Before the start of the competition to build in the initial tables. The message has status START_LIST.
 - * When an event unit of the corresponding phase finishes (not waiting for official). The message has status INTERMEDIATE.
 - * When the phase finishes (there are no more event units/games to compete). The message has status UNOFFICIAL/OFFICIAL.
- Trigger also after any change.

2.3.6.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9	Level 10
Competition (0,1)									
	Gen								



	Sport	
	Codes	
	ExtendedInfos (0,1)	
	Progress (0,1)	
	LastUnit	
	UnitsTotal	
	UnitsComplete	
	Extension (0,N)	
	Code	
	Pos	
	Value	
	SportDescription (0,1)	
	DisciplineName	
	EventName	
	SubEventName	
	Gender	
	VenueDescription (0,1)	
	Venue	
	VenueName	
	Location	
	LocationName	
	Result (1,N)	
	Rank	
	RankEqual	
	ResultType	
	Result	
	IRM	
	QualificationMark	
	SortOrder	
	Won	
	Lost	
	Tied	
	Played	
	For	
	Against	
	Diff	
	Ratio	
	ExtendedResults (0,1)	
	ExtendedResult (1,N)	



	Type
	Code
	Pos
	Value
Competitor (1,1)	
Code	
Type	
Organisation	
Description (0,1)	
TeamName	
Composition (0,1)	
Athlete (1,N)	
Code	
Order	
Description (1,1)	
GivenName	
FamilyName	
Gender	
Organisation	
BirthDate	
IFId	
Class	
Opponent (0,N)	
Code	
Type	
Pos	
Organisation	
Date	
Time	
TimeStamp	
Unit	
HomeAway	
Result	
ExtendedResults (0,1)	
ExtendedResult (1,N)	
Type	
Code	
Pos	
Value	



	Description (0,1)
	TeamName
	Composition (0,1)
	Athlete (1,N)
	Code
	Order
	Description (1,1)
	GivenName
	FamilyName
	Gender
	Organisation
	BirthDate
	IFld
	Class

2.3.6.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /Progress (0,1)			
Attribute	M/O	Value	Description
LastUnit	O	CC@EVENT_UNIT Code	Send the full RSC of the most recently unit made official for the pool included in this message.
UnitsTotal	O	##0	Total number of units (games) to be played in the pool included in the message.
UnitsComplete	O	##0	Total number of units (games) which are official in the pool included in this message.

Element: Competition /ExtendedInfos /SportDescription (0,1)			
Sport Descriptions in Text.			
Attribute	M/O	Value	Description
DisciplineName	M	CC@DISCIPLINE ENG Description	Discipline ENG Description (not code) from Common Codes
EventName	M	CC@EVENT ENG Description	Event ENG Description (not code) from Common Codes.
SubEventName	M	CC@PHASE ENG ShortDescription	Phase ENG Description (not code) from Common Codes
Gender	M	CC@DISCIPLINE_GENDER Gender	Gender code for the event unit



Element: Competition /ExtendedInfos /VenueDescription (0,1)			
Venue Names in Text.			
Attribute	M/O	Value	Description
Venue	M	CC@VENUE Id	Venue Code
VenueName	M	CC@VENUE ENG Description	Venue ENG Description (not code) from Common Codes
Location	M	CC@LOCATION Id	Location code
LocationName	M	CC@LOCATION ENG Description	Location ENG Description (not code) from Common Codes

Element: Competition /Result (1,N)			
For any message, there should be at least one competitor being awarded a result for the pool.			
Attribute	M/O	Value	Description
Rank	O	Positive Integer	Rank at the group. It is optional because the team can be disqualified
RankEqual	O	Y	Identifies if a rank has been equalled. Send Y if applicable else not sent.
Result	O	#0.#	Game points
QualificationMark	O	SC@QualificationMark Code	Qualification indicator
IRM	O	SC@IRM Code	The invalid result mark, in case it is assigned
SortOrder	M	Positive Integer	This attribute is a sequential number with the order of the results for the group, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified teams.
Won	O	#0	Number of games won by the team in the group. Do not send if the team has not played.
Lost	O	#0	Number of games lost by the team in the group. Do not send if the team has not played.
Played	O	#0	Number of games played by the team in the group Do not send if the team has not played.
For	O	#0	Total number of shots for. Do not send if the team has not played.
Against	O	#0	Total number of shots against. Do not send if the team has not played.
Diff	O	#0	Shot difference, can be negative.
Ratio	O	##0	Send the winning percentage for the team



Element: Result /ExtendedResults /ExtendedResult (1,N)				
Type	Code	Pos	Description	
SETS	WON	N/A	Element Expected: If available	
	M/O	Value	Description	
	Value	M	#0	Number of sets won
SETS	POINTS	N/A	Element Expected: If available	
	M/O	Value	Description	
	Value	M	#0.#	Number of set points
GAMES	BYES	N/A	Element Expected: If available	
	M/O	Value	Description	
	Value	M	#0	Number of byes games

Element: Competition /Result /Competitor (1,1)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor's ID
Type	M	T	T for team
Organisation	M	CC@ORGANISATION Id	Competitor's organisation

Element: Competition /Result /Competitor /Description (0,1)			
Competitors extended information.			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team.

Element: Competition /Result /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeros	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Positive Integer	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Preferred Given Name
FamilyName	M	S(25)	Preferred Family Name
Gender	M	CC@PERSON_GENDER Id	Gender of the athlete
Organisation	M	CC@ORGANISATION Id	Athletes' organisation
BirthDate	O	YYYY-MM-DD	Date Of Birth
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games).



Element: Competition /Result /Competitor /Opponent (0,N)			
Details of the opposing competitor in competitions within the pool. (The Opponent of the competitor in the Opponent @Pos column of the Pool)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Competitor ID
Type	M	T	T for team
Pos	M	#0	1 to n. Normally expected to be the same as Result/SortOrder for the same competitor.
Organisation	M	CC@ORGANISATION Id	Competitor's organisation (code). Must include if data is available
Date	M	Date	Date of match between the competitor and opponent (example: YYYY-MM-DD). Must include if the data is available, send even after the match is complete.
Time	O	S(5)	Time of match (example HH:MM) Must include if the data is available.
TimeStamp	O	DateTime	Scheduled date and time of the match including the timezone offset. Send for future and completed matches.
Unit	O	CC@EVENT_UNIT Code	Full RSC of the Unit for the Pool Item
HomeAway	O	H, A	Home / Away indicator. Send H if the opponent is the home team, send A if the opponent is the away team.
Result	O	S(50)	Result of the match if match is complete and formatted as in CRIS respecting the H/A and who won the match. This should include the indication of winner in case of tie break and the set scores like this 1-1 (Win) (8-6, 6-8, 1-0)

Element: Competition /Result /Competitor /Opponent /ExtendedResults /ExtendedResult (1,N)				
Type	Code	Pos	Description	
GAME	WLT	HOME/AWAY	Pos: HOME and AWAY indicator Element Expected: HOME and AWAY indicator	
Attribute	M/O	Value	Description	
Value	M	SC@WLT	Indication of game winner and loser	
SETS	HOME/AWAY	1..3	Pos: Set number Element Expected: If available	
Attribute	M/O	Value	Description	
Value	M	#0	Set score for HOME or AWAY competitor	

Element: Competition /Result /Competitor /Opponent /Description (0,1)			
Competitors extended information.			
Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the opposition team.

Element: Competition /Result /Competitor /Opponent /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeros	Athletes ID, corresponding to either a team member or an individual athlete



Order	M	Positive Integer	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".
-------	---	------------------	---

Element: Competition /Result /Competitor /Opponent /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Preferred Given Name
FamilyName	M	S(25)	Preferred Family Name
Gender	M	CC@PERSON_GENDER Id	Gender of the athlete
Organisation	M	CC@ORGANISATION Id	Athletes' organisation
BirthDate	O	YYYY-MM-DD	Date Of Birth
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games).

Sample (General)

```
<Result Rank="3" SortOrder="3" Played="2" Won="1" Lost="1" For="33" Against="35" Ratio="50">
  <ExtendedResults>
    <ExtendedResult Type="ER" Code="PTS_AVG" Value="16.5"/>
  </ExtendedResults>
  <Competitor Code="BK3MTEAM3-----EGY01" Type="T" Organisation="EGY">
    <Description TeamName="Egypt"/>
    <Opponent Code="BK3MTEAM3-----BRA01" Type="T" Pos="1" Organisation="BRA" Date="2012-07-27" Time="14:00"
Unit="BK3MTEAM3-----GPA-000200--" HomeAway="H" Result="12-20">
      <Description TeamName="Brazil"/>
    </Opponent>
    <Opponent Code="BK3MTEAM3-----BLR01" Type="T" Pos="2" Organisation="BLR" Date="2012-08-01" Time="09:00"
Unit="BK3MTEAM3-----GPA-000400--" HomeAway="A" >
      <Description TeamName="Belarus"/>
    </Opponent>
  </Competitor>
</Result>
```

2.3.6.6 Message Sort

The attribute used to sort the results is Result @SortOrder.



2.3.7 Brackets

2.3.7.1 Description

The brackets message contains the brackets information for one particular event. It is used in events where there is a necessity to know in advance how successive event units will be filled as the competition progresses. In the early stages of the competition, it indicates how each of the event units will be built from the winners/losers, or other competition rules of the previous event units.

2.3.7.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Unique ID for competition
DocumentCode	CC@Event Code	Full RSC of the Event
DocumentSubcode	N/A	N/A
DocumentType	DT_BRACKETS	Brackets message
DocumentSubtype	N/A	N/A
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	CC@RESULTSTATUS Code	Status of the message. Expected statuses are: START_LIST: (before the start of the competition) INTERMEDIATE (during the competition) UNOFFICIAL (when last match unofficial) OFFICIAL (when all matches official) PROVISIONAL
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.7.3 Trigger and Frequency

- * Before the competition. (START_LIST)
- * After every match in the preliminaries which determines a position in the bracket. (INTERMEDIATE)
- * After every match during final phases, except last. (INTERMEDIATE)
- * After the last match (OFFICIAL)
- * Trigger after any change

2.3.7.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9	Level 10	Level 11
Competition (0,1)										
	Gen									
	Sport									



	Codes	
	ExtendedInfos (0,1)	
	Progress (0,1)	
	LastUnit	
	UnitsTotal	
	UnitsComplete	
	SportDescription (0,1)	
	DisciplineName	
	EventName	
	Gender	
	VenueDescription (0,1)	
	Venue	
	VenueName	
	Bracket (1,N)	
	Code	
	BracketItems (1,N)	
	Code	
	BracketItem (1,N)	
	Code	
	Order	
	Position	
	Date	
	Time	
	TimeStamp	
	Unit	
	Result	
	CompetitorPlace (1,N)	
	Pos	
	Code	
	WLT	
	Result	
	ResultType	
	IRM	
	StrikeOut	
	PreviousUnit (0,1)	
	Unit	
	Value	
	WLT	
	Competitor (0,1)	



	Code
	Type
	Organisation
	Description (0,1)
	TeamName
	Composition (0,1)
	Athlete (1,N)
	Code
	Order
	Description (1,1)
	GivenName
	FamilyName
	Gender
	Organisation
	BirthDate
	Class

2.3.7.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /Progress (0,1)			
Attribute	M/O	Value	Description
LastUnit	O	CC@EVENT_UNIT Code	Send the full RSC of the most recently completed unit in the event.
UnitsTotal	O	Positive Integer	Total number of units to be played in the event
UnitsComplete	O	#0	Total number of units which are official of the UnitsTotal.

Element: Competition /ExtendedInfos /SportDescription (0,1)			
Sport Description in Text			
Attribute	M/O	Value	Description
DisciplineName	M	CC@DISCIPLINE ENG Description	Discipline ENG Description (not code) from Common Codes
EventName	M	CC@EVENT ENG Description	Event ENG Description (not code) from Common Codes.
Gender	M	CC@DISCIPLINE_GENDER Gender	Gender code for the event unit



Element: Competition /ExtendedInfos /VenueDescription (0,1)			
Venue Names in Text.			
Attribute	M/O	Value	Description
Venue	M	CC@VENUE Id	Venue Code
VenueName	M	CC@VENUE ENG Description	Venue ENG Description (not code) from Common Codes

Element: Competition /Bracket (1,N)			
Attribute	M/O	Value	Description
Code	M	SC@Bracket Code	Bracket code to identify a bracket item. One for each individual bracket as defined in ORIS.

Element: Competition /Bracket /BracketItems (1,N)			
Attribute	M/O	Value	Description
Code	M	SC@BracketItems Code	Bracket code to identify a set of bracket items. The quarterfinals, semifinals or finals phases etc.

Element: Competition /Bracket /BracketItems /BracketItem (1,N)			
Attribute	M/O	Value	Description
Code	O	Positive Integer	Bracket code to identify a bracket item. Unique identifier for the BracketItem. The game number for each bracket item (e.g.: 17, 18, 19, 20,...)
Order	M	Positive Integer	Sequential number inside of BracketItems to indicate the order, always start at 1
Position	M	##0	Bracket position when drawing the bracket. For example a quarter final has 4 items, with positions 1, 2, 3 and 4 from the top. Use the appropriate number to draw the position. If there is only 3 items in a quarterfinal and the fourth is not displayed and would logically be the first then the positions are 2, 3, 4. In case of placement matches (bronze or maybe 7_8), where participants are the losers of semifinals those matches are included in the originating bracket in the same phase (with Position=2) as the match with the winner of the semifinal (with Position=1).
Date	O	Date	YYYY-MM-DD. Must be filled if known
Time	O	S(5)	HH:MM. Must be filled if known TBD can be sent
TimeStamp	O	DateTime	Scheduled date and time of the match/unit including the time zone offset. Send for future and completed matches.
Unit	O	CC@EVENT_UNIT Code	Full RSC of the unit for the BracketItem
Result	O	S(50)	Fill when match is complete, filled and formatted in the same format as in ORIS (for example 21-12 or w-0(f)). If the match is cancelled, "Cancelled" should be sent. The result should include the set score like 2-0 (7-3, 8-1)

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace (1,N)			
---	--	--	--



- If the competitors are known, this element is used to place the competitors in the bracket. - If they are not yet known, it contains some information (on the rule to access to this bracket...)			
Attribute	M/O	Value	Description
Pos	M	Positive Integer	This attribute is a sequential number to place the different competitors in the bracket (1 or 2).
Code	O	SC@CompetitorPlace Code	Sent when there is no competitor team (BYE) or when it is not known yet (TBD).
WLT	O	SC@WLT Code	W or L, indicates the winner or loser of the bracket item. Always send when known
Result	O	S(5)	The result (score) of the competitor in the event unit. In the case of a forfeit w and 0(f) are appropriate.
ResultType	O	SC@ResultType Code	Type of the @Result attribute.
IRM	O	SC@IRM Code	The invalid rank mark, if applicable Do not end in the case of forfeit
StrikeOut	O	Y	If the competitor should be struck out in this bracket item send Y, usually only used for DQB.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /PreviousUnit (0,1)

Previous event unit related to the CompetitorPlace@Pos competitor of the current bracket item. It is always informed except for the bracket items whose CompetitorPlace@Pos competitor do not have preceding event units in the bracket graph unless coming from a pool.

Attribute	M/O	Value	Description
Unit	O	CC@EVENT_UNIT Code	Full RSC code of the previous event unit for the CompetitorPlace@Pos competitor of the bracket item. Must send if a winner/loser from a single unit. If from a pool then this is the RSC of the pool.
Value	O	Integer	Rank in the pool, if the previous phase is the pool phase.
WLT	O	SC@WLT Code	Send W or L for winner or loser of previous match (if not Pool) do not send if participant is unknown from a pool.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor (0,1)

CompetitorPlace @Pos competitor related to the bracket item. Only include if the competitor is known.

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or SC@CompetitorPlace Code	If the competitor in the current unit is unknown due to coming from previous matches then fill this the appropriate indicator (SC@CompetitorPlace) which may include possible options of TBD in case that the competitor is unknown at this time but will be available NOCOMP is sent when there is no competitor (and will not come later) Otherwise send the Competitor ID of the a known competitor.
Type	M	T	T for team
Organisation	O	CC@ORGANISATION Id	Competitors' organisation if known.

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Description (0,1)

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team.



Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete (1,N)			
Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeros	Athlete's ID, corresponding to either a team member or an individual athlete
Order	M	Positive Integer	Order attribute used to sort team members in a team (if Competitor @Type="T") or 1 if Competitor @Type="A".

Element: Competition /Bracket /BracketItems /BracketItem /CompetitorPlace /Competitor /Composition /Athlete /Description (1,1)			
Attribute	M/O	Value	Description
GivenName	O	S(25)	Preferred Given Name
FamilyName	M	S(25)	Preferred Family Name
Gender	M	CC@PERSON_GENDER Id	Gender of the athlete
Organisation	M	CC@ORGANISATION Id	Athletes' organisation
BirthDate	O	YYYY-MM-DD	Date Of Birth
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games).

Sample (General)

```
<Bracket Code="FNL-">
  <BracketItems Code="SFNL">
    <BracketItem Code="33" Order="1" Position="1" Date="2012-08-10" Time="15:00" Unit="BK3WTEAM3-----SFNL000100--">
      <CompetitorPlace Pos="1">
        <Competitor Code="BK3WTEAM3-----NED01" Type="T" Organisation="NED">
          <Description TeamName="Netherlands"/>
        </Competitor>
      </CompetitorPlace>
      <CompetitorPlace Pos="2">
        <Competitor Code="BK3WTEAM3-----NZL01" Type="T" Organisation="NZL">
          <Description TeamName="New Zealand"/>
        </Competitor>
      </CompetitorPlace>
    </BracketItem>
  </BracketItems>
</Bracket Code="FNL-">
```

2.3.7.6 Message Sort

Bracket @Code (using order in sport codes) then Bracket/BracketItems @Code (descending, using order in sport codes) then Bracket/BracketItems/BracketItem @Position

2.3.8 Event Final Ranking

2.3.8.1 Description

The event final ranking is a message containing the final results and ranking at the completion of one particular event, either for individual athletes or for aggregated athletes.

The final ranking message is a generic message for all sports, including the full event final result for all competitors who were either ranked, got an Invalid Rank Mark (disqualified, etc.), or both.

2.3.8.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC@EVENT Code	Event RSC
DocumentSubcode	N/A	N/A
DocumentType	DT_RANKING	Event Final ranking message
DocumentSubtype	N/A	N/A
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	CC@RESULTSTATUS Code	Expected statuses are: PARTIAL OFFICIAL PROVISIONAL
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.8.3 Trigger and Frequency

This message is only triggered after a unit which affects the final ranking is official and that particular ranking is not subject to change.

* After each final position is known.

2.3.8.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7
Competition (0,1)						
	Gen					
	Sport					
	Codes					
	ExtendedInfos (0,1)					
		Progress (0,1)				



		LastUnit
		UnitsTotal
		UnitsComplete
	SportDescription (0,1)	
		DisciplineName
		EventName
		Gender
	VenueDescription (0,1)	
		Venue
		VenueName
	Result (1,N)	
	Rank	
	RankEqual	
	Played	
	Won	
	Lost	
	IRM	
	SortOrder	
	Competitor (1,1)	
		Code
		Type
		Organisation
		Description (0,1)
		TeamName
		Composition (1,1)
		Athlete (0,N)
		Code
		Order
		Description (1,1)
		GivenName
		FamilyName
		Gender
		Organisation
		BirthDate
		Class

2.3.8.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of General Data Dictionary applicable to the message



Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /ExtendedInfos /Progress (0,1)

Attribute	M/O	Value	Description
LastUnit	O	CC@EVENT_UNIT Code	Send the full RSC of the most recently completed unit in the event.
UnitsTotal	O	Positive Integer	Total number of units to be played in the event
UnitsComplete	O	#0	Total number of units which are official of the UnitsTotal.

Element: Competition /ExtendedInfos /SportDescription (0,1)

Sport Description in text

Attribute	M/O	Value	Description
DisciplineName	M	CC@DISCIPLINE ENG Description	Discipline ENG Description (not code) from Common Codes
EventName	M	CC@EVENT ENG Description	Event ENG Description (not code) from Common Codes
Gender	O	CC@DISCIPLINE_GENDER Gender	Gender code for the event.

Element: Competition /ExtendedInfos /VenueDescription (0,1)

Attribute	M/O	Value	Description
Venue	M	CC@VENUE Id	Venue Code
VenueName	M	CC@VENUE ENG Description	Venue ENG Description (not code) from Common Codes

Element: Competition /Result (1,N)

For any event final ranking message, there should be at least one competitor being awarded a result for the event.

Attribute	M/O	Value	Description
Rank	O	S(3)	Rank of the competitor in the result. It is optional because the competitor can be disqualified
RankEqual	O	Y	Send "Y" if the Rank is equalled else do not send.
Played	O	##0	Send number of matches played
Won	O	##0	Send number of matches won
Lost	O	##0	Send number of matches lost
IRM	O	SC@IRM Code	Send just if the competitor has been disqualified
SortOrder	M	Positive Integer	This attribute is a sequential number with the order of the competitors at the end of the event, if they were to be presented. It is mostly based on the rank, but it should be used to sort out disqualified teams.

Element: Competition /Result /Competitor (1,1)

Competitor related to one final event result.



Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes or SC@CompetitorPlace Code	Competitor's ID or another indicator (SC@CompetitorPlace) in the case where there is no competitor in the rank due to IRM. NOAWARD if the place is not awarded.
Type	M	T	T for team
Organisation	O	CC@ORGANISATION Id	Organisation of the competitor

Element: Competition /Result /Competitor /Description (0,1)

Attribute	M/O	Value	Description
TeamName	M	S(73)	Name of the team.

Element: Competition /Result /Competitor /Composition /Athlete (0,N)

Attribute	M/O	Value	Description
Code	M	S(20) with no leading zeroes	Athlete's ID, corresponding to an individual athlete or a team member. Team members should be participating in the event.
Order	M	Positive Integer	Order attribute used to sort team members in a team

Element: Competition /Result /Competitor /Composition /Athlete /Description (1,1)

	M/O	Value	Description
GivenName	O	S(25)	Given name in WNPA format (mixed case)
FamilyName	M	S(25)	Family name in WNPA format (mixed case)
Gender	M	CC@PERSON_GENDER Id	Gender of the athlete
Organisation	M	CC@ORGANISATION Id	Athletes' organisation
BirthDate	O	Date	Birth date (example: YYYY-MM-DD). Must include if the data is available
Class	O	CC@DISCIPLINE_CLASS Class	Code to identify the sport class in the case of events with athletes with a disability (e.g: Paralympic Games).

Sample (General)

```
<Result Rank="1" SortOrder="1" Played="8" Won="8" Lost="0" >
  <ExtendedResults>
    <ExtendedResult Type="ER" Code="WIN_PERCENT" Value="100" />
    <ExtendedResult Type="ER" Code="PTS_AVG" Value="21.1" />
    <ExtendedResult Type="ER" Code="PTS_TOTAL" Value="169" />
  </ExtendedResults>
  <Competitor Code="BK3MTEAM3-----CRO01" Type="T" Organisation="CRO">
    <Description TeamName="Croatia"/>
    <Composition>
      <Athlete Code="1085534" Order="1" Bib="12" >
```

2.3.8.6 Message Sort

Sort by Result @SortOrder

2.3.9 Configuration

2.3.9.1 Description

The Configuration is a message containing general configuration.

Send before the competition for each phase in separate messages.

2.3.9.2 Header Values

The following table describes the message header attributes.

Attribute	Value	Comment
CompetitionCode	CC@COMPETITION_CODE Id	Competition ID
DocumentCode	CC@PHASE Code	Full RSC of the phase
DocumentSubcode	N/A	N/A
DocumentType	DT_CONFIG	Configuration message
DocumentSubtype	N/A	N/A
Version	Positive Integer	Version number (ascending) associated to the message content.
ResultStatus	N/A	N/A
FeedFlag	P, T	P – Production / T - Test
Date	Date	Refer to ODF header definition
Time	Time	Refer to ODF header definition
LogicalDate	Date	Refer to ODF header definition
Source	SCGEN@Source Code	Code indicating the system which generated the message.

2.3.9.3 Trigger and Frequency

The message is sent prior to any ODF Sports message sending one message for each phase.

Trigger also after any change, but considering that, if possible, the configuration for one phase must be provided before the start list or resend the DT_RESULT if there are changes in DT_CONFIG.

2.3.9.4 Message Structure

The following table defines the structure of the message.

Level 1	Level 2	Level 3	Level 4	Level 5
Competition (0,1)				
	Gen			
	Sport			
	Codes			
	Configs (1,1)			
		Config (1,N)		
			Unit	
			ExtendedConfig (1,N)	
				Type



	Code
	Pos
	Value

2.3.9.5 Message Values

Element: Competition (0,1)			
Attribute	M/O	Value	Description
Gen	O	S(20)	Version of the General Data Dictionary applicable to the message
Sport	O	S(20)	Version of the Sport Data Dictionary applicable to the message
Codes	O	S(20)	Version of the Codes applicable to the message

Element: Competition /Configs /Config (1,N)			
Attribute	M/O	Value	Description
Unit	M	CC@Phase Code	Full RSC of the phase.

Element: Competition /Configs /Config /ExtendedConfig (1,N)				
Type	Code	Pos	Description	
BRACKET	SIZE	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	SC@BracketItems Code	Send the code for the first elimination phase of the event
BRACKET	COUNT	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Positive Integer	Send the number of brackets
MATCH	PERIODS	N/A	Element Expected: Always	
	Attribute	M/O	Value	Description
	Value	M	Positive Integer	Number of periods in the match

2.3.9.6 Message Sort

There is no message sorting rule.



3 Message Timeline

3.1 Preparation Phase

Trigger	Message	Status	D	E	P	S	U
As soon as ODF operation start	DT_CODES						
Periodically as soon as ODF operations start	DT_PARTIC		x				
	DT_PARTIC_TEAMS		x				
	DT_SCHEDULE		x				

3.2 Before competition

Trigger	Message	Status	D	E	P	S	U
As soon as Participant verification process finish (ORIS C38 process)	DT_PARTIC_UPDATE		x				
	DT_PARTIC_TEAMS_UPDATE		x				
In any Competition Schedule change	DT_SCHEDULE_UPDATE		x				o
	DT_RESULT	START_LIST					x
	DT_BRACKETS	START_LIST		x			
One for each pool	DT_POOL_STANDINGS	START_LIST			x		
After Event Briefing	DT_PDF C33 - Team Roster			x			

3.3 During competition

Trigger	Message	Status	D	E	P	S	U
45 minutes before the first match starts	DT_PDF C51 - Start List	START_LIST					x
	DT_RESULT	START_LIST					x
	DT_PLAY_BY_PLAY	START_LIST					x
When Competition is ready to start	DT_SCHEDULE_UPDATE	GETTING_READY	x				o
When Competition starts	DT_SCHEDULE_UPDATE	RUNNING	x				o
Triggering when competition is LIVE	DT_RESULT	LIVE					x
	DT_PLAY_BY_PLAY	LIVE					x
	DT_CURRENT						x
In every Period break	DT_SCHEDULE_UPDATE	SCHEDULED_BREAK	x				o
	DT_PLAY_BY_PLAY	INTERMEDIATE					x
	DT_RESULT	INTERMEDIATE					x

3.4 After competition

Trigger	Message	Status	D	E	P	S	U
After a match is FINISHED	DT_SCHEDULE_UPDATE	FINISHED	x				o
	DT_CURRENT						x



When results are UNOFFICIAL	DT_RESULT	UNOFFICIAL					x
	DT_PLAY_BY_PLAY	UNOFFICIAL					x
Only after Preliminary Round matches	DT_POOL_STANDINGS	INTERMEDIATE			x		
Only after the last match of a pool is finished	DT_POOL_STANDINGS	UNOFFICIAL			x		
Only after the last match of a pool and after each match of the Final round	DT_BRACKETS	INTERMEDIATE		x			
Unofficial after the Gold Medal match	DT_BRACKETS	UNOFFICIAL		x			
When results are OFFICIAL	DT_RESULT	OFFICIAL					x
	DT_PLAY_BY_PLAY	OFFICIAL					x
	DT_PDF C69 - play by play	OFFICIAL					x
	DT_PDF C73 - Result	OFFICIAL					x
	DT_PDF C76 - Tournament Summary	INTERMEDIATE		x			
	DT_PDF C84A - Cumulative Statistics			x			
	DT_PDF C84B - Overall Team Statistics			x			
	DT_PDF C85 - Individual Statistics Leaders			x			
Only after Preliminary round is finished; after play in games and after Semi-finals	DT_SCHEDULE_UPDATE		x				
Only after Preliminary round is finished; after play in games and after Semi-finals	DT_RESULT	START_LIST					x
Official only after the last match of a pool is finished	DT_POOL_STANDINGS	OFFICIAL			x		
	DT_STATS - IND_RANKING	INTERMEDIATE		x			
	DT_STATS - IND_RANKING	OFFICIAL		x			
One for each team	DT_STATS - CUM	INTERMEDIATE		x			
Official after the last match of a team in the competition	DT_STATS - CUM	OFFICIAL		x			
	DT_STATS - TOU	OFFICIAL		x			
Official after the Gold Medal match	DT_BRACKETS	OFFICIAL		x			
Only after last match of the Preliminary round, after the last play in games match and after the Bronze and Gold matches	DT_RANKING	PARTIAL/OFFICIAL		x			
Only after final rankings of the pools and after the last match of play in games and SF	DT_PDF C08 - Competition Schedule		x				
Partial after Bronze Medal Match / Official After Gold Medal Match	DT_MEDALLISTS	PARTIAL/OFFICIAL		x			
Only after Bronze and Gold Medal matches	DT_MEDALLISTS_DISCIPLINE		x				
Only after Bronze and Gold Medal matches	DT_MEDALS		x				
	DT_PDF C92C - Medallists	PARTIAL/OFFICIAL		x			



	DT_PDF C93 - Medallists by Event		x				
	DT_PDF C95 - Medal Standings		x				

Legend:

D Discipline; **E** Event; **P** Phase; **S** Session; **U** Unit

x Sent on that level; **o** Includes info from that level



4 Document Control

Version history		
Version	Date	Comments
V1.0	20 Aug 2025	First Version
V1.1	31 Jan 2026	Update due to change in CRIS to have 2 sets
V1.2	12 Mar 2026	Update to consistently applied new set format
V1.3	8 Apr 2026	Update for byes games
V1.4	23 Apr 2026	Updated after receiving comments from Glasgow 2026
V1.5	6 May 2026	Update based on implementation
V1.6	13 May 2026	DT_BRACKET Clarification
V1.7	23 July 2026	Update based on MIS findings

File Reference: SCOG-2026-LBO-1.7 SFR

Change Log		
Version	Status	Changes on version
V1.0	SFR	First Version updated to MiCo schema
V1.1	SFR	DT_RESULT: - Period added HomePeriodScore and AwayPeriodScore - ExtendedPeriod was added with END/HOME, END/AWAY and EP/WINNER extensions added.
V1.2	SFR	DT_POOL_STANDINGS: Result and Diff attribute added, SETS WON and SETS POINTS added as ExtendedResult. ExtendedResult for Opponent added for Set score and WLT information. Opponent.Result added clarification for format DT_BRACKET: BracketItem.Result clarification added to include set scores and tie breaker and winner identification for games with tie break.
V1.3	SFR	DT_POOL_STANDING: ExtendedResult with GAMES BYES was included to send number of byes games. QualificationMark was added to the Result Structure, as this is required by TV graphics.
V1.4	SFR	DT_ENTRIES: GROUP Extension will stay at Entry level for both individual and team competitions. GROUP on ATHLETE level is deleted ROLE extension was deleted as it was agreed, that POSITION extension could cover such data.
V1.5	SFR	DT_SCHEDULE and DT_BRACKETS: PreviousUnit.Value format and explanation of data send was updated. It will be sent in case the rank from the pool round will be needed to determine the match participant.
V1.6	SFR	Discipline Overview (2.1.) DT_BRACKET usage explanation was added DT_BRACKET: BracketItem.Position explanation extended to explain the new case, where classification matches might stay in the same bracket.
V1.7	SFR	DT_RESULT: EUE for Athlete added for UNIFORM and HOME_AWAY. Clarification, that UNIFORM color is in fact the color of the balls played by the team or individual.